REPORT DOCUMENTATION PAGE

1. Recipient's Reference	2. Originator's Reference	3. Further Reference	4. Security Classification of Document
	AGARD-R-702 Addendum No.1	ISBN 92-835-1495-5	UNCLASSIFIED

5. Originator Advisory Group for Aerospace Research and Development
North Atlantic Treaty Organization
7 rue Ancelle, 92200 Neuilly sur Seine, France

6. Title

COMPENDIUM OF UNSTEADY AERODYNAMIC MEASUREMENTS

7. Presented at

8. Author(s)/Editor(s)	9. Date
Various	May 1985

10. Author's/Editor's Address	11. Pages
Various	128

12. Distribution Statement This document is distributed in accordance with AGARD policies and regulations, which are outlined on the Outside Back Covers of all AGARD publications.

13. Keywords/Descriptors

Aerodynàmic characteristics	Aerodynamic configurations
Unsteady flow	Experimental data
Transonic flow	Applications of mathematics
Aeroelasticity	

14. Abstract

This Addendum contains two further sets of windtunnel measurements made on the AGARD Aeroelastic Configurations already chosen as computational test cases.

General comments on the experimental programme and its relationship to the theoretical computations are contained in the initial volume of R-702.

This report was sponsored by the Structures and Materials Panel of AGARD.

AGARD-R-702 ADDENDUM No.I

AGARD

ADVISORY GROUP FOR AEROSPACE RESEARCH & DEVELOPMENT

7 RUE ANCELLE 92200 NEUILLY SUR SEINE FRANCE

AGARD REPORT No.702

Compendium of Unsteady Aerodynamic Measurements

Addendum No.1

NORTH ATLANTIC TREATY ORGANIZATION

DISTRIBUTION AND AVAILABILITY
ON BACK COVER

NORTH ATLANTIC TREATY ORGANISATION

ADVISORY GROUP FOR AEROSPACE RESEARCH AND DEVELOPMENT

(ORGANISATION DU TRAITE DE L'ATLANTIQUE NORD)

AGARD Report No.702

ADDENDUM No.1

COMPENDIUM OF UNSTEADY AERODYNAMIC MEASUREMENTS

THE MISSION OF AGARD

The mission of AGARD is to bring together the leading personalities of the NATO nations in the fields of science and technology relating to aerospace for the following purposes:

— Exchanging of scientific and technical information;

— Continuously stimulating advances in the aerospace sciences relevant to strengthening the common defence posture;

— Improving the co-operation among member nations in aerospace research and development;

— Providing scientific and technical advice and assistance to the North Atlantic Military Committee in the field of aerospace research and development;

— Rendering scientific and technical assistance, as requested, to other NATO bodies and to member nations in connection with research and development problems in the aerospace field;

— Providing assistance to member nations for the purpose of increasing their scientific and technical potential;

— Recommending effective ways for the member nations to use their research and development capabilities for the common benefit of the NATO community.

The highest authority within AGARD is the National Delegates Board consisting of officially appointed senior representatives from each member nation. The mission of AGARD is carried out through the Panels which are composed of experts appointed by the National Delegates, the Consultant and Exchange Programme and the Aerospace Applications Studies Programme. The results of AGARD work are reported to the member nations and the NATO Authorities through the AGARD series of publications of which this is one.

Participation in AGARD activities is by invitation only and is normally limited to citizens of the NATO nations.

INTRODUCTION

by

N.C.Lambourne
62 Putnoe Lane
Bedford MK41 9AE
England

Publication of the Compendium (AGARD R-702) in August 1982 made data for seven of the AGARD Aeroelastic Configurations promptly available. However, data for three of the AGARD Configurations could not be included because the experiments on these had not been completed; for these the intention was to issue addenda.

This, the first addendum, comprises data sets for the ZKP wing and the LANN wing. At a later date it may be possible to issue a data set for the remaining AGARD Configuration, the Rectangular Wing, on which experiments have not yet been performed.

Note concerning the test cases of AGARD AR-167*

The cases specified in AR-167 for the computations were, for some configurations, based on proposals made before the experiments had been started. It is not unusual to find that test programmes need to be modified once the experiments have commenced. This has happened for both of the wings included here; the cases of the present Data Sets whilst covering the same kind of parameter variations, do not agree in detail with those given in AR-167.

It follows that researchers making calculations for the Rectangular Wing should take warning that the experimental results may relate to cases which differ somewhat from those of AR-167.

---

*S.R.Bland: AGARD Three-Dimensional Aeroelastic Configurations AGARD AR-167, March 1982.

SUMMARY

The Compendium contains two further sets of wind tunnel measurements made on AGARD Aeroelastic Configurations already chosen as computational test cases.

General comments on the experimental programme and its relationship to the theoretical computations are contained in the initial volume of R-702.

CONTENTS

DATA SET 8

ZKP WING, OSCILLATING AILERON

by

Dipl. Ing. K.Dau
Dipl. Ing. S.Vogel
Dipl. Ing. H.Zimmermann
MBB Transport und Verkehrsflugzeuge
TE 234
Postfach 10 78 45
2800 Bremen 1
Fed. Rep. of Germany

INTRODUCTION

This Data Set contains pressure distributions measured on the ZKP wing for an oscillating aileron in the ONERA transonic S1 wind tunnel at Modane, France, in late 1982. The tests were part of a cooperative project between MBB, ONERA, and the Aerospatiale corporation. The purpose of the tests was to obtain steady and unsteady pressures due to fast-moving control surfaces in transonic flow, likely to be encountered in the operation of active control systems for transport aircraft.

The following is a number of comments on the diagrams and tables.

GEOMETRY OF EXPERIMENTAL MODEL

The model geometry is shown in Fig. 8.3 to 8.5. Figure 8.3 shows the model including the major dimensions of the half-fuselage in a coordinate system parallel to the tunnel floor and walls. Figure 8.4 shows the dimensions of the wing and the aileron when rotated by the dihedral angle of 4.787 deg into the plane z = 0 of the coordinate system in which the profile coordinates are given by Ref. 8.1. Figure 8.5 shows the details of the aileron geometry in cross-section, including nose and gap geometry.

COMPARISON WITH AGARD COMPUTATIONAL PROGRAMME OF REF. 8.1

Model geometry

Unlike the computational model (Ref. 8.1, Fig. 7) the experimental model has a half-fuselage as shown in Fig. 8.3. This changes the definition of the root chord which is now smaller than the computational root chord because of the taper of the wing (see Fig. 8.4). The difference in the definition of the root chord affects the specifications of reduced frequency and Reynold's number as shown in Para. 12, NOTATION. Otherwise the two planforms and their coordinate origins are identical. Furthermore, the gap between aileron and wing spar (Fig. 8.5) of the experimental model was not sealed, as stated in Ref. 8.1. The gap is 0.3-0.5 mm wide.

Instrumentation

The number and location of the sections at which pressures were measured where changed from the values given in Ref. 8.1 to those given in Fig. 8.6.

Design Condition

The design condition of the experimental model is M = 0.78 and α_m = 1.5 deg as listed in Ref. 8.1, Sect. 3.4. The experimental lift coefficient may be somewhat different from the listed theoretical value of 0.5 at the design condition, depending on how the fuselage contribution is interpreted.

Experimental Cases

The experimental cases for which data are provided in the Data Set are not identical with the computational test cases originally suggested in Ref. 8.1, Table 9; this may affect the choices for future calculations. The correspondence between the experimental and the original computational cases is shown in Table 8.2. It will be seen that, of the computational choices, only the three priority cases have closely related experimental cases. No experimental results are available for M = 0.73 to match the computational cases 2 and 3.

TEST SET-UP AND INSTRUMENTATION

The wind tunnel test set-up for measuring unsteady pressures on the wing is shown in Fig. 8.1 and 8.2. To prevent the wing tip from executing large bending motions due to aileron forces, the wing tip was braced by four cables, all attached to a point of the wing tip, and lying in a plane roughly parallel to the aircraft plane of symmetry. The other ends of the cables were led outside the test section, and preloaded with a two-ton weight each.

Prior to every unsteady run the brakes on all cables were released permitting the wing to assume a mean position under aerodynamic load without additional cable constraint, while the new mean test parameters (Mach no., wing and flap incidences) were established. The cables were then clamped, and remained clamped during aileron oscillation.

The aileron was actuated by a hydraulic servo motor producing a harmonic aileron rotation about its swept hinge axis. The instantaneous aileron displacement was measured relative to the wing by potentiometers in the streamwise direction at the two aileron stations.

The wing was equipped with 509 pressure taps for steady pressures, and 387 Kulite transducers for unsteady pressures. The tap coordinates are listed in Tables 8.3 to 8.7 with their corresponding pressures.

The pressure taps were arrayed in streamwise wing sections as shown in Fig. 8.6. For reasons of space the sections containing steady-pressure taps were not congruent with those for unsteady pressures, but are considered to be close enough to reflect flow conditions for the neighboring unsteady pressures with sufficient accuracy for most purposes.

Steady pressures were measured via tubing and scanivalve by tunnel system transducers, unsteady pressures were measured by Kulite transducers installed directly below each pressure tap. Furthermore 17 accelerometers were installed on the wing, one of them on the aileron, see Fig. 8.7.

DATA PROCESSING

Only the fundamental component was recorded for each response signal. Response signal phase was defined to be relative to aileron motion. All listed pressures correspond to an aileron amplitude of $\delta_o = 1°$, the aileron deflection angles δ_m and δ_o being defined in the streamwise direction.

Both steady and unsteady pressures are presented in uncorrected form. Those pressure values which were obviously spurious (transducer failure, etc.) were eliminated. Besides these data additional data, listed in Table 8.1, could be made available.

DISCUSSION

The unsteady pressures generally exhibit the distribution typical for ailerons on transport aircraft wings, i.e. they are virtually zero outside the neighborhood of the aileron sections. Therefore only the aileron section pressures are shown as plots against x/c on Fig. 8.8 to 8.14.

Concerning the sectional lift and moment coefficients, which are listed in the same tables as the pressure distribution from which they were derived, it should be pointed out that they are uncorrected in the sense that no attempt has been made to introduce supplementary points where a pressure peak was obviously not properly defined by the array of pressure taps, see for instance Fig. 8.11, top left plot. Furthermore the integration interval extended only from the first to the last tap on a given section. The section coefficients should therefore be viewed only as a rough guide to the spanwise distribution.

Because of the uncorrected values, the spanwise distribution of load coefficients is likely to show some fluctuation. The wiggle near the wing tip, however, seems to be genuine; and is believed to have been caused by a geometric irregularity behind the aileron gap.

During the course of the test program certain steady test cases were repeated a number of times for nominally the same test parameters. Since repeatability is a good indicator of data quality, the pressures on the mid-aileron section have been plotted on top of each other for a number of nominally identical cases, see Fig. 8.15.

The right-hand plot corresponds to five runs, one of which (case 94) was made entirely without wing-tip cable braces, entailing a tunnel shut-down before the remaining cases were run. In spite of the shut-down, repeatability may be said to be very good. The left-hand plot shows pressures for a larger number of repetitions for the same case, with two intervening shut-downs. Agreement here is still good, but two runs show a marked deviation from the mean near the hinge position, which is known to be sensitive to changes in flow parameters. The two runs in question were separated by two shut-downs from the other runs of the series.

No comparable repetitions were made for unsteady pressures, but they are felt to be of the same quality as the steady ones.

1   GENERAL DESCRIPTION OF MODEL

    1.1   Designation   ZKP Wing

    1.2   Type   Half-model of wing-fuselage combination, transport aircraft with oscillating aileron, no tail surfaces

    1.3   Derivation   Research wing, representative of a medium-range transport aircraft with a supercritical wing

    1.4   Additional remarks

    1.5   References

2   MODEL GEOMETRY

2.1	Planform	high aspect ratio, tapered
2.2	Leading edge sweep	30.08 deg
2.4	Trailing edge sweep	20.89 deg for outer wing
2.5	Taper ratio	0.26
2.6	Twist	washout type, see Ref. 8.1, Table 4
2.7	Root chord	1.5055 m
2.8	Span of model	4.0161 m semi-span·
2.9	Area of planform	3.5989 sq. m
2.10	Location of reference section and definition of profiles	15%, 40%, and 85% semi-span (see Ref. 8.1, Sect. 2.4)
2.11	Lofting procedure between reference sections	linear on constant-chord lines between reference sections (see Ref. 8.1, Sect. 2.4)
2.12	Form of wing body, or wing-root junction	Gap between half-fuselage and floor sealed with brushes
2.13	Form of wing tip	rounded
2.14	Control surface details	unsealed aileron-wing gap abt. 0.3 to 0.5 mm wide (see Fig. 8.5)

3   WIND TUNNEL

3.1	Designation	ONERA S1 transonic tunnel, Modane, France
3.2	Type of tunnel	Closed-circuit, ambient press.
3.3	Test section dimensions	6.855 m high and wide 14.0 m long (see Fig. 8.1, 2)
3.4	Type of roof and floor	solid, except for 2 slots (see also Fig. 8.1,2)
3.5	Type of side walls	solid
3.6	Ventilation geometry	one slot each at intersection of floor with W/T shell, 0.13 m wide, running from 5 m to 9 m from test section entrance.
3.7	Thickness of side wall boundary layer	ca. 0.1 m
3.8	Thickness of boundary layers at roof and floor	ca. 0.1 m
3.9	Method of measuring Mach number	by measurement of static pressure, 4.5 m upstream of test section, and by previous calibration.
3.10	Flow angularity	not measured
3.11	Uniformity of Mach number over test section	not measured
3.12	Sources and levels of noise or turbulence in empty tunnel	considered very small
3.13	Tunnel resonances	at f = N/5, N/6, N/5 + N/6, N = 246 M
3.14	Additional remarks	-
3.15	References on tunnel	-

4   MODEL MOTION

4.1	General description	Aileron oscillation with braced wing tip
4.2	Reference coordinate and definition of motion	Flap angle measured relative to wing and in streamwise direction. Aileron harmonic rotation about swept axis at the 77.4% chord line, measured at inboard and center aileron section.

4.3	Range of amplitude	1 and 2 deg.
4.4	Range of frequency	6, 12, 21 Hz
4.5	Method of applying motion	aileron oscillation driven by electro-hydraulic servo system
4.6	Timewise purity of motion	not evaluated
4.7	Natural frequencies and normal modes of model and support system	15.6, 27.3, and 44.4 Hz with cable braces
4.8	Actual mode of applied motion including any elastic deformation	direct-drive servo near center of aileron
4.9	Additional remarks	-

5 TEST CONDITIONS

5.1	Model planform area/ Tunnel area	0.08
5.2	Model span/ Tunnel width	0.5858
5.3	Blockage	-
5.4	Position of model in tunnel	x-mac 6.19 m downstream of test section inlet (see Fig. 8.1)
5.5	Range of Mach number	0.5, 0.78, 0.83
5.6	Range of tunnel total pressure	0.9 bar
5.7	Range of tunnel total temperature	298 to 322 deg K
5.8	Range of model steady, or mean, incidence	-1 to +3 deg
5.9	Definition of model incidence	the model incidence α_m is defined to be zero when the fuselage reference line (FRL) is parallel to the tunnel walls. The FRL lies in the plane z = 0 of the profile coordinate system as listed in Ref. 8.1
5.10	Position of transition, if free	-
5.11	Position and type of trip, if transition fixed	x/c = 0.07, upper and lower wing surface, 5 mm wide band of 80K carborundum. Same type of trip on fuselage, 105 mm from nose
5.12	Flow instabilities during tests	none detected
5.13	Changes to mean shape model due to steady aerodynamic load	not measured
5.14	Additional remarks	-
5.15	References describing tests	-

6 MEASUREMENTS AND OBSERVATIONS

6.1	Steady pressures for the mean conditions	x
6.2	Steady pressures for small changes from the mean conditions	x
6.3	Quasi-steady pressures	6Hz
6.4	Unsteady pressures	X
6.5	Steady section forces for the mean conditions by integration of pressures	X
6.6	Steady section forces for small changes from the mean conditions by integration	-
6.7	Quasi-steady section forces by integration	6 Hz
6.8	Unsteady section forces by integration	X

6.9 Measurement of actual motion at points   x
     on model

6.10 Observation or measurement of boundary   not done
     layer properties

6.11 Visualization of surface flow   not done

6.12 Visualization of shockwave movements   not done

6.13 Additional remarks   -

7. INSTRUMENTATION

7.1   Steady pressures

   7.1.1 Position of orifices   see Fig. 8.6,
         spanwise and chordwise   and Table 8.3 to 8.7

   7.1.2 Type of measuring system   taps connected via tubing and scanivalve to tunnel
                                                    system transducers

7.2   Unsteady pressures

   7.2.1 Position of orifices   see Fig. 8.6,
         spanwise and chordwise   and Table 8.3 to 8.7

   7.2.2 Diameter of orifices   0.3 mm

   7.2.3 Type of measuring system   Transducer installed directly below each tap

   7.2.4 Type of transducers   Kulite

   7.2.5 Principle and accuracy   calibrated by 30 Hz sinusoidal signal
         of calibration   before tests. Checked at various intervals during
                                                    testing. Variation less than 1%.

7.3   Model motion

   7.3.1 Method of measuring motion   Aileron angle measured relative to wing structure
         reference co-ord   by rotatory potentiomers

   7.3.2 Method of determining spatial   By accelerometers on wing and aileron, and
         mode of motion   potentiometers on aileron

   7.3.3 Accuracy of measured motions   2%

7.4 Processing of unsteady measurements

   7.4.1 Method of acquiring   signal digitized (12 bit ADC) and Fourier transformed.
         and processing measurements   Transfer function for motion-pressure by HP 5451
                                                    Analyzer.

   7.4.2 Type of analysis   Only 1. harmonic kept

   7.4.3 Unsteady pressure quantities obtained   Presented data are amplitudes of fundamental of
         and accuracies achieved   all response signals. Response phases are defined
                                                    relative to zero aileron deflection

   7.4.4 Method of integration to obtain forces   Cubic spline, uncorrected for possible missed
                                                    peaks. Integration interval between first and
                                                    last pressure taps on section

7.5   Additional remarks   -

7.6   References on techniques   -

8. DATA PRESENTATION

8.1   Test cases for which data   See Table 8.1
      could be made available

8.2   Test cases for which data are included   See Table 8.2
      in this document

8.3 Steady pressures	Tables 8.3 to 8.7
8.4 Quasi-steady or steady perturbation pressures	6 Hz, unsteady pressures
8.5 Unsteady pressures	Tables 8.3 to 8.7
8.6 Steady forces or moments	Tables 8.3 to 8.7
8.7 Quasi-steady or steady perturbation forces	6 Hz, unsteady loads
8.8 Unsteady forces and moments	Tables 8.3 to 8.7
8.9 Other forms in which data could be made available	magnetic tape
8.10 References giving other presentations of data	See Ref. 8.2

9. COMMENTS ON DATA

9.1   Accuracy

9.1.1 Mach number	ca. 0.002
9.1.2 Steady incidence	ca. 0.1 deg
9.1.3 Reduced frequency	ca. 2% variation
9.1.4 Steady pressure coefficients	see discussion and Fig. 8.15
9.1.5 Steady pressure derivatives	not calculated
9.1.6 Unsteady pressure coefficients	see discussion
9.2 Sensitivity to small changes of parameter	not calculated
9.3 Non-linearities	none detected
9.4 Influence of tunnel total pressure	total pressure was kept constant
9.5 Effects on data of uncertainty, or variation, in mode of motion	not checked
9.6 Wall interference corrections	All pressures are uncorrected.
9.7 Other relevant tests on same model	None
9.8 Relevant tests on other models of nominally the same shape	None
9.9 Any remarks relevant to comparison between experiment and theory	-
9.10 Additional remarks	
9.11 References and discussion of data	See Ref. 8.2
10. PERSONAL CONTACT FOR FURTHER INFORMATION	Dipl.-Phys. H. Zimmermann, MBB-Bremen, Abt. TE234 Hünefeldstr. 1-5 2800 Bremen, West Germany

11. LIST OF REFERENCES

8.1 Bland, S.R.	AGARD three-dimensional aeroelastic configurations AGARD Advisory Report No. 167 March 1982

8.2 Couston, M.,
   Angélini, J.J.
   Meurzec, J.P.
	Comparaison des champs de pression
	instationnaires calcules et mesures sur le
	modele ZKP. AGARD Report No. 688, April 1980.
	(Also available as RAE Library Translation 2061,
	November 1980).

12 NOTATION

Standard AGARD Notation is set out in Ref. 8.1. The notation in this Data Set differs in the following respects because:

The reduced frequency K is based on the half chord at the wing-body junction (c = 1.5055 m) whereas the reduced frequency k of Ref. 8.1 is based on the half chord of the computational planform (c = 1.802). See Fig. 8.4.

The computer symbols in Tables 8.3-8.7 have the following meaning:

ALPHA = α_m , mean wing incidence, as defined in Para. 5.9

C = c, local chord

CL = c_l , sectional lift coefficient

CM = c_m , sectional moment coefficient about quarter-chord point

CPL = C_p , lower surface

CPU = C_p , upper surface

CPL/RAD = lower surface ⎫
CPU/RAD = upper surface ⎬ unsteady pressure coefficients/unit amplitude

DELM = δ_m , mean streamwise aileron angle

FREQ = f, frequency

K = reduced frequency based on half-chord at wing-body junction, AGARD k = 1.197 K

PTOT = p , total pressure

QINF = q, dynamic pressure

RE = Reynolds number, based on chord at wing-body junction, AGARD Re = 1.197 RE

S = s, semi-span

TO = T_o, total temperature of flow

X/C = non-dimensional chordwise position aft of local leading edge

Y/S = η , spanwise position relative to plane of symmetry.

Table 8.1 List of run numbers available for release

	< Run parameters >					< Run Indices >			
M	pt (bar)	To (°K)	α_m (°)	δ_m (°)	δ_0 (°)	Steady	6 Hz	12Hz	21Hz
0.50	0.9	297.7	3.0	-5.0	1.0	21	18	--	21
0.50	0.9	297.9	3.0	0.0	1.0	26	23	25 *	26
0.50	0.9	297.9	3.0	10.0	1.0	33	31	--	33
0.78	0.9	311.3	-1.0	-5.0	1.0	58	56	--	58
0.78	0.9	315.9	-1.0	0.0	1.0	75	61	64	75
0.78	0.9	317.4	-1.0	0.0	2.0	144	63	144	--
0.78	0.9	320.8	-1.0	5.0	1.0	80	78	--	80
0.78	0.9	322.6	0.0	-5.0	1.0	90	88	--	90 *
0.78	0.9	322.7	0.0	0.0	1.0	97	94	96	97 *
0.78	0.9	319.2	0.0	0.0	2.0	143	95	143	--
0.78	0.9	322.0	0.0	5.0	1.0	102	--	--	102
0.78	0.9	318.0	2.0	-5.0	1.0	109	107	--	109
0.78	0.9	319.2	2.0	0.0	1.0	116	112	115	116 *
0.78	0.9	316.5	2.0	0.0	2.0	145	114	145	--
0.78	0.9	319.4	2.0	5.0	1.0	119	119	--	121
0.83	0.9	321.6	0.0	-2.0	1.0	140	131	137	140 *
0.83	0.9	321.6	0.0	0.0	1.0	141	133	138	141
0.83	0.9	322.2	0.0	2.0	1.0	142	135	139	142

Note: The starred case numbers correspond
to the data in Tables 8.3 to 8.7

Table 8.2 Experimental cases for which data are included,
related to computational cases of Ref 8.1

Experimental Case					Computational Case				
Run Index	M	α_m (deg)	δ_m (deg)	f (Hz)	Case No	M	α_m (deg)	δ_m (deg)	f (Hz)
25	0.50	3	0	12	1	0.30	0	-4.60	10
97	0.78	0	0	21	4 *	0.78	0	0	20
90	0.78	0	-5	21	5 *	0.78	0	-5.52	20
116	0.78	2	0	21	6 *	0.78	2	0	20
140	0.83	0	-2	21	7	0.83	0	-5.52	20

* indicates priority case

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 1

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 25

M	0.500	PTOT	0.900 BAR	K	0.336	DELTM	0.0 DEG.
ALPHA	3.000 DEG.	QINF	0.133 BAR	FREQ	12.0 HZ		
RE	0.134D+08	TO	297.850 DEG. K	Y/S	0.254		

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -------------						----------- CPL/RAD ------------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	-2.067	0.100	0.008	-0.008	0.011	-45.00	0.0	0.392	0.050	0.023	-0.008	0.025	-19.98
0.020	-2.040	0.200	0.0	-0.001	0.001	-90.00	0.010	0.676	0.100	0.029	-0.007	0.030	-12.99
0.030	-1.657	0.300	-0.003	-0.004	0.005	-123.69	0.030	0.447	0.200	0.030	-0.013	0.033	-23.96
0.050	-1.324	0.350	0.005	-0.003	0.006	-33.69	0.050	0.298	0.300	0.027	-0.008	0.028	-17.10
0.100	-1.033	0.400	0.001	0.0	0.001	0.0	0.100	0.068	0.400	0.019	-0.006	0.020	-18.44
0.150	-0.867	0.450	0.002	-0.003	0.004	-63.44	0.200	-0.146	0.500	0.020	-0.008	0.021	-22.62
0.200	-0.769	0.500	0.004	0.0	0.004	0.0	0.300	-0.207	0.600	0.015	-0.010	0.018	-33.69
0.250	-0.725	0.600	0.007	-0.002	0.007	-14.04	0.400	-0.225	0.700	0.011	-0.009	0.014	-39.80
0.300	-0.659	0.650	0.004	-0.002	0.004	-26.57	0.500	-0.162	0.750	0.014	-0.010	0.017	-35.54
0.350	-0.604	0.700	0.007	-0.002	0.007	-14.04	0.600	-0.059	0.800	0.012	-0.009	0.015	-36.87
0.375	-0.578	0.720	0.009	-0.005	0.011	-30.96	0.700	0.056	0.850	0.009	-0.006	0.011	-30.96
0.400	-0.559	0.750	0.007	-0.002	0.007	-14.04	0.800	0.136	0.900	0.010	-0.005	0.012	-26.56
0.425	-0.523	0.800	0.003	-0.003	0.005	-45.00	0.850	0.156	0.950	0.011	-0.005	0.012	-26.56
0.450	-0.499	0.850	0.011	-0.004	0.011	-18.44	0.900	0.167					
0.475	-0.480	0.900	0.009	0.0	0.009	0.0	0.950	0.166					
0.500	-0.451	0.950	0.014	-0.002	0.014	-7.12							
0.525	-0.422	0.970	0.009	-0.002	0.009	-9.46							
0.550	-0.398												
0.575	-0.366												
0.600	-0.335												
0.625	-0.306												
0.650	-0.273												
0.675	-0.256												
0.700	-0.234												
0.750	-0.185												
0.800	-0.134												
0.850	-0.083												
0.900	-0.021												
0.950	0.053												
1.000	0.139												

	STEADY	UNSTEADY		
		REAL	IMAG	
CL	0.4742	0.0121	-0.0055	UNCORRECTED
CM	-0.0182	-0.0012	0.0014	

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 2

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 25

M	0.500	PTOT	0.900 BAR	K	0.336	DELTM	0.0 DEG.
ALPHA	3.000 DEG.	QINF	0.133 BAR	FREQ	12.0 HZ		
RE	0.134D+08	TO	297.850 DEG. K	Y/S	0.353		

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -------------						----------- CPL/RAD ------------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.968	0.050	-0.032	0.035	0.047	132.40	0.0	0.301	0.050	-0.046	-0.005	0.046	-174.09
0.050	-1.289	0.100	-0.011	0.022	0.025	116.57	0.050	0.276	0.100	-0.030	-0.009	0.031	-162.47
0.100	-0.987	0.200	-0.001	0.011	0.011	97.12	0.100	0.055	0.200	-0.013	-0.013	0.018	-135.00
0.140	-0.884	0.300	-0.014	0.011	0.018	143.13	0.140	-0.017	0.300	-0.005	-0.014	0.015	-108.44
0.200	-0.789	0.350	-0.009	0.017	0.019	118.30	0.200	-0.146	0.400	-0.006	-0.011	0.012	-119.05
0.250	-0.717	0.400	-0.004	0.006	0.007	123.69	0.250	-0.182	0.500	-0.004	-0.015	0.015	-104.04
0.300	-0.655	0.450	-0.002	0.002	0.002	135.00	0.300	-0.199	0.600	-0.007	-0.013	0.014	-119.74
0.325	-0.634	0.500	-0.016	-0.002	0.016	-171.87	0.350	-0.217	0.700	-0.004	-0.005	0.007	-123.69
0.350	-0.605	0.600	-0.014	-0.004	0.014	-164.05	0.400	-0.232	0.750	-0.002	-0.002	0.003	-135.00
0.375	-0.582	0.650	-0.016	-0.008	0.018	-153.43	0.450	-0.213	0.800	0.0	-0.002	0.002	-90.00
0.425	-0.550	0.700	-0.016	-0.010	0.019	-147.99	0.500	-0.158	0.850	-0.002	0.004	0.005	116.57
0.450	-0.530	0.720	-0.013	-0.009	0.016	-146.31	0.550	-0.097	0.900	-0.002	0.002	0.003	135.00
0.475	-0.513	0.750	-0.014	-0.006	0.016	-156.80	0.600	-0.009	0.950	-0.002	0.004	0.005	116.56
0.500	-0.508	0.800	-0.014	-0.008	0.016	-150.95	0.650	0.071					
0.550	-0.479	0.850	-0.015	-0.012	0.019	-142.12	0.700	0.155					
0.650	-0.401	0.900	-0.011	-0.013	0.018	-129.81	0.750	0.223					
0.700	-0.357	0.950	-0.014	-0.008	0.016	-150.26	0.800	0.256					
0.750	-0.280	0.970	-0.008	-0.006	0.010	-143.13	0.850	0.267					
0.800	-0.247						0.900	0.265					
0.850	-0.181						0.950	0.244					
0.900	-0.103												
0.950	-0.006												
1.000	0.109												

	STEADY	UNSTEADY		
		REAL	IMAG	
CL	0.5283	0.0032	-0.0093	UNCORRECTED
CM	-0.0679	-0.0030	0.0014	

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   4

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   25

M	0.500		PTOT	0.900 BAR		K	0.336		DELTM	0.0 DEG.
ALPHA	3.000 DEG.		QINF	0.133 BAR		FREQ	12.0 HZ			
RE	0.134D+08		TO	297.850 DEG. K		Y/S	0.479			

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -----------						----------- CPL/RAD -----------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.722	0.050	0.061	0.035	0.070	29.43	0.0	0.486	0.050	-0.037	-0.026	0.045	-144.46
0.050	-1.175	0.100	0.058	0.040	0.070	34.51	0.050	0.263	0.100	-0.016	-0.013	0.021	-141.34
0.100	-0.908	0.200	0.035	0.032	0.047	42.40	0.100	0.065	0.200	0.003	-0.007	0.008	-68.20
0.200	-0.773	0.300	0.026	0.021	0.034	39.09	0.200	-0.149	0.300	0.015	-0.006	0.017	-22.62
0.250	-0.676	0.350	0.027	0.030	0.040	48.65	0.250	-0.147	0.400	0.028	0.003	0.029	5.44
0.300	-0.613	0.400	0.021	0.019	0.028	40.92	0.300	-0.165	0.500	0.025	0.001	0.025	2.60
0.325	-0.594	0.450	0.008	0.029	0.030	74.05	0.350	-0.179	0.600	0.026	-0.015	0.031	-30.47
0.350	-0.573	0.500	0.020	0.024	0.031	50.91	0.400	-0.184	0.700	0.007	-0.017	0.018	-66.04
0.375	-0.560	0.600	0.025	0.011	0.027	23.20	0.450	-0.169	0.800	0.006	-0.011	0.013	-63.43
0.400	-0.543	0.650	0.007	0.010	0.013	56.31	0.500	-0.114	0.930	0.004	-0.014	0.015	-74.05
0.425	-0.533	0.690	0.005	0.012	0.013	69.44	0.550	-0.032	0.970	0.006	-0.009	0.011	-56.31
0.450	-0.531	0.700	0.0	0.004	0.004	90.00	0.600	0.044					
0.500	-0.508	0.730	0.002	0.023	0.023	85.24	0.650	0.139					
0.550	-0.493	0.750	0.005	0.004	0.007	33.69	0.700	0.213					
0.600	-0.471	0.930	-0.006	0.0	0.006	180.00	0.750	0.264					
0.650	-0.418	0.950	-0.005	-0.002	0.006	-161.57	0.800	0.292					
0.720	-0.405	0.970	-0.004	0.0	0.004	180.00	0.910	0.283					
0.800	-0.288						0.950	0.252					
0.910	-0.092												
0.950	-0.031												
0.970	0.010												
1.000	0.066												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------	UNCORRECTED
CL	0.5550	0.0087	-0.0235	
CM	-0.0876	-0.0025	0.0031	

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   6

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   25

M	0.500		PTOT	0.900 BAR		K	0.336		DELTM	0.0 DEG.
ALPHA	3.000 DEG.		QINF	0.133 BAR		FREQ	12.0 HZ			
RE	0.134D+08		TO	297.850 DEG. K		Y/S	0.566			

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -----------						----------- CPL/RAD -----------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.585	0.050	-0.017	-0.017	0.024	-135.00	0.0	0.521	0.050	0.012	-0.009	0.015	-35.54
0.050	-1.122	0.100	0.033	0.025	0.041	36.87	0.050	0.243	0.100	0.018	0.0	0.018	0.0
0.100	-0.880	0.200	0.027	0.010	0.029	20.22	0.100	0.067	0.200	0.036	0.005	0.036	7.43
0.150	-0.764	0.300	0.028	0.010	0.030	19.44	0.200	-0.108	0.300	0.049	0.0	0.049	0.0
0.200	-0.719	0.350	0.031	0.017	0.035	29.36	0.250	-0.139	0.400	0.043	-0.001	0.043	-1.79
0.250	-0.648	0.400	0.024	0.016	0.029	33.69	0.300	-0.155	0.500	0.041	-0.002	0.041	-2.20
0.300	-0.596	0.450	0.028	0.015	0.032	28.81	0.350	-0.163	0.600	0.006	0.0	0.006	0.0
0.325	-0.573	0.500	0.025	0.014	0.029	29.36	0.400	-0.170	0.700	0.010	-0.006	0.012	-33.69
0.350	-0.555	0.600	-0.004	0.004	0.006	135.00	0.450	-0.150	0.800	-0.005	0.007	0.009	126.87
0.375	-0.546	0.630	0.014	-0.006	0.015	-23.20	0.500	-0.114	0.870	0.0	0.0	0.0	0.0
0.400	-0.532	0.690	-0.005	0.013	0.014	113.20	0.550	-0.027	0.910	0.002	0.004	0.005	63.44
0.425	-0.522	0.700	-0.004	0.012	0.013	108.44	0.600	0.046	0.950	0.010	-0.002	0.010	-11.31
0.450	-0.513	0.730	-0.006	0.006	0.008	135.00	0.650	0.131					
0.475	-0.502	0.750	-0.002	0.017	0.017	97.13	0.700	0.200					
0.500	-0.499	0.910	0.0	0.003	0.003	90.00	0.750	0.259					
0.550	-0.458	0.950	0.0	-0.002	0.002	-90.00	0.800	0.284					
0.600	-0.440	0.970	-0.003	0.0	0.003	180.00	0.850	0.297					
0.650	-0.402												
0.740	-0.350												
0.780	-0.298												
0.820	-0.241												
0.910	-0.104			STEADY	UNSTEADY								
0.950	-0.028				REAL	IMAG							
0.970	0.007			-------	-------	-------	UNCORRECTED						
1.000	0.051	CL	0.5087	0.0069	-0.0106								
		CM	-0.0665	-0.0015	0.0021								

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   8

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX :   25

```
M       0.500              PTOT    0.900 BAR          K      0.336          DELTM   0.0 DEG.
ALPHA   3.000 DEG.         QINF    0.133 BAR          FREQ   12.0 HZ
RE   0.134D+08             TO      297.850 DEG. K     Y/S    0.618
```

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			------------ CPU/RAD ------------						------------ CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.553	0.050	0.023	0.047	0.052	64.13	0.0	0.531	0.050	0.029	0.016	0.033	28.81
0.050	-1.099	0.100	0.015	0.064	0.066	76.33	0.050	0.236	0.100	0.028	0.008	0.029	16.70
0.100	-0.864	0.200	0.023	0.036	0.043	57.26	0.100	0.064	0.200	0.053	-0.004	0.053	-4.18
0.150	-0.759	0.300	0.032	0.035	0.047	47.39	0.150	-0.033	0.300	0.063	-0.003	0.063	-2.86
0.200	-0.706	0.350	0.029	0.027	0.040	42.40	0.200	-0.103	0.400	0.063	-0.008	0.064	-6.95
0.250	-0.636	0.400	0.036	0.026	0.045	35.36	0.250	-0.136	0.500	0.055	-0.009	0.056	-9.25
0.300	-0.581	0.450	0.034	0.029	0.044	40.10	0.300	-0.148	0.600	0.062	-0.034	0.070	-28.74
0.325	-0.566	0.500	0.038	0.022	0.044	29.98	0.350	-0.158	0.700	0.022	-0.011	0.025	-26.57
0.350	-0.548	0.600	-0.015	0.016	0.022	131.99	0.400	-0.158	0.800	0.013	-0.010	0.017	-36.87
0.375	-0.532	0.650	-0.015	0.015	0.021	135.00	0.450	-0.148	0.970	0.006	-0.003	0.007	-26.56
0.400	-0.530	0.690	-0.002	0.005	0.005	108.43	0.500	-0.114					
0.425	-0.517	0.730	0.015	-0.003	0.015	-12.53	0.550	-0.040					
0.450	-0.508	0.750	-0.005	0.011	0.012	116.57	0.600	0.047					
0.475	-0.501	0.800	-0.002	0.002	0.002	135.00	0.650	0.128					
0.500	-0.499	0.970	0.0	0.002	0.002	90.00	0.700	0.176					
0.550	-0.469						0.750	0.257					
0.600	-0.440						0.800	0.286					
0.650	-0.414												
0.720	-0.369												
0.760	-0.321												
0.800	-0.268												
0.830	-0.222			STEADY	UNSTEADY								
0.950	-0.009				REAL	IMAG							
0.970	0.094			-------	-------	-------		UNCORRECTED					
1.000	0.053		CL	0.4886	0.0244	-0.0280							
			CM	-0.0570	-0.0058	0.0040							

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   9

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX :   25

```
M       0.500              PTOT    0.900 BAR          K      0.336          DELTM   0.0 DEG.
ALPHA   3.000 DEG.         QINF    0.133 BAR          FREQ   12.0 HZ
RE   0.134D+08             TO      297.850 DEG. K     Y/S    0.665
```

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			------------ CPU/RAD ------------						------------ CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.501	0.050	0.100	-0.058	0.116	-29.95	0.0	0.524	0.050	0.086	-0.078	0.116	-42.27
0.050	-1.093	0.100	-0.048	0.091	0.103	117.82	0.050	0.207	0.100	0.028	-0.035	0.045	-51.84
0.100	-0.841	0.200	0.017	0.040	0.043	67.07	0.100	0.067	0.200	0.092	-0.033	0.097	-19.54
0.150	-0.752	0.300	0.025	0.022	0.034	41.42	0.150	-0.039	0.300	0.075	-0.032	0.082	-22.99
0.200	-0.683	0.350	0.026	0.021	0.033	39.09	0.200	-0.108	0.400	0.083	-0.009	0.083	-6.07
0.250	-0.622	0.400	0.027	0.024	0.036	41.42	0.250	-0.139	0.500	0.082	-0.018	0.084	-12.09
0.300	-0.516	0.450	-0.030	0.007	0.031	166.61	0.300	-0.152	0.600	0.024	-0.003	0.024	-8.13
0.325	-0.555	0.500	0.036	0.012	0.038	18.43	0.350	-0.158	0.700	0.006	-0.013	0.015	-66.04
0.350	-0.540	0.600	0.024	-0.004	0.024	-10.31	0.400	-0.163	0.800	0.019	-0.002	0.019	-6.34
0.375	-0.525	0.680	0.021	-0.003	0.022	-7.59	0.450	-0.153	0.870	0.020	0.002	0.020	5.19
0.400	-0.515	0.700	0.025	-0.005	0.025	-12.09	0.500	-0.119	0.950	0.017	0.002	0.017	7.13
0.425	-0.506	0.730	-0.007	-0.014	0.016	-116.57	0.600	0.050					
0.450	-0.502	0.810	-0.007	-0.003	0.008	-153.44	0.650	0.123					
0.475	-0.495	0.870	0.0	-0.002	0.002	-90.00	0.700	0.199					
0.500	-0.488	0.910	0.004	-0.018	0.019	-77.47	0.750	0.251					
0.600	-0.401	0.930	0.002	-0.011	0.011	-80.54	0.850	0.292					
0.630	-0.430	0.950	-0.008	0.006	0.010	141.34	0.910	0.282					
0.680	-0.379						0.950	0.255					
0.720	-0.352												
0.760	-0.308												
0.800	-0.255												
0.830	-0.208			STEADY	UNSTEADY								
0.910	-0.130				REAL	IMAG							
0.930	-0.037			-------	-------	-------		UNCORRECTED					
0.970	0.004		CL	0.5160	0.0360	-0.0289							
1.000	0.046		CM	-0.0833	-0.0039	-0.0012							

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 11

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   25

```
M      0.500                PTOT    0.900 BAR          K     0.336           DELTM   0.0 DEG.
ALPHA  3.000 DEG.           QINF    0.133 BAR          FREQ  12.0 HZ
RE     0.134D+08            TO    297.850 DEG. K       Y/S   0.751
```

------------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | | ----------- CPU/RAD ----------- | | | | | ----------- CPL/RAD ----------- |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.100	-0.807	0.050	-0.144	0.146	0.205	134.63	0.0	0.208	0.050	0.106	-0.070	0.127	-33.31
0.200	-0.655	0.100	-0.049	0.103	0.114	115.16	0.050	0.166	0.100	0.104	-0.046	0.113	-23.96
0.250	-0.603	0.200	-0.006	0.057	0.058	96.17	0.100	0.032	0.200	0.126	-0.021	0.127	-9.69
0.300	-0.559	0.300	0.007	0.045	0.046	81.38	0.200	-0.118	0.300	0.125	-0.024	0.128	-10.89
0.325	-0.539	0.350	0.014	0.037	0.039	68.55	0.250	-0.151	0.400	0.137	0.0	0.137	0.0
0.350	-0.526	0.400	0.004	0.027	0.027	80.54	0.300	-0.163	0.500	0.135	-0.012	0.136	-5.04
0.375	-0.515	0.450	0.009	0.026	0.027	70.56	0.350	-0.164	0.600	0.057	-0.017	0.060	-16.86
0.400	-0.503	0.500	0.012	0.025	0.027	63.43	0.400	-0.153	0.700	0.136	-0.010	0.136	-4.01
0.425	-0.500	0.600	-0.012	0.006	0.013	153.43	0.450	-0.151	0.800	0.145	-0.028	0.148	-10.95
0.450	-0.492	0.630	-0.006	0.017	0.018	110.56	0.500	-0.121	0.910	0.096	-0.008	0.097	-4.86
0.475	-0.488	0.680	0.002	0.002	0.002	45.00	0.550	-0.041	0.950	0.085	-0.011	0.086	-7.70
0.500	-0.497	0.700	0.005	-0.005	0.007	-45.00	0.600	0.035					
0.550	-0.442	0.730	0.017	-0.004	0.018	-12.53	0.700	0.195					
0.600	-0.439	0.750	0.017	-0.011	0.021	-33.69	0.750	0.251					
0.634	-0.414	0.800	0.022	-0.013	0.026	-30.26	0.910	0.278					
0.680	-0.384	0.910	0.028	-0.010	0.029	-19.65	0.950	0.253					
0.720	-0.349	0.930	0.031	-0.009	0.032	-15.95							
0.800	-0.250	0.950	0.030	-0.011	0.032	-21.04							
0.830	-0.216	0.970	0.034	-0.011	0.036	-18.43							
0.910	-0.080												
0.950	-0.032												
0.970	0.007												
1.000	0.072												
```
                                        STEADY      UNSTEADY
                                    |           |  REAL  |  IMAG  |
                                    | ------- | ------- | ------- |    UNCORRECTED
                                CL  |  0.4112 |  0.1064 | -0.0417 |
                                CM  | -0.1003 | -0.0225 |  0.0009 |
```


TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 13

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   25

```
M      0.500                PTOT    0.900 BAR          K     0.336           DELTM   0.0 DEG.
ALPHA  3.000 DEG.           QINF    0.133 BAR          FREQ  12.0 HZ
RE     0.134D+08            TO    297.850 DEG. K       Y/S   0.854
```

------------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | | ----------- CPU/RAD ----------- | | | | | ----------- CPL/RAD ----------- |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	-0.922	0.050	-0.288	0.296	0.412	134.22	0.0	0.383	0.050	0.318	-0.112	0.337	-19.33
0.020	-1.193	0.100	-0.203	0.185	0.275	137.76	0.010	0.564	0.100	0.302	-0.083	0.313	-15.45
0.030	-1.117	0.200	-0.137	0.118	0.180	139.14	0.030	0.198	0.200	0.326	-0.043	0.329	-7.52
0.050	-0.999	0.300	-0.144	0.084	0.167	149.78	0.050	0.073	0.300	0.385	-0.024	0.386	-3.52
0.100	-0.754	0.350	-0.171	0.074	0.186	156.74	0.200	-0.135	0.400	0.448	-0.008	0.448	-1.01
0.150	-0.650	0.400	-0.190	0.065	0.200	161.13	0.300	-0.170	0.500	0.511	0.021	0.511	2.32
0.200	-0.604	0.450	-0.248	0.061	0.255	166.15	0.400	-0.160	0.600	0.605	0.024	0.606	2.25
0.250	-0.553	0.500	-0.284	0.056	0.289	168.77	0.500	-0.107	0.800	1.204	0.163	1.215	7.72
0.300	-0.519	0.650	-0.718	-0.023	0.718	-178.17	0.600	-0.039					
0.350	-0.484	0.700	-0.965	-0.030	0.966	-178.20	0.700	0.159					
0.375	-0.484	0.720	-1.247	-0.040	1.247	-178.18	0.800	0.285					
0.400	-0.478	0.820	-1.246	-0.126	1.252	-174.23	0.850	0.296					
0.425	-0.472	0.910	-0.246	-0.112	0.270	-155.48	0.900	0.285					
0.450	-0.459	0.950	0.038	-0.042	0.057	-47.86	0.950	0.254					
0.475	-0.450												
0.500	-0.447												
0.575	-0.409												
0.600	-0.379												
0.650	-0.346												
0.675	-0.314												
0.700	-0.310												
0.750	-0.264				STEADY	UNSTEADY							
0.800	-0.266					REAL	IMAG						
0.850	-0.198												
0.900	-0.125												
0.950	-0.033												
1.000	0.076												
```
                                        STEADY      UNSTEADY
                                    |           |  REAL  |  IMAG  |
                                    | ------- | ------- | ------- |    UNCORRECTED
                                CL  |  0.4504 |  0.9827 |  0.0003 |
                                CM  | -0.0758 | -0.3683 | -0.0395 |
```

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 14

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   25

M	0.500	PTOT	0.900 BAR	K	0.336	DELTM 0.0 DEG.
ALPHA	3.000 DEG.	QINF	0.133 BAR	FREQ	12.0 HZ	
RE	0.134D+08	TO	297.850 DEG. K	Y/S	0.885	

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
		----------- CPU/RAD ------------						----------- CPL/RAD ------------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE

UPPER SURFACE:

STEADY DATA		UNSTEADY DATA — CPU/RAD			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE
---	---	---	---	---	---	---
0.010	-0.840	0.050	-0.442	0.140	0.463	162.45
0.020	-1.010	0.100	-0.277	0.093	0.292	161.48
0.030	-1.011	0.140	-0.287	0.093	0.302	162.07
0.050	-0.935	0.200	-0.218	0.068	0.228	162.73
0.100	-0.730	0.250	-0.238	0.055	0.244	166.89
0.200	-0.577	0.300	-0.246	0.054	0.252	167.61
0.250	-0.511	0.350	-0.277	0.054	0.282	168.88
0.300	-0.482	0.400	-0.337	0.034	0.338	174.32
0.350	-0.469	0.450	-0.383	0.046	0.386	173.22
0.375	-0.451	0.500	-0.454	0.020	0.454	177.50
0.400	-0.449	0.550	-0.728	-0.031	0.729	-177.53
0.425	-0.442	0.600	-0.863	-0.045	0.864	-177.02
0.450	-0.436	0.700	-1.881	-0.127	1.886	-176.14
0.475	-0.425	0.800	-1.909	-0.179	1.918	-174.64
0.500	-0.404	0.900	-0.002	-0.142	0.142	-90.80
0.525	-0.392					
0.550	-0.385					
0.575	-0.370					
0.600	-0.340					
0.625	-0.313					
0.675	-0.304					
0.700	-0.309					
0.750	-0.265					
0.850	-0.183					
0.900	-0.105					
0.950	-0.019					
1.000	0.079					

LOWER SURFACE:

STEADY DATA		UNSTEADY DATA — CPL/RAD			
X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
---	---	---	---	---	---	---
0.0	0.497	0.050	0.444	-0.048	0.447	-6.12
0.010	-0.017	0.100	0.389	-0.027	0.390	-3.92
0.030	0.142	0.200	0.453	-0.022	0.453	-2.74
0.050	0.026	0.300	0.534	-0.013	0.535	-1.39
0.300	-0.184	0.400	0.613	0.0	0.613	0.0
0.400	-0.171	0.500	0.711	0.029	0.712	2.30
0.500	-0.142	0.700	1.096	0.060	1.098	3.14
0.600	-0.039	0.850	1.204	0.232	1.226	10.90
0.700	0.155					
0.800	0.266					
0.850	0.285					
0.900	0.276					
0.950	0.252					

	STEADY	UNSTEADY	
		REAL	IMAG
CL	0.3834	1.3027	0.0511	UNCORRECTED
CM	-0.0728	-0.4532	-0.0456	

TABLE 8. 3 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 15

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   25

M	0.500	PTOT	0.900 BAR	K	0.336	DELTM 0.0 DEG.
ALPHA	3.000 DEG.	QINF	0.133 BAR	FREQ	12.0 HZ	
RE	0.134D+08	TO	297.850 DEG. K	Y/S	0.944	

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

UPPER SURFACE:

STEADY DATA		UNSTEADY DATA — CPU/RAD			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE
---	---	---	---	---	---	---
0.010	-0.329	0.050	-0.729	0.273	0.778	159.49
0.020	-0.879	0.100	-0.549	0.198	0.584	160.17
0.030	-0.910	0.140	-0.425	0.141	0.448	161.71
0.050	-0.832	0.200	-0.348	0.122	0.368	160.59
0.100	-0.713	0.250	-0.392	0.125	0.411	162.27
0.150	-0.593	0.300	-0.367	0.087	0.377	166.62
0.200	-0.522	0.350	-0.398	0.087	0.407	167.74
0.250	-0.463	0.400	-0.456	0.087	0.464	169.18
0.300	-0.435	0.450	-0.535	0.091	0.542	170.37
0.350	-0.428	0.500	-0.609	0.061	0.612	174.27
0.375	-0.423	0.550	-0.492	0.071	0.498	171.83
0.400	-0.405	0.600	-0.591	0.063	0.594	173.91
0.425	-0.401	0.650	-0.806	0.065	0.809	175.39
0.450	-0.391	0.700	-0.927	0.037	0.928	177.73
0.475	-0.390	0.850	-1.100	-0.102	1.104	-174.68
0.500	-0.384	0.900	-0.513	-0.092	0.521	-169.78
0.525	-0.362					
0.575	-0.348					
0.600	-0.325					
0.650	-0.292					
0.675	-0.277					
0.700	-0.265					
0.750	-0.264					
0.800	-0.253					
0.850	-0.164					
0.900	-0.100					
0.950	-0.021					
1.000	0.079					

LOWER SURFACE:

STEADY DATA		UNSTEADY DATA — CPL/RAD			
X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
---	---	---	---	---	---	---
0.0	0.593	0.050	0.754	-0.114	0.762	-8.58
0.030	0.018	0.100	0.589	-0.042	0.591	-4.10
0.100	-0.052	0.200	0.645	0.002	0.645	0.15
0.200	-0.175	0.400	0.770	0.045	0.772	3.34
0.300	-0.197	0.500	0.867	0.082	0.871	5.43
0.400	-0.168	0.600	0.574	-0.084	0.580	-8.29
0.500	-0.148	0.700	1.147	0.097	1.151	4.83
0.600	-0.047	0.800	1.633	0.222	1.649	7.75
0.700	0.102	0.850	0.751	0.150	0.766	11.29
0.800	0.256					
0.850	0.265					
0.900	0.253					
0.950	0.216					

	STEADY	UNSTEADY	
		REAL	IMAG
CL	0.3561	1.2125	-0.0210	UNCORRECTED
CM	-0.0649	-0.3389	-0.0217	

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 1

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M	0.780	PTOT	0.900 BAR	K	0.375	DELTM	0.0 DEG.
ALPHA	0.0 DEG.	QINF	0.255 BAR	FREQ	21.0 HZ		
RE	0.163D+08	TO	322.650 DEG. K	Y/S	0.254		

-------------------< UPPER SURFACE >-------------------   -------------------< LOWER SURFACE >-------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
				---- CPU/RAD ----						---- CPL/RAD ----	
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	-0.509	0.100	-0.002	-0.039	0.039	-93.50	0.0	0.762	0.050	0.0	0.015	0.015	90.00
0.020	-0.892	0.200	0.006	-0.049	0.049	-83.16	0.010	0.480	0.100	0.0	0.006	0.006	90.00
0.030	-0.930	0.300	-0.042	0.038	0.056	137.86	0.030	0.179	0.200	-0.009	-0.003	0.009	-158.20
0.050	-0.838	0.350	-0.074	-0.062	0.096	-139.82	0.050	0.018	0.300	-0.017	-0.017	0.024	-135.00
0.100	-0.803	0.400	-0.022	-0.064	0.068	-109.26	0.100	-0.215	0.400	-0.005	-0.023	0.023	-103.39
0.150	-0.740	0.450	-0.004	-0.067	0.067	-93.72	0.200	-0.458	0.500	-0.003	-0.019	0.019	-97.77
0.200	-0.712	0.500	0.0	-0.043	0.043	-90.00	0.300	-0.526	0.600	0.002	-0.018	0.018	-84.56
0.250	-0.754	0.600	0.017	-0.023	0.028	-53.84	0.400	-0.526	0.700	0.004	-0.016	0.017	-76.76
0.300	-0.683	0.650	0.012	-0.014	0.019	-49.08	0.500	-0.370	0.750	0.006	-0.009	0.011	-56.31
0.350	-0.606	0.700	0.013	-0.014	0.019	-46.98	0.600	-0.173	0.800	-0.002	-0.011	0.011	-98.13
0.375	-0.606	0.720	0.014	-0.010	0.017	-33.69	0.700	0.006	0.850	0.010	-0.009	0.013	-41.99
0.400	-0.599	0.750	0.016	-0.011	0.019	-35.22	0.800	0.125	0.900	0.006	-0.005	0.008	-40.60
0.425	-0.549	0.800	0.020	-0.007	0.021	-19.18	0.850	0.155	0.950	0.005	-0.006	0.007	-50.19
0.450	-0.530	0.850	0.014	-0.011	0.018	-38.66	0.900	0.177					
0.475	-0.507	0.900	0.015	-0.009	0.017	-32.01	0.950	0.188					
0.500	-0.478	0.950	0.015	-0.006	0.016	-20.56							
0.525	-0.446	0.970	0.010	-0.012	0.016	-49.09							
0.550	-0.413												
0.575	-0.373												
0.600	-0.345												
0.625	-0.318												
0.650	-0.283												
0.675	-0.264												
0.700	-0.239												
0.750	-0.186												
0.800	-0.130												
0.850	-0.076												
0.900	-0.006												
0.950	0.079												
1.000	0.179												

```
                              STEADY      UNSTEADY
                          |        |  REAL   |  IMAG   |
                          | ------ | ------- | ------- |   UNCORRECTED
                       CL | 0.2454 | -0.0013 | 0.0109  |
                       CM | -0.0204 | 0.0018 | -0.0008 |
```

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 2

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M	0.780	PTOT	0.900 BAR	K	0.375	DELTM	0.0 DEG.
ALPHA	0.0 DEG.	QINF	0.255 BAR	FREQ	21.0 HZ		
RE	0.163D+08	TO	322.650 DEG. K	Y/S	0.353		

-------------------< UPPER SURFACE >-------------------   -------------------< LOWER SURFACE >-------------------

STEADY D. TA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
				---- CPU/RAD ----						---- CPL/RAD ----	
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.943	0.050	0.017	0.019	0.025	48.81	0.0	0.713	0.050	0.053	-0.003	0.053	-3.58
0.050	-0.842	0.100	0.010	0.051	0.052	79.25	0.050	-0.087	0.100	0.053	-0.015	0.055	-15.48
0.100	-0.741	0.200	0.068	0.059	0.090	40.70	0.100	-0.308	0.200	0.050	-0.029	0.058	-30.50
0.140	-0.775	0.300	0.056	0.328	0.333	80.38	0.140	-0.357	0.300	0.057	-0.029	0.064	-26.89
0.200	-0.716	0.350	-0.178	0.017	0.179	174.46	0.200	-0.549	0.400	0.069	-0.017	0.071	-13.67
0.250	-0.690	0.400	-0.052	0.055	0.076	133.39	0.250	-0.591	0.500	0.013	0.013	0.019	45.00
0.300	-0.657	0.450	0.077	0.040	0.087	27.81	0.300	-0.613	0.600	0.020	0.009	0.022	25.46
0.325	-0.625	0.500	0.029	0.011	0.031	19.80	0.350	-0.609	0.700	0.018	-0.001	0.018	-3.01
0.350	-0.609	0.600	0.016	-0.004	0.017	-14.04	0.400	-0.629	0.750	0.028	0.011	0.030	22.17
0.375	-0.599	0.650	0.019	0.0	0.019	0.0	0.450	-0.531	0.800	0.024	0.008	0.026	18.43
0.425	-0.551	0.700	0.022	0.002	0.022	5.44	0.500	-0.378	0.850	0.020	0.001	0.020	3.37
0.450	-0.519	0.720	0.023	0.008	0.024	19.29	0.550	-0.247	0.900	0.025	0.001	0.025	2.12
0.475	-0.501	0.750	0.017	0.005	0.018	17.35	0.600	-0.108	0.950	0.0	0.015	0.015	90.00
0.500	-0.527	0.800	0.020	0.007	0.021	18.43	0.650	0.009					
0.550	-0.522	0.850	0.020	0.011	0.023	27.55	0.700	0.115					
0.650	-0.438	0.900	0.023	0.011	0.026	24.23	0.750	0.199					
0.700	-0.389	0.950	0.015	0.008	0.017	28.07	0.800	0.251					
0.750	-0.300	0.970	0.025	0.004	0.025	9.46	0.850	0.277					
0.800	-0.254						0.900	0.286					
0.850	-0.185						0.950	0.271					
0.900	-0.089												
0.950	0.024												
1.000	0.145												

```
                              STEADY      UNSTEADY
                          |        |  REAL   |  IMAG   |
                          | ------ | ------- | ------- |   UNCORRECTED
                       CL | 0.2918 | 0.0160  | -0.0502 |
                       CM | -0.0689 | -0.0009 | 0.0006  |
```

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 4

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M	0.780	PTOT	0.900 BAR	K	0.375	DELTM	0.0 DEG.
ALPHA	0.0 DEG.	QINF	0.255 BAR	FREQ	21.0 HZ		
RE	0.163D+08	TO	322.650 DEG. K	Y/S	0.479		

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

| STEADY DATA | | UNSTEADY DATA | | | | STEADY DATA | | UNSTEADY DATA | | | |
| | | ------------ CPU/RAD ------------ | | | | | | ------------ CPL/RAD ------------ | | | |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.586	0.050	0.037	-0.005	0.037	-7.59	0.0	0.788	0.050	0.005	0.010	0.012	61.93
0.050	-0.640	0.100	0.052	-0.015	0.054	-16.22	0.050	-0.192	0.100	0.011	0.012	0.016	47.12
0.100	-0.595	0.200	-0.060	0.037	0.070	147.93	0.100	-0.382	0.200	0.012	0.007	0.014	32.00
0.200	-0.697	0.300	0.073	-0.080	0.108	-47.57	0.200	-0.585	0.300	0.020	-0.017	0.026	-39.81
0.250	-0.602	0.350	0.048	-0.026	0.054	-28.66	0.250	-0.624	0.400	0.044	-0.013	0.046	-16.19
0.300	-0.556	0.400	0.039	0.003	0.040	4.32	0.300	-0.587	0.500	0.027	-0.011	0.029	-22.89
0.325	-0.540	0.450	0.006	0.024	0.024	76.37	0.350	-0.557	0.600	0.021	-0.024	0.032	-49.09
0.350	-0.522	0.500	0.039	-0.002	0.039	-3.50	0.400	-0.513	0.700	0.008	-0.020	0.022	-69.15
0.375	-0.523	0.600	0.003	0.012	0.012	77.01	0.450	-0.422	0.800	0.009	-0.010	0.013	-48.01
0.400	-0.520	0.650	-0.003	0.0	0.003	180.00	0.500	-0.291	0.930	-0.008	-0.001	0.008	-172.87
0.425	-0.520	0.690	-0.016	-0.030	0.034	-117.76	0.550	-0.146	0.970	0.0	0.001	0.001	90.00
0.450	-0.532	0.700	-0.011	-0.024	0.026	-115.56	0.600	-0.021					
0.500	-0.527	0.730	-0.006	0.003	0.007	153.44	0.650	0.087					
0.550	-0.546	0.750	-0.004	-0.017	0.018	-102.53	0.700	0.165					
0.600	-0.512	0.930	0.004	-0.012	0.012	-71.57	0.750	0.222					
0.650	-0.451	0.950	0.007	-0.013	0.015	-63.43	0.800	0.266					
0.720	-0.449	0.970	0.015	-0.009	0.018	-29.74	0.910	0.294					
0.800	-0.290						0.950	0.269					
0.910	-0.065												
0.950	0.002												
0.970	0.041												
1.000	0.089												

| | STEADY | UNSTEADY | | |
		REAL	IMAG	
CL	0.2852	0.0019	0.0018	UNCORRECTED
CM	-0.0929	-0.0008	-0.0003	

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 6

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M	0.780	PTOT	0.900 BAR	K	0.375	DELTM	0.0 DEG.
ALPHA	0.0 DEG.	QINF	0.255 BAR	FREQ	21.0 HZ		
RE	0.163D+08	TO	322.650 DEG. K	Y/S	0.566		

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

| STEADY DATA | | UNSTEADY DATA | | | | STEADY DATA | | UNSTEADY DATA | | | |
| | | ------------ CPU/RAD ------------ | | | | | | ------------ CPL/RAD ------------ | | | |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.457	0.050	0.073	-0.049	0.088	-33.96	0.0	0.793	0.050	0.074	0.028	0.079	20.48
0.050	-0.552	0.100	0.055	-0.055	0.078	-45.00	0.050	-0.243	0.100	0.039	0.007	0.039	10.31
0.100	-0.551	0.200	0.148	-0.084	0.170	-29.56	0.100	-0.399	0.200	0.050	0.007	0.051	8.39
0.150	-0.566	0.300	0.073	-0.009	0.073	-6.79	0.200	-0.616	0.300	0.017	-0.021	0.027	-50.19
0.200	-0.601	0.350	0.052	-0.003	0.053	-3.30	0.250	-0.580	0.400	0.054	-0.018	0.057	-18.21
0.250	-0.549	0.400	0.045	0.0	0.045	0.0	0.300	-0.554	0.500	0.033	-0.022	0.040	-33.37
0.300	-0.520	0.450	0.034	-0.013	0.036	-21.37	0.350	-0.511	0.600	0.007	0.007	0.010	45.00
0.325	-0.512	0.500	0.054	-0.010	0.054	-10.30	0.400	-0.469	0.700	-0.011	-0.013	0.017	-129.09
0.350	-0.513	0.600	0.009	0.037	0.038	76.37	0.450	-0.386	0.800	0.004	-0.003	0.005	-36.87
0.375	-0.507	0.630	0.007	-0.007	0.010	-45.00	0.500	-0.276	0.870	0.004	0.001	0.004	14.04
0.400	-0.507	0.690	-0.002	0.039	0.039	92.79	0.550	-0.140	0.910	0.001	-0.001	0.002	-45.00
0.425	-0.508	0.700	-0.007	0.038	0.039	101.00	0.600	-0.021	0.950	-0.001	-0.002	0.002	-116.57
0.450	-0.515	0.730	-0.006	0.032	0.032	100.30	0.650	0.081					
0.475	-0.510	0.750	-0.016	0.038	0.041	112.38	0.700	0.154					
0.500	-0.514	0.910	-0.010	0.020	0.023	116.57	0.750	0.208					
0.550	-0.497	0.950	-0.006	0.013	0.014	115.02	0.800	0.248					
0.600	-0.472	0.970	0.0	0.012	0.012	90.00	0.850	0.275					
0.650	-0.434												
0.740	-0.374												
0.780	-0.306												
0.820	-0.235												
0.910	-0.068												
0.950	0.007				STEADY	UNSTEADY							
0.970	0.042												
1.000	0.080												

| | STEADY | UNSTEADY | | |
		REAL	IMAG	
CL	0.2226	-0.0146	-0.0019	UNCORRECTED
CM	-0.0716	-0.0020	0.0088	

8-16

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 8

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M 0.780	PTOT 0.900 BAR	K 0.375	DELTM 0.0 DEG.
ALPHA 0.0 DEG.	QINF 0.255 BAR	FREQ 21.0 HZ	
RE 0.163D+08	TO 322.650 DEG. K	Y/S 0.618	

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA / UNSTEADY DATA (CPU/RAD) — STEADY DATA / UNSTEADY DATA (CPL/RAD)

X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.412	0.050	0.071	-0.066	0.097	-42.54	0.0	0.794	0.050	0.037	0.019	0.042	26.56
0.050	-0.507	0.100	0.092	-0.030	0.096	-17.93	0.050	-0.295	0.100	0.043	0.014	0.045	18.14
0.100	-0.507	0.200	0.087	-0.027	0.091	-17.23	0.100	-0.415	0.200	0.073	0.002	0.073	1.59
0.150	-0.532	0.300	0.092	0.015	0.093	9.02	0.150	-0.487	0.300	0.073	-0.012	0.074	-9.57
0.200	-0.569	0.350	0.078	0.023	0.082	16.65	0.200	-0.572	0.400	0.069	-0.012	0.070	-10.01
0.250	-0.534	0.400	0.060	0.029	0.067	26.10	0.250	-0.575	0.500	0.062	-0.012	0.063	-11.07
0.300	-0.500	0.450	0.046	0.022	0.051	26.10	0.300	-0.544	0.600	0.047	-0.012	0.048	-14.93
0.325	-0.494	0.500	0.027	0.018	0.033	33.69	0.350	-0.495	0.700	0.008	0.012	0.014	56.31
0.350	-0.494	0.600	-0.022	0.037	0.043	120.58	0.400	-0.457	0.800	0.015	0.016	0.022	48.18
0.375	-0.494	0.650	-0.022	0.037	0.043	120.58	0.450	-0.391	0.970	0.0	0.012	0.012	90.00
0.400	-0.510	0.690	-0.030	0.027	0.040	138.27	0.500	-0.289					
0.425	-0.508	0.730	-0.019	-0.011	0.022	-149.42	0.550	-0.153					
0.450	-0.509	0.750	-0.021	0.026	0.033	129.17	0.600	-0.021					
0.475	-0.511	0.800	-0.022	0.027	0.035	129.47	0.650	0.075					
0.500	-0.537	0.970	-0.021	0.017	0.027	140.19	0.700	0.131					
0.550	-0.502						0.750	0.202					
0.600	-0.474						0.800	0.243					
0.650	-0.441												
0.720	-0.389												
0.760	-0.325												
0.800	-0.257												
0.830	-0.204												
0.950	-0.003												
0.970	0.075												
1.000	0.105												

	STEADY	UNSTEADY REAL	IMAG	
CL	0.1991	0.0137	-0.0096	UNCORRECTED
CM	-0.0643	-0.0100	0.0056	

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 9

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M 0.780	PTOT 0.900 BAR	K 0.375	DELTM 0.0 DEG.
ALPHA 0.0 DEG.	QINF 0.255 BAR	FREQ 21.0 HZ	
RE 0.163D+08	TO 322.650 DEG. K	Y/S 0.665	

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA / UNSTEADY DATA (CPU/RAD) — STEADY DATA / UNSTEADY DATA (CPL/RAD)

X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.365	0.050	0.115	0.019	0.117	9.18	0.0	0.789	0.050	0.002	-0.011	0.011	-79.38
0.050	-0.493	0.100	0.081	0.001	0.081	0.93	0.050	-0.357	0.100	0.028	0.007	0.029	13.39
0.100	-0.483	0.200	0.087	-0.026	0.091	-16.84	0.100	-0.389	0.200	0.061	-0.030	0.068	-26.27
0.150	-0.537	0.300	0.083	-0.018	0.085	-12.13	0.150	-0.487	0.300	0.084	-0.032	0.090	-20.96
0.200	-0.526	0.350	0.082	-0.010	0.082	-6.98	0.200	-0.584	0.400	0.079	-0.036	0.087	-24.39
0.250	-0.499	0.400	0.080	-0.003	0.080	-2.36	0.250	-0.589	0.500	0.083	-0.016	0.084	-11.00
0.300	-0.434	0.450	-0.005	0.043	0.043	96.01	0.300	-0.537	0.600	0.018	-0.006	0.019	-19.29
0.325	-0.488	0.500	0.047	0.021	0.052	23.46	0.350	-0.499	0.700	-0.007	0.004	0.008	150.95
0.350	-0.481	0.600	0.0	-0.030	0.030	-90.00	0.400	-0.463	0.800	0.019	-0.007	0.020	-19.44
0.375	-0.487	0.680	0.009	-0.011	0.014	-51.34	0.450	-0.393	0.870	0.011	-0.006	0.013	-26.57
0.400	-0.492	0.700	0.006	-0.017	0.018	-68.75	0.500	-0.291	0.950	0.013	0.002	0.014	9.46
0.425	-0.491	0.730	-0.041	-0.005	0.041	-173.52	0.600	-0.023					
0.450	-0.501	0.810	-0.034	0.003	0.034	175.60	0.650	0.073					
0.475	-0.508	0.870	-0.022	-0.003	0.022	-172.57	0.700	0.148					
0.500	-0.511	0.910	-0.026	-0.012	0.028	-155.38	0.750	0.200					
0.600	-0.432	0.930	-0.017	-0.008	0.019	-156.04	0.850	0.271					
0.630	-0.436	0.950	0.0	-0.001	0.001	-90.00	0.910	0.284					
0.680	-0.441						0.950	0.262					
0.720	-0.388												
0.760	-0.325												
0.800	-0.259												
0.830	-0.206												
0.910	-0.093												
0.930	-0.001												
0.970	0.036												
1.000	0.081												

	STEADY	UNSTEADY REAL	IMAG	
CL	0.2223	0.0088	-0.0070	UNCORRECTED
CM	-0.0899	-0.0084	0.0006	

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 11

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M 0.780	PTOT 0.900 BAR	K 0.375	DELTM 0.0 DEG.
ALPHA 0.0 DEG.	QINF 0.255 BAR	FREQ 21.0 HZ	
RE 0.163D+08	TO 322.650 DEG. K	Y/S 0.751	

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

STEADY DATA		UNSTEADY DATA ------------ CPU/RAD ------------					STEADY DATA		UNSTEADY DATA ------------ CPL/RAD ------------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.100	-0.439	0.050	0.146	0.010	0.147	3.81	0.0	0.781	0.050	0.081	-0.102	0.130	-51.67
0.200	-0.477	0.100	0.137	-0.002	0.137	-1.02	0.050	-0.452	0.100	0.099	-0.086	0.131	-41.01
0.250	-0.481	0.200	0.114	0.016	0.115	8.07	0.100	-0.457	0.200	0.046	-0.085	0.096	-61.73
0.300	-0.478	0.300	0.100	0.019	0.102	10.52	0.200	-0.614	0.300	0.180	-0.085	0.199	-25.27
0.325	-0.466	0.350	0.097	0.018	0.099	10.38	0.250	-0.614	0.400	0.161	-0.079	0.180	-26.10
0.350	-0.462	0.400	0.084	0.020	0.087	13.11	0.300	-0.552	0.500	0.195	-0.048	0.201	-13.75
0.375	-0.469	0.450	0.067	0.025	0.071	20.85	0.350	-0.500	0.600	0.081	0.020	0.084	13.74
0.400	-0.473	0.500	0.050	0.027	0.057	28.35	0.400	-0.435	0.700	0.148	-0.036	0.152	-13.70
0.425	-0.480	0.600	-0.015	0.018	0.023	129.81	0.450	-0.384	0.800	0.157	-0.045	0.163	-16.12
0.450	-0.482	0.630	-0.027	0.012	0.029	155.38	0.500	-0.292	0.910	0.109	-0.028	0.113	-14.30
0.475	-0.486	0.680	-0.023	-0.004	0.023	-169.51	0.550	-0.148	0.950	0.093	-0.025	0.097	-15.07
0.500	-0.513	0.700	-0.018	-0.014	0.023	-142.69	0.600	-0.034					
0.550	-0.448	0.730	-0.014	-0.019	0.023	-126.38	0.700	0.141					
0.600	-0.479	0.750	-0.011	-0.019	0.022	-120.07	0.750	0.191					
0.634	-0.451	0.800	0.005	-0.028	0.028	-80.22	0.910	0.278					
0.680	-0.406	0.910	0.030	-0.008	0.031	-15.42	0.950	0.264					
0.720	-0.364	0.930	0.032	-0.006	0.033	-10.12							
0.800	-0.247	0.950	0.036	-0.006	0.036	-9.46							
0.830	-0.205	0.970	0.042	-0.004	0.042	-5.44							
0.910	-0.056												
0.950	-0.002												
0.970	0.037												
1.000	0.102												

	STEADY	UNSTEADY	
		REAL	IMAG
	-------	-------	-------
CL	0.1549	0.0700	-0.0528	UNCORRECTED
CM	-0.0958	-0.0315	0.0055

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 13

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 97

M 0.780	PTOT 0.900 BAR	K 0.375	DELTM 0.0 DEG.
ALPHA 0.0 DEG.	QINF 0.255 BAR	FREQ 21.0 HZ	
RE 0.163D+08	TO 322.650 DEG. K	Y/S 0.854	

----------------------< UPPER SURF E >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA   UN"TEADY DATA   STEADY DATA   UNSTEADY DATA

X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.213	0.050	0.141	0.068	0.157	25.66	0.0	0.810	0.050	0.080	-0.171	0.189	-65.02
0.020	-0.156	0.100	0.113	0.049	0.123	23.44	0.010	-0.080	0.100	0.139	-0.127	0.188	-42.27
0.030	-0.243	0.200	0.043	0.066	0.079	56.89	0.030	-0.554	0.200	0.245	-0.138	0.281	-29.39
0.050	-0.337	0.300	-0.002	0.069	0.069	92.07	0.050	-0.644	0.300	0.419	-0.117	0.435	-15.64
0.100	-0.370	0.350	-0.038	0.070	0.080	118.84	0.200	-0.606	0.400	0.476	-0.076	0.482	-9.10
0.150	-0.392	0.400	-0.091	0.074	0.118	140.83	0.300	-0.539	0.500	0.585	-0.033	0.586	-3.25
0.200	-0.424	0.450	-0.150	0.061	0.162	157.90	0.400	-0.414	0.600	0.689	0.053	0.691	4.39
0.250	-0.418	0.500	-0.247	0.064	0.255	165.52	0.500	-0.266	0.800	1.105	0.135	1.113	6.96
0.300	-0.416	0.650	-0.781	-0.010	0.781	-179.28	0.600	-0.088					
0.350	-0.415	0.700	-1.103	-0.053	1.105	-177.27	0.700	0.115					
0.375	-0.430	0.720	-1.459	-0.088	1.462	-176.53	0.800	0.228					
0.400	-0.441	0.820	-1.443	-0.309	1.475	-167.90	0.850	0.267					
0.425	-0.443	0.910	-0.237	-0.163	0.287	-145.38	0.900	0.279					
0.450	-0.441	0.950	0.164	-0.102	0.194	-31.87	0.950	0.261					
0.475	-0.443												
0.500	-0.453												
0.575	-0.421												
0.600	-0.393												
0.650	-0.356												
0.675	-0.318												
0.700	-0.314												
0.750	-0.256												
0.800	-0.272												
0.850	-0.201												
0.900	-0.109												
0.950	-0.008												
1.000	0.108												

	STEADY	UNSTEADY	
		REAL	IMAG
	-------	-------	-------
CL	0.1029	0.9224	0.0068	UNCORRECTED
CM	-0.0916	-0.3892	-0.0476

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 14

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   97

```
M       0.780              PTOT    0.900 BAR           K      0.375            DELTM   0.0 DEG.
ALPHA   0.0  DEG.          QINF    0.255 BAR           FREQ   21.0 HZ
RE    0.163D+08            TO    322.650 DEG. K        Y/S    0.885
```

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD ------------						----------- CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.251	0.050	0.021	0.043	0.048	63.89	0.0	0.812	0.050	0.387	-0.237	0.454	-31.43
0.020	-0.017	0.100	0.048	0.013	0.050	15.26	0.010	-0.038	0.100	0.306	-0.141	0.337	-24.78
0.030	-0.169	0.140	0.018	0.028	0.033	56.66	0.030	-0.661	0.200	0.465	-0.202	0.507	-23.52
0.050	-0.285	0.200	0.010	0.030	0.031	72.12	0.050	-0.728	0.300	0.670	-0.146	0.685	-12.27
0.100	-0.364	0.250	-0.024	0.035	0.042	124.33	0.300	-0.567	0.400	0.744	-0.072	0.748	-5.50
0.200	-0.408	0.300	-0.052	0.036	0.063	145.08	0.400	-0.413	0.500	0.941	0.022	0.941	1.33
0.250	-0.380	0.350	-0.099	0.041	0.107	157.58	0.500	-0.298	0.700	1.061	0.140	1.070	7.51
0.300	-0.387	0.400	-0.163	0.038	0.167	166.82	0.600	-0.108	0.850	1.280	0.286	1.311	12.60
0.350	-0.393	0.450	-0.249	0.029	0.251	173.35	0.700	0.119					
0.375	-0.386	0.500	-0.364	0.013	0.365	177.97	0.800	0.209					
0.400	-0.400	0.550	-0.702	-0.003	0.702	-179.73	0.850	0.248					
0.425	-0.403	0.600	-0.881	-0.036	0.881	-177.68	0.900	0.263					
0.450	-0.411	0.700	-2.258	-0.261	2.273	-173.41	0.950	0.256					
0.475	-0.414	0.800	-2.253	-0.433	2.294	-169.12							
0.500	-0.399	0.900	0.184	-0.375	0.418	-63.88							
0.525	-0.397												
0.550	-0.389												
0.575	-0.373												
0.600	-0.340												
0.625	-0.313												
0.675	-0.308												
0.700	-0.322												
0.750	-0.273												
0.850	-0.186												
0.900	-0.090												
0.950	0.005												
1.000	0.100												

```
                        STEADY      UNSTEADY
                |         |  REAL  |  IMAG  |
                | ------- | ------ | ------ |    UNCORRECTED
            CL  |  0.0405 | 1.3289 | 0.0859 |
            CM  | -0.0859 |-0.5055 |-0.0832 |
```

TABLE 8. 4 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 15

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   97

```
M       0.780              PTOT    0.900 BAR           K      0.375            DELTM   0.0 DEG.
ALPHA   0.0  DEG.          QINF    0.255 BAR           FREQ   21.0 HZ
RE    0.163D+08            TO    322.650 DEG. K        Y/S    0.944
```

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD ------------						----------- CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.491	0.050	-0.011	0.142	0.142	94.62	0.0	0.811	0.050	0.676	-0.457	0.817	-34.07
0.020	0.078	0.100	-0.042	0.126	0.133	108.22	0.030	-0.134	0.100	0.338	-0.107	0.355	-17.55
0.030	-0.088	0.140	-0.074	0.123	0.144	120.92	0.100	-0.545	0.200	0.728	-0.146	0.742	-11.34
0.050	-0.248	0.200	-0.100	0.119	0.155	130.15	0.200	-0.598	0.400	0.823	0.020	0.823	1.38
0.100	-0.373	0.250	-0.147	0.111	0.184	143.13	0.300	-0.476	0.500	1.065	0.093	1.069	5.00
0.150	-0.375	0.300	-0.202	0.093	0.222	155.22	0.400	-0.342	0.600	1.748	0.024	1.748	0.80
0.200	-0.355	0.350	-0.253	0.074	0.264	163.68	0.500	-0.272	0.700	1.132	0.187	1.147	9.36
0.250	-0.337	0.400	-0.337	0.069	0.344	168.46	0.600	-0.106	0.800	1.305	0.300	1.339	12.95
0.300	-0.340	0.450	-0.434	0.050	0.437	173.40	0.700	0.083	0.850	0.674	0.256	0.721	20.84
0.350	-0.349	0.500	-0.589	0.013	0.589	178.74	0.800	0.206					
0.375	-0.362	0.550	-0.532	0.031	0.533	176.63	0.850	0.230					
0.400	-0.357	0.600	-0.659	-0.012	0.659	-178.93	0.900	0.235					
0.425	-0.362	0.650	-0.839	-0.059	0.841	-175.99	0.950	0.206					
0.450	-0.364	0.700	-0.967	-0.140	0.977	-171.77							
0.475	-0.377	0.850	-1.060	-0.276	1.096	-165.39							
0.500	-0.381	0.900	-0.265	-0.179	0.320	-145.96							
0.525	-0.363												
0.575	-0.356												
0.600	-0.341												
0.650	-0.314												
0.675	-0.294												
0.700	-0.307												
0.750	-0.303												
0.800	-0.314												
0.850	-0.199												
0.900	-0.116												
0.950	-0.027												
1.000	0.072												

```
                        STEADY      UNSTEADY
                |         |  REAL  |  IMAG  |
                | ------- | ------ | ------ |    UNCORRECTED
            CL  |  0.1018 | 1.2220 | 0.0447 |
            CM  | -0.0794 |-0.3837 |-0.0666 |
```

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP HALFSPAN : 4.0161 M SECTION 1

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 90

M 0.780	PTOT 0.900 BAR	K 0.375	DELTM -5.0 DEG.
ALPHA 0.0 DEG.	QINF 0.254 BAR	FREQ 21.0 HZ	
RE 0.163D+08	TO 322.550 DEG. K	Y/S 0.254	

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

| STEADY DATA | | UNSTEADY DATA | | | | STEADY DATA | | UNSTEADY DATA | | | |
| | | ----------- CPU/RAD ----------- | | | | | | ----------- CPL/RAD ----------- | | | |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	-0.504	0.100	0.020	-0.004	0.021	-11.31	0.0	0.759	0.050	0.011	-0.018	0.021	-57.99
0.020	-0.899	0.200	-0.010	0.025	0.027	111.04	0.010	0.482	0.100	0.020	-0.011	0.023	-27.90
0.030	-0.879	0.300	0.044	-0.284	0.287	-81.21	0.030	0.176	0.200	0.023	-0.007	0.024	-17.10
0.050	-0.838	0.350	0.041	-0.074	0.084	-60.95	0.050	0.021	0.300	0.026	-0.005	0.026	-11.77
0.100	-0.793	0.400	0.136	-0.046	0.143	-18.63	0.100	-0.212	0.400	0.017	0.014	0.022	39.09
0.150	-0.731	0.450	0.080	0.031	0.086	21.58	0.200	-0.458	0.500	0.007	0.008	0.010	48.37
0.200	-0.703	0.500	0.059	0.042	0.072	35.54	0.300	-0.530	0.600	0.005	0.0	0.005	0.0
0.250	-0.749	0.600	0.022	0.005	0.023	13.50	0.400	-0.543	0.700	0.008	-0.001	0.008	-7.13
0.300	-0.735	0.650	0.021	0.004	0.021	10.30	0.500	-0.364	0.750	0.0	0.0	0.0	0.0
0.350	-0.610	0.700	0.017	0.007	0.019	22.83	0.600	-0.168	0.800	0.005	0.004	0.007	35.54
0.375	-0.598	0.720	0.018	0.005	0.019	14.74	0.700	0.011	0.850	0.005	0.006	0.008	50.19
0.400	-0.602	0.750	0.017	0.004	0.018	11.89	0.800	0.126	0.900	0.008	0.004	0.009	23.96
0.425	-0.565	0.800	0.018	0.002	0.018	5.71	0.850	0.162	0.950	0.008	0.002	0.008	14.04
0.450	-0.529	0.850	0.009	0.003	0.009	18.43	0.900	0.182					
0.475	-0.500	0.900	0.015	0.003	0.015	10.62	0.950	0.187					
0.500	-0.476	0.950	0.006	0.001	0.007	8.13							
0.525	-0.438	0.970	0.004	0.005·	0.006	50.19							
0.550	-0.418												
0.575	-0.377												
0.600	-0.349												
0.625	-0.315												
0.650	-0.278												
0.675	-0.252												
0.700	-0.236												
0.750	-0.187												
0.800	-0.129												
0.850	-0.071												
0.900	-0.002												
0.950	0.078												
1.000	0.177												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------		UNCORRECTED
CL	0.2460	-0.0158	0.0191	
CM	-0.0210	0.0049	-0.0008	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP HALFSPAN : 4.0161 M SECTION 2

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 90

M 0.780	PTOT 0.900 BAR	K 0.375	DELTM -5.0 DEG.
ALPHA 0.0 DEG.	QINF 0.254 BAR	FREQ 21.0 HZ	
RE 0.163D+08	TO 322.550 DEG. K	Y/S 0.353	

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

| STEADY DATA | | UNSTEADY DATA | | | | STEADY DATA | | UNSTEADY DATA | | | |
| | | ----------- CPU/RAD ----------- | | | | | | ----------- CPL/RAD ----------- | | | |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG·	PHASE
0.020	-0.944	0.050	0.014	0.017	0.021	51.01	0.0	0.714	0.050	0.004	0.036	0.036	83.37
0.050	-0.829	0.100	0.096	0.011	0.096	6.55	0.050	-0.082	0.100	0.014	0.033	0.036	66.97
0.100	-0.731	0.200	0.109	0.010	0.110	5.40	0.100	-0.305	0.200	0.001	0.021	0.021	88.15
0.140	-0.780	0.300	-0.038	-0.006	0.038	-171.67	0.140	-0.363	0.300	-0.008	0.001	0.008	174.29
0.200	-0.721	0.350	0.025	0.026	0.036	46.51	0.200	-0.554	0.400	-0.020	0.016	0.026	140.91
0.250	-0.702	0.400	0.132	0.132	0.187	45.00	0.250	-0.591	0.500	-0.022	-0.014	0.026	-146.89
0.300	-0.661	0.450	-0.067	0.016	0.068	166.48	0.300	-0.611	0.600	-0.012	-0.014	0.019	-130.91
0.325	-0.642	0.500	-0.054	-0.041	0.068	-142.73	0.350	-0.612	0.700	-0.013	-0.005	0.014	-160.35
0.350	-0.606	0.600	-0.021	-0.019	0.028	-138.01	0.400	-0.627	0.750	-0.009	-0.009	0.013	-135.00
0.375	-0.603	0.650	-0.018	-0.019	0.026	-133.36	0.450	-0.531	0.800	-0.013	-0.004	0.014	-162.90
0.425	-0.542	0.700	-0.016	-0.020	0.025	-128.29	0.500	-0.374	0.850	-0.019	0.002	0.019	172.87
0.450	-0.525	0.720	-0.016	-0.020	0.026	-127.87	0.550	-0.246	0.900	-0.019	0.002	0.020	174.56
0.475	-0.506	0.750	-0.015	-0.017	0.023	-131.19	0.600	-0.112	0.950	0.004	0.001	0.005	14.04
0.500	-0.522	0.800	-0.013	-0.020	0.024	-122.00	0.650	0.013					
0.550	-0.512	0.850	-0.010	-0.018	0.020	-118.81	0.700	0.120					
0.650	-0.426	0.900	-0.002	-0.023	0.024	-95.71	0.750	0.202					
0.700	-0.385	0.950	-0.009	-0.018	0.020	-117.90	0.800	0.254					
0.750	-0.301	0.970	-0.010	-0.024	0.026	-113.50	0.850	0.276					
0.800	-0.255						0.900	0.290					
0.850	-0.179						0.950	0.271					
0.900	-0.087												
0.950	0.021												
1.000	0.142												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------		UNCORRECTED
CL	0.2912	-0.0202	0.0048	
CM	-0.0687	-0.0014	-0.0025	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   4

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   90

M	0.780	PTOT	0.900 BAR	K	0.375	DELTM -5.0 DEG.
ALPHA	0.0 DEG.	QINF	0.254 BAR	FREQ	21.0 HZ	
RE	0.163D+08	TO	322.550 DEG. K	Y/S	0.479	

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA			UNSTEADY DATA				STEADY DATA			UNSTEADY DATA			
				CPU/RAD								CPL/RAD			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE		X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.576	0.050	0.063	0.008	0.063	7.50		0.0	0.788	0.050	0.035	-0.035	0.049	-45.00
0.050	-0.635	0.100	0.108	-0.051	0.119	-25.35		0.050	-0.187	0.100	0.049	-0.024	0.054	-26.56
0.100	-0.587	0.200	0.352	0.046	0.355	7.48		0.100	-0.386	0.200	0.076	-0.011	0.077	-8.29
0.200	-0.712	0.300	0.024	0.023	0.033	43.96		0.200	-0.587	0.300	0.030	0.005	0.030	9.04
0.250	-0.634	0.350	0.081	-0.045	0.093	-29.21		0.250	-0.624	0.400	0.072	0.013	0.073	10.01
0.300	-0.564	0.400	0.098	0.029	0.102	16.58		0.300	-0.593	0.500	0.045	0.014	0.047	17.75
0.325	-0.542	0.450	0.050	0.084	0.098	59.32		0.350	-0.559	0.600	0.024	-0.023	0.033	-43.03
0.350	-0.529	0.500	0.036	0.069	0.078	62.92		0.400	-0.511	0.700	0.010	-0.028	0.030	-70.97
0.375	-0.527	0.600	0.037	0.024	0.044	33.02		0.450	-0.420	0.800	0.001	-0.032	0.032	-88.21
0.400	-0.514	0.650	0.008	0.008	0.012	45.00		0.500	-0.291	0.930	0.002	-0.026	0.026	-85.43
0.425	-0.517	0.690	-0.002	0.106	0.106	91.30		0.550	-0.150	0.970	0.012	-0.017	0.021	-53.97
0.450	-0.525	0.700	0.005	0.054	0.054	84.51		0.600	-0.020					
0.500	-0.532	0.730	0.0	0.058	0.058	90.00		0.650	0.090					
0.550	-0.539	0.750	-0.014	0.012	0.019	139.09		0.700	0.168					
0.600	-0.503	0.930	-0.003	-0.004	0.005	-126.87		0.750	0.223					
0.650	-0.445	0.950	-0.003	-0.011	0.012	-104.04		0.800	0.270					
0.720	-0.445	0.970	-0.011	-0.020	0.023	-119.05		0.910	0.299					
0.800	-0.287							0.950	0.269					
0.910	-0.062													
0.950	0.001													
0.970	0.039													
1.000	0.089													

	STEADY	UNSTEADY REAL	UNSTEADY IMAG	
CL	0.2861	-0.0312	-0.0268	UNCORRECTED
CM	-0.0929	-0.0044	0.0084	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   6

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   90

M	0.780	PTOT	0.900 BAR	K	0.375	DELTM -5.0 DEG.
ALPHA	0.0 DEG.	QINF	0.254 BAR	FREQ	21.0 HZ	
RE	0.163D+08	TO	322.550 DEG. K	Y/S	0.566	

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA			UNSTEADY DATA				STEADY DATA			UNSTEADY DATA			
				CPU/RAD								CPL/RAD			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE		X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.460	0.050	0.082	-0.032	0.088	-21.35		0.0	0.798	0.050	-0.040	0.031	0.051	142.93
0.050	-0.547	0.100	0.083	-0.018	0.085	-12.34		0.050	-0.246	0.100	-0.031	0.010	0.032	162.55
0.100	-0.544	0.200	0.173	0.072	0.188	22.64		0.100	-0.404	0.200	-0.044	-0.027	0.051	-148.09
0.150	-0.560	0.300	0.021	-0.009	0.023	-22.62		0.200	-0.611	0.300	0.041	0.019	0.045	24.23
0.200	-0.603	0.350	0.016	-0.021	0.027	-52.69		0.250	-0.584	0.400	0.010	-0.060	0.060	-80.54
0.250	-0.551	0.400	0.016	-0.024	0.029	-57.09		0.300	-0.554	0.500	0.047	-0.015	0.050	-17.24
0.300	-0.528	0.450	0.007	-0.021	0.022	-72.18		0.350	-0.509	0.600	-0.010	-0.036	0.038	-105.52
0.325	-0.521	0.500	-0.007	-0.024	0.025	-104.93		0.400	-0.467	0.700	-0.003	-0.044	0.044	-93.24
0.350	-0.516	0.600	-0.034	-0.027	0.043	-141.31		0.450	-0.388	0.800	-0.016	-0.031	0.035	-117.26
0.375	-0.518	0.630	-0.018	-0.052	0.055	-109.44		0.500	-0.282	0.870	-0.006	-0.036	0.037	-98.97
0.400	-0.510	0.690	-0.028	-0.040	0.049	-124.62		0.550	-0.139	0.910	-0.007	-0.026	0.027	-105.26
0.425	-0.501	0.700	-0.031	-0.035	0.047	-131.31		0.600	-0.020	0.950	-0.013	-0.017	0.021	-126.87
0.450	-0.509	0.730	-0.022	-0.033	0.039	-124.08		0.650	0.083					
0.475	-0.502	0.750	-0.016	-0.024	0.029	-122.47		0.700	0.154					
0.500	-0.519	0.910	-0.016	-0.036	0.039	-114.34		0.750	0.211					
0.550	-0.490	0.950	-0.008	-0.033	0.034	-102.99		0.800	0.252					
0.600	-0.467	0.970	-0.006	-0.024	0.024	-104.04		0.850	0.275					
0.650	-0.427													
0.740	-0.376													
0.780	-0.306													
0.820	-0.237													
0.910	-0.066													
0.950	0.007													
0.970	0.040													
1.000	0.079													

	STEADY	UNSTEADY REAL	UNSTEADY IMAG	
CL	0.2219	-0.0217	-0.0078	UNCORRECTED
CM	-0.0718	-0.0063	0.0004	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   8

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   90

M	0.780		PTOT	0.900 BAR		K	0.375		DELTM -5.0 DEG.
ALPHA	0.0 DEG.		QINF	0.254 BAR		FREQ	21.0 HZ		
RE	0.163D+08		T0	322.550 DEG. K		Y/S	0.618		

-------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >--------------------

STEADY DATA			UNSTEADY DATA				STEADY DATA			UNSTEADY DATA			
				----------- CPU/RAD ------------							----------- CPL/RAD -----------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.406	0.050	0.160	-0.010	0.160	-3.71	0.0	0.793	0.050	0.0	0.035	0.035	90.00
0.050	-0.503	0.100	0.121	0.003	0.121	1.27	0.050	-0.285	0.100	0.015	0.047	0.049	71.83
0.100	-0.494	0.200	0.077	-0.009	0.077	-6.56	0.100	-0.405	0.200	0.037	0.056	0.067	56.47
0.150	-0.543	0.300	0.082	0.032	0.088	21.28	0.150	-0.488	0.300	0.041	0.016	0.044	20.81
0.200	-0.579	0.350	0.075	0.047	0.089	32.37	0.200	-0.582	0.400	0.049	-0.006	0.049	-6.65
0.250	-0.542	0.400	0.068	0.046	0.082	34.29	0.250	-0.577	0.500	0.042	-0.009	0.044	-12.53
0.300	-0.502	0.450	0.052	0.060	0.080	48.81	0.300	-0.542	0.600	0.046	-0.021	0.050	-24.44
0.325	-0.505	0.500	0.029	0.072	0.078	67.99	0.350	-0.500	0.700	-0.006	0.009	0.010	123.69
0.350	-0.496	0.600	-0.061	0.068	0.092	131.99	0.400	-0.456	0.800	-0.005	0.008	0.009	123.69
0.375	-0.487	0.650	-0.067	0.044	0.080	146.65	0.450	-0.391	0.970	-0.014	-0.005	0.015	-160.56
0.400	-0.503	0.690	-0.081	0.038	0.090	154.83	0.500	-0.287					
0.425	-0.500	0.730	-0.044	-0.032	0.054	-143.84	0.550	-0.153					
0.450	-0.513	0.750	-0.065	0.022	0.068	161.31	0.600	-0.023					
0.475	-0.515	0.800	-0.053	0.014	0.055	165.17	0.650	0.076					
0.500	-0.528	0.970	-0.035	-0.003	0.036	-174.47	0.700	0.131					
0.550	-0.493						0.750	0.204					
0.600	-0.465						0.800	0.243					
0.650	-0.438												
0.720	-0.388												
0.760	-0.323												
0.800	-0.256												
0.830	-0.202												
0.950	-0.004												
0.970	0.051												
1.000	0.092												

	STEADY	UNSTEADY		
		REAL	IMAG	
	-------	-------	-------	UNCORRECTED
CL	0.1982	0.0057	-0.0148	
CM	-0.0635	-0.0133	0.0078	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   9

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :   90

M	0.780		PTOT	0.900 BAR		K	0.375		DELTM -5.0 DEG.
ALPHA	0.0 DEG.		QINF	0.254 BAR		FREQ	21.0 HZ		
RE	0.163D+08		T0	322.550 DEG. K		Y/S	0.665		

-------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >--------------------

STEADY DATA			UNSTEADY DATA				STEADY DATA			UNSTEADY DATA			
				----------- CPU/RAD ------------							----------- CPL/RAD -----------			
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.360	0.050	0.138	-0.041	0.144	-16.53	0.0	0.794	0.050	0.013	-0.004	0.014	-17.53
0.050	-0.487	0.100	0.103	-0.026	0.107	-14.38	0.050	-0.349	0.100	-0.022	-0.008	0.023	-160.02
0.100	-0.480	0.200	0.121	-0.022	0.123	-10.07	0.100	-0.394	0.200	0.066	-0.037	0.076	-29.45
0.150	-0.538	0.300	0.112	-0.003	0.112	-1.59	0.150	-0.494	0.300	0.030	-0.070	0.076	-67.04
0.200	-0.535	0.350	0.098	0.009	0.098	5.37	0.200	-0.588	0.400	0.095	-0.036	0.101	-20.74
0.250	-0.511	0.400	0.096	0.009	0.096	5.42	0.250	-0.585	0.500	0.071	-0.061	0.094	-40.70
0.300	-0.502	0.450	0.010	0.056	0.057	80.17	0.300	-0.543	0.600	0.033	-0.010	0.034	-16.56
0.325	-0.492	0.500	0.054	0.011	0.055	11.31	0.350	-0.502	0.700	-0.008	-0.036	0.037	-103.17
0.350	-0.491	0.600	0.005	-0.019	0.020	-76.76	0.400	-0.465	0.800	0.028	-0.008	0.029	-15.07
0.375	-0.490	0.680	0.006	-0.001	0.006	-14.04	0.450	-0.394	0.870	0.015	0.007	0.017	23.63
0.400	-0.484	0.700	0.010	-0.008	0.013	-39.29	0.500	-0.295	0.950	0.013	0.009	0.016	33.69
0.425	-0.485	0.730	-0.034	0.012	0.036	160.15	0.600	-0.024					
0.450	-0.494	0.810	-0.019	0.018	0.026	137.73	0.650	0.073					
0.475	-0.513	0.870	-0.009	0.009	0.013	135.00	0.700	0.147					
0.500	-0.514	0.910	-0.001	0.006	0.007	99.46	0.750	0.199					
0.600	-0.435	0.930	0.0	0.008	0.008	90.00	0.850	0.273					
0.630	-0.429	0.950	-0.007	0.001	0.008	173.66	0.910	0.281					
0.680	-0.436						0.950	0.261					
0.720	-0.384												
0.760	-0.323												
0.800	-0.258												
0.830	-0.207												
0.910	-0.093												
0.930	-0.002												
0.970	0.034												
1.000	0.081												

	STEADY	UNSTEADY		
		REAL	IMAG	
	-------	-------	-------	UNCORRECTED
CL	0.2216	-0.0118	-0.0258	
CM	-0.0895	-0.0077	0.0063	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 11

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 90

M	0.780		PTOT	0.900 BAR		K	0.375		DELTM	−5.0 DEG.
ALPHA	0.0 DEG.		QINF	0.254 BAR		FREQ	21.0 HZ			
RE	0.163D+08		TO	322.550 DEG. K		Y/S	0.751			

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -----------							----------- CPL/RAD -----------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.100	−0.437	0.050	0.096	0.033	0.101	19.13	0.0	0.782	0.050	0.070	−0.091	0.115	−52.58
0.200	−0.482	0.100	0.089	0.025	0.093	15.88	0.050	−0.441	0.100	0.080	−0.075	0.109	−43.09
0.250	−0.492	0.200	0.076	0.023	0.079	16.59	0.100	−0.464	0.200	0.109	−0.115	0.159	−46.64
0.300	−0.477	0.300	0.080	0.018	0.082	12.58	0.200	−0.624	0.300	0.138	−0.097	0.168	−35.04
0.325	−0.467	0.350	0.070	0.019	0.073	15.35	0.250	−0.615	0.400	0.177	−0.086	0.197	−25.86
0.350	−0.468	0.400	0.052	0.021	0.056	21.80	0.300	−0.561	0.500	0.175	−0.059	0.185	−18.74
0.375	−0.465	0.450	0.038	0.027	0.047	35.31	0.350	−0.506	0.600	0.073	−0.010	0.074	−7.73
0.400	−0.461	0.500	0.026	0.030	0.040	49.03	0.400	−0.441	0.700	0.153	−0.037	0.158	−13.71
0.425	−0.468	0.600	−0.031	0.016	0.035	152.70	0.450	−0.390	0.800	0.170	−0.033	0.174	−10.99
0.450	−0.470	0.630	−0.044	0.007	0.044	171.25	0.500	−0.300	0.910	0.115	−0.019	0.116	−9.55
0.475	−0.485	0.680	−0.030	−0.019	0.035	−147.85	0.550	−0.153	0.950	0.099	−0.010	0.100	−5.51
0.500	−0.510	0.700	−0.025	−0.025	0.035	−136.00	0.600	−0.034					
0.550	−0.439	0.730	−0.021	−0.029	0.036	−125.91	0.700	0.137					
0.600	−0.465	0.750	−0.013	−0.036	0.038	−109.86	0.750	0.186					
0.634	−0.436	0.800	0.003	−0.033	0.033	−84.96	0.910	0.278					
0.680	−0.401	0.910	0.035	−0.012	0.037	−19.44	0.950	0.260					
0.720	−0.360	0.930	0.040	−0.009	0.041	−12.88							
0.800	−0.243	0.950	0.042	−0.011	0.043	−14.42							
0.830	−0.203	0.970	0.047	−0.012	0.049	−14.32							
0.910	−0.052												
0.950	−0.001												
0.970	0.037												
1.000	0.102												

	STEADY	UNSTEADY		
		REAL	IMAG	
	-------	-------	-------	
CL	0.1484	0.0898	−0.0596	UNCORRECTED
CM	−0.0937	−0.0330	0.0039	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 13

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 90

M	0.780		PTOT	0.900 BAR		K	0.375		DELTM	−5.0 DEG.
ALPHA	0.0 DEG.		QINF	0.254 BAR		FREQ	21.0 HZ			
RE	0.163D+08		TO	322.550 DEG. K		Y/S	0.854			

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -----------							----------- CPL/RAD -----------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.223	0.050	0.060	0.094	0.111	57.50	0.0	0.810	0.050	0.219	−0.241	0.325	−47.67
0.020	−0.149	0.100	0.070	0.066	0.097	43.08	0.010	−0.086	0.100	0.210	−0.174	0.272	−39.68
0.030	−0.237	0.200	0.011	0.076	0.077	82.07	0.030	−0.571	0.200	0.300	−0.168	0.344	−29.28
0.050	−0.332	0.300	−0.037	0.074	0.083	116.82	0.050	−0.655	0.300	0.484	−0.196	0.522	−22.07
0.100	−0.357	0.350	−0.086	0.072	0.113	140.09	0.200	−0.625	0.400	0.518	−0.095	0.527	−10.39
0.150	−0.375	0.400	−0.153	0.068	0.167	156.04	0.300	−0.566	0.500	0.619	−0.041	0.620	−3.81
0.200	−0.413	0.450	−0.208	0.047	0.214	167.15	0.400	−0.451	0.600	0.728	0.046	0.729	3.59
0.250	−0.405	0.500	−0.331	0.040	0.333	173.18	0.500	−0.300	0.800	1.544	0.186	1.555	6.87
0.300	−0.409	0.650	−0.875	−0.069	0.878	−175.52	0.600	−0.143					
0.350	−0.411	0.700	−1.178	−0.122	1.185	−174.07	0.700	0.046					
0.375	−0.421	0.720	−1.460	−0.160	1.468	−173.75	0.800	0.131					
0.400	−0.425	0.820	−1.690	−0.387	1.733	−167.09	0.850	0.169					
0.425	−0.431	0.910	−0.410	−0.211	0.461	−152.74	0.900	0.197					
0.450	−0.418	0.950	0.313	−0.109	0.331	−19.19	0.950	0.204					
0.475	−0.409												
0.500	−0.416												
0.575	−0.378												
0.600	−0.341												
0.650	−0.293												
0.675	−0.247												
0.700	−0.216												
0.750	−0.110			STEADY	UNSTEADY								
0.800	−0.101				REAL	IMAG							
0.850	−0.109			-------	-------	-------							
0.900	−0.082		CL	0.0188	1.1298	0.0229	UNCORRECTED						
0.950	−0.020		CM	−0.0580	−0.4752	−0.0670							
1.000	0.108												

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 14

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 90

M	0.780		PTOT	0.900 BAR		K	0.375		DELTM	-5.0 DEG.
ALPHA	0.0	DEG.	QINF	0.254 BAR		FREQ	21.0 HZ
RE	0.163D+08		TO	322.550 DEG. K		Y/S	0.885

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

			----------- CPU/RAD ------------						----------- CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.264	0.050	0.061	0.163	0.174	69.44	0.0	0.813	0.050	0.264	-0.314	0.410	-50.00
0.020	-0.004	0.100	0.044	0.120	0.128	69.79	0.010	-0.030	0.100	0.245	-0.142	0.283	-30.15
0.030	-0.157	0.140	0.006	0.130	0.130	87.41	0.030	-0.686	0.200	0.358	-0.183	0.401	-27.05
0.050	-0.273	0.200	-0.031	0.133	0.136	102.96	0.050	-0.751	0.300	0.598	-0.129	0.611	-12.18
0.100	-0.344	0.250	-0.088	0.128	0.155	124.48	0.300	-0.610	0.400	0.716	-0.061	0.718	-4.89
0.200	-0.388	0.300	-0.132	0.112	0.173	139.78	0.400	-0.471	0.500	0.924	0.035	0.924	2.16
0.250	-0.357	0.350	-0.213	0.109	0.239	152.90	0.500	-0.366	0.700	1.178	0.199	1.194	9.57
0.300	-0.370	0.400	-0.292	0.096	0.308	161.75	0.600	-0.196	0.850	1.486	0.277	1.512	10.55
0.350	-0.376	0.450	-0.413	0.072	0.419	170.06	0.700	0.029					
0.375	-0.364	0.500	-0.533	0.036	0.535	176.11	0.800	0.132					
0.400	-0.369	0.550	-0.882	0.020	0.882	178.72	0.850	0.178					
0.425	-0.373	0.600	-1.061	-0.028	1.062	-178.49	0.900	0.203					
0.450	-0.369	0.700	-2.104	-0.276	2.122	-172.52	0.950	0.211					
0.475	-0.359	0.800	-2.480	-0.430	2.517	-170.17							
0.500	-0.340	0.900	-0.340	-0.448	0.563	-127.18							
0.525	-0.331												
0.550	-0.317												
0.575	-0.292												
0.600	-0.249												
0.625	-0.210												
0.675	-0.181												
0.700	-0.171												
0.750	-0.087												
0.850	-0.084												
0.900	-0.057												
0.950	0.003												
1.000	0.121												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------	
CL	-0.0722	1.4361	0.0672	UNCORRECTED
CM	-0.0458	-0.5629	-0.0903	

TABLE 8. 5 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 15

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 90

M	0.780		PTOT	0.900 BAR		K	0.375		DELTM	-5.0 DEG.
ALPHA	0.0	DEG.	QINF	0.254 BAR		FREQ	21.0 HZ
RE	0.163D+08		TO	322.550 DEG. K		Y/S	0.944

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

			----------- CPU/RAD ------------						----------- CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.509	0.050	-0.084	0.144	0.167	120.20	0.0	0.808	0.050	0.736	-0.572	0.932	-37.87
0.020	0.101	0.100	-0.133	0.131	0.187	135.51	0.030	-0.140	0.100	0.187	0.058	0.195	17.12
0.030	-0.065	0.140	-0.165	0.111	0.199	146.10	0.100	-0.570	0.200	0.679	-0.171	0.700	-14.16
0.050	-0.225	0.200	-0.189	0.103	0.215	151.35	0.200	-0.647	0.400	0.802	-0.002	0.802	-0.13
0.100	-0.342	0.250	-0.249	0.088	0.264	160.53	0.300	-0.521	0.500	1.031	0.070	1.033	3.88
0.150	-0.342	0.300	-0.301	0.059	0.307	168.88	0.400	-0.402	0.600	1.625	0.046	1.625	1.63
0.200	-0.326	0.350	-0.349	0.043	0.351	173.04	0.500	-0.345	0.700	1.362	0.222	1.380	9.25
0.250	-0.304	0.400	-0.451	0.033	0.452	175.85	0.600	-0.198	0.800	1.913	0.329	1.941	9.76
0.300	-0.309	0.450	-0.547	0.006	0.547	179.32	0.700	-0.029	0.850	1.033	0.272	1.068	14.75
0.350	-0.321	0.500	-0.715	-0.040	0.716	-176.80	0.800	0.122					
0.375	-0.326	0.550	-0.668	-0.035	0.669	-177.03	0.850	0.162					
0.400	-0.314	0.600	-0.836	-0.077	0.840	-174.75	0.900	0.182					
0.425	-0.319	0.650	-1.018	-0.131	1.026	-172.67	0.950	0.175					
0.450	-0.313	0.700	-1.175	-0.209	1.193	-169.93							
0.475	-0.312	0.850	-1.464	-0.316	1.497	-167.80							
0.500	-0.311	0.900	-0.751	-0.220	0.782	-163.68							
0.525	-0.290												
0.575	-0.276												
0.600	-0.249												
0.650	-0.209												
0.675	-0.184												
0.700	-0.158												
0.750	-0.106												
0.800	-0.091												
0.850	-0.099												
0.900	-0.083												
0.950	-0.032												
1.000	0.092												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------	
CL	-0.0245	1.4065	0.0885	UNCORRECTED
CM	-0.0366	-0.4726	-0.0791	

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   1

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 116

M 0.780	PTOT 0.900 BAR	K 0.377	DELTM 0.0 DEG.
ALPHA 2.000 DEG.	QINF 0.256 BAR	FREQ 21.0 HZ	
RE 0.165D+08	TO 319.150 DEG. K	Y/S 0.254	

-------------------< UPPER SURFACE >---------------------   --------------------< LOWER SURFACE >---------------------

STEADY DATA | UNSTEADY DATA | STEADY DATA | UNSTEADY DATA

		----------- CPU/RAD ------------				----------- CPL/RAD ------------
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	-0.770	0.100	0.004	-0.001	0.004	-11.31	0.0	0.690	0.050	0.019	0.020	0.027	46.64
0.020	-1.209	0.200	0.020	-0.014	0.024	-34.12	0.010	0.615	0.100	0.019	0.020	0.027	46.74
0.030	-1.288	0.300	0.009	-0.023	0.025	-68.20	0.030	0.336	0.200	0.029	0.003	0.029	5.19
0.050	-1.273	0.350	-0.004	-0.060	0.060	-93.87	0.050	0.183	0.300	0.030	0.010	0.031	17.82
0.100	-1.200	0.400	0.021	-0.033	0.039	-57.88	0.100	-0.055	0.400	0.030	0.014	0.033	24.90
0.150	-0.992	0.450	0.355	-0.124	0.376	-19.23	0.200	-0.312	0.500	0.010	0.027	0.029	69.44
0.200	-0.973	0.500	0.102	0.091	0.137	41.60	0.300	-0.403	0.600	0.003	0.027	0.027	82.87
0.250	-0.962	0.600	0.024	0.104	0.106	77.11	0.400	-0.420	0.700	0.003	0.028	0.029	84.29
0.300	-0.963	0.650	0.006	0.090	0.090	86.39	0.500	-0.300	0.750	-0.002	0.027	0.027	94.40
0.350	-0.913	0.700	0.001	0.072	0.072	89.28	0.600	-0.130	0.800	-0.002	0.020	0.020	94.40
0.375	-0.879	0.720	-0.004	0.067	0.067	93.22	0.700	0.033	0.850	-0.003	0.027	0.027	96.12
0.400	-0.962	0.750	-0.010	0.059	0.060	99.61	0.800	0.143	0.900	-0.005	0.029	0.029	98.88
0.425	-0.839	0.800	-0.013	0.051	0.053	104.26	0.850	0.170	0.950	-0.009	0.026	0.028	109.65
0.450	-0.579	0.850	-0.014	0.037	0.039	111.04	0.900	0.188					
0.475	-0.489	0.900	-0.018	0.036	0.041	116.56	0.950	0.191					
0.500	-0.461	0.950	-0.014	0.025	0.029	118.18							
0.525	-0.441	0.970	-0.016	0.016	0.023	135.00							
0.550	-0.416												
0.575	-0.390												
0.600	-0.359												
0.625	-0.326												
0.650	-0.296												
0.675	-0.272												
0.700	-0.252												
0.750	-0.198												
0.800	-0.134												
0.850	-0.068												
0.900	-0.003												
0.950	0.080												
1.000	0.172												

	STEADY	UNSTEADY	
		REAL	IMAG
CL	0.4559	-0.0158	-0.0039
CM	-0.0200	0.0035	0.0061

UNCORRECTED

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   2

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 116

M 0.780	PTOT 0.900 BAR	K 0.377	DELTM 0.0 DEG.
ALPHA 2.000 DEG.	QINF 0.256 BAR	FREQ 21.0 HZ	
RE 0.165D+08	TO 319.150 DEG. K	Y/S 0.353	

-------------------< UPPER SURFACE >---------------------   --------------------< LOWER SURFACE >---------------------

STEADY DATA | UNSTEADY DATA | STEADY DATA | UNSTEADY DATA

		----------- CPU/RAD ------------				----------- CPL/RAD ------------
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.287	0.050	-0.002	-0.044	0.044	-93.07	0.0	0.634	0.050	0.021	0.021	0.030	43.88
0.050	-1.243	0.100	0.011	-0.069	0.070	-81.05	0.050	0.108	0.100	0.024	0.018	0.030	36.25
0.100	-1.148	0.200	0.029	-0.043	0.052	-56.54	0.100	-0.119	0.200	0.015	0.016	0.021	46.27
0.140	-1.153	0.300	0.018	-0.037	0.041	-64.59	0.140	-0.194	0.300	0.005	0.022	0.022	77.47
0.200	-1.137	0.350	0.044	-0.004	0.044	-5.12	0.200	-0.362	0.400	-0.001	0.014	0.014	94.97
0.250	-1.055	0.400	0.213	-0.070	0.224	-18.11	0.250	-0.412	0.500	-0.006	0.004	0.007	146.31
0.300	-0.938	0.450	0.222	-0.099	0.244	-24.10	0.300	-0.433	0.600	0.002	0.008	0.009	77.47
0.325	-0.943	0.500	0.072	0.051	0.088	35.36	0.350	-0.457	0.700	0.003	0.008	0.008	69.44
0.350	-0.962	0.600	0.020	0.060	0.064	71.27	0.400	-0.479	0.750	0.007	0.010	0.013	55.01
0.375	-0.936	0.650	0.009	0.052	0.053	79.80	0.450	-0.424	0.800	0.004	0.011	0.012	70.02
0.425	-0.747	0.700	0.004	0.041	0.041	84.29	0.500	-0.312	0.850	0.007	0.009	0.012	53.13
0.450	-0.560	0.720	-0.004	0.032	0.033	97.85	0.550	-0.210	0.900	0.0	0.014	0.014	90.00
0.475	-0.490	0.750	-0.005	0.030	0.030	100.12	0.600	-0.073	0.950	0.0	0.010	0.010	90.00
0.500	-0.488	0.800	-0.004	0.022	0.022	100.89	0.650	0.039					
0.550	-0.502	0.850	-0.006	0.012	0.014	116.57	0.700	0.145					
0.650	-0.449	0.900	-0.006	0.014	0.015	112.62	0.750	0.224					
0.700	-0.403	0.950	0.002	0.003	0.004	56.31	0.800	0.269					
0.750	-0.314	0.970	0.001	0.005	0.005	78.69	0.850	0.291					
0.800	-0.256						0.900	0.296					
0.850	-0.172						0.950	0.273					
0.900	-0.082												
0.950	0.024												
1.000	0.131												

	STEADY	UNSTEADY	
		REAL	IMAG
CL	0.5275	-0.0239	0.0157
CM	-0.0674	0.0050	0.0045

UNCORRECTED

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   4

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 116

M 0.780   PTOT 0.900 BAR   K 0.377   DELTM 0.0 DEG.
ALPHA 2.000 DEG.   QINF 0.256 BAR   FREQ 21.0 HZ
RE 0.165D+08   TO 319.150 DEG. K   Y/S 0.479

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | ----------- CPU/RAD ----------- | | | | ----------- CPL/RAD ----------- |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.139	0.050	0.028	-0.028	0.039	-45.00	0.0	0.749	0.050	0.002	-0.007	0.007	-73.30
0.050	-1.103	0.100	0.010	-0.040	0.042	-75.65	0.050	0.055	0.100	0.008	-0.002	0.008	-11.31
0.100	-1.066	0.200	0.019	-0.003	0.019	-9.46	0.100	-0.148	0.200	0.009	-0.008	0.012	-42.51
0.200	-1.050	0.300	-0.003	0.006	0.007	119.74	0.200	-0.352	0.300	0.009	-0.013	0.016	-55.01
0.250	-1.071	0.350	-0.080	-0.107	0.134	-126.76	0.250	-0.395	0.400	0.008	-0.015	0.018	-61.39
0.300	-1.040	0.400	0.047	0.172	0.178	74.87	0.300	-0.405	0.500	0.013	-0.014	0.019	-47.49
0.325	-1.021	0.450	0.006	0.057	0.057	83.58	0.350	-0.407	0.600	0.018	-0.014	0.022	-37.69
0.350	-0.978	0.500	0.010	0.031	0.033	72.00	0.400	-0.392	0.700	0.008	-0.017	0.019	-66.04
0.375	-0.736	0.600	-0.011	0.012	0.016	132.71	0.450	-0.339	0.800	0.011	-0.027	0.029	-67.83
0.400	-0.539	0.650	-0.007	0.003	0.008	159.44	0.500	-0.235	0.930	0.015	-0.003	0.015	-12.09
0.425	-0.509	0.690	-0.071	0.012	0.072	170.54	0.550	-0.107	0.970	0.015	-0.008	0.017	-30.07
0.450	-0.520	0.700	-0.032	-0.005	0.032	-170.84	0.600	0.010					
0.500	-0.543	0.730	-0.025	-0.006	0.026	-166.50	0.650	0.121					
0.550	-0.570	0.750	-0.009	-0.013	0.016	-125.54	0.700	0.200					
0.600	-0.542	0.930	-0.002	0.0	0.002	180.00	0.750	0.256					
0.650	-0.476	0.950	-0.001	0.003	0.003	108.44	0.800	0.295					
0.720	-0.465	0.970	-0.001	-0.002	0.002	-116.56	0.910	0.305					
0.800	-0.300						0.950	0.273					
0.910	-0.064												
0.950	-0.006												
0.970	0.032												
1.000	0.076												

	STEADY	UNSTEADY REAL	IMAG	
CL	0.5512	0.0108	-0.0153	UNCORRECTED
CM	-0.0906	-0.0046	0.0049	

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   6

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 116

M 0.780   PTOT 0.900 BAR   K 0.377   DELTM 0.0 DEG.
ALPHA 2.000 DEG.   QINF 0.256 BAR   FREQ 21.0 HZ
RE 0.165D+08   TO 319.150 DEG. K   Y/S 0.566

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | ----------- CPU/RAD ----------- | | | | ----------- CPL/RAD ----------- |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.046	0.050	0.091	-0.057	0.107	-32.05	0.0	0.763	0.050	0.018	0.011	0.021	30.96
0.050	-1.011	0.100	0.086	-0.061	0.105	-35.37	0.050	0.030	0.100	0.006	0.024	0.025	75.96
0.100	-1.024	0.200	0.051	-0.040	0.065	-38.16	0.100	-0.150	0.200	0.015	0.013	0.020	40.10
0.150	-1.001	0.300	0.148	-0.216	0.261	-55.63	0.200	-0.351	0.300	0.010	-0.018	0.021	-60.02
0.200	-1.008	0.350	0.845	-0.561	1.014	-33.55	0.250	-0.375	0.400	0.018	0.001	0.018	2.29
0.250	-0.986	0.400	0.744	0.234	0.780	17.45	0.300	-0.378	0.500	0.019	-0.023	0.030	-49.40
0.300	-0.921	0.450	0.020	0.330	0.331	86.60	0.350	-0.367	0.600	-0.010	0.008	0.013	141.34
0.325	-0.923	0.500	-0.087	0.305	0.317	105.95	0.400	-0.357	0.700	-0.022	-0.013	0.025	-148.39
0.350	-0.858	0.600	-0.171	0.121	0.210	144.78	0.450	-0.310	0.800	-0.021	0.002	0.021	174.81
0.375	-0.637	0.630	-0.127	0.029	0.130	166.94	0.500	-0.220	0.870	-0.021	0.003	0.021	172.23
0.400	-0.526	0.690	-0.131	0.044	0.138	161.57	0.550	-0.100	0.910	-0.021	0.003	0.021	170.54
0.425	-0.533	0.700	-0.111	0.038	0.118	161.08	0.600	0.010	0.950	-0.029	0.009	0.031	162.18
0.450	-0.541	0.730	-0.091	0.024	0.095	165.40	0.650	0.112					
0.475	-0.549	0.750	-0.072	0.017	0.074	167.01	0.700	0.188					
0.500	-0.562	0.910	-0.038	-0.006	0.038	-171.16	0.750	0.246					
0.550	-0.551	0.950	-0.037	0.019	0.042	153.43	0.800	0.281					
0.600	-0.514	0.970	-0.042	0.028	0.050	145.78	0.850	0.297					
0.650	-0.470												
0.740	-0.397												
0.780	-0.319												
0.820	-0.243												
0.910	-0.065												
0.950	-0.002												
0.970	0.027												
1.000	0.059												

	STEADY	UNSTEADY REAL	IMAG	
CL	0.4919	-0.0555	-0.0139	UNCORRECTED
CM	-0.0689	-0.0058	0.0147	

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   8

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 116

M   0.780   PTOT   0.900 BAR   K   0.377   DELTM   0.0 DEG.
ALPHA   2.000 DEG.   QINF   0.256 BAR   FREQ   21.0 HZ
RE   0.165D+08   TO   319.150 DEG. K   Y/S   0.618

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | | ----------- CPU/RAD ----------- | | | | | | ----------- CPL/RAD ----------- | | |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-1.000	0.050	0.045	-0.010	0.046	-12.93	0.0	0.764	0.050	0.010	-0.013	0.017	-52.12
0.050	-1.042	0.100	0.047	-0.015	0.050	-17.78	0.050	0.009	0.100	0.013	-0.004	0.014	-15.52
0.100	-1.000	0.200	0.055	-0.019	0.058	-19.48	0.100	-0.155	0.200	0.027	-0.015	0.031	-29.29
0.150	-1.027	0.300	0.119	-0.084	0.146	-35.11	0.150	-0.253	0.300	0.033	-0.015	0.037	-24.86
0.200	-1.007	0.350	-0.206	0.421	0.469	116.02	0.200	-0.339	0.400	0.037	-0.022	0.043	-30.41
0.250	-0.963	0.400	-0.041	-0.004	0.042	-174.96	0.250	-0.362	0.500	0.035	-0.018	0.039	-27.44
0.300	-0.896	0.450	-0.029	-0.027	0.039	-136.91	0.300	-0.364	0.600	0.028	-0.008	0.029	-16.50
0.325	-0.843	0.500	-0.057	-0.008	0.058	-171.66	0.350	-0.359	0.700	0.006	-0.011	0.013	-63.44
0.350	-0.613	0.600	-0.029	0.008	0.030	165.17	0.400	-0.343	0.800	0.003	-0.010	0.011	-71.56
0.375	-0.529	0.650	-0.049	0.001	0.049	179.01	0.450	-0.303	0.970	-0.004	-0.003	0.005	-141.34
0.400	-0.532	0.690	-0.043	-0.008	0.044	-169.51	0.500	-0.231					
0.425	-0.537	0.730	-0.018	-0.034	0.038	-117.70	0.550	-0.114					
0.450	-0.551	0.750	-0.029	-0.008	0.030	-165.53	0.600	0.006					
0.475	-0.575	0.800	-0.027	-0.014	0.031	-152.78	0.650	0.104					
0.500	-0.604	0.970	-0.006	-0.007	0.009	-129.81	0.700	0.164					
0.550	-0.569						0.750	0.238					
0.600	-0.530						0.800	0.275					
0.650	-0.481												
0.720	-0.415												
0.760	-0.342												
0.800	-0.267												
0.830	-0.209												
0.950	-0.014												
0.970	0.049												
1.000	0.060												

| | STEADY | UNSTEADY | |
		REAL	IMAG	
CL	0.4700	0.0261	-0.0130	UNCORRECTED
CM	-0.0596	-0.0115	0.0021	

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   9

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 116

M   0.780   PTOT   0.900 BAR   K   0.377   DELTM   0.0 DEG.
ALPHA   2.000 DEG.   QINF   0.256 BAR   FREQ   21.0 HZ
RE   0.165D+08   TO   319.150 DEG. K   Y/S   0.665

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | | ----------- CPU/RAD ----------- | | | | | | ----------- CPL/RAD ----------- | | |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REA	IMAG	MAG	PHASE
0.020	-0.893	0.050	0.048	-0.027	0.055	-29.86	0.0	0.747	0.050	-0.009	-0.001	0.010	-175.91
0.050	-0.967	0.100	0.067	-0.019	0.070	-15.87	0.050	-0.057	0.100	0.007	-0.033	0.033	-78.69
0.100	-0.996	0.200	0.049	-0.047	0.068	-43.58	0.100	-0.142	0.200	0.041	-0.012	0.043	-15.52
0.150	-1.008	0.300	0.186	-0.219	0.287	-49.68	0.150	-0.256	0.300	0.044	-0.055	0.071	-51.12
0.200	-0.960	0.350	0.083	0.337	0.347	76.16	0.200	-0.338	0.400	0.048	-0.024	0.053	-26.57
0.250	-0.936	0.400	0.011	0.052	0.053	77.47	0.250	-0.366	0.500	0.066	-0.038	0.076	-30.17
0.300	-0.757	0.450	-0.055	0.052	0.076	136.59	0.300	-0.366	0.600	-0.005	-0.012	0.013	-113.20
0.325	-0.623	0.500	0.006	0.045	0.046	82.18	0.350	-0.358	0.700	0.024	-0.024	0.035	-45.00
0.350	-0.525	0.600	-0.091	-0.067	0.113	-143.93	0.400	-0.345	0.800	0.017	-0.017	0.025	-45.00
0.375	-0.529	0.680	-0.013	-0.022	0.026	-120.96	0.450	-0.310	0.870	0.011	-0.011	0.016	-45.00
0.400	-0.555	0.700	-0.004	-0.023	0.023	-99.09	0.500	-0.241	0.950	0.010	-0.010	0.014	-45.00
0.425	-0.569	0.730	-0.054	-0.019	0.057	-160.97	0.600	0.006					
0.450	-0.590	0.810	-0.048	-0.010	0.049	-167.69	0.650	0.101					
0.475	-0.612	0.870	-0.024	-0.011	0.027	-155.22	0.700	0.181					
0.500	-0.643	0.910	-0.028	-0.015	0.031	-151.70	0.750	0.236					
0.600	-0.499	0.930	-0.026	-0.011	0.028	-156.04	0.850	0.296					
0.630	-0.481	0.950	0.0	0.0	0.0	0.0	0.910	0.292					
0.680	-0.483						0.950	0.265					
0.720	-0.416												
0.760	-0.344												
0.800	-0.272												
0.830	-0.215												
0.910	-0.092												
0.930	-0.013												
0.970	0.018												
1.000	0.058												

| | STEADY | UNSTEADY | |
		REAL	IMAG	
CL	0.4929	0.0155	-0.0094	UNCORRECTED
CM	-0.0893	-0.0140	0.0032	

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 11

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 116

M   0.780   PTOT   0.900 BAR   K   0.377   DELTM   0.0 DEG.
ALPHA   2.000 DEG.   QINF   0.256 BAR   FREQ   21.0 HZ
RE   0.165D+08   TO   319.150 DEG. K   Y/S   0.751

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | ----------- CPU/RAD ----------- | | | | ----------- CPL/RAD ----------- |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.100	-0.966	0.050	0.064	-0.015	0.066	-12.80	0.0	0.620	0.050	0.078	-0.032	0.085	-22.29
0.200	-0.880	0.100	0.077	-0.005	0.077	-3.61	0.050	-0.085	0.100	0.084	-0.032	0.090	-20.49
0.250	-0.747	0.200	0.173	0.107	0.203	31.74	0.100	-0.186	0.200	0.053	0.013	0.055	13.43
0.300	-0.589	0.300	0.245	-0.083	0.259	-18.63	0.200	-0.355	0.300	0.111	-0.036	0.117	-17.92
0.325	-0.588	0.350	0.016	0.028	0.032	59.66	0.250	-0.383	0.400	0.096	-0.005	0.096	-3.22
0.350	-0.600	0.400	-0.034	0.083	0.089	112.62	0.300	-0.380	0.500	0.131	-0.033	0.135	-14.14
0.375	-0.618	0.450	-0.101	0.080	0.129	141.45	0.350	-0.363	0.600	0.056	0.018	0.058	17.88
0.400	-0.628	0.500	-0.099	0.178	0.204	118.97	0.400	-0.330	0.700	0.121	-0.017	0.122	-8.13
0.425	-0.641	0.600	-0.065	-0.032	0.072	-153.79	0.450	-0.306	0.800	0.145	-0.029	0.148	-11.40
0.450	-0.643	0.630	-0.092	-0.011	0.093	-173.13	0.500	-0.244	0.910	0.094	-0.012	0.094	-7.13
0.475	-0.652	0.680	-0.059	-0.014	0.061	-167.12	0.550	-0.107	0.950	0.078	-0.006	0.079	-4.33
0.500	-0.668	0.700	-0.042	-0.024	0.048	-149.74	0.600	-0.001					
0.550	-0.523	0.730	-0.026	-0.028	0.038	-132.88	0.700	0.178					
0.600	-0.539	0.750	-0.015	-0.034	0.037	-113.81	0.750	0.233					
0.634	-0.506	0.800	-0.002	-0.037	0.037	-92.94	0.910	0.291					
0.680	-0.453	0.910	0.024	-0.014	0.028	-31.33	0.950	0.266					
0.720	-0.397	0.930	0.029	-0.007	0.029	-13.50							
0.800	-0.265	0.950	0.021	-0.007	0.023	-18.43							
0.830	-0.219	0.970	0.023	-0.005	0.023	-12.26							
0.910	-0.058												
0.950	-0.009												
0.970	0.026												
1.000	0.079												

		STEADY	UNSTEADY		
			REAL	IMAG	
		-------	-------	-------	
CL	0.3864	0.0680	-0.0304	UNCORRECTED
CM	-0.1044	-0.0337	0.0029	

TABLE 8. 6 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 13

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 116

M   0.780   PTOT   0.900 BAR   K   0.377   DELTM   0.0 DEG.
ALPHA   2.000 DEG.   QINF   0.256 BAR   FREQ   21.0 HZ
RE   0.165D+08   TO   319.150 DEG. K   Y/S   0.854

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

| | | ----------- CPU/RAD ----------- | | | | ----------- CPL/RAD ----------- |
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	-0.219	0.050	0.114	0.060	0.129	27.93	0.0	0.701	0.050	0.159	-0.095	0.185	-30.71
0.020	-0.692	0.100	0.139	0.161	0.213	49.08	0.010	0.334	0.100	0.184	-0.087	0.204	-25.18
0.030	-0.742	0.200	-0.026	0.278	0.279	95.32	0.030	-0.090	0.200	0.241	-0.088	0.257	-20.08
0.050	-0.810	0.300	-0.185	0.030	0.187	170.66	0.050	-0.207	0.300	0.345	-0.079	0.354	-12.84
0.100	-0.878	0.350	0.022	0.097	0.099	77.28	0.200	-0.372	0.400	0.437	-0.057	0.440	-7.49
0.150	-0.737	0.400	-0.064	0.097	0.116	123.46	0.300	-0.389	0.500	0.532	-0.020	0.533	-2.16
0.200	-0.725	0.450	-0.197	0.160	0.254	140.80	0.400	-0.324	0.600	0.708	0.042	0.709	3.42
0.250	-0.647	0.500	-0.427	0.245	0.492	150.18	0.500	-0.214	0.800	1.116	0.183	1.131	9.34
0.300	-0.626	0.650	-0.786	-0.035	0.787	-177.48	0.600	-0.071					
0.350	-0.584	0.700	-1.095	-0.074	1.097	-176.11	0.700	0.140					
0.375	-0.590	0.720	-1.420	-0.108	1.424	-175.63	0.800	0.267					
0.400	-0.597	0.820	-1.431	-0.269	1.456	-169.34	0.850	0.296					
0.425	-0.597	0.910	-0.166	-0.153	0.226	-137.21	0.900	0.297					
0.450	-0.580	0.950	-0.028	-0.082	0.086	-109.09	0.950	0.264					
0.475	-0.565												
0.500	-0.560												
0.575	-0.485												
0.600	-0.448												
0.650	-0.404												
0.675	-0.358												
0.700	-0.349												
0.750	-0.285												
0.800	-0.287												
0.850	-0.212												
0.900	-0.120												
0.950	-0.021												
1.000	0.083												

		STEADY	UNSTEADY		
			REAL	IMAG	
		-------	-------	-------	
CL	0.3783	0.9470	-0.0234	UNCORRECTED
CM	-0.0873	-0.3906	-0.0474	

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   4

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 140

M	0.830		PTOT	0.900 BAR		K	0.355		DELTM	-2.0 DEG.
ALPHA	0.0 DEG.		QINF	0.275 BAR		FREQ	21.0 HZ			
RE	0.169D+08		TO	321.550 DEG. K		Y/S	0.479			

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA			UNSTEADY DATA					STEADY DATA			UNSTEADY DATA			
				----------- CPU/RAD ------------								----------- CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE		X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.506	0.050	0.005	0.007	0.009	52.12		0.0	0.792	0.050	0.047	-0.009	0.048	-10.71
0.050	-0.588	0.100	0.051	0.017	0.053	18.14		0.050	-0.194	0.100	0.042	-0.002	0.042	-3.18
0.100	-0.610	0.200	0.064	-0.007	0.064	-5.91		0.100	-0.397	0.200	0.031	-0.010	0.032	-18.43
0.200	-0.706	0.300	0.035	0.002	0.035	3.90		0.200	-0.644	0.300	0.030	-0.001	0.030	-1.19
0.250	-0.747	0.350	0.037	0.011	0.039	16.78		0.250	-0.718	0.400	-0.174	0.037	0.178	168.15
0.300	-0.758	0.400	0.062	0.008	0.062	6.97		0.300	-0.778	0.500	0.025	-0.026	0.036	-46.24
0.325	-0.753	0.450	0.002	0.015	0.015	82.23		0.350	-0.842	0.600	0.034	-0.037	0.051	-47.39
0.350	-0.745	0.500	0.039	0.003	0.039	4.24		0.400	-0.878	0.700	0.006	-0.039	0.040	-80.96
0.375	-0.744	0.600	0.211	-0.119	0.242	-29.45		0.450	-0.366	0.800	0.052	-0.054	0.075	-45.99
0.400	-0.692	0.650	-0.084	0.196	0.213	113.11		0.500	-0.230	0.930	0.024	0.034	0.042	54.46
0.425	-0.699	0.690	-0.031	0.013	0.034	156.80		0.550	-0.116	0.970	0.036	0.024	0.044	33.69
0.450	-0.721	0.700	0.008	0.012	0.014	56.31		0.600	-0.014					
0.500	-0.738	0.730	-0.012	0.008	0.015	145.30		0.650	0.061					
0.550	-0.746	0.750	-0.012	-0.073	0.074	-99.57		0.700	0.111					
0.600	-0.654	0.930	0.010	-0.003	0.010	-15.26		0.750	0.168					
0.650	-0.392	0.950	0.004	-0.004	0.006	-38.66		0.800	0.222					
0.720	-0.401	0.970	0.019	-0.002	0.019	-6.01		0.910	0.271					
0.800	-0.228							0.950	0.255					
0.910	-0.035													
0.950	0.023													
0.970	0.058													
1.000	0.098													

		STEADY	UNSTEADY		
			REAL	IMAG	
		-------	-------	-------	UNCORRECTED
CL		0.2842	-0.0289	0.0075	
CM		-0.0886	0.0021	-0.0064	

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   6

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX : 140

M	0.830		PTOT	0.900 BAR		K	0.355		DELTM	-2.0 DEG.
ALPHA	0.0 DEG.		QINF	0.275 BAR		FREQ	21.0 HZ			
RE	0.169D+08		TO	321.550 DEG. K		Y/S	0.566			

----------------------< UPPER SURFACE >----------------------   ----------------------< LOWER SURFACE >----------------------

STEADY DATA			UNSTEADY DATA					STEADY DATA			UNSTEADY DATA			
				----------- CPU/RAD ------------								----------- CPL/RAD ------------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE		X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.401	0.050	-0.086	-0.008	0.086	-174.97		0.0	0.793	0.050	0.017	-0.089	0.090	-79.41
0.050	-0.459	0.100	0.030	-0.007	0.031	-13.32		0.050	-0.264	0.100	0.084	-0.071	0.110	-40.24
0.100	-0.537	0.200	0.013	-0.042	0.044	-72.70		0.100	-0.458	0.200	0.065	-0.064	0.092	-44.66
0.150	-0.504	0.300	0.008	-0.061	0.062	-82.50		0.200	-0.678	0.300	0.093	-0.100	0.137	-47.08
0.200	-0.685	0.350	-0.005	-0.079	0.079	-93.37		0.250	-0.776	0.400	0.368	0.006	0.368	0.92
0.250	-0.758	0.400	-0.028	-0.085	0.089	-108.43		0.300	-0.822	0.500	0.066	0.021	0.070	17.65
0.300	-0.773	0.450	-0.074	-0.089	0.116	-129.55		0.350	-0.853	0.600	0.066	0.001	0.066	0.81
0.325	-0.742	0.500	-0.129	-0.237	0.270	-118.42		0.400	-0.461	0.700	0.016	-0.073	0.075	-77.54
0.350	-0.725	0.600	0.731	-0.907	1.165	-51.14		0.450	-0.353	0.800	-0.005	-0.125	0.125	-92.40
0.375	-0.739	0.630	0.417	0.015	0.418	2.07		0.500	-0.254	0.870	0.015	-0.093	0.094	-80.80
0.400	-0.738	0.690	0.523	0.379	0.646	35.91		0.550	-0.126	0.910	0.011	-0.080	0.081	-82.30
0.425	-0.712	0.700	0.386	0.323	0.503	39.91		0.600	-0.014	0.950	0.038	-0.036	0.052	-43.49
0.450	-0.707	0.730	0.208	0.274	0.344	52.86		0.650	0.071					
0.475	-0.709	0.750	0.125	0.224	0.256	60.77		0.700	0.132					
0.500	-0.699	0.910	0.021	0.075	0.078	74.29		0.750	0.183					
0.550	-0.495	0.950	0.071	0.051	0.088	35.42		0.800	0.221					
0.600	-0.407	0.970	0.098	0.057	0.113	30.43		0.850	0.242					
0.650	-0.403													
0.740	-0.379													
0.780	-0.292													
0.820	-0.214													
0.910	-0.044													
0.950	0.023				STEADY	UNSTEADY								
0.970	0.054					REAL	IMAG							
1.000	0.087				-------	-------	-------	UNCORRECTED						

CL		0.2226	-0.0251	0.0088	
CM		-0.0730	0.0295	0.0122	

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   8

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 140

M	0.830		PTOT	0.900 BAR		K	0.355		DELTM	-2.0 DEG.
ALPHA	0.0 DEG.		QINF	0.275 BAR		FREQ	21.0 HZ			
RE	0.169D+08		TO	321.550 DEG. K		Y/S	0.618			

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

			----------- CPU/RAD -----------						----------- CPL/RAD -----------	
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.347	0.050	-0.045	-0.235	0.240	-100.83	0.0	0.789	0.050	0.167	0.060	0.177	19.77
0.050	-0.463	0.100	0.076	-0.052	0.092	-34.70	0.050	-0.300	0.100	0.107	0.034	0.112	17.56
0.100	-0.522	0.200	0.099	-0.141	0.173	-55.04	0.100	-0.446	0.200	0.123	0.021	0.125	9.74
0.150	-0.582	0.300	0.127	-0.137	0.187	-47.34	0.150	-0.560	0.300	0.190	0.076	0.204	21.80
0.200	-0.663	0.350	0.136	-0.171	0.219	-51.54	0.200	-0.676	0.400	0.011	0.194	0.195	86.70
0.250	-0.726	0.400	0.147	-0.203	0.251	-54.12	0.250	-0.794	0.500	-0.002	-0.030	0.030	-93.58
0.300	-0.719	0.450	0.648	-0.301	0.714	-24.89	0.300	-0.832	0.600	0.023	-0.053	0.058	-66.43
0.325	-0.724	0.500	1.213	-0.454	1.295	-20.54	0.350	-0.787	0.700	-0.008	0.051	0.051	98.97
0.350	-0.731	0.600	-0.060	0.807	0.809	94.24	0.400	-0.440	0.800	0.013	0.050	0.051	75.53
0.375	-0.714	0.650	-0.261	0.604	0.658	113.37	0.450	-0.380	0.970	-0.024	0.077	0.081	107.58
0.400	-0.720	0.690	-0.634	0.960	1.150	123.43	0.500	-0.277					
0.425	-0.713	0.730	-0.386	0.137	0.410	160.43	0.550	-0.144					
0.450	-0.695	0.750	-0.257	0.161	0.304	147.87	0.600	-0.018					
0.475	-0.570	0.800	-0.197	0.073	0.210	159.81	0.650	0.072					
0.500	-0.455	0.970	-0.107	0.058	0.122	151.43	0.700	0.121					
0.550	-0.438						0.750	0.183					
0.600	-0.455						0.800	0.225					
0.650	-0.444												
0.720	-0.392												
0.760	-0.317												
0.800	-0.243												
0.830	-0.186												
0.950	0.009												
0.970	0.054												
1.000	0.085												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------	
CL	0.1947	-0.0327	-0.0030	UNCORRECTED
CM	-0.0632	-0.0107	0.0347	

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION   9

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 140

M	0.830		PTOT	0.900 BAR		K	0.355		DELTM	-2.0 DEG.
ALPHA	0.0 DEG.		QINF	0.275 BAR		FREQ	21.0 HZ			
RE	0.169D+08		TO	321.550 DEG. K		Y/S	0.665			

---------------------< UPPER SURFACE >---------------------   ---------------------< LOWER SURFACE >---------------------

STEADY DATA   UNSTEADY DATA   STEADY DATA   UNSTEADY DATA

			----------- CPU/RAD -----------						----------- CPL/RAD -----------	
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.020	-0.306	0.050	0.054	-0.053	0.076	-44.56	0.0	0.789	0.050	0.001	0.021	0.021	88.32
0.050	-0.466	0.100	0.037	-0.028	0.046	-36.42	0.050	-0.395	0.100	0.046	0.018	0.050	21.54
0.100	-0.506	0.200	0.067	-0.021	0.070	-17.68	0.100	-0.433	0.200	-0.004	-0.041	0.041	-95.01
0.150	-0.623	0.300	0.042	-0.009	0.043	-11.50	0.150	-0.597	0.300	0.056	-0.055	0.079	-44.43
0.200	-0.680	0.350	0.037	-0.011	0.039	-16.26	0.200	-0.687	0.400	0.145	-0.212	0.257	-55.68
0.250	-0.678	0.400	-0.032	-0.027	0.042	-139.40	0.250	-0.788	0.500	0.119	-0.054	0.131	-24.34
0.300	-0.581	0.450	0.063	0.413	0.418	81.38	0.300	-0.830	0.600	0.031	-0.069	0.076	-65.66
0.325	-0.628	0.500	-0.737	-0.044	0.739	-176.59	0.350	-0.722	0.700	0.035	-0.043	0.056	-51.23
0.350	-0.668	0.600	0.168	-0.264	0.313	-57.48	0.400	-0.470	0.800	0.037	-0.034	0.051	-42.58
0.375	-0.676	0.680	0.128	-0.200	0.237	-57.41	0.450	-0.400	0.870	0.029	-0.034	0.045	-49.03
0.400	-0.646	0.700	0.151	-0.151	0.214	-45.00	0.500	-0.286	0.950	0.028	-0.041	0.050	-55.98
0.425	-0.650	0.730	0.111	-0.068	0.130	-31.68	0.600	-0.021					
0.450	-0.540	0.810	0.047	-0.033	0.058	-35.26	0.650	0.067					
0.475	-0.497	0.870	0.037	-0.035	0.051	-42.93	0.700	0.131					
0.500	-0.509	0.910	0.043	-0.031	0.053	-35.79	0.750	0.181					
0.600	-0.479	0.930	0.038	-0.041	0.056	-46.93	0.850	0.259					
0.630	-0.473	0.950	0.002	0.008	0.009	79.70	0.910	0.274					
0.680	-0.511						0.950	0.257					
0.720	-0.408												
0.760	-0.322												
0.800	-0.249												
0.830	-0.195												
0.910	-0.072												
0.930	0.010												
0.970	0.042												
1.000	0.080												

	STEADY	UNSTEADY	
		REAL	IMAG	
	-------	-------	-------	
CL	0.2204	0.0547	-0.0105	UNCORRECTED
CM	-0.0913	-0.0115	-0.0036	

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

```
WING MODEL  : ZKP          HALFSPAN : 4.0161 M                                              SECTION 11

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :  140

M       0.830              PTOT    0.900 BAR          K     0.355              DELTM  -2.0 DEG.
ALPHA   0.0  DEG.          QINF    0.275 BAR          FREQ  21.0 HZ
RE   0.169D+08             TO   321.550 DEG. K        Y/S   0.751
```

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
				---- CPU/RAD ----						---- CPL/RAD ----		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.100	-0.475	0.050	0.117	-0.018	0.119	-8.75	0.0	0.788	0.050	0.019	-0.095	0.097	-78.69
0.200	-0.607	0.100	0.087	-0.036	0.094	-22.23	0.050	-0.478	0.100	0.019	-0.077	0.079	-76.10
0.250	-0.544	0.200	0.091	-0.063	0.110	-34.77	0.100	-0.495	0.200	0.101	-0.038	0.108	-20.56
0.300	-0.514	0.300	0.021	-0.213	0.214	-84.48	0.200	-0.709	0.300	0.091	-0.139	0.166	-56.83
0.325	-0.492	0.350	0.161	-0.225	0.277	-54.42	0.250	-0.819	0.400	0.316	-0.101	0.332	-17.78
0.350	-0.499	0.400	0.194	-0.176	0.262	-42.20	0.300	-0.868	0.500	0.219	-0.062	0.228	-15.68
0.375	-0.496	0.450	0.129	-0.021	0.131	-9.04	0.350	-0.802	0.600	0.113	-0.022	0.116	-10.82
0.400	-0.476	0.500	0.238	-0.040	0.241	-9.55	0.400	-0.442	0.700	0.159	-0.076	0.176	-25.56
0.425	-0.506	0.600	0.312	0.097	0.327	17.31	0.450	-0.377	0.800	0.199	-0.072	0.212	-19.98
0.450	-0.526	0.630	-0.025	0.090	0.093	105.42	0.500	-0.278	0.910	0.118	-0.033	0.122	-15.50
0.475	-0.560	0.680	-0.225	0.155	0.273	145.39	0.550	-0.143	0.950	0.113	-0.020	0.115	-10.01
0.500	-0.629	0.700	-0.285	0.106	0.304	159.68	0.600	-0.032					
0.550	-0.590	0.730	-0.149	0.0	0.149	180.00	0.700	0.126					
0.600	-0.519	0.750	-0.082	-0.031	0.088	-159.09	0.750	0.175					
0.634	-0.480	0.800	-0.029	-0.053	0.060	-119.22	0.910	0.272					
0.680	-0.459	0.910	0.020	-0.027	0.033	-53.13	0.950	0.259					
0.720	-0.372	0.930	0.024	-0.031	0.039	-51.58							
0.800	-0.234	0.950	0.033	-0.019	0.038	-29.54							
0.830	-0.191	0.970	0.044	-0.007	0.045	-9.46							
0.910	-0.037												
0.950	0.014												
0.970	0.050												
1.000	0.103												

```
                          STEADY      UNSTEADY
                   |        |  REAL  |  IMAG  |
                   | ------ | ------ | ------ |   UNCORRECTED
                CL | 0.1387 | 0.0689 | -0.0232 |
                CM | -0.0961 | -0.0352 | 0.0119 |
```

```
WING MODEL  : ZKP          HALFSPAN : 4.0161 M                                              SECTION 13

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   :  140

M       0.830              PTOT    0.900 BAR          K     0.355              DELTM  -2.0 DEG.
ALPHA   0.0  DEG.          QINF    0.275 BAR          FREQ  21.0 HZ
RE   0.169D+08             TO   321.550 DEG. K        Y/S   0.854
```

--------------------< UPPER SURFACE >--------------------   --------------------< LOWER SURFACE >--------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
				---- CPU/RAD ----						---- CPL/RAD ----		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.242	0.050	0.199	-0.041	0.203	-11.63	0.0	0.815	0.050	0.078	-0.133	0.154	-59.55
0.020	-0.132	0.100	0.183	-0.041	0.187	-12.65	0.010	-0.050	0.100	0.155	-0.085	0.177	-28.69
0.030	-0.222	0.200	0.252	-0.039	0.255	-8.84	0.030	-0.549	0.200	0.141	-0.177	0.226	-51.57
0.050	-0.332	0.300	0.170	0.069	0.183	22.07	0.050	-0.678	0.300	0.283	-0.373	0.469	-52.81
0.100	-0.385	0.350	0.139	0.096	0.169	34.51	0.200	-0.733	0.400	0.695	-0.044	0.696	-3.62
0.150	-0.508	0.400	0.119	0.113	0.164	43.45	0.300	-0.870	0.500	0.668	0.009	0.669	0.74
0.200	-0.444	0.450	0.071	0.196	0.208	70.10	0.400	-0.420	0.600	0.746	0.082	0.750	6.31
0.250	-0.474	0.500	-0.278	0.485	0.559	119.79	0.500	-0.268	0.800	1.192	0.124	1.198	5.93
0.300	-0.470	0.650	-1.007	0.025	1.008	178.57	0.600	-0.099					
0.350	-0.470	0.700	-1.237	-0.087	1.240	-175.99	0.700	0.082					
0.375	-0.489	0.720	-1.484	-0.120	1.489	-175.38	0.800	0.184					
0.400	-0.497	0.820	-1.740	-0.362	1.777	-168.25	0.850	0.223					
0.425	-0.531	0.910	-0.203	-0.165	0.262	-140.98	0.900	0.242					
0.450	-0.557	0.950	0.238	-0.104	0.260	-23.68	0.950	0.237					
0.475	-0.559												
0.500	-0.578												
0.575	-0.455												
0.600	-0.408												
0.650	-0.356												
0.675	-0.299												
0.700	-0.277												
0.750	-0.194												
0.800	-0.200												
0.850	-0.165												
0.900	-0.093												
0.950	-0.003												
1.000	0.115												

```
                          STEADY      UNSTEADY
                   |        |  REAL  |  IMAG  |
                   | ------ | ------ | ------ |   UNCORRECTED
                CL | 0.0591 | 0.9473 | -0.0465 |
                CM | -0.0828 | -0.4320 | -0.0320 |
```

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 14

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 140

M 0.830	PTOT 0.900 BAR	K 0.355	DELTM -2.0 DEG.
ALPHA 0.0 DEG.	QINF 0.275 BAR	FREQ 21.0 HZ	
RE 0.169D+08	TO 321.550 DEG. K	Y/S 0.885	

-------------------< UPPER SURFACE >-------------------   -------------------< LOWER SURFACE >-------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -----------						----------- CPL/RAD -----------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.271	0.050	0.296	-0.028	0.297	-5.45	0.0	0.816	0.050	0.078	-0.037	0.086	-25.20
0.020	0.002	0.100	0.218	0.015	0.218	3.92	0.010	-0.045	0.100	0.064	-0.107	0.125	-58.98
0.030	-0.151	0.140	0.425	0.097	0.436	12.80	0.030	-0.634	0.200	0.174	-0.080	0.192	-24.70
0.050	-0.281	0.200	0.185	0.092	0.207	26.35	0.050	-0.793	0.300	0.209	-0.089	0.227	-23.03
0.100	-0.376	0.250	0.217	0.181	0.282	39.91	0.300	-0.924	0.400	0.976	-0.309	1.023	-17.55
0.200	-0.451	0.300	0.160	0.212	0.266	52.98	0.400	-0.413	0.500	0.926	0.049	0.927	3.01
0.250	-0.442	0.350	0.105	0.258	0.279	67.85	0.500	-0.304	0.700	1.025	0.162	1.037	9.01
0.300	-0.457	0.400	-0.088	0.355	0.366	103.84	0.600	-0.129	0.850	1.243	0.216	1.262	9.85
0.350	-0.465	0.450	-0.519	0.428	0.673	140.51	0.700	0.083					
0.375	-0.440	0.500	-0.790	0.169	0.808	167.93	0.800	0.177					
0.400	-0.448	0.550	-0.970	-0.030	0.971	-178.21	0.850	0.216					
0.425	-0.472	0.600	-1.315	0.296	1.347	167.30	0.900	0.233					
0.450	-0.490	0.700	-2.390	-0.280	2.407	-173.32	0.950	0.234					
0.475	-0.478	0.800	-2.561	-0.464	2.603	-169.73							
0.500	-0.461	0.900	-0.053	-0.411	0.415	-97.39							
0.525	-0.450												
0.550	-0.416												
0.575	-0.375												
0.600	-0.320												
0.625	-0.285												
0.675	-0.269												
0.700	-0.271												
0.750	-0.204												
0.850	-0.156												
0.900	-0.082												
0.950	0.006												
1.000	0.111												

	STEADY	UNSTEADY	
		REAL	IMAG
	-------	-------	-------
CL	-0.0637	1.2937	-0.0052	UNCORRECTED
CM	-0.0795	-0.5628	-0.0626

TABLE 8. 7 STEADY AND UNSTEADY PRESSURE DISTRIBUTION, ZKP

WING MODEL : ZKP   HALFSPAN : 4.0161 M   SECTION 15

WING MOTION : AILERON ROTAT., HARMONIC

RUN INDEX   : 140

M 0.830	PTOT 0.900 BAR	K 0.355	DELTM -2.0 DEG.
ALPHA 0.0 DEG.	QINF 0.275 BAR	FREQ 21.0 HZ	
RE 0.169D+08	TO 321.550 DEG. K	Y/S 0.944	

-------------------< UPPER SURFACE >-------------------   -------------------< LOWER SURFACE >-------------------

STEADY DATA		UNSTEADY DATA				STEADY DATA		UNSTEADY DATA			
			----------- CPU/RAD -----------						----------- CPL/RAD -----------		
X/C	CPU	X/C	REAL	IMAG	MAG	PHASE	X/C	CPL	X/C	REAL	IMAG	MAG	PHASE
0.010	0.506	0.050	0.175	0.079	0.192	24.44	0.0	0.818	0.050	0.154	-0.152	0.216	-44.61
0.020	0.093	0.100	0.136	0.109	0.174	38.58	0.030	-0.129	0.100	0.293	-0.429	0.520	-55.67
0.030	-0.071	0.140	0.098	0.100	0.140	45.69	0.100	-0.826	0.200	0.312	-0.094	0.326	-16.79
0.050	-0.254	0.200	0.037	0.135	0.140	74.64	0.200	-0.702	0.400	0.281	0.260	0.383	42.79
0.100	-0.394	0.250	-0.042	0.144	0.150	106.19	0.300	-0.849	0.500	1.008	0.205	1.029	11.47
0.150	-0.405	0.300	-0.136	0.150	0.202	132.31	0.400	-0.297	0.600	1.736	0.047	1.737	1.56
0.200	-0.398	0.350	-0.232	0.166	0.285	144.54	0.500	-0.298	0.700	1.234	0.211	1.252	9.69
0.250	-0.388	0.400	-0.309	0.149	0.343	154.24	0.600	-0.150	0.800	1.546	0.360	1.587	13.10
0.300	-0.393	0.450	-0.460	0.131	0.478	164.05	0.700	0.030	0.850	0.773	0.284	0.823	20.15
0.350	-0.388	0.500	-0.712	0.062	0.715	175.04	0.800	0.171					
0.375	-0.396	0.550	-0.627	0.041	0.628	176.22	0.850	0.199					
0.400	-0.373	0.600	-0.749	-0.016	0.750	-178.74	0.900	0.204					
0.425	-0.387	0.650	-0.893	-0.108	0.900	-173.11	0.950	0.174					
0.450	-0.393	0.700	-0.992	-0.199	1.012	-168.67							
0.475	-0.403	0.850	-1.317	-0.326	1.357	-166.11							
0.500	-0.409	0.900	-0.363	-0.209	0.419	-150.10							
0.525	-0.376												
0.575	-0.362												
0.600	-0.337												
0.650	-0.309												
0.675	-0.296												
0.700	-0.281												
0.750	-0.256												
0.800	-0.258												
0.850	-0.193												
0.900	-0.132												
0.950	-0.048												
1.000	0.064												

	STEADY	UNSTEADY	
		REAL	IMAG
	-------	-------	-------
CL	0.0265	1.0889	0.0885	UNCORRECTED
CM	-0.0725	-0.4171	-0.0857

FIG. 8.1 Model set-up in test section, side view

FIG. 8.2 Model set-up in test section, head-on view

FIG. 8.3 Geometry of experimental ZKP model

Half-Wing Area	3.5989	m²
Half-Wing Span	4.0161	m
MAC	1.0415	m
Aspect Ratio	9	
Sweep of 1/4 Chord	28°	
Dihedral	4.787°	

FIG. 8.4 Geometry of experimental ZKP wing,
rotated into profile-coordinate plane
by dihedral angle φ = 4.787 deg

FIG. 8.5   Aileron geometry in cross-section
           at wing section 14

Steady press. taps			Unsteady press. taps		
Section	η	Number	Section	η	Number
DV1	0.250	45	K1	0.254	31
DV2	0.357	45	K2	0.353	31
DV3	0.450	3	K3	0.450	19
DV4	0.483	58	K4	0.479	32
DV5	0.528	2	K5	0.528	19
DV6	0.573	53	K6	0.569	34
DV7	0.588	3	K7	0.584	5
DV8	0.618	52	K8	0.618	31
DV9	0.669	55	K9	0.665	37
DV10	0.703	2	K10	0.700	20
DV11	0.755	54	K11	0.751	35
DV12	0.800	2	K12	0.800	19
DV13	0.850	45	K13	0.854	26
DV14	0.889	45	K14	0.885	23
DV15	0.940	45	K15	0.944	23

FIG. 8.6   Pressure taps, spanwise location

FIG. 8.7   Accelerometers, spanwise location

UNSTEADY

UPPER SURFACE 13   LOWER SURFACE 13

STEADY SECTION 13

Case	97	
M	0.78	
α_m	0.00	°
δ_m	0.00	°
δ_0	1.00	°
f	21.0	Hz

FIG. 8.8   Sample pressure distribution for aileron section

UNSTEADY

UPPER SURFACE 14

LOWER SURFACE 14

STEADY SECTION 14

Case	97	
M	0.78	
α_m	0.00	°
δ_m	0.00	°
δ_0	1.00	°
f	21.0	Hz

FIG. 8.9   Sample pressure distribution for aileron section

UNSTEADY

UPPER SURFACE 15

LOWER SURFACE 15

STEADY SECTION 15

Case	97	
M	0.78	
α_m	0.00	°
δ_m	0.00	°
δ_0	1.00	°
f	21.0	Hz

FIG. 8.10 Sample pressure distribution for aileron section

UNSTEADY

UPPER SURFACE 14   LOWER SURFACE 14

STEADY SECTION 14

Case	25	
M	0.50	
α_m	3.00	°
δ_m	0.00	°
δ_0	1.00	°
f	12.0	Hz

FIG. 8.11   Sample pressure distribution for aileron section

UNSTEADY

UPPER SURFACE 14

LOWER SURFACE 14

STEADY SECTION 14

Case	90	
M	0.78	
α_m	0.00	°
δ_m	-5.00	°
δ_0	1.00	°
f	21.0	Hz

FIG. 8.12   Sample pressure distribution for aileron section

UNSTEADY

UPPER SURFACE 14   LOWER SURFACE 14

STEADY SECTION 14

Case	116
M	0.78
α_m	2.00 °
δ_m	0.00 °
δ_0	1.00 °
f	21.0 Hz

FIG. 8.13 Sample pressure distribution for aileron section

UNSTEADY

UPPER SURFACE 14 LOWER SURFACE 14

STEADY SECTION 14

Case	140	
M	0.83	
α_m	0.00	°
δ_m	-2.00	°
δ_0	1.00	°
f	21.0	Hz

FIG. 8.14 Sample pressure distribution for aileron section

⊟	DELT = -0.73	CASE=96.
⊙	DELT = -0.73	CASE=94.
▷	DELT = -0.71	CASE=104.
+	DELT = -0.71	CASE=95.
✕	DELT = -0.70	CASE=143.
◇	DELT = -0.69	CASE=97.
⟡	DELT = -0.64	CASE=93.
⋈	DELT = -0.63	CASE=159.
N	DELT = -0.62	CASE=161.
⋎	DELT = -0.57	CASE=164.
⋈	DELT = -0.51	CASE=105.

⊟	DELT = -0.73	CASE=96.
⊙	DELT = -0.73	CASE=94.
▷	DELT = -0.71	CASE=95.
+	DELT = -0.69	CASE=97.
✕	DELT = -0.64	CASE=93.

M = 0.78 α_m = -0.01°   Y/S = 0.885

FIG. 8.15   Repeatability check for various cases

DATA SET 9

LANN WING. PITCHING OSCILLATION

by

Ir R.J.Zwaan,
Head of Aeroelasticity Dept.
National Aerospace Lab. NLR
P.O. Box 90502
1006 BM Amsterdam
The Netherlands

INTRODUCTION

This Data Set relates to a semi-span model of a transport-type wing with a supercritical aerofoil from root to tip (Fig. 9.1). The data were obtained during a co-operative programme of Lockheed-Georgia, Air Force Flight Dynamics Laboratory, NASA-Langley and NLR, through which the model received its name LANN model (Refs. 9.1, 9.2). One of the objectives of this programme, being of interest here, was to create an experimental data base for steady and unsteady transonic computer code evaluation.

The wing geometry was designed by Lockheed-Georgia, where the wing became known as wing A (Ref. 9.3). A smaller scale model was already tested in steady flow.

The mean test conditions are shown in Fig. 9.2. In view of the intended correlations of experimental and calculated data, the greater part of the test runs was carried out with attached flow. The results were presented in a revised form in Ref. 9.2. Examples of the mean steady and the unsteady pressure distributions are given in Fig. 9.3 and of spanwise load distributions in Fig. 9.4.

In Ref. 9.4 CT cases were proposed at a time when the test had still to be carried out. As all test runs were made at more or less different conditions, a modified set of CT cases is proposed in this Data Set. The modifications,however, leave the kind of parameter variations as foreseen in the original set of Ref. 9.4 practically unchanged. The modified cases have been used already as a basis for calculations at NLR with the so-called quasi-three-dimensional unsteady transonic method (Refs. 9.5, 9.6). From the correlation of experimental and calculated data it appears that the correlation can be made most appropriately for the pressure distributions. The correlation of sectional coefficients is hampered by less accurate experimental values caused by a number of failing pressure tubes (see Ref. 9.1, Part I) in regions of strong pressure gradients (shock, leading edge).

1   GENERAL DESCRIPTION OF MODEL

    1.1   Designation   LANN wing

    1.2   Type   Half model

    1.3   Derivation   Wing A, Ref. 9.3

    1.4   Additional remarks   –

    1.5   References   Ref. 9.1, Part I

2   MODEL GEOMETRY

    2.1   Planform   Tapered

    2.2   Aspect ratio   7.92

    2.3   Leading-edge sweep   27.493 deg

    2.4   Trailing-edge sweep   16.908 deg

    2.5   Taper ratio   0.4

    2.6   Twist   -4.8 deg

    2.7   Root chord   360.8 mm

    2.8   Span of model   1000 mm (tapered part, excluding tip fairing of 8.7 mm)

    2.9   Area of planform   0,2526 m^2 (idem)

    2.10   Location of reference   12% supercritical airfoil. Measured co-ordinates of 8
           sections and definition of   wing sections relative to model reference plane, are
           profiles   given in Table 9.1. For computational model see Table 5
                                       of Ref. 9.4.

2.11	Lofting procedure between reference sections	Linearly lofted from root to tip
2.12	Form of wing-body, or wing-root junction	No body; labyrinth at root
2.13	Form of wing tip	Actual model: tip fairing with radius equal to half tip aerofoil thickness Computational model: square cut at 1000 mm span
2.14	Control surface details	None
2.15	Additional remarks	-
2.16	References	Ref. 9.1, Part I

3 WIND TUNNELS

3.1	Designation	NLR High Speed Tunnel (HST)
3.2	Type of tunnel	Continuous, variable pressure
3.3	Test section dimensions	Height = 1.60 m, width = 2.00 m, length = 2.50 m
3.4	Type of roof and floor	Slotted, each having 4 whole slots and a ½ slot at each corner
3.5	Type of side walls	Solid
3.6	Ventilation geometry	Roof and floor are 12% open
3.7	Thickness of side wall boundary layer	About 7 mm
3.8	Thickness of boundary layers at roof and floor	-
3.9	Method of measuring Mach number	Derived from settling chamber stagnation and plenum chamber static pressures
3.10	Flow angularity	-
3.11	Uniformity of Mach number over test section	-
3.12	Sources and levels of noise or turbulence in empty tunnel	Less than 1% in rms p/q for M = 0.8
3.13	Tunnel resonances	No evidence of resonance in present test
3.14	Additional remarks	Information about flow angularity and Mach number uniformity available only along test section centre-line
3.15	References on tunnel	Ref. 9.7

4 MODEL MOTION

4.1	General description	Sinusoidal pitching about axis normal to wind tunnel side-wall. Axis location at x = 224.0 mm
4.2	Reference coordinate and definition of motion	Model displacements relative to displacement transducer (LVDT) at x = 101.5 mm, y = -200 mm. Intended rigid-body pitching influenced by elastic deformations at all test frequencies. See 4.8
4.3	Range of amplitude	0 to 1 deg. in streamwise plane, at the root
4.4	Range of frequency	0, 12, 24, 36, 48, 60, 72 Hz
4.5	Method of applying motion	Forced by hydraulic excitation
4.6	Timewise purity of motion	Adequate purity of sinusoid
4.7	Natural frequencies and normal modes of model and support system	First bending frequency at 30.6 Hz, second bending frequency at 104.5 Hz
4.8	Actual mode of applied motion including any elastic deformation	See tables 9.11 to 9.20 under "DISPLACEMENTS REL. TO LVDT". Variations of nodal line positions are shown in Fig. 9.5
4.9	Additional remarks	

5   TEST CONDITIONS

    5.1   Model planform area/   0.079
            tunnel area

    5.2   Model span/tunnel width   0.5

    5.3   Blockage   0.5%

    5.4   Position of model in tunnel   Standard side-wall position

    5.5   Range of Mach number   0.62, 0.72, 0.77, 0.82, 0.87, 0.95

    5.6   Range of tunnel total pressure   1.3 to 1.5 Kpa

    5.7   Range of tunnel total temperature   12 to 35° C

    5.8   Range of model steady, or mean,   0.6, 2.6, 3.0, 5.0 deg
            incidence

    5.9   Definition of model incidence   Model incidence defined relative to model reference
                                   plane

    5.10   Position of transition, if free   -

    5.11   Position and type of trip, if   5.4 mm behind leading edge at each side; width = 2 mm.
            transition fixed   Grit: 62 μm carborundum 220

    5.12   Flow instabilities during tests   None encountered

    5.13   Changes to mean shape of model   Not measured. Mean model deflections can be calculated
            due to steady aerodynamic load   using the spanwise stiffness distributions given in
                                     Ref. 9.1, Part I, App. C

    5.14   Additional remarks   -

    5.15   References describing tests   Ref. 9.1, Part I

6   MEASUREMENTS AND OBSERVATIONS

    6.1   Steady pressures for the mean conditions | √ |

    6.2   Steady pressures for small changes from the mean conditions | √ |

    6.3   Quasi-steady pressures | - |

    6.4   Unsteady pressures | √ |

    6.5   Steady section forces for the mean conditions by integration of pressures | √ |

    6.6   Steady section forces for small changes from the mean conditions by integration | √ |

    6.7   Quasi-steady section forces by integration | - |

    6.8   Unsteady section forces by integration | √ |

    6.9   Measurement of actual motion at points on model | √ |

    6.10   Observation or measurement of boundary layer properties | - |

    6.11   Visualization of surface flow | - |

    6.12   Visualization of shock wave movements | - |

    6.13   Additional remarks | - |

7   INSTRUMENTATION

    7.1   Steady pressure
           7.1.1 Position of orifices   See table 9.2
                    spanwise and chordwise

           7.1.2 Type of measuring system   Combination of 212 tubes and 22 miniature pressure
                                         transducers, measuring mean values and first harmonics
                                         (and higher, if necessary) of each pressure signal.
                                         See Fig. 9.6

    7.2   Unsteady pressures
           7.2.1 Position of orifices   See tables 9.2 and 9.3
                    spanwise and chordwise

7.2.2	Diameter of orifices	0.79 mm
7.2.3	Type of measuring system	See 7.1.2
7.2.4	Type of transducers	In scanning values: Statham type PM 131 TC In situ: Endevco type 8507-SMI
7.2.5	Principle and accuracy of calibration	Data acquisition system was calibrated daily, pressure transducers before and after wind tunnel test. Accuracy is 1%

7.3 Model motion

7.3.1	Method of measuring motion reference coordinate	Linear variable differential transducer Sangamo type AFG 5.0 S
7.3.2	Method of determining spatial mode of motion	Twelve accelerometers Endevco type 2220 C installed within model, of which eight operative. See table 9.4 and Fig. 9.6
7.3.3	Accuracy of measured motions	Accelerometers: response deviation at 50 Hz is 1% LVDT: better than 0.015 mm

7.4 Processing of unsteady measurements

7.4.1	Method of acquiring and processing measurements	See Fig. 9.7
7.4.2	Type of analysis	Averaging and determination of first and higher harmonics took place over signal lengths of 1s (steady) or about 1s with round-off to integral number of cycles (unsteady)
7.4.3	Unsteady pressure quantities obtained and accuracies achieved	Fundamental harmonics and occasionally second and third harmonics. For accuracy, see 9.1.6
7.4.4	Method of integration to obtain forces	Trapezoidal rule. For accuracy, see 9.9
7.5	Additional remarks	Temperature within model was measured by a Unicurve thermistor (accuracy $\pm 0.2^{\circ}$C)
7.6	References on techniques	Refs. 9.8, 9.9

8 DATA PRESENTATION

8.1	Test cases for which data could be made available	Tables 9.5 to 9.9
8.2	Test cases for which data are included in this document	Table 9.10
8.3	Steady pressures	Tables 9.11 to 9.24
8.4	Quasi-steady or steady perturbation pressures	Tables 9.21 to 9.24
8.5	Unsteady pressures	Tables 9.11 to 9.20
8.6	Steady forces or moments	Tables 9.11 to 9.24
8.7	Quasi-steady or steady perturbation forces	Tables 9.21 to 9.24
8.8	Unsteady forces and moments	Tables 9.11 to 9.20
8.9	Other forms in which data could be made available	Data were stored on tape: see Ref. 9.1, Part I
8.10	References giving other presentations of data	Data are presented in plotted form in Ref. 9.1, Parts I and II

COMMENTS ON DATA

9.1 Accuracy

9.1.1	Mach number	± 0.001
9.1.2	Steady incidence	± 0.01 deg at LVDT position
9.1.3	Reduced frequency	± 0.0005

9.1.4 Steady pressure coefficients C_p better than $\pm$ 0.005

9.1.5 Steady pressure derivatives   -

9.1.6 Unsteady pressure coefficients   Uncertainty in the real and imaginary parts of the coefficients is probably $\pm$ (0.02 + 0.05 Q), where $Q = |R|$ or $|I|$

9.2 Sensitivity to small changes of parameter   -

9.3 Non-linearities   Negligible at 24 Hz. At 48 Hz higher, but still acceptable

9.4 Influence of tunnel total pressure   Effects of Reynolds number not examined

9.5 Effects on data of uncertainty, or variation, in mode of model motion   For uncertainty in values of oscillatory aerodynamic coefficients, see Introduction and 9.9. A list of failing pressure tubes is given in Ref. 9.1, Part I. For model oscillatory deformation see at the end of section 12, "Table 9.11 to 9.20", subsection 2

9.6 Wall interference corrections   None. Values of M and α_m are wind tunnel settings

9.7 Other relevant tests on <u>same model</u>   -

9.8 Relevant tests on other models of nominally the <u>same</u> shape   Ref. 9.3 for relevant steady tests

9.9 Any remarks relevant to comparison between experiment and theory   If pressure tubes were operative in regions of large pressure gradients, the relative error of oscillatory sectional lift coefficients is estimated to be better than 5% in real and imaginary parts. If pressure tubes failed in these regions, the lift coefficients are less accurate. Correction of these coefficients is considered to be almost completely arbitrary and has not been applied

9.10 Additional remarks   -

9.11 References on discussion of data   Ref. 9.1, Part I

10 PERSONAL CONTACT FOR FURTHER INFORMATION

J.J. Horsten, National Aerospace Laboratory (NLR), Anthony Fokkerweg 2, 1059 CM Amsterdam, The Netherlands

11 LIST OF REFERENCES

9.1   J.J. Horsten, R.G. den Boer, R.J. Zwaan   Unsteady transonic pressure measurements on a semi-span wind-tunnel model of a transport-type supercritical wing (LANN model) Part I: General description, aerodynamic coefficients and vibration modes. Part II: Pressure distributions (plotted and printed) and plots of the vibration modes. AFWAL-TR-83-3039 (1983). Also: NLR TR 82069 U (1982)

9.2   R.G. den Boer   Revised results of the unsteady transonic pressure measurements on the LANN model NLR TR 85   U (1985)(to be published)

9.3   B.L. Hinson, K.P. Burdges   An evaluation of three-dimensional transonic codes using new correlation-tailored test data AIAA 18th Aerospace Sciences Meeting, Jan. 14-16, 1980/Pasadena, California. Paper AIAA-80-0003

9.4   S.R. Bland   AGARD Three-dimensional aeroelastic configurations AGARD-AR-167 (1982)

9.5   A. Steiginga, R. Houwink   Correlation of experimental and quasi-3-d theoretical airloads on the oscillating LANN supercritical wing model AFWAL-TR-83-3050 (1983). Also: NLR TR 83003 U (1983)

9.6   J.B. Malone, S.Y. Ruo, J.J. Horsten, R. Houwink   The LANN program: An experimental and theoretical study of steady and unsteady transonic airloads on a supercritical wing AIAA 16th Fluid and Plasma Dynamics Conference, Danvers, Mass., July 12-14, 1983, Paper AIAA-83-1686

9.7   -   Users' guide to the High Speed Wind tunnel (HST). Revised edition (1977)

9.8   J.J. Horsten   Recent developments in the unsteady pressure measuring technique at NLR International Symposium on Aeroelasticity, Oct. 5-7, 1981/Nuremberg.

DGLR-Bericht 82-01 (1982). Also: NLR MP 81055 U (1981)

9.9   R.G. den Boer   Boundary layer effects in the NLR measuring technique of unsteady pressures on oscillating windtunnel models.
NLR TR 85   U (1985) (to be published).

12   NOTATION

DATA SET:	STANDARD:
ALFA	mean model incidence, α_m, deg
c_{AC}	mean aerodynamic chord, $c_{AC} = 0.268$ m

Cm   steady sectional pitching moment coefficient about quarter-chord, C_m, or steady wing pitching moment coefficient about aerodynamic centre,

$$\int_o^s [C_m + C_1 (x_{AC}/c-0.25)]c^2dy/(Sc_{AC})$$

Cz   steady sectional normal force coefficient, C_1, or steady wing normal force coefficient, $\int_o^s C_1 c\, dy/S$

Cmi RE, IM   real and imaginary components of oscillatory sectional pitching moment coefficient about quarter-chord, $2\bar{C}_m/(\pi\alpha_o)$, rad^{-1}, or of oscillatory wing pitching moment coefficient about aerodynamic centre, $2\int_o^s[\bar{C}_m + \bar{C}_1 (x_{AC}/c-0.25)\, c^2dy/(\pi Sc_{AC}\alpha_o)$, rad^{-1}

Cp RE, IM   real and imaginary components of oscillatory pressure coefficient, $\bar{C}_p/\alpha_o$, rad^{-1}

Czi RE, IM   real and imaginary components of oscillatory sectional normal force coefficient, $\bar{C}_1/(\pi\alpha_o)$, rad^{-1}, or of oscillatory wing normal force coefficient,

$$\int_o^s \bar{C}_1 \, c\, dy/(\pi S\alpha_o),\ \mathrm{rad}^{-1}$$

DALFA	amplitude of oscillatory wing incidence at LVDT position, α_o, deg
FREQ.	frequency, f, Hz
HARM.	order of harmonic
MACH	Mach number
M-LOC.	local Mach number
P-SETTL.	total pressure in settling chamber, p_t, kPa
Q	dynamic pressure, q, kPa
RE*10**-6	Reynolds number (x 10^{-6}) based on c_{AC} (Note: not based on c_r as in Ref. 9.4)
REDFR.	reduced frequency, $\omega c_{AC}/2V$ (Note: $k = (\omega c_r/2V) = 1.346$ x REDFR.)
s	model semi-span, s = 1.000 m
S	model surface, S = 0.2526 m^2
T-SETTL.	temperature in settling chamber, T_o, ^{o}C
α_o	amplitude of oscillatory wing incidence at LVDT position, deg. In aerodynamic coefficients, α_o in radians
η	relative spanwise co-ordinate, y/s

Note: Symbols not mentioned here conform to the notation in the General Review in the main body of the Compendium.

Tables 9.1 to 9.20
1. In the section concerning displacements relative to LVDT, "CALC." means that due to failing of the accelerometer the amplitude and phase values were interpolated or extrapolated.
2. In the section concerning the vibration mode, the values for "HEAVE AT X = .224 M (MM)" and "PITCH (DEG)" indicate absolute values of the sectional model displacements, the sections being considered as rigid. Comparison of the pitch value with "DALFA" gives an idea of the model oscillatory deformation.

TABLE 9.1

Measured coordinates of the LANN wing model

Root chord   η = 0

Local chord = 360.60 mm

upper side

ζ	$-z/c$	ζ	$-z/c$
0.00000	0.02072	0.67021	0.02644
0.00011	0.02465	0.70680	0.02166
0.00021	0.02525	0.75335	0.01526
0.00046	0.02606	0.79293	0.00954
0.00063	0.02663	0.83247	0.00361
0.00074	0.02683	0.85618	0.00000
0.00092	0.02722	0.88211	-0.00398
0.00120	0.02787	0.91717	-0.00939
0.00134	0.02795	0.95282	-0.01489
0.00204	0.02937	0.98323	-0.01955
0.00297	0.03089	1.00000	-0.02206
0.00361	0.03170		
0.00404	0.03227		
0.00500	0.03342		
0.00609	0.03459		
0.00673	0.03521		
0.00753	0.03590		
0.00858	0.03680		
0.00952	0.03750		
0.01150	0.03885		
0.01231	0.04019		
0.01708	0.04200		
0.02166	0.04398		
0.02477	0.04513		
0.02819	0.04630		
0.03240	0.04758		
0.03530	0.04836		
0.03914	0.04934		
0.04283	0.05016		
0.04627	0.05089		
0.04935	0.05147		
0.05640	0.05265		
0.06372	0.05366		
0.07053	0.05448		
0.07834	0.05523		
0.08503	0.05576		
0.09867	0.05659		
0.11279	0.05721		
0.12695	0.05767		
0.14162	0.05802		
0.17966	0.05840		
0.21579	0.05819		
0.25344	0.05756		
0.28613	0.05667		
0.32399	0.05528		
0.36076	0.05364		
0.40032	0.05157		
0.43068	0.04970		
0.48496	0.04581		
0.52839	0.04204		
0.57015	0.03793		
0.60347	0.03443		
0.63598	0.03064		

lower side

ζ	$-z/c$	ζ	$-z/c$	ζ	$-z/c$
0.00000	0.02072	0.01765	-0.00102	0.39998	-0.06824
0.00012	0.01631	0.01838	-0.00140	0.40512	-0.06832
0.00029	0.01543	0.01917	-0.00177	0.42387	-0.06843
0.00050	0.01476	0.01979	-0.00207	0.44041	-0.06839
0.00063	0.01434	0.02047	-0.00236	0.46039	-0.06795
0.00087	0.01371	0.02121	-0.00266	0.49747	-0.06709
0.00099	0.01351	0.02205	-0.00310	0.53007	-0.06525
0.00122	0.01298	0.02267	-0.00337	0.56550	-0.06251
0.00135	0.01276	0.02335	-0.00368	0.60232	-0.05889
0.00161	0.01228	0.02414	-0.00403	0.63587	-0.05477
0.00170	0.01208	0.02467	-0.00423	0.67183	-0.04986
0.00194	0.01170	0.02645	-0.00499	0.70588	-0.04504
0.00216	0.01138	0.02834	-0.00578	0.74071	-0.03990
0.00237	0.01112	0.02999	-0.00646	0.77586	-0.03487
0.00247	0.01095	0.03192	-0.00722	0.81117	-0.03006
0.00282	0.01051	0.03351	-0.00785	0.84987	-0.02539
0.00311	0.00994	0.03541	-0.00859	0.86314	-0.02401
0.00334	0.00974	0.03709	-0.00918	0.88042	-0.02246
0.00363	0.00928	0.03890	-0.00985	0.89810	-0.02116
0.00382	0.00902	0.04059	-0.01045	0.91640	-0.02015
0.00402	0.00878	0.04235	-0.01107	0.93319	-0.01972
0.00425	0.00859	0.04608	-0.01243	0.95104	-0.01994
0.00459	0.00815	0.04943	-0.01356	0.98629	-0.02186
0.00499	0.00775	0.05294	-0.01472	0.98974	-0.02222
0.00533	0.00740	0.05646	-0.01586	0.99372	-0.02269
0.00565	0.00714	0.05999	-0.01698	0.99699	-0.02308
0.00602	0.00688	0.06344	-0.01803	1.00000	-0.02342
0.00642	0.00633	0.06697	-0.01909		
0.00678	0.00599	0.07052	-0.02017		
0.00710	0.00571	0.07775	-0.02222		
0.00740	0.00550	0.08485	-0.02422		
0.00776	0.00523	0.09168	-0.02605		
0.00814	0.00488	0.09894	-0.02796		
0.00852	0.00461	0.10599	-0.02977		
0.00885	0.00433	0.11285	-0.03149		
0.00916	0.00411	0.12029	-0.03332		
0.00953	0.00382	0.12722	-0.03498		
0.00995	0.00352	0.13426	-0.03663		
0.01059	0.00310	0.14121	-0.03821		
0.01090	0.00285	0.15856	-0.04203		
0.01131	0.00259	0.17722	-0.04582		
0.01167	0.00235	0.19374	-0.04889		
0.01207	0.00211	0.21247	-0.05205		
0.01243	0.00188	0.22897	-0.05459		
0.01278	0.00166	0.24773	-0.05718		
0.01310	0.00147	0.26472	-0.05932		
0.01351	0.00120	0.28495	-0.06156		
0.01385	0.00101	0.30013	-0.06301		
0.01412	0.00085	0.31759	-0.06440		
0.01486	0.00045	0.33513	-0.06557		
0.01568	-0.00001	0.35216	-0.06652		
0.01622	-0.00028	0.36988	-0.06734		
0.01694	-0.00066	0.38788	-0.06797		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Section 1   η = 0.200

Local chord = 317.65 mm

upper side				lower side					
ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c
0.00000	0.01699	0.67919	0.02904	0.00000	0.01699	0.02840	-0.00856	0.39985	-0.06681
0.00060	0.02144	0.71651	0.02431	0.00020	0.01375	0.02916	-0.00887	0.41363	-0.06691
0.00073	0.02187	0.75558	0.01910	0.00063	0.01203	0.03015	-0.00928	0.43448	-0.06681
0.00094	0.02238	0.79784	0.01312	0.00081	0.01159	0.03103	-0.00964	0.47547	-0.06595
0.00154	0.02393	0.83404	0.00774	0.00100	0.01107	0.03191	-0.00997	0.51461	-0.06411
0.00170	0.02431	0.87604	0.00126	0.00129	0.01032	0.03276	-0.01029	0.55696	-0.06081
0.00206	0.02506	0.91421	-0.00476	0.00146	0.01016	0.03380	-0.01070	0.59506	-0.05697
0.00231	0.02551	0.95548	-0.01130	0.00188	0.00908	0.03586	-0.01115	0.63517	-0.05188
0.00245	0.02556	0.99395	-0.01698	0.00207	0.00880	0.03775	-0.01135	0.67346	-0.04638
0.00257	0.02559	1.00000	-0.01787	0.00236	0.00832	0.03979	-0.01299	0.71408	-0.04033
0.00317	0.02663			0.00245	0.00816	0.04186	-0.01367	0.75530	-0.03401
0.00406	0.02806			0.00277	0.00772	0.04383	-0.01435	0.79383	-0.02838
0.00447	0.02843			0.00311	0.00720	0.04579	-0.01491	0.81346	-0.02576
0.00526	0.02947			0.00326	0.00704	0.04787	-0.01562	0.83359	-0.02322
0.00561	0.02963			0.00366	0.00666	0.04994	-0.01631	0.85343	-0.02096
0.00611	0.03006			0.00384	0.00664	0.05177	-0.01679	0.87345	-0.01899
0.00733	0.03163			0.00437	0.00573	0.05381	-0.01750	0.88165	-0.01830
0.00824	0.03244			0.00464	0.00544	0.05583	-0.01813	0.88980	-0.01770
0.00856	0.03274			0.00510	0.00488	0.05789	-0.01874	0.89764	-0.01713
0.00937	0.03350			0.00530	0.00472	0.05976	-0.01932	0.90535	-0.01664
0.00976	0.03372			0.00569	0.00429	0.06189	-0.01993	0.91338	-0.01634
0.01063	0.03446			0.00627	0.00366	0.06385	-0.02051	0.92139	-0.01606
0.01214	0.03551			0.00663	0.00332	0.06608	-0.02117	0.92966	-0.01586
0.01378	0.03642			0.00701	0.00292	0.06785	-0.02167	0.93738	-0.01578
0.01619	0.03789			0.00724	0.00271	0.06985	-0.02224	0.94538	-0.01579
0.01782	0.03849			0.00772	0.00228	0.07180	-0.02279	0.95337	-0.01587
0.01942	0.03945			0.00827	0.00180	0.07399	-0.02339	0.96145	-0.01603
0.02101	0.04025			0.00868	0.00151	0.07778	-0.02444	0.96959	-0.01632
0.02240	0.04084			0.00905	0.00118	0.08203	-0.02555	0.97739	-0.01671
0.02368	0.04137			0.00947	0.00089	0.08585	-0.02655	0.98557	-0.01730
0.02580	0.04214			0.00980	0.00068	0.09013	-0.02765	0.98940	-0.01764
0.02976	0.04344			0.01065	0.00001	0.09383	-0.02858	0.99343	-0.01800
0.03390	0.04467			0.01131	-0.00040	0.09799	-0.02959	0.99735	-0.01835
0.04184	0.04681			0.01212	-0.00095	0.10183	-0.03047	1.00000	-0.01858
0.04998	0.04865			0.01293	-0.00144	0.10613	-0.03153		
0.05812	0.05014			0.01376	-0.00190	0.11010	-0.03246		
0.06583	0.05130			0.01459	-0.00231	0.11376	-0.03331		
0.07393	0.05230			0.01539	-0.00282	0.12226	-0.03526		
0.09429	0.05413			0.01618	-0.00324	0.13003	-0.03698		
0.11535	0.05544			0.01696	-0.00359	0.13792	-0.03869		
0.15487	0.05697			0.01780	-0.00400	0.14591	-0.04037		
0.19378	0.05763			0.01882	-0.00448	0.15395	-0.04202		
0.23695	0.05765			0.01939	-0.00473	0.17359	-0.04583		
0.27537	0.05717			0.02019	-0.00507	0.19497	-0.04954		
0.31752	0.05613			0.02116	-0.00560	0.21414	-0.05250		
0.35529	0.05485			0.02197	-0.00595	0.23417	-0.05525		
0.39668	0.05306			0.02261	-0.00617	0.25386	-0.05771		
0.43402	0.05110			0.02340	-0.00645	0.27470	-0.06000		
0.47759	0.04838			0.02424	-0.00688	0.29386	-0.06177		
0.51703	0.04546			0.02496	-0.00720	0.31896	-0.06361		
0.55461	0.04228			0.02576	-0.00752	0.33451	-0.06453		
0.59686	0.03829			0.02675	-0.00789	0.35411	-0.06547		
0.63420	0.03434			0.02746	-0.00820	0.37371	-0.06622		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Section 2   η = 0.325

Local chord = 290.71 mm

upper side				lower side					
ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c
0.00000	0.01168	0.07153	0.04993	0.00000	0.01168	0.02818	-0.01118	0.77772	-0.02833
0.00015	0.01245	0.07602	0.05048	0.00015	0.01090	0.03010	-0.01191	0.80290	-0.02476
0.00033	0.01559	0.09870	0.05269	0.00045	0.00986	0.03250	-0.01275	0.82381	-0.02201
0.00045	0.01661	0.12119	0.05426	0.00065	0.00931	0.03456	-0.01348	0.84819	-0.01910
0.00064	0.01663	0.14165	0.05534	0.00101	0.00832	0.03673	-0.01428	0.86682	-0.01716
0.00090	0.01853	0.16391	0.05622	0.00124	0.00769	0.03896	-0.01513	0.88459	-0.01569
0.00122	0.01946	0.18573	0.05684	0.00176	0.00657	0.04118	-0.01589	0.90635	-0.01432
0.00146	0.01980	0.20796	0.05721	0.00216	0.00591	0.04329	-0.01659	0.92796	-0.01358
0.00197	0.02121	0.25206	0.05744	0.00231	0.00571	0.04552	-0.01732	0.93718	-0.01346
0.00202	0.02153	0.29941	0.05688	0.00259	0.00521	0.04777	-0.01802	0.94135	-0.01345
0.00213	0.02140	0.34086	0.05588	0.00293	0.00496	0.04996	-0.01868	0.95000	-0.01350
0.00266	0.02278	0.38489	0.05443	0.00328	0.00419	0.05220	-0.01935	0.95865	-0.01365
0.00296	0.02331	0.42814	0.05255	0.00353	0.00411	0.05420	-0.01996	0.96722	-0.01391
0.00318	0.02357	0.47169	0.05020	0.00385	0.00389	0.05884	-0.02129	0.97610	-0.01432
0.00353	0.02424	0.51395	0.04741	0.00412	0.00322	0.06334	-0.02254	0.98489	-0.01493
0.00389	0.02440	0.55782	0.04398	0.00440	0.00292	0.06762	-0.02373	0.99363	-0.01575
0.00425	0.02520	0.60544	0.03966	0.00469	0.00266	0.07167	-0.02480	0.99796	-0.01620
0.00446	0.02547	0.64628	0.03546	0.00488	0.00249	0.07627	-0.02603	1.00000	-0.01642
0.00477	0.02585	0.69276	0.03014	0.00524	0.00190	0.08053	-0.02711		
0.00525	0.02652	0.73249	0.02515	0.00570	0.00139	0.08538	-0.02831		
0.00562	0.02694	0.77591	0.01934	0.00601	0.00108	0.08926	-0.02925		
0.00593	0.02713	0.82161	0.01270	0.00626	0.00086	0.09365	-0.03030		
0.00654	0.02787	0.86295	0.00633	0.00662	0.00054	0.09791	-0.03129		
0.00695	0.02822	0.90637	-0.00059	0.00702	0.00012	0.10243	-0.03232		
0.00735	0.02882	0.95044	-0.00779	0.00751	-0.00052	0.11145	-0.03433		
0.00777	0.02922	0.99507	-0.01450	0.00794	-0.00073	0.11973	-0.03615		
0.00837	0.02975	1.00000	-0.01525	0.00834	-0.00105	0.12874	-0.03808		
0.00875	0.03002			0.00877	-0.00140	0.13769	-0.03992		
0.00951	0.03073			0.00920	-0.00172	0.14593	-0.04158		
0.00993	0.03108			0.00973	-0.00213	0.15476	-0.04328		
0.01034	0.03129			0.01055	-0.00271	0.16345	-0.04490		
0.01085	0.03173			0.01144	-0.00330	0.17234	-0.04651		
0.01148	0.03224			0.01190	-0.00359	0.18526	-0.04868		
0.01198	0.03256			0.01235	-0.00385	0.20704	-0.05201		
0.01281	0.03311			0.01281	-0.00412	0.22912	-0.05497		
0.01374	0.03362			0.01325	-0.00435	0.25090	-0.05757		
0.01459	0.03411			0.01362	-0.00449	0.27265	-0.05984		
0.01578	0.03486			0.01410	-0.00471	0.29472	-0.06175		
0.01659	0.03520			0.01446	-0.00499	0.31643	-0.06325		
0.01762	0.03582			0.01487	-0.00514	0.33870	-0.06443		
0.01843	0.03624			0.01582	-0.00564	0.36021	-0.06529		
0.01966	0.03686			0.01667	-0.00611	0.38236	-0.06591		
0.02233	0.03807			0.01758	-0.00654	0.39996	-0.06618		
0.02408	0.03874			0.01844	-0.00688	0.42134	-0.06618		
0.02707	0.03990			0.01924	-0.00737	0.42688	-0.06613		
0.03002	0.04092			0.02006	-0.00779	0.47369	-0.06501		
0.03407	0.04224			0.02103	-0.00825	0.51291	-0.06304		
0.03901	0.04371			0.02210	-0.00872	0.55791	-0.05931		
0.04321	0.04480			0.02300	-0.00910	0.60082	-0.05464		
0.04884	0.04611			0.02384	-0.00946	0.64583	-0.04851		
0.05477	0.04731			0.02537	-0.01008	0.68572	-0.04252		
0.06026	0.04829			0.02645	-0.01051	0.71566	-0.03793		
0.06702	0.04933			0.02718	-0.01080	0.75486	-0.03179		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Section 3   η = 0.475
Local chord = 258.06 mm

upper side				lower side					
ξ	-z/c	ξ	-z/c	ξ	-z/c	ξ	-z/c	ξ	-z/c
0.00000	0.01001	0.02822	0.03617	0.00000	0.01001	0.04299	-0.02058	0.91418	-0.01005
0.00003	0.01043	0.03114	0.03717	0.00008	0.00569	0.04542	-0.02130	0.93438	-0.00963
0.00039	0.01308	0.03310	0.03784	0.00018	0.00515	0.04798	-0.02206	0.94849	-0.00974
0.00053	0.01281	0.03566	0.03868	0.00048	0.00394	0.05045	-0.02275	0.96149	-0.01006
0.00089	0.01466	0.03851	0.03957	0.00088	0.00305	0.05315	-0.02349	0.96965	-0.01042
0.00133	0.01589	0.04086	0.04025	0.00100	0.00282	0.05785	-0.02477	0.97750	-0.01089
0.00166	0.01658	0.04347	0.04095	0.00143	0.00203	0.06279	-0.02605	0.98324	-0.01133
0.00204	0.01741	0.04668	0.04176	0.00172	0.00142	0.06792	-0.02736	0.98728	-0.01169
0.00229	0.01784	0.04886	0.04227	0.00210	0.00083	0.07281	-0.02852	0.99289	-0.01224
0.00267	0.01855	0.05101	0.04276	0.00255	0.00014	0.07745	-0.02963	0.99588	-0.01255
0.00313	0.01933	0.05309	0.04321	0.00278	-0.00002	0.08323	-0.03098	1.00000	-0.01298
0.00338	0.01943	0.05520	0.04365	0.00328	-0.00078	0.08734	-0.03188		
0.00384	0.02013	0.05646	0.04392	0.00345	-0.00090	0.09256	-0.03303		
0.00438	0.02105	0.05776	0.04416	0.00391	-0.00150	0.09715	-0.03402		
0.00476	0.02150	0.06279	0.04512	0.00429	-0.00192	0.10215	-0.03507		
0.00494	0.02164	0.06762	0.04593	0.00469	-0.00237	0.10725	-0.03613		
0.00533	0.02207	0.07253	0.04670	0.00525	-0.00284	0.11690	-0.03807		
0.00563	0.02248	0.07749	0.04739	0.00560	-0.00326	0.12674	-0.03999		
0.00619	0.02312	0.08732	0.04861	0.00615	-0.00386	0.13650	-0.04185		
0.00657	0.02339	0.09770	0.04975	0.00644	-0.00412	0.14639	-0.04366		
0.00698	0.02392	0.10686	0.05065	0.00652	-0.00404	0.15625	-0.04541		
0.00723	0.02407	0.11705	0.05152	0.00716	-0.00483	0.16622	-0.04709		
0.00766	0.02469	0.12658	0.05226	0.00770	-0.00531	0.17611	-0.04866		
0.00821	0.02522	0.15216	0.05387	0.00815	-0.00563	0.18594	-0.05015		
0.00853	0.02552	0.17651	0.05499	0.00861	-0.00600	0.19641	-0.05163		
0.00901	0.02593	0.20061	0.05585	0.00907	-0.00635	0.20584	-0.05289		
0.00953	0.02638	0.22548	0.05640	0.00963	-0.00675	0.21521	-0.05407		
0.00964	0.02644	0.25834	0.05683	0.01011	-0.00702	0.22575	-0.05533		
0.01004	0.02672	0.31258	0.05679	0.01069	-0.00741	0.25009	-0.05794		
0.01068	0.02730	0.37718	0.05573	0.01110	-0.00769	0.27463	-0.06020		
0.01113	0.02761	0.42746	0.05418	0.01153	-0.00794	0.29886	-0.06197		
0.01195	0.02819	0.47585	0.05201	0.01249	-0.00848	0.32343	-0.06334		
0.01251	0.02858	0.52187	0.04929	0.01355	-0.00901	0.34891	-0.06433		
0.01324	0.02908	0.57090	0.04580	0.01456	-0.00951	0.37271	-0.06495		
0.01381	0.02947	0.62482	0.04129	0.01540	-0.00990	0.39978	-0.06522		
0.01442	0.02980	0.67201	0.03658	0.01642	-0.01040	0.42228	-0.06507		
0.01492	0.03007	0.71828	0.03132	0.01739	-0.01088	0.44655	-0.06452		
0.01546	0.03040	0.77026	0.02474	0.01841	-0.01135	0.47114	-0.06361		
0.01601	0.03076	0.81917	0.01771	0.01950	-0.01187	0.49612	-0.06232		
0.01630	0.03085	0.86493	0.01053	0.02041	-0.01230	0.52041	-0.06061		
0.01687	0.03119	0.91586	0.00224	0.02144	-0.01282	0.55624	-0.05725		
0.01745	0.03155	0.92894	0.00000	0.02235	-0.01321	0.58729	-0.05374		
0.01800	0.03182	0.96489	-0.00594	0.02342	-0.01368	0.62017	-0.04935		
0.01844	0.03204	1.00000	-0.01165	0.02434	-0.01405	0.65092	-0.04474		
0.01960	0.03256			0.02537	-0.01443	0.68218	-0.03987		
0.02036	0.03292			0.02659	-0.01487	0.71732	-0.03435		
0.02129	0.03341			0.02732	-0.01517	0.75083	-0.02898		
0.02227	0.03385			0.02843	-0.01556	0.76832	-0.02599		
0.02328	0.03426			0.03079	-0.01641	0.79117	-0.02259		
0.02428	0.03469			0.03318	-0.01719	0.81581	-0.01915		
0.02553	0.03518			0.03561	-0.01809	0.84046	-0.01603		
0.02637	0.03552			0.03810	-0.01904	0.86483	-0.01340		
0.02731	0.03587			0.04044	-0.01979	0.88946	-0.01136		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Section 4 η = 0.650

Local chord = 220.29 mm

upper side				lower side					
ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c
0.00000	0.00273	0.05984	0.04008	0.00000	0.00273	0.07031	-0.03173	0.98140	-0.00322
0.00009	0.00348	0.06325	0.04078	0.00020	0.00197	0.07305	-0.03232	0.98692	-0.00375
0.00031	0.00514	0.06674	0.04145	0.00053	-0.00086	0.07589	-0.03291	0.99282	-0.00445
0.00055	0.00685	0.07026	0.04213	0.00081	-0.00176	0.07893	-0.03353	0.99834	-0.00513
0.00083	0.00769	0.07624	0.04317	0.00134	-0.00315	0.08170	-0.03408	1.00000	-0.00533
0.00121	0.00891	0.08170	0.04409	0.00156	-0.00355	0.08744	-0.03521		
0.00145	0.00957	0.08759	0.04500	0.00191	-0.00417	0.09334	-0.03634		
0.00166	0.01009	0.09378	0.04589	0.00225	-0.00482	0.09912	-0.03739		
0.00203	0.01094	0.09924	0.04663	0.00261	-0.00532	0.10475	-0.03843		
0.00231	0.01137	0.10515	0.04739	0.00295	-0.00567	0.11053	-0.03946		
0.00263	0.01207	0.11076	0.04808	0.00330	-0.00609	0.11652	-0.04049		
0.00310	0.01286	0.12208	0.04935	0.00371	-0.00657	0.12232	-0.04147		
0.00348	0.01346	0.13399	0.05055	0.00424	-0.00713	0.12819	-0.04245		
0.00401	0.01414	0.14592	0.05161	0.00447	-0.00729	0.13368	-0.04332		
0.00452	0.01482	0.15730	0.05253	0.00491	-0.00784	0.14002	-0.04433		
0.00493	0.01509	0.16856	0.05335	0.00541	-0.00844	0.15123	-0.04605		
0.00555	0.01562	0.17965	0.05404	0.00587	-0.00884	0.16250	-0.04770		
0.00615	0.01649	0.19136	0.05474	0.00628	-0.00913	0.17445	-0.04934		
0.00658	0.01710	0.22579	0.05632	0.00668	-0.00954	0.18573	-0.05078		
0.00730	0.01814	0.26734	0.05763	0.00721	-0.00999	0.19731	-0.05216		
0.00787	0.01871	0.29128	0.05812	0.00766	-0.01041	0.20897	-0.05344		
0.00831	0.01913	0.31685	0.05835	0.00821	-0.01100	0.22014	-0.05457		
0.00898	0.01975	0.34111	0.05846	0.00873	-0.01140	0.22577	-0.05514		
0.00967	0.02035	0.37006	0.05839	0.00917	-0.01174	0.25473	-0.05759		
0.01037	0.02093	0.39920	0.05810	0.00985	-0.01222	0.28349	-0.05953		
0.01099	0.02143	0.42853	0.05758	0.01035	-0.01254	0.31243	-0.06091		
0.01154	0.02185	0.45701	0.05684	0.01085	-0.01286	0.34120	-0.06178		
0.01220	0.02236	0.48610	0.05585	0.01146	-0.01320	0.37028	-0.06219		
0.01282	0.02281	0.51407	0.05462	0.01231	-0.01370	0.39992	-0.06215		
0.01342	0.02323	0.54285	0.05319	0.01301	-0.01404	0.42761	-0.06157		
0.01430	0.02381	0.57203	0.05143	0.01363	-0.01431	0.45643	-0.06045		
0.01538	0.02439	0.60050	0.04954	0.01478	-0.01493	0.48548	-0.05878		
0.01661	0.02512	0.62935	0.04740	0.01589	-0.01547	0.54662	-0.05319		
0.01765	0.02568	0.65815	0.04501	0.01719	-0.01605	0.57714	-0.04938		
0.01886	0.02637	0.68697	0.04231	0.01853	-0.01664	0.60718	-0.04499		
0.01997	0.02697	0.71647	0.03931	0.01958	-0.01698	0.62797	-0.04172		
0.02116	0.02759	0.74524	0.03619	0.02063	-0.01733	0.65825	-0.03682		
0.02239	0.02821	0.75069	0.03557	0.02185	-0.01801	0.68714	-0.03205		
0.02343	0.02877	0.75448	0.03417	0.02298	-0.01848	0.71652	-0.02713		
0.02458	0.02924	0.77376	0.03219	0.02417	-0.01894	0.74475	-0.02232		
0.02573	0.02979	0.80270	0.02816	0.02695	-0.01995	0.75095	-0.02122		
0.02748	0.03050	0.83148	0.02390	0.02982	-0.02090	0.75339	-0.02045		
0.02926	0.03118	0.86045	0.01924	0.03262	-0.02183	0.77360	-0.01746		
0.03093	0.03185	0.89056	0.01424	0.03830	-0.02373	0.80241	-0.01302		
0.03264	0.03243	0.91853	0.00970	0.04146	-0.02470	0.83136	-0.00911		
0.03438	0.03304	0.92933	0.00794	0.04363	-0.02552	0.86016	-0.00582		
0.03577	0.03354	0.94083	0.00606	0.04716	-0.02629	0.88897	-0.00326		
0.03898	0.03465	0.95230	0.00420	0.05010	-0.02772	0.91192	-0.00193		
0.04248	0.03574	0.96369	0.00232	0.05586	-0.02846	0.92379	-0.00150		
0.04607	0.03671	0.97624	0.00015	0.05901	-0.02919	0.93540	-0.00142		
0.04942	0.03767	0.98681	-0.00157	0.06159	-0.02978	0.94860	-0.00152		
0.05290	0.03852	1.00000	-0.00382	0.06473	-0.03051	0.95854	-0.00178		
0.05620	0.03929			0.06734	-0.03111	0.96984	-0.00234		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Section 5   η = 0.825

Local chord = 182.35 mm

upper side						lower side			
ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c
0.00000	-0.00585	0.05110	0.03178	0.78232	0.04357	0.00000	-0.00585	0.07537	-0.03829
0.00010	-0.00403	0.05241	0.03217	0.81725	0.03880	0.00052	-0.01049	0.07894	-0.03885
0.00077	-0.00120	0.05376	0.03253	0.85259	0.03329	0.00111	-0.01185	0.08629	-0.03998
0.00145	0.00132	0.05519	0.03293	0.88690	0.02776	0.00182	-0.01293	0.09264	-0.04092
0.00164	0.00180	0.05656	0.03322	0.92244	0.02159	0.00259	-0.01386	0.09969	-0.04191
0.00244	0.00341	0.05790	0.03357	0.94248	0.01812	0.00312	-0.01447	0.10653	-0.04286
0.00293	0.00435	0.06131	0.03441	0.95669	0.01559	0.00366	-0.01515	0.11373	-0.04381
0.00334	0.00486	0.06492	0.03530	0.97038	0.01316	0.00419	-0.01573	0.12071	-0.04475
0.00404	0.00584	0.06834	0.03611	0.98427	0.01068	0.00462	-0.01620	0.12793	-0.04563
0.00461	0.00655	0.07040	0.03657	0.99812	0.00818	0.00554	-0.01717	0.14173	-0.04729
0.00518	0.00737	0.07332	0.03721	1.00000	0.00780	0.00609	-0.01765	0.15537	-0.04884
0.00564	0.00790	0.07605	0.03781			0.00680	-0.01821	0.17034	-0.05040
0.00606	0.00846	0.07883	0.03838			0.00745	-0.01879	0.18356	-0.05165
0.00655	0.00900	0.08218	0.03906			0.00809	-0.01931	0.19040	-0.05222
0.00720	0.00977	0.08569	0.03973			0.00896	-0.01990	0.22535	-0.05480
0.00770	0.01027	0.08917	0.04038			0.00944	-0.02010	0.26004	-0.05671
0.00833	0.01095	0.09274	0.04103			0.01017	-0.02074	0.29491	-0.05799
0.00905	0.01166	0.09612	0.04160			0.01109	-0.02130	0.32967	-0.05863
0.00983	0.01233	0.09960	0.04221			0.01113	-0.02131	0.36494	-0.05871
0.01029	0.01257	0.10313	0.04282			0.01170	-0.02151	0.39978	-0.05814
0.01114	0.01358	0.10655	0.04334			0.01230	-0.02190	0.43449	-0.05668
0.01176	0.01401	0.11013	0.04389			0.01279	-0.02213	0.46866	-0.05452
0.01259	0.01467	0.11352	0.04440			0.01330	-0.02247	0.50425	-0.05151
0.01336	0.01520	0.12094	0.04548			0.01397	-0.02282	0.53950	-0.04744
0.01404	0.01569	0.12859	0.04653			0.01478	-0.02323	0.57338	-0.04273
0.01459	0.01613	0.13461	0.04729			0.01541	-0.02347	0.60830	-0.03707
0.01530	0.01658	0.14151	0.04817			0.01624	-0.02390	0.64273	-0.03096
0.01619	0.01718	0.14839	0.04897			0.01752	-0.02446	0.67786	-0.02450
0.01683	0.01759	0.15530	0.04976			0.01915	-0.02516	0.71249	-0.01823
0.01741	0.01796	0.16249	0.05053			0.02024	-0.02559	0.74031	-0.01315
0.01907	0.01893	0.16928	0.05122			0.02176	-0.02617	0.76950	-0.00820
0.02030	0.01963	0.18339	0.05257			0.02300	-0.02666	0.79644	-0.00375
0.02184	0.02046	0.19738	0.05377			0.02439	-0.02713	0.82396	0.00028
0.02297	0.02108	0.21166	0.05490			0.02581	-0.02757	0.85175	0.00382
0.02434	0.02175	0.22545	0.05588			0.02733	-0.02798	0.88078	0.00660
0.02604	0.02257	0.23917	0.05677			0.02871	-0.02833	0.89456	0.00759
0.02730	0.02311	0.25334	0.05760			0.03014	-0.02875	0.90875	0.00839
0.02864	0.02375	0.26691	0.05830			0.03131	-0.02920	0.92202	0.00890
0.03030	0.02445	0.28101	0.05897			0.03275	-0.02957	0.93570	0.00905
0.03144	0.02492	0.29494	0.05955			0.03440	-0.02981	0.94944	0.00898
0.03295	0.02552	0.33001	0.06074			0.03587	-0.03042	0.96351	0.00862
0.03427	0.02606	0.36483	0.06152			0.03719	-0.03081	0.97755	0.00787
0.03552	0.02655	0.39923	0.06198			0.03872	-0.03119	0.99122	0.00670
0.03697	0.02711	0.43396	0.06213			0.04044	-0.03162	0.99816	0.00602
0.03829	0.02753	0.46903	0.06200			0.04399	-0.03237	1.00000	0.00589
0.03981	0.02810	0.50392	0.06153			0.04736	-0.03312		
0.04135	0.02871	0.53861	0.06067			0.05094	-0.03390		
0.04256	0.02913	0.57369	0.05941			0.05437	-0.03453		
0.04405	0.02962	0.60815	0.05790			0.05790	-0.03523		
0.04546	0.03008	0.64295	0.05601			0.06132	-0.03588		
0.04686	0.03051	0.67770	0.05377			0.06477	-0.03648		
0.04819	0.03088	0.71390	0.05089			0.06841	-0.03711		
0.04959	0.03133	0.74734	0.04771			0.07210	-0.03773		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Section 6   η = 0.950
Local chord = 155.34 mm

upper side				lower side			
ζ	$-z/c$	ζ	$-z/c$	ζ	$-z/c$	ζ	$-z/c$
0.00000	-0.01515	0.09807	0.03590	0.00000	-0.01514	0.07407	-0.04529
0.00047	-0.01261	0.10630	0.03754	0.00043	-0.01753	0.08148	-0.04616
0.00119	-0.01062	0.11448	0.03916	0.00129	-0.01992	0.08979	-0.04706
0.00137	-0.01063	0.12254	0.04056	0.00186	-0.02119	0.09808	-0.04789
0.00182	-0.00842	0.13062	0.04195	0.00244	-0.02219	0.10679	-0.04873
0.00227	-0.00733	0.13895	0.04333	0.00298	-0.02312	0.11431	-0.04940
0.00280	-0.00640	0.14711	0.04455	0.00371	-0.02405	0.12252	-0.05012
0.00319	-0.00561	0.15598	0.04586	0.00425	-0.02463	0.13075	-0.05079
0.00397	-0.00523	0.16342	0.04688	0.00476	-0.02520	0.14900	-0.05218
0.00455	-0.00368	0.17155	0.04799	0.00531	-0.02570	0.16496	-0.05329
0.00525	-0.00270	0.18843	0.05003	0.00572	-0.02602	0.17939	-0.05421
0.00581	-0.00204	0.20429	0.05183	0.00628	-0.02651	0.19246	-0.05491
0.00636	-0.00180	0.22084	0.05355	0.00697	-0.02709	0.20647	-0.05558
0.00697	-0.00146	0.23699	0.05507	0.00764	-0.02757	0.22050	-0.05615
0.00788	-0.00049	0.25344	0.05651	0.00824	-0.02794	0.25320	-0.05710
0.00865	0.00008	0.27063	0.05787	0.00894	-0.02842	0.28619	-0.05757
0.00924	0.00155	0.28632	0.05898	0.00961	-0.02888	0.31882	-0.05764
0.01011	0.00257	0.30307	0.06009	0.01045	-0.02947	0.35174	-0.05733
0.01073	0.00319	0.31915	0.06103	0.01125	-0.02991	0.38459	-0.05640
0.01140	0.00383	0.33545	0.06191	0.01210	-0.03041	0.39957	-0.05578
0.01196	0.00427	0.36818	0.06345	0.01277	-0.03072	0.41675	-0.05488
0.01255	0.00481	0.40049	0.06462	0.01342	-0.03092	0.45809	-0.05201
0.01315	0.00527	0.43374	0.06556	0.01423	-0.03153	0.49868	-0.04809
0.01392	0.00590	0.46591	0.06616	0.01504	-0.03190	0.53977	-0.04268
0.01457	0.00640	0.49876	0.06647	0.01602	-0.03234	0.58603	-0.03499
0.01546	0.00703	0.53183	0.06647	0.01679	-0.03267	0.61996	-0.02860
0.01627	0.00747	0.54828	0.06641	0.01766	-0.03305	0.66283	-0.02024
0.01796	0.00833	0.56469	0.06629	0.01833	-0.03336	0.70479	-0.01187
0.01937	0.00950	0.58054	0.06608	0.01897	-0.03355	0.74429	-0.00427
0.02099	0.01055	0.61373	0.06534	0.01979	-0.03380	0.77654	0.00232
0.02264	0.01153	0.64583	0.06428	0.02075	-0.03403	0.80921	0.00755
0.02447	0.01250	0.67920	0.06273	0.02176	-0.03404	0.84198	0.01200
0.02614	0.01351	0.71190	0.06073	0.02304	-0.03400	0.87473	0.01540
0.02766	0.01431	0.74468	0.05815	0.02400	-0.03498	0.90765	0.01751
0.02916	0.01487	0.77690	0.05483	0.02464	-0.03558	0.92372	0.01805
0.03101	0.01585	0.81072	0.05054	0.02556	-0.03604	0.93217	0.01815
0.03276	0.01654	0.82703	0.04810	0.02747	-0.03674	0.94004	0.01815
0.03425	0.01726	0.84255	0.04567	0.02938	-0.03731	0.94815	0.01808
0.03625	0.01814	0.85886	0.04294	0.03131	-0.03787	0.95695	0.01794
0.03751	0.01868	0.87595	0.04009	0.03259	-0.03823	0.96468	0.01766
0.03930	0.01942	0.89123	0.03749	0.03429	-0.03869	0.97271	0.01723
0.04094	0.02012	0.90790	0.03461	0.03594	-0.03906	0.98126	0.01665
0.04480	0.02156	0.92452	0.03165	0.03759	-0.03960	0.98968	0.01593
0.04912	0.02308	0.94028	0.02880	0.03942	-0.04005	1.00000	0.01498
0.05293	0.02434	0.95695	0.02568	0.04103	-0.04032		
0.05723	0.02570	0.96505	0.02422	0.04399	-0.04081		
0.06127	0.02692	0.97362	0.02265	0.04745	-0.04153		
0.06520	0.02787	0.98130	0.02125	0.05048	-0.04197		
0.06937	0.02911	0.98978	0.01968	0.05389	-0.04253		
0.07369	0.03031	0.99756	0.01816	0.05730	-0.04304		
0.08157	0.03224	1.00000	0.01762	0.06114	-0.04359		
0.08564	0.03329			0.06532	-0.04417		
0.08975	0.03420			0.06949	-0.04474		

TABLE 9.1 (cont'd)

Measured coordinates of the LANN wing model

Tip section   η = 1.0

Local chord = 144.45 mm

upper side				lower side			
ζ	-z/c	ζ	-z/c	ζ	-z/c	ζ	-z/c
0.00000	-0.02163	0.09960	0.03237	0.00000	-0.02163	0.17946	-0.05566
0.00070	-0.01802	0.10853	0.03436	0.00051	-0.02379	0.19833	-0.05634
0.00135	-0.01621	0.11739	0.03649	0.00125	-0.02641	0.22271	-0.05696
0.00165	-0.01532	0.12643	0.03805	0.00186	-0.02770	0.26678	-0.05745
0.00229	-0.01400	0.13480	0.03962	0.00250	-0.02879	0.31064	-0.05729
0.00260	-0.01328	0.14416	0.04125	0.00299	-0.02954	0.35566	-0.05622
0.00320	-0.01213	0.15251	0.04266	0.00357	-0.03023	0.39981	-0.05416
0.00371	-0.01103	0.16164	0.04414	0.00426	-0.03097	0.44253	-0.05117
0.00459	-0.00958	0.17015	0.04544	0.00487	-0.03157	0.48658	-0.04674
0.00503	-0.00886	0.17977	0.04681	0.00535	-0.03199	0.53111	-0.04080
0.00594	-0.00747	0.19635	0.04904	0.00596	-0.03236	0.57495	-0.03341
0.00640	-0.00693	0.21404	0.05124	0.00623	-0.03253	0.61844	-0.02495
0.00760	-0.00543	0.23169	0.05323	0.00681	-0.03296	0.66244	-0.01602
0.00818	-0.00501	0.25012	0.05515	0.00770	-0.03376	0.70646	-0.00726
0.00913	-0.00373	0.26711	0.05676	0.00825	-0.03417	0.71354	-0.00563
0.01002	-0.00278	0.28452	0.05826	0.00883	-0.03454	0.75065	0.00130
0.01092	-0.00185	0.30231	0.05961	0.00927	-0.03482	0.79454	0.00909
0.01168	-0.00155	0.31068	0.06024	0.00995	-0.03517	0.83830	0.01562
0.01270	-0.00037	0.35558	0.06311	0.01062	-0.03552	0.88279	0.02031
0.01340	0.00026	0.39854	0.06522	0.01124	-0.03593	0.89174	0.02094
0.01474	0.00135	0.44252	0.06689	0.01229	-0.03646	0.90395	0.02161
0.01533	0.00172	0.48646	0.06796	0.01308	-0.03682	0.91765	0.02209
0.01655	0.00274	0.53040	0.06856	0.01389	-0.03718	0.92646	0.02224
0.01709	0.00317	0.56573	0.06865	0.01451	-0.03746	0.93516	0.02226
0.01815	0.00389	0.57442	0.06862	0.01512	-0.03770	0.94378	0.02223
0.01908	0.00440	0.61894	0.06823	0.01579	-0.03797	0.94814	0.02217
0.02012	0.00489	0.66303	0.06700	0.01657	-0.03832	0.95340	0.02164E
0.02129	0.00571	0.70781	0.06487	0.01722	-0.03857	0.96147	0.02142E
0.02228	0.00642	0.75032	0.06184	0.01803	-0.03886	0.97054	0.02099E
0.02395	0.00728	0.79431	0.05717	0.01894	-0.03920	0.97893	0.02043E
0.02585	0.00830	0.81199	0.05483	0.01975	-0.03946	0.98776	0.01973E
0.02761	0.00920	0.82983	0.05221	0.02045	-0.03959	0.99650	0.01895E
0.02931	0.01002	0.84958	0.04906	0.02163	-0.03990	1.00000	0.01861E
0.03088	0.01064	0.86460	0.04658	0.02237	-0.04008		
0.03299	0.01171	0.88213	0.04352	0.02469	-0.04071		
0.03499	0.01261	0.90133	0.04004	0.02611	-0.04108		
0.03636	0.01310	0.91941	0.03673	0.02773	-0.04150		
0.03839	0.01400	0.93587	0.03367	0.02942	-0.04192		
0.04036	0.01493	0.95301	0.03050E	0.03155	-0.04240		
0.04263	0.01581	0.97060	0.02725E	0.03324	-0.04279		
0.04394	0.01635	0.98795	0.02402E	0.03814	-0.04379		
0.04565	0.01706	1.00000	0.02155E	0.04233	-0.04451		
0.04727	0.01741			0.04692	-0.04525		
0.05121	0.01880			0.05128	-0.04586		
0.05581	0.02042			0.05601	-0.04648		
0.06016	0.02189			0.06477	-0.04755		
0.06487	0.02335			0.07419	-0.04857		
0.06895	0.02455			0.08227	-0.04938		
0.07342	0.02581			0.09087	-0.05014		
0.07830	0.02715			0.10938	-0.05161		
0.08219	0.02817			0.12653	-0.05283		
0.08660	0.02928			0.14417	-0.05392		
0.09111	0.03037			0.16221	-0.05487		

Note: "E" denotes "extrapolated"

TABLE 9.2

Location of the 212 pressure orifices (see also Fig. 9.6)

section:	1 (η = .200)		2 (η = .325)		3 (η = .475)		4 (η = .650)		5 (η = .825)		6 (η = .950)	
% c	upper	lower	upper	lower	upper	lower	upper	lower	upper	lower	upper	lower
.0	o		o		o		o		o		o	
.5	o	o	o	o	o	o	o	o	o	o		o
1.5	x	x	x	x	x	x	x	x	x		x	
3.0	x	x	x	x	x	x	x	x	x			
5.0	x	x	x	x	x	x	x		x		x	
7.5	o	o	o	o	o	o	o		o		o	x
10.0	x	x	x	x	x	x			x	x	x	
15.0	x	x	x	x	x		x	x	x		x	x
20.0	x	x	x	x	x	x	x	x	x	x	x	
25.0	x	o	x	o	x	o	x	o	x	o	x	x
30.0	x	x	x	x					x		x	x
35.0	x		x		x		x		x		x	
40.0	x	x	x	x	x		x	x	x		x	x
45.0	x		x		x		x		x		x	
50.0	x	x	x	x	x	x	x	x	x	x	x	x
55.0	x		x		x		x		x		x	
60.0	x	x	x	x	x	x	x	x	x		x	
65.0	x		x		x		x		x		x	
70.0	x	x	x	x	x	x	x	x	x		x	
75.0	x		x		x		x		x		x	
80.0	x	x	x	x	x	x	x	x	x	x	x	x
85.0	o		o		o		o		o		o	
90.0	x	x	x	x	x	x	x	x	x	x	x	x
95.0	o		o		o		o		o		o	

(o indicates inner diameter tube : 1.07 mm)
(x indicates inner diameter tube : 1.60 mm)
all orifices at model surface inner diameter : 0.79 mm

TABLE 9.3

Location of the 22 pressure transducers (see also Fig. 9.6)

section:	η = .189	η = .4625	η = .639	η = .814
% c				
5.0	x	x	x	x
10.0		x	x	
20.0		x	x	
30.0				
40.0		x	x	
50.0		x	x	
60.0		x	x	
70.0	x	x	x	x
80.0		x	x	
90.0		x	x	

TABLE 9.4

Location of the 12 accelerometers (x in mm; see also Fig. 9.6)

section:	η = .100	η = .420	η = .700	η = .920
number	x = 73.7 (6.4 % c) 1	x = 236.4 (6.6 % c) 4	x = 376.2 (5.7 % c) 7	x = 492.2 (8.3 % c) 10
number	x = 175.8 (36.5 % c) 2	x = 325.7 (39.7 % c) 5	x = 447.2 (39.6 % c) 8	x = 542.3 (39.3 % c) 11
number	x = 300.3 (73.2 % c) 3	x = 414.2 (72.5 % c) 6	x = 512.9 (71.0 % c) 9	x = 593.1 (70.7 % c) 12

Note: Asterisks mean inoperative

TABLE 9.5

Steady test programme for LANN model (Run numbers)

α_m \ M	0.62	0.72	0.77	0.82	0.87	0.95
-0.4	16	27	46	67	88	97
0.35	17			68		
0.60*)	15/19	28	47	69	89	98
0.85	18			70		
1.60	20	29	48	71	90	99
2.00	183			218		
2.35	235	238	240	132		155
2.50				219		
2.60*)	234	109	121	222/133		154
2.75				220	242	245
2.85	236	237	241	134		156
2.90				231		230
3.00*)	184			221	168	246
3.25				223	244	247
3.50				224		
3.60	104/232	110	122	135		157
4.00				225	169	248
4.50				226		
4.75			201	205		
5.00*)	185	193	202	206		228
5.25			203	207		
5.50				227		
6.00	186	194	204	208		229

*) Steady incidences for which unsteady measurements were performed as well

TABLE 9.6

Steady perturbation test results for LANN model to complete
the unsteady programme (Run numbers)

α_o		0.25	0.50	0.75	1.00
α_m	M				
0.6	.62	260			261
	.72				262
	.77				263
	.82	264			265
	.87				266
	.95				267
2.6	.62	268			269
	.72	270			271
	.77	272			273
	.82	274			275
3.0	0.72				
	0.77				
	0.82	276	277		278
	0.87	279			
	0.95	280			
5.0	0.62				
	0.72				
	0.82	281	282		283

Note: Data are included in this Data Set for underlined run numbers

TABLE 9.7

Steady perturbations test results for LANN model to show the
influence of α_m (Run numbers)

α_o		0.25	1.00
α_m	M		
1.60	.62		284
	.72		285
	.77		286
	.82		287
	.95		288
2.60	.95	289	290
2.75	.82	291	
3.25	.82	292	
3.50	.82		293
4.00	.82		294
	.95		295
4.50	.82		296
4.75	.82	297	
5.00	.77	300	
	.95		298
5.25	.82	299	

TABLE 9.8

Unsteady test programme for LANN model (Run numbers)

f		12	24	36	48	60	72
α_o		1.0	0.25	0.25	0.25	0.25	.025
α_m	M						
0.6	0.62	36	129/22	23	24	25	26
	0.72		30		31	32	33
	0.77	117	118	119	120	65	66
	0.82	83	73	77	85	86	87
	0.87	91	92	93	94	95	96
	0.95		100		101	102	103
2.6	0.62		105		106	107	108
	0.72	111	112	113	114	115	116
	0.77	123	124	125	126		128
	0.82	139	143	150	151	152	153
3.0	0.72		165				
	0.77		166				
	0.82		167				
	0.87		170		171	172	173
	0.95	250	175	179	180	181	182
5.0	0.62	187	188	189	190	191	192
	0.72	195	196	197	198	199	200
	0.82	211	212	214	215	216	217

Note: Data are included in this Data Set for underlined run numbers

TABLE 9.9

Test programme for amplitude variation and higher harmonics
for LANN model (Run numbers)

M	α_m	f	α_o / harm	0.125	0.25	0.5	1.0
0.62	0.6	12	1	34	21	35	36
		24	1	37	22/39/129	42	
		24	2		40/130	43	
		24	3		41/131	44	
		36	1	45	23		
0.82	0.6	12	1		72	82	83
		24	1	78	73	79	
		24	2		74	80	
		24	3		75	81	
		36	1	76	77		
0.82	2.6	12	1	136	137	138	139
		24	1	140	143	146	
		24	2	141	144	147	
		24	3	142	145	148	
		36	1	149	150		
0.95	2.6	12	1		161	162	163
0.95	3.0	24	1		175	178	
		24	2		176		
		24	3		177		
0.82	5.0	12	1		209	210	211
		24	1		212	213	

Note: Data are included in this Data Set for underlined run numbers

Table 9.10

CASES FOR WHICH DATA ARE INCLUDED IN THIS DATA SET

(Note: These differ from the cases of Ref. 9.4; Case 5 is now the central transonic case.
Those marked * are priority cases.)

Case	M	α_m (deg)	α_o (deg)	f (Hz)	REDFR= $\omega c_{AC}/2V$	k= $\omega c_r/2V$	Type of flow	Unsteady & Steady		Steady Perturbation	
								Run N^o	Table N^o	Run N^o	Table N^o
1	0.62	0.6	0.25	24	0.099	0.133	subsonic	22	9.11	260	9.21
2*	0.77	0.6	0.25	24	0.080	0.108	transonic	118	9.12	–	–
3*	0.77	2.6	0.25	24	0.080	0.108	attached	124	9.13	272	9.22
4*	0.82	0.6	0.25	12	0.038	0.051		72	9.14	264	9.23
5*	0.82	0.6	0.25	24	0.076	0.102		73,74,75	9.15 a,b,c	264	9.23
6	0.82	0.6	0.5	12	0.038	0.051		82	9.16	–	–
7	0.82	0.6	0.5	24	0.076	0.102		79	9.17	–	–
8	0.82	0.6	0.25	48	0.151	0.203		85	9.18	264	9.23
9	0.82	2.6	0.25	24	0.075	0.103	partly	143,144,145	9.19 a,b,c	274	9.24
10	0.87	0.6	0.25	24	0.071	0.096	attached	92	9.20	–	–

```
***   LANN   *** RUN 22 ***                    TABLE 9.11
```

TEST CONDITIONS				NORM. COEFF.		MOM. COEFF.					DISPLACEMENTS	**	VIBRATION MODE	
											REL. TO LVDT	**Y/(B/2)	HEAVE AT	PITCH
			Cz	Czi	Cm	Cmi				AMPL.	PHASE	**	X=.224 M	
				RE	IM		RE	IM			(-)	(DEG)	**	(MM)	(DEG)

RUNNR. = 22		SECT.1	.260	1.253	-.053	.015	-.017	.083	LVDT	1.00	0.00	**	.000		
		SECT.2	.292	1.362	-.103	.020	-.034	.068	CALC. 1	1.02	1.65	**	.100		
ALFA = .59 (DEG)		SECT.3	.330	1.478	.096	.030	-.053	.059	ACC. 2	.26	2.34	**	.100	.05	.23
MACH = .621		SECT.4	.331	1.661	.248	.043	-.058	.020	ACC. 3	.67	-178.94	**	.100		
RE*10**-6= 4.82		SECT.5	.311	1.368	.158	.054	.002	.003	ACC. 4	.51	-174.33	**	.420		
Q =30.92 (KPA)		SECT.6	.261	.938	.186	.057	-.083	-.021	ACC. 5	1.28	-180.74	**	.420	.25	.24
P-SETTL. =148.7 (KPA)									ACC. 6	1.92	-179.36	**	.420		
T-SETTL. =15.00		WING	.285	1.326	.047	.042	.087	.164	ACC. 7	2.33	-178.35	**	.700		
						(WING : CM ABOUT			CALC. 8	2.88	-180.42	**	.700	.62	.24
DALFA = .250 (DEG)						AERODYN. CENTER)			CALC. 9	3.35	-179.93	**	.700		
FREQ. =24.00 (Hz)									CALC.10	3.89	-180.33	**	.920		
REDFR. = .099									ACC.11	4.29	-180.33	**	.920	.92	.25
HARM. = 1									ACC.12	4.70	-180.32	**	.920		

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)			**	CALIBRATION (TRANSD.)			
			Cp	M-LOC.	Cp	Cp	**	Cp	Cp	NR.
UP	LOW		STEADY		RE	IM	**	RE	IM	
1		0.0	.595	.401			**			
2		.5	-.228	.696			**			
3		1.5	-.924	.919	-12.98	1.971	**			
4		3.0	-1.036	.956	-14.01	2.020	**			
5		5.0	-1.014	.949			**	-10.56	1.978	105
6		7.5	-.837	.891			**			
7		10.0	-.686	.842	-5.193	1.118	**			
8		15.0	-.565	.804	-3.541	.679	**			
9		20.0	-.491	.780	-3.183	.403	**			
10		25.0	-.455	.768	-2.774	.273	**			
11		30.0	-.418	.757	-2.286	.227	**			
12		35.0	-.395	.749	-1.779	.130	**			
13		40.0	-.376	.743	-1.755	-.028	**			
14		45.0	-.360	.738	-1.551	-.028	**			
15		50.0	-.339	.731	-1.452	-.053	**			
16		55.0	-.311	.722	-1.077	-.111	**			
17		60.0	-.283	.713	-1.075	-.202	**			
18		65.0	-.246	.701	-.854	-.143	**			
19		70.0	-.201	.687	-.646	-.091	**	-.714	-.263	119
20		75.0	-.162	.674	-.375	-.032	**			
21		80.0	-.116	.659	-.371	.012	**			
22		85.0	-.051	.638			**			
23		90.0	-.002	.621	-.221	-.075	**			
24		95.0	.068	.598			**			
	25	.5	.705	.352			**			
	26	1.5	.383	.486	5.746	1.051	**			
	27	3.0	.299	.517	5.558	.927	**			
	28	5.0	.209	.549	4.814	-.492	**			
	29	7.5	.072	.596			**			
		10.0					**			
	31	15.0	-.087	.649	3.077	-.453	**			
	32	20.0	-.196	.685	2.924	-.151	**			
	33	25.0	-.259	.706			**			
	34	30.0	-.327	.727	2.146	-.157	**			
	35	40.0	-.348	.734	1.614	-.118	**			
	36	50.0	-.324	.726	1.500	.117	**			
	37	60.0	-.198	.686	1.089	.326	**			
	38	70.0	-.004	.622	.674	.424	**			
	39	80.0	.152	.569	.364	.269	**			
	40	90.0	.251	.534	.310	.359	**			

OVERALL COEFFICIENTS			** SECTION 1 **		
			STEADY	RE	IM
Cz	UPPER	.335	.715	-.079
Cz	LOWER	-.075	.538	.025
Cz	TOTAL	.260	1.253	-.053
Cm	UPPER	.016	-.049	.038
Cm	LOWER	-.001	.031	.046
Cm	TOTAL	.015	-.017	.083

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)			**	CALIBRATION (TRANSD.)			
			Cp	M-LOC.	Cp	Cp	**	Cp	Cp	NR.
UP	LOW		STEADY		RE	IM	**	RE	IM	
1		0.0	.631	.386			**			
2		.5	-.204	.688			**			
3		1.5	-.928	.921	-18.60	.973	**			
4		3.0	-1.070	.967	-15.24	.968	**			
5		5.0	-1.098	.977	-9.024	1.918	**			
6		7.5	-.872	.902			**			
7		10.0	-.731	.857	-5.319	1.299	**			
8		15.0	-.598	.814	-3.953	.487	**			
		20.0					**			
10		25.0	-.487	.779	-2.927	.233	**			
11		30.0	-.459	.770	-2.317	.406	**			
12		35.0	-.415	.756	-2.079	-.063	**			
13		40.0	-.392	.748	-1.968	-.282	**			
		45.0					**			
15		50.0	-.360	.738	-1.481	.100	**			
16		55.0	-.325	.727	-1.144	-.052	**			
17		60.0	-.295	.717	-1.061	-.252	**			
18		65.0	-.268	.709	-.821	-.188	**			
19		70.0	-.217	.692	-.746	-.366	**			
20		75.0	-.168	.676	-.372	-.075	**			
21		80.0	-.127	.663	-.362	-.069	**			
22		85.0	-.068	.643			**			
23		90.0	-.006	.623	-.343	-.057	**			
24		95.0	.067	.598			**			
	25	.5	.719	.345			**			
	26	1.5	.401	.479	7.395	1.642	**			
		3.0					**			
	28	5.0	.177	.560	3.123	-1.822	**			
	29	7.5	.087	.591			**			
	30	10.0	.041	.607	3.591	-.858	**			
	31	15.0	-.089	.650	3.231	-.811	**			
	32	20.0	-.193	.684	2.733	-.358	**			
	33	25.0	-.253	.704			**			
	34	30.0	-.309	.722	2.429	-.635	**			
	35	40.0	-.343	.733	2.317	-.146	**			
	36	50.0	-.316	.724	1.694	-.052	**			
	37	60.0	-.177	.679	.785	.164	**			
	38	70.0	.014	.616	.655	.280	**			
	39	80.0	.168	.564	.316	.042	**			
	40	90.0	.261	.531	.314	.211	**			

OVERALL COEFFICIENTS			** SECTION 2 **		
			STEADY	RE	IM
Cz	UPPER	.356	.805	-.055
Cz	LOWER	-.064	.558	-.048
Cz	TOTAL	.292	1.362	-.103
Cm	UPPER	.018	-.068	.040
Cm	LOWER	.002	.034	.028
Cm	TOTAL	.020	-.034	.068

*** L..ANN *** RUN 22 *** TABLE 9.11 (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.664	.371			**			
2		.5	-.205	.688			**			
3		1.5	-.940 L	.924	-18.20	-.453	**			
4		3.0	-1.027	.953	-15.52	.201	**			
5		5.0	-1.022	.951	-11.17	.021	**			
6		7.5	-.883	.906			**			
7		10.0	-.739	.859	-6.879	.539	**	-7.346	.418	307
8		15.0	-.623	.822	-4.667	.056	**			
9		20.0	-.545	.797	-3.838	-.005	**	-4.154	-.040	309
10		25.0	-.496	.782	-3.347	-.119	**			
		30.0					**			
12		35.0	-.433	.762	-2.338	-.212	**			
13		40.0	-.414	.755	-1.971	-.362	**	-2.194	-.263	313
14		45.0	-.395	.749	-1.718	-.409	**			
15		50.0	-.372	.742	-1.072	-.044	**	-1.652	-.289	315
16		55.0	-.340	.732	-1.242	-.199	**			
17		60.0	-.314	.723	-1.129	-.277	**	-1.137	-.309	317
18		65.0	-.281	.713	-.934	-.219	**			
19		70.0	-.240	.700	-.664	-.304	**	-.689	-.244	319
20		75.0	-.194	.684	-.436	-.042	**			
21		80.0	-.143	.668	-.317	-.062	**	-.333	-.154	321
22		85.0	-.088	.650			**			
23		90.0	-.021	.628	-.196	-.120	**	-.110	-.112	323
24		95.0	.058	.601			**			
	25	.5	.731	.340			**			
	26	1.5	.440	.464	.060	-.078	**			
	27	3.0	.302	.516	9.042	2.300	**			
		5.0					**			
	29	7.5	.087	.591			**			
	30	10.0	.014	.616	3.964	-.503	**			
		15.0					**			
	32	20.0	-.184	.681	3.107	-.105	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.294	.717	1.830	.276	**			
	37	60.0	-.162	.674	1.074	.273	**			
	38	70.0	.024	.613	.637	.360	**			
	39	80.0	.182	.559	.321	.236	**			
	40	90.0	.275	.526	.328	.238	**			

OVERALL COEFFICIENTS		STEADY	RE	IM	SECTION 3
C_z	UPPER	.368	.881	.035	
C_z	LOWER	-.038	.597	.061	
C_z	TOTAL	.330	1.478	.096	
C_m	UPPER	.023	-.093	.027	
C_m	LOWER	.007	.039	.033	
C_m	TOTAL	.030	-.053	.059	

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.739	.336			**			
2		.5	-.103	.655			**			
3		1.5	-.728	.856	-20.34	-3.405	**			
4		3.0	-.896	.910	-15.44	-1.145	**			
5		5.0	-.936	.923	-9.181	.010	**	-13.71	.607	405
6		7.5	-.790	.876			**			
7		10.0					**	-5.522	.157	407
8		15.0	-.616	.820	-5.705	-.126	**			
9		20.0	-.550	.799	-4.347	-.244	**	-4.636	-.240	409
10		25.0	-.505	.784	-3.697	-.244	**			
		30.0					**			
12		35.0	-.444	.765	-2.596	-.113	**			
13		40.0	-.429	.760	-2.366	-.364	**	-2.486	-.308	413
14		45.0	-.411	.754	-1.888	-.326	**			
15		50.0	-.387	.747	-1.777	-.182	**	-1.842	-.336	415
16		55.0	-.368	.741	-1.190	.074	**			
17		60.0	-.341	.732	-1.465	-.280	**	-1.297	-.280	417
18		65.0	-.315	.724	-1.134	-.281	**			
19		70.0	-.279	.712	-.791	-.010	**			
20		75.0	-.262	.706	-.571	-.131	**			
21		80.0	-.175	.678	-.393	-.002	**	-.492	-.172	421
22		85.0	-.098	.653			**			
23		90.0	-.027	.630	-.146	.045	**			
24		95.0	.046	.605			**			
	25	.5	.673	.367			**			
	26	1.5	.333	.505	8.837	3.921	**			
	27	3.0	.204	.551	7.622	3.071	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.102	.654	4.032	.088	**			
	32	20.0	-.186	.682	3.441	.162	**			
	33	25.0	-.238	.699			**			
		30.0					**			
	35	40.0	-.308	.721	2.602	.465	**			
	36	50.0	-.283	.713	1.725	.329	**			
	37	60.0	-.129	.663	1.218	.487	**			
	38	70.0	.046	.605	.707	.384	**			
	39	80.0	.207	.550	.399	.296	**			
	40	90.0	.285	.522	.325	.407	**			

OVERALL COEFFICIENTS		STEADY	RE	IM	SECTION 4
C_z	UPPER	.374	.931	.066	
C_z	LOWER	-.043	.730	.183	
C_z	TOTAL	.331	1.661	.248	
C_m	UPPER	.032	-.072	-.002	
C_m	LOWER	.012	.013	.022	
C_m	TOTAL	.043	-.058	.020	

*** L∆NN *** RUN 22 ***   TABLE 9.11 (cont'd)

!	NR.	!		XCHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** ** **	CALIBRATION (TRANSD.)! Cp RE	Cp IM	NR.!
! UP	! LOW!											
! 1 !		!	0.0	!	.781 !	.315 !	!		**	!	!	!
! 2 !		!	.5	!	.097 !	.588 !	!		**	!	!	!
! 3 !		!	1.5	!	-.483 !	.778 !	-17.08 !	-4.605	**	!	!	!
! 4 !		!	3.0	!	-.670 !	.837 !	-12.94 !	-2.189	**	!	!	!
! 5 !		!	5.0	!	-.687 !	.843 !	-14.72 !	-3.391	**	-12.57 !	-.212 !	505 !
! 6 !		!	7.5	!	-.705 !	.849 !	!		**	!	!	!
! 7 !		!	10.0	!	-.602 !	.815 !	-4.660 !	.313	**	!	!	!
! !		!	15.0	!	!	!			**	!	!	!
! 9 !		!	20.0	!	-.518 !	.788 !	-4.320 !	-.322	**	!	!	!
! 10 !		!	25.0	!	-.489 !	.779 !	-3.745 !	-.254	**	!	!	!
! 11 !		!	30.0	!	-.459 !	.770 !	-3.340 !	-.373	**	!	!	!
! !		!	35.0	!	!	!			**	!	!	!
! 13 !		!	40.0	!	-.418 !	.757 !	-2.350 !	-.374	**	!	!	!
! 14 !		!	45.0	!	-.406 !	.753 !	-1.980 !	-.443	**	!	!	!
! 15 !		!	50.0	!	-.390 !	.748 !	-1.710 !	-.182	**	!	!	!
! 16 !		!	55.0	!	-.372 !	.742 !	-1.429 !	-.216	**	!	!	!
! 17 !		!	60.0	!	-.354 !	.736 !	-1.255 !	-.331	**	!	!	!
! 18 !		!	65.0	!	-.339 !	.731 !	-.998 !	-.149	**	!	!	!
! 19 !		!	70.0	!	-.314 !	.723 !	-.809 !	-.149	**	-.851 !	-.196 !	519 !
! 20 !		!	75.0	!	-.293 !	.717 !	-.311 !	.026	**	!	!	!
! 21 !		!	80.0	!	-.237 !	.698 !	-.193 !	.005	**	!	!	!
! 22 !		!	85.0	!	-.134 !	.665 !	!		**	!	!	!
! 23 !		!	90.0	!	-.053 !	.638 !	-.079 !	-.014	**	!	!	!
! 24 !		!	95.0	!	.042 !	.607 !	!		**	!	!	!
!	! 25 !		.5	!	.599 !	.400 !	!		**	!	!	!
!	!	!	1.5	!	!	!			**	!	!	!
!	!	!	3.0	!	!	!			**	!	!	!
!	!~--!		5.0	!	!	!			**	!	!	!
!	!	!	7.5	!	!	!			**	!	!	!
!	! 30 !		10.0	!	-.142 !	.668 !	!		**	!	!	!
!	!	!	15.0	!	!	!			**	!	!	!
!	! 32 !		20.0	!	-.202 !	.687 !	4.001 !	.256	**	!	!	!
!	!	!	25.0	!	!	!			**	!	!	!
!	! 34 !		30.0	!	-.272 !	.710 !	2.602 !	.101	**	!	!	!
!	!	!	40.0	!	!	!			**	!	!	!
!	! 36 !		50.0	!	-.301 !	.719 !	1.474 !	.043	**	!	!	!
!	!	!	60.0	!	!	!			**	!	!	!
!	!	!	70.0	!	!	!			**	!	.!	!
!	! 39 !		80.0	!	.214 !	.547 !	.291 !	.209	**	!	!	!
!	! 40 !		90.0	!	.289 !	.521 !	.252 !	.177	**	!	!	!

! OVERALL ! COEFFICIENTS		** SECTION 5 **		
		! STEADY!	RE	! IM	!
! Cz	UPPER	! .357 !	.910 !	.128	!
! Cz	LOWER	! -.047 !	.458 !	.030	!
! Cz	TOTAL	! .311 !	1.368 !	.158	!
! Cm	UPPER	! .042 !	-.080 !	-.017	!
! Cm	LOWER	! .012 !	.082 !	.020	!
! Cm	TOTAL	! .054 !	.002 !	.003	!

!	NR.	!		XCHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** ** **	CALIBRATION (TRANSD.)! Cp RE	Cp IM	NR.!
! UP	! LOW!											
! 1 !		!	0.0	!	.789 !	.311 !	!		**	!	!	!
! !		!	.5	!	!	!			**	!	!	!
! 3 !		!	1.5	!	-.176 !	.679 !	!		**	!	!	!
! !		!	3.0	!	!	!			**	!	!	!
! 5 !		!	5.0	!	-.480 !	.776 !	-13.55 !	-5.273	**	!	!	!
! !		!	7.5	!	!	!			**	!	!	!
! 7 !		!	10.0	!	-.499 !	.782 !	-6.213 !	-.626	**	!	!	!
! 8 !		!	15.0	!	-.469 !	.773 !	-4.329 !	-.400	**	!	!	!
! 9 !		!	20.0	!	-.511 !	.786 !	!		**	!	!	!
! 10 !		!	25.0	!	-.434 !	.762 !	-2.287 !	-.207	**	!	!	!
! 11 !		!	30.0	!	-.408 !	.753 !	!		**	!	!	!
! 12 !		!	35.0	!	-.388 !	.747 !	-1.565 !	-.248	**	!	!	!
! 13 !		!	40.0	!	-.362 !	.739 !	-1.459 !	-.273	**	!	!	!
! 14 !		!	45.0	!	-.350 !	.735 !	-1.183 !	-.256	**	!	!	!
! 15 !		!	50.0	!	-.340 !	.732 !	-1.083 !	-.102	**	!	!	!
! 16 !		!	55.0	!	-.331 !	.729 !	-.823 !	-.094	**	!	!	!
! 17 !		!	60.0	!	-.317 !	.724 !	-.785 !	-.201	**	!	!	!
! 18 !		!	65.0	!	-.316 !	.724 !	-.582 !	-.030	**	!	!	!
! 19 !		!	70.0	!	-.309 !	.722 !	-.521 !	-.015	**	!	!	!
! 20 !		!	75.0	!	-.289 !	.715 !	-.280 !	-.012	**	!	!	!
! 21 !		!	80.0	!	-.246 !	.701 !	-.218 !	.004	**	!	!	!
! 22 !		!	85.0	!	-.137 !	.666 !	!		**	!	!	!
! 23 !		!	90.0	!	-.028 !	.630 !	-.138 !	.021	**	!	!	!
! 24 !		!	95.0	!	.060 !	.600 !	!		**	!	!	!
!	! 25 !		.5	!	.402 !	.479 !	!		**	!	!	!
!	!	!	1.5	!	!	!			**	!	!	!
!	!	!	3.0	!	!	!			**	!	!	!
!	!~--!		5.0	!	!	!			**	!	!	!
!	!	!	7.5	!	!	!			**	!	!	!
!	!	!	10.0	!	!	!			**	!	!	!
!	! 31 !		15.0	!	-.199 !	.686 !	3.173 !	.080	**	!	!	!
!	!	!	20.0	!	!	!			**	!	!	!
!	! 33 !		25.0	!	-.255 !	.704 !	!		**	!	!	!
!	! 34 !		30.0	!	-.268 !	.709 !	1.555 !	.140	**	!	!	!
!	! 35 !		40.0	!	-.294 !	.717 !	.948 !	.060	**	!	!	!
!	! 36 !		50.0	!	-.263 !	.707 !	.669 !	.104	**	!	!	!
!	!	!	60.0	!	!	!			**	!	!	!
!	!	!	70.0	!	!	!			**	!	!	!
!	! 39 !		80.0	!	.219 !	.546 !	-.130 !	.139	**	!	!	!
!	! 40 !		90.0	!	.281 !	.523 !	-.055 !	.179	**	!	!	!

! OVERALL ! COEFFICIENTS		** SECTION 6 **		
		! STEADY!	RE	! IM	!
! Cz	UPPER	! .303 !	.698 !	.154	!
! Cz	LOWER	! -.042 !	.240 !	.032	!
! Cz	TOTAL	! .261 !	.938 !	.186	!
! Cm	UPPER	! .043 !	-.084 !	-.041	!
! Cm	LOWER	! .014 !	.000 !	.020	!
! Cm	TOTAL	! .057 !	-.083 !	-.021	!

```
***  LANN   *** RUN 118 ***           TABLE 9.12
```

TEST CONDITIONS				NORM. COEFF.		MOM. COEFF.					DISPLACEMENTS ** VIBRATION MODE				
											REL.TO LVDT **Y/(B/2)! HEAVE AT ! PITCH				
			Cz	Czi		Cm	Cmi				AMPL.! PHASE ** ! X=.224 M !				
			RE	IM		RE	IM				(-) ! (DEG) ** ! (MM) ! (DEG)				

RUNNR. = 118		SECT.1 .285 1.475 -.134	.013 .049 .108	LVDT	1.00	0.00 ** .000		
		SECT.2 .304 2.058 -.408	.017 -.101 .168	CALC. 1!	1.10	1.77 ** .100		
ALFA = .60 (DEG)		SECT.3 .353 1.709 .083	.025 -.066 .109	ACC. 2!	.34	.67 ** .100		
MACH = .773		SECT.4 .342 2.428 .065	.040 -.211 .123	ACC. 3!	.60 -176.85 ** .100		.01	.23
RE*10**-6= 5.26		SECT.5 .329 2.194 .031	.051 -.126 .063	ACC. 4!	.27 -166.63 ** .420		
Q = 42.10 (KPA)		SECT.6 .261 1.180 .089	.056 -.100 .029	ACC. 5!	1.02 -179.51 ** .420		.11	.24
P-SETTL. =149.5 (KPA)				ACC. 6!	1.67 -177.45 ** .420		
T-SETTL. =27.00		WING .302 1.767 -.078	.037 .285 .179	ACC. 7!	1.85 -175.99 ** .700		
			(WING : CM ABOUT	CALC. 8!	2.37 -178.72 ** .700		.38	.23
DALFA = .249 (DEG)			AERODYN. CENTER)	ACC. 9!	2.86 -178.02 ** .700		
FREQ. =24.00 (Hz)				CALC.10!	3.13 -178.02 ** .920		
REDFR. = .080				ACC.11!	3.54 -178.23 ** .920		.50	.25
HARM. = 1				ACC.12!	3.95 -178.40 ** .920		

Section 1:

NR. UP ! LOW!	%CHORD	Cp STEADY!	M-LOC.!	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.!
1	0.0	.704	.447			**			
2	.5	.030	.760			**			
3	1.5	-.637	1.056	-5.115	1.175	**			
4	3.0	-1.019	1.248	-9.081	2.561	**			
5	5.0	-1.002	1.239			**	-9.471	2.680	105
6	7.5	-1.185	1.343			**			
7	10.0	-1.172	1.335	-10.93	3.891	**			
8	15.0	-.626	1.050	-3.605	.306	**			
9	20.0	-.566	1.022	-3.148	.187	**			
10	25.0	-.532	1.007	-2.971	.018	**			
11	30.0	-.495	.990	-2.815	.127	**			
12	35.0	-.469	.978			**			
13	40.0	-.450	.970	-2.200	-.487	**			
14	45.0	-.431	.961	-1.795	-.409	**			
15	50.0	-.405	.949	-1.613	-.429	**			
16	55.0	-.368	.933	-1.172	-.227	**			
17	60.0	-.331	.917	-1.180	-.312	**			
18	65.0	-.280	.894	-.851	-.482	**			
19	70.0	-.225	.870	-.633	-.388	**	-.643	-.334	119
20	75.0	-.174	.848	-.359	-.285	**			
21	80.0	-.118	.824	-.341	-.260	**			
22	85.0	-.045	.792			**			
23	90.0	.013	.767	-.071	-.285	**			
24	95.0	.087	.735			**			
25	.5	.703	.447			**			
26	1.5	.371	.609	4.620	-.098	**			
27	3.0	.301	.641	5.137	.172	**			
28	5.0	.217	.678	6.207	-.529	**			
29	7.5	.069	.743			**			
30	10.0					**			
31	15.0	-.104	.818	2.952	-.755	**			
32	20.0	-.234	.874	3.614	-.734	**			
33	25.0	-.319	.911			**			
34	30.0	-.414	.953	3.995	-.671	**			
35	40.0	-.420	.956	2.684	-.647	**			
36	50.0	-.423	.958	2.460	-.209	**			
37	60.0	-.239	.876	1.491	.074	**			
38	70.0	-.007	.775	.933	.310	**			
39	80.0	.163	.702	.489	.096	**			
40	90.0	.269	.655	.496	.085	**			

OVERALL COEFFICIENTS ** SECTION 1 **

		STEADY!	RE	IM
Cz	UPPER	.391	.778	-.062
Cz	LOWER	-.106	.697	-.072
Cz	TOTAL	.285	1.475	-.134
Cm	UPPER	.018	-.044	.093
Cm	LOWER	-.004	.093	.014
Cm	TOTAL	.013	.049	.108

Section 2:

NR. UP ! LOW!	%CHORD	Cp STEADY!	M-LOC.!	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.!
1	0.0	.736	.429			**			
2	.5	.063	.745			**			
3	1.5	-.640	1.057	-8.453	2.315	**			
4	3.0	-.953	1.213	-8.123	2.819	**			
5	5.0	-1.059	1.270	-8.619	2.690	**			
6	7.5	-1.204	1.354			**			
7	10.0	-1.227	1.369	-5.036	1.905	**			
8	15.0	-.799	1.134	-52.30	22.548	**			
9	20.0	-.561	1.020	-2.500	-.663	**			
10	25.0	-.540	1.010	-.997	-.922	**			
11	30.0	-.519	1.001	-1.302	-.263	**			
12	35.0	-.474	.981	-1.700	-.434	**			
13	40.0	-.454	.971	-1.609	-.498	**			
14	45.0	-.430	.961			**			
15	50.0	-.416	.954	-1.015	-.319	**			
16	55.0	-.372	.935	-.744	-.078	**			
17	60.0	-.332	.917	-.798	-.084	**			
18	65.0	-.292	.899	-.616	-.209	**			
19	70.0	-.233	.874	-.387	-.215	**			
20	75.0	-.174	.848	-.233	-.071	**			
21	80.0	-.122	.825	-.220	-.063	**			
22	85.0	-.056	.797			**			
23	90.0	.012	.767	-.135	.033	**			
24	95.0	.088	.734			**			
25	.5	.708	.444			**			
26	1.5	.379	.606	5.460	.436	**			
27	3.0	.277	.651			**			
28	5.0	.165	.701	3.165	-.977	**			
29	7.5	.071	.742			**			
30	10.0	.021	.763	3.435	-.725	**			
31	15.0	-.121	.825	3.100	-.690	**			
32	20.0	-.247	.880	3.810	-.580	**			
33	25.0	-.328	.915			**			
34	30.0	-.406	.950	4.368	-.330	**			
35	40.0	-.455	.972	3.544	-.216	**			
36	50.0	-.406	.950	2.372	.079	**			
37	60.0	-.210	.863	1.373	.363	**			
38	70.0	.016	.766	.845	.357	**			
39	80.0	.180	.694	.492	.214	**			
40	90.0	.278	.651	.496	.203	**			

OVERALL COEFFICIENTS ** SECTION 2 **

		STEADY!	RE	IM
Cz	UPPER	.406	1.339	-.384
Cz	LOWER	-.102	.718	-.025
Cz	TOTAL	.304	2.058	-.408
Cm	UPPER	.018	-.203	.125
Cm	LOWER	-.001	.101	.043
Cm	TOTAL	.017	-.101	.168

*** LANN *** RUN 118 *** TABLE 9.12 (cont'd)

NR. UP	LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.760	.416			**			
2		.5	.047	.752			**			
3		1.5	-.645	1.059	-7.300	.584	**			
4		3.0	-.924	1.197	-9.164	1.257	**			
5		5.0	-1.034	1.256	-8.047	.961	**			
6		7.5	-1.174	1.337			**			
7		10.0	-1.183	1.342	-4.290	.474	**	-4.598	.897	307
8		15.0	-1.087	1.286	-28.81	4.653	**			
9		20.0	-.563	1.021	-11.58	-.435	**	-8.644	.323	309
10		25.0	-.514	.999	1.383	-2.362	**			
		30.0					**			
12		35.0	-.482	.984	-.506	-1.176	**			
13		40.0	-.469	.978	-.683	-1.067	**	-.890	-.854	313
14		45.0	-.449	.969	-.914	-1.135	**			
15		50.0	-.423	.957	-.597	-.541	**	-.707	-.645	315
16		55.0	-.380	.938	-.592	-.518	**			
17		60.0	-.346	.923	-.730	-.408	**	-.501	-.497	317
18		65.0	-.301	.903	-.562	-.435	**			
19		70.0	-.251	.881	-.305	-.437	**	-.238	-.354	319
20		75.0	-.194	.856	-.196	-.373	**			
21		80.0	-.132	.830	-.332	-.194	**	-.145	-.142	321
22		85.0	-.070	.803			**			
23		90.0	.001	.772	-.113	-.182	**	-.039	-.107	323
24		95.0	.081	.737			**			
	25	.5	.715	.441			**			
	26	1.5	.395	.590	6.289	.854	**			
	27	3.0	.275	.652	7.572	1.384	**			
		5.0					**			
	29	7.5	.062	.746			**			
	30	10.0	-.015	.779	3.312	-.624	**			
		15.0					**			
	32	20.0	-.243	.878	3.937	-.448	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.377	.937	3.161	.232	**			
	37	60.0	-.189	.854	1.257	.078	**			
	38	70.0	.029	.760	.712	.181	**			
	39	80.0	.192	.689	.520	.171	**			
	40	90.0	.291	.645	.438	.140	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.423	.967	.077
Cz	LOWER	-.070	.742	.006
Cz	TOTAL	.353	1.709	.083
Cm	UPPER	.020	-.156	.089
Cm	LOWER	.005	.091	.020
Cm	TOTAL	.025	-.066	.109

***** SECTION 3 *****

NR. UP	LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.812	.386			**			
2		.5	.117	.722			**			
3		1.5	-.525	1.004	-10.90	.349	**			
4		3.0	-.842	1.155	-7.635	.940	**			
5		5.0	-1.004	1.240	-5.136	1.023	**	-7.941	1.345	405
6		7.5	-1.086	1.286			**			
7		10.0					**	-6.300	1.405	407
8		15.0	-.864	1.166	-66.93	8.977	**			
9		20.0	-.575	1.026	-.434	-2.584	**	-.478	-2.153	409
10		25.0	-.551	1.015	3.927	-2.147	**			
		30.0					**			
12		35.0	-.509	.996	-1.476	-.634	**			
13		40.0	-.495	.990	-1.342	-.548	**	-1.447	-.538	413
14		45.0	-.475	.981	-1.203	-.463	**			
15		50.0	-.445	.967	-.978	-.592	**	-1.254	-.425	415
16		55.0	-.416	.954	-.955	-.317	**			
17		60.0	-.380	.938	-.940	-.297	**	-.856	-.321	417
		65.0					**			
19		70.0	-.295	.901	-.300	-.315	**			
20		75.0	-.263	.887	-.059	-.119	**			
21		80.0	-.167	.845	0.000	0.000	**	-.143	-.126	421
22		85.0	-.080	.807			**			
23		90.0	-.003	.774	.031	-.127	**			
24		95.0	.072	.742			**			
	25	.5	.657	.471			**			
	26	1.5	.301	.641	7.456	1.375	**			
	27	3.0	.177	.696	6.780	1.308	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.148	.837	4.012	-.267	**			
	32	20.0	-.249	.881	4.301	-.286	**			
	33	25.0	-.318	.911			**			
		30.0					**			
	35	40.0	-.411	.952	4.732	.649	**			
	36	50.0	-.365	.931	2.992	.355	**			
	37	60.0	-.152	.838	1.555	.429	**			
	38	70.0	.051	.750	.887	.361	**			
	39	80.0	.220	.677	.621	.346	**			
	40	90.0	.302	.640	.556	.256	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.422	1.511	-.040
Cz	LOWER	-.080	.917	.105
Cz	TOTAL	.342	2.428	.065
Cm	UPPER	.030	-.308	.081
Cm	LOWER	.010	.097	.043
Cm	TOTAL	.040	-.211	.123

***** SECTION 4 *****

*** LANN *** RUN 118 *** TABLE 9.12 (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.827	.377			**			
2		.5	.238	.669			**			
3		1.5	-.342	.921	-12.24	-.984	**			
4		3.0	-.617	1.046	-7.621	.401	**			
5		5.0	-.735	1.102	-12.59	.125	**	-15.24	1.997	505
6		7.5	-.806	1.137			**			
7		10.0	-.823	1.146	-28.76	1.091	**			
		15.0					**			
9		20.0	-.633	1.054	-5.173	.393	**			
10		25.0	-.585	1.031	-4.568	-.103	**			
11		30.0	-.549	1.014	-3.720	-.065	**			
		35.0					**			
13		40.0	-.494	.989	-2.619	-.740	**			
14		45.0	-.475	.981	-2.033	-.744	**			
15		50.0	-.453	.971	-1.613	-.512	**			
16		55.0	-.426	.959	-1.456	-.118	**			
17		60.0	-.398	.946	-1.250	-.161	**			
18		65.0	-.372	.935	-.588	-.275	**			
19		70.0	-.339	.920	-.449	-.190	**	-.384	-.132	519
20		75.0	-.304	.904	.108	.041	**			
21		80.0	-.227	.871	.231	-.032	**			
22		85.0	-.115	.822			**			
23		90.0	-.025	.783	.170	-.035	**			
24		95.0	.069	.743			**			
	25	.5	.584	.509			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.120	.824	4.569	-.470	**			
		15.0					**			
	32	20.0	-.270	.890	5.255	-.265	**			
		25.0					**			
	34	30.0	-.359	.929	4.997	.001	**			
		40.0					**			
	36	50.0	-.372	.935	2.364	.206	**			
		60.0					**			
		70.0					**			
	39	80.0	.226	.674	.403	.202	**			
	40	90.0	.307	.633	.276	.105	**			

OVERALL COEFFICIENTS ** SECTION 5 **

		STEADY	RE	IM
Cz	UPPER	.407	1.420	.022
Cz	LOWER	-.078	.774	.009
Cz	TOTAL	.329	2.194	.031
Cm	UPPER	.043	-.243	.031
Cm	LOWER	.008	.118	.032
Cm	TOTAL	.051	-.126	.063

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.824	.378			**			
		.5					**			
3		1.5	-.095	.814			**			
		3.0					**			
5		5.0	-.512	.998	-13.26	-1.197	**			
		7.5					**			
7		10.0	-.603	1.039	-8.535	.429	**			
8		15.0	-.603	1.040	-6.325	.295	**			
9		20.0	-.570	1.024	-4.597	-.158	**			
10		25.0	-.532	1.007	-2.590	-.201	**			
11		30.0	-.483	.984			**			
12		35.0	-.452	.970	-1.011	-.603	**			
13		40.0	-.417	.955	-1.581	-.471	**			
14		45.0	-.398	.946	-1.369	-.746	**			
15		50.0	-.382	.939	-.742	-.397	**			
16		55.0	-.366	.932	-.575	.067	**			
17		60.0	-.348	.924	-.814	-.053	**			
18		65.0	-.341	.921	-.462	-.052	**			
19		70.0	-.329	.916	-.259	-.114	**			
20		75.0	-.296	.901	-.098	.247	**			
21		80.0	-.231	.873	0.000	0.000	**			
22		85.0	-.107	.819			**			
23		90.0	.006	.770	-.081	-.021	**			
24		95.0	.092	.733			**			
	25	.5	.398	.597			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.268	.889	4.353	-.244	**			
		20.0					**			
	33	25.0	-.340	.920			**			
	34	30.0	-.351	.925	3.282	.301	**			
	35	40.0	-.370	.934	2.108	.108	**			
	36	50.0	-.309	.907	.745	.170	**			
		60.0					**			
		70.0					**			
	39	80.0	.233	.671	-.024	.131	**			
	40	90.0	.296	.643	.104	.145	**			

OVERALL COEFFICIENTS ** SECTION 6 **

		STEADY	RE	IM
Cz	UPPER	.336	.775	.059
Cz	LOWER	-.075	.405	.030
Cz	TOTAL	.261	1.180	.089
Cm	UPPER	.042	-.119	.005
Cm	LOWER	.014	.019	.024
Cm	TOTAL	.056	-.100	.029

*** L.ANN *** RUN 124 ***   TABLE 9.13

TEST CONDITIONS		NORM. COEFF.			MOM. COEFF.				DISPLACEMENTS REL.TO LVDT	**	VIBRATION MODE	
			Cz	Czi		Cm	Cmi			AMPL.	PHASE	**Y/(B/2)	HEAVE AT X=.224 M	PITCH
				RE	IM		RE	IM		(-)	(DEG)	**	(MM)	(DEG)
RUNNR. = 124		SECT.1	.447	1.386	-.142	.013	.063	.130	LVDT	1.00	0.00	** .000		
		SECT.2	.487	1.523	-.203	.013	.035	.145	CALC. 1	1.09	2.48	** .100		
ALFA = 2.60 (DEG)		SECT.3	.550	2.251	-.094	.020	-.022	.139	ACC. 2	.34	1.69	** .100	.01	.22
MACH = .771		SECT.4	.557	1.644	.212	.033	-.139	.157	ACC. 3	.57	-176.46	** .100		
RE*10**-6= 5.22		SECT.5	.526	1.996	.050	.043	-.134	.083	ACC. 4	.24	-156.77	** .420		
Q =41.71 (KPA)		SECT.6	.409	1.424	.158	.044	-.165	.023	ACC. 5	.98	-179.19	** .420	.10	.24
P-SETTL. =148.5 (KPA)									ACC. 6	1.61	-177.35	** .420		
T-SETTL. =27.00		WING	.480	1.614	-.049	.045	.247	.231	ACC. 7	1.78	-175.51	** .700		
						(WING : CM ABOUT			CALC. 8	2.27	-178.41	** .700	.37	.22
DALFA = .249 (DEG)						AERODYN. CENTER)			CALC. 9	2.75	-177.82	** .700		
FREQ. =24.00 (Hz)									CALC.10	2.97	-177.75	** .920		
REDFR. = .080									ACC.11	3.37	-177.95	** .920	.43	.25
HARM. = 1									ACC.12	3.78	-178.11	** .920		

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.600	.500			**			
2		.5	-.175	.847			**			
3		1.5	-.913	1.189	-6.012	1.354	**			
4		3.0	-1.265	1.388	-5.124	.801	**			
5		5.0	-1.310	1.416			**	-6.617	1.911	105
6		7.5	-1.368	1.455			**			
7		10.0	-1.375	1.460	-4.070	2.166	**			
8		15.0	-1.305	1.413	-4.576	1.957	**			
9		20.0	-.747	1.106	-17.85	6.178	**			
10		25.0	-.620	1.045	-4.758	.559	**			
11		30.0	-.567	1.021	-2.719	-.123	**			
12		35.0	-.531	1.004			**			
13		40.0	-.498	.989	-1.589	-.621	**			
14		45.0	-.473	.978	-1.216	-.678	**			
15		50.0	-.439	.962	-1.138	-.841	**			
16		55.0	-.394	.943	-1.062	-.669	**			
17		60.0	-.351	.924	-.725	-.627	**			
18		65.0	-.296	.899	-.630	-.465	**			
19		70.0	-.237	.873	-.295	-.527	**	-.403	-.481	119
20		75.0	-.182	.850	-.270	-.238	**			
21		80.0	-.123	.824	-.076	-.334	**			
22		85.0	-.046	.791			**			
23		90.0	.011	.766	.047	-.248	**			
24		95.0	.085	.734			**			
	25	.5	.791	.397			**			
	26	1.5	.517	.540	3.798	.397	**			
	27	3.0	.429	.581	4.334	.868	**			
	28	5.0	.335	.624	2.568	-.332	**			
	29	7.5	.190	.688			**			
	31	15.0	.004	.769	2.473	-.670	**			
	32	20.0	-.123	.824	2.857	-.568	**			
	33	25.0	-.209	.861			**			
	34	30.0	-.303	.902	3.307	-.671	**			
	35	40.0	-.320	.910	2.329	-.301	**			
	36	50.0	-.345	.921	2.681	.044	**			
	37	60.0	-.195	.855	1.455	.136	**			
	38	70.0	.022	.762	.905	.133	**			
	39	80.0	.184	.691	.474	.211	**			
	40	90.0	.286	.646	.338	.237	**			

****
** SECTION 1 **
****

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.484	.816	-.111
Cz	LOWER	-.037	.570	-.031
Cz	TOTAL	.447	1.386	-.142
Cm	UPPER	.012	-.048	.107
Cm	LOWER	.001	.111	.023
Cm	TOTAL	.013	.063	.130

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.628	.485			**			
2		.5	-.137	.830			**			
3		1.5	-.960	1.214	-6.869	1.695	**			
4		3.0	-1.207	1.352	-6.192	2.055	**			
5		5.0	-1.314	1.419	-5.168	1.878	**			
6		7.5	-1.425	1.494			**			
7		10.0	-1.427	1.496	-4.099	2.539	**			
8		15.0	-1.369	1.456	-5.055	2.611	**			
9		20.0	-1.332	1.431	-3.889	2.438	**			
10		25.0	-.763	1.113	-19.67	5.790	**			
11		30.0	-.587	1.030	-11.59	3.841	**			
12		35.0	-.486	.984	-3.580	-.318	**			
13		40.0	-.451	.968	.532	-1.727	**			
14		45.0	-.432	.959			**			
15		50.0	-.419	.954	.418	-1.204	**			
16		55.0	-.376	.934	.296	-.908	**			
17		60.0	-.336	.917	.151	-.815	**			
18		65.0	-.297	.900	.145	-.504	**			
19		70.0	-.236	.873	.155	-.549	**			
20		75.0	-.175	.846	.004	-.316	**			
21		80.0	-.124	.824	-.019	-.230	**			
22		85.0	-.056	.795			**			
23		90.0	.011	.767	.011	-.059	**			
24		95.0	.086	.734			**			
	25	.5	.799	.393			**			
	26	1.5	.527	.535	4.567	.954	**			
	27	3.0	.416	.587			**			
	28	5.0	.288	.645	1.757	-.592	**			
	29	7.5	.198	.685			**			
	30	10.0	.141	.710	2.955	-.625	**			
	31	15.0	-.003	.772	2.764	-.514	**			
	32	20.0	-.128	.826	2.965	-.443	**			
	33	25.0	-.211	.862			**			
	34	30.0	-.290	.896	3.423	-.629	**			
	35	40.0	-.352	.924	3.460	.154	**			
	36	50.0	-.330	.914	2.178	.143	**			
	37	60.0	-.168	.843	1.584	.297	**			
	38	70.0	.044	.752	.819	.187	**			
	39	80.0	.202	.683	.500	.205	**			
	40	90.0	.297	.641	.427	.237	**			

****
** SECTION 2 **
****

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.518	.900	-.194
Cz	LOWER	-.031	.623	-.009
Cz	TOTAL	.487	1.523	-.203
Cm	UPPER	.008	-.078	.109
Cm	LOWER	.005	.113	.036
Cm	TOTAL	.013	.035	.145

*** L∩NN *** RUN 124 *** TABLE 9.13 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.651	.474			**			
2		.5	-.165	.842			**			
3		1.5	-.915	1.190	-6.131	.474	**			
4		3.0	-1.214	1.357	-6.485	.051	**			
5		5.0	-1.311	1.418	-6.863	-.762	**			
6		7.5	-1.403	1.479			**			
7		10.0	-1.387	1.468	-4.964	.973	**	-5.070	1.166	307
8		15.0	-1.382	1.464	-4.987	1.190	**			
9		20.0	-1.335	1.433	-6.515	1.355	**	-6.487	1.629	309
10		25.0	-1.138	1.312	-40.09	7.311	**			
		30.0					**			
12		35.0	-.537	1.007	-16.23	2.396	**			
13		40.0	-.442	.964	-4.152	-.647	**	-4.311	-.380	313
14		45.0	-.409	.949	2.287	-2.267	**			
15		50.0	-.392	.942	2.006	-1.873	**	2.540	-2.067	315
16		55.0	-.361	.928	2.128	-1.686	**			
17		60.0	-.332	.915	1.440	-1.274	**	1.461	-1.330	317
18		65.0	-.291	.897	1.097	-1.101	**			
19		70.0	-.244	.876	.731	-.724	**	.854	-.833	319
20		75.0	-.188	.852	.564	-.629	**			
21		80.0	-.128	.826	.242	-.588	**	.322	-.367	321
22		85.0	-.068	.800			**			
23		90.0	.001	.771	.130	-.273	**	.145	-.195	323
24		95.0	.081	.736			**			
	25	.5	.807	.388			**			
	26	1.5	.548	.525	4.680	1.205	**			
	27	3.0	.423	.584	5.053	1.149	**			
		5.0					**			
	29	7.5	.199	.685			**			
	30	10.0	.114	.722	2.704	-.595	**			
		15.0					**			
	32	20.0	-.118	.822	3.075	-.424	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.300	.901	2.549	.124	**			
	37	60.0	-.146	.834	1.199	.151	**			
	38	70.0	.056	.747	.737	.086	**			
	39	80.0	.215	.678	.527	.160	**			
	40	90.0	.309	.636	.355	.248	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 3 ** RE	IM
Cz	UPPER	.549	1.656	-.098
Cz	LOWER	.001	.595	.004
Cz	TOTAL	.550	2.251	-.094
Cm	UPPER	.010	-.113	.118
Cm	LOWER	.010	.091	.020
Cm	TOTAL	.020	-.022	.139

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.714	.440			**			
2		.5	-.125	.825			**			
3		1.5	-.898	1.181	-9.442	.197	**			
4		3.0	-1.106	1.293	-6.812	.166	**			
5		5.0	-1.276	1.395	-5.249	-.069	**	-7.187	1.405	405
6		7.5	-1.328	1.428			**			
7		10.0					**	-4.483	1.040	407
8		15.0	-1.310	1.416	-8.163	.272	**			
9		20.0	-1.298	1.409	-7.198	.712	**	-7.185	1.362	409
10		25.0	-1.262	1.386	-9.636	1.469	**			
		30.0					**			
12		35.0	-.542	1.009	-18.74	.230	**			
13		40.0	-.451	.968	-5.087	-1.341	**	-5.903	-.406	413
14		45.0	-.422	.955	2.538	-2.061	**			
15		50.0	-.406	.948	4.034	-2.032	**	3.161	-1.945	415
16		55.0	-.390	.941	2.971	-1.899	**			
17		60.0	-.362	.928	2.634	-1.159	**	2.301	-1.334	417
		65.0					**			
19		70.0	-.285	.895	1.307	-.833	**			
20		75.0	-.254	.881	1.177	-.563	**			
21		80.0	-.163	.841	.592	-.336	**	.860	-.458	421
22		85.0	-.077	.804			**			
23		90.0	-.004	.773	.241	-.210	**			
24		95.0	.070	.741			**			
	25	.5	.773	.408			**			
	26	1.5	.483	.556	5.222	1.592	**			
	27	3.0	.349	.618	4.820	1.320	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.014	.777	3.024	-.239	**			
	32	20.0	-.119	.822	3.251	-.119	**			
	33	25.0	-.192	.854			**			
		30.0					**			
	35	40.0	-.307	.904	3.466	.405	**			
	36	50.0	-.287	.896	2.436	.211	**			
	37	60.0	-.111	.819	1.245	.384	**			
	38	70.0	.077	.738	.818	.393	**			
	39	80.0	.243	.665	.469	.248	**			
	40	90.0	.322	.630	.390	.270	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 4 ** RE	IM
Cz	UPPER	.560	.960	.117
Cz	LOWER	-.003	.684	.095
Cz	TOTAL	.557	1.644	.212
Cm	UPPER	.018	-.222	.123
Cm	LOWER	.015	.084	.034
Cm	TOTAL	.033	-.139	.157

*** LANN *** RUN 124 ***   TABLE 9.13 (cont'd)

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.732	.431			**			
2		.5	-.044	.790			**			
3		1.5	-.653	1.061	-7.437	-.055	**			
4		3.0	-1.008	1.239	-7.094	-.121	**			
5		5.0	-1.114	1.298	-8.880	-.021	**	-7.776	1.283	505
6		7.5	-1.153	1.320			**			
7		10.0	-1.191	1.343	-7.917	.205	**			
		15.0					**			
9		20.0	-1.169	1.330	-11.41	.125	**			
10		25.0	-1.094	1.287	-22.71	1.087	**			
11		30.0	-.612	1.042	-35.68	2.370	**			
		35.0					**			
13		40.0	-.460	.972	5.762	-2.407	**			
14		45.0	-.457	.971	5.837	-1.787	**			
15		50.0	-.446	.966	4.075	-1.357	**			
16		55.0	-.426	.957	2.711	-.869	**			
17		60.0	-.399	.945	1.838	-.837	**			
18		65.0	-.373	.933	1.229	-.419	**			
19		70.0	-.338	.918	1.011	-.366	**	1.014	-.322	519
20		75.0	-.301	.901	.213	-.279	**			
21		80.0	-.226	.869	.128	-.068	**			
22		85.0	-.113	.820			**			
23		90.0	-.026	.782	-.151	-.036	**			
24		95.0	.067	.742			**			
	25	.5	.737	.427			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	.044	.752	2.932	-.429	**			
		15.0					**			
	32	20.0	-.130	.827	3.476	-.088	**			
		25.0					**			
	34	30.0	-.239	.874	2.978	-.529	**			
		40.0					**			
	36	50.0	-.304	.903	1.951	.076	**			
		60.0					**			
		70.0					**			
	39	80.0	.244	.665	.423	.134	**			
	40	90.0	.320	.631	.222	.091	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
C_z	UPPER	.527	1.461	.074
C_z	LOWER	-.001	.535	-.024
C_z	TOTAL	.526	1.996	.050
C_m	UPPER	.031	-.239	.067
C_m	LOWER	.012	.105	.016
C_m	TOTAL	.043	-.134	.083

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.734	.429			**			
		.5					**			
3		1.5	-.437	.962			**			
		3.0					**			
5		5.0	-.916	1.190	-8.674	-.321	**			
		7.5					**			
7		10.0	-.992	1.231	-10.54	-.710	**			
8		15.0	-1.011	1.240	-7.087	-.510	**			
9		20.0	-.939	1.202	-39.10	-1.774	**			
10		25.0	-.515	.997	-7.908	-2.169	**			
11		30.0	-.460	.972			**			
12		35.0	-.459	.971	5.016	-.677	**			
13		40.0	-.435	.961	1.973	-.133	**			
14		45.0	-.417	.953	.958	-.443	**			
15		50.0	-.399	.945	.359	-.003	**			
16		55.0	-.381	.937	.067	-.142	**			
17		60.0	-.361	.928	-.277	-.128	**			
18		65.0	-.354	.925	-.330	.014	**			
19		70.0	-.339	.918	-.316	.020	**			
20		75.0	-.305	.903	-.344	.155	**			
21		80.0	-.238	.874	-.577	.199	**			
22		85.0	-.115	.821			**			
23		90.0	-.007	.774	-.664	.111	**			
24		95.0	.077	.738			**			
	25	.5	.639	.480			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.132	.828	2.686	-.097	**			
		20.0					**			
	33	25.0	-.243	.876			**			
	34	30.0	-.272	.889	2.163	-.102	**			
	35	40.0	-.317	.909	1.743	.260	**			
	36	50.0	-.282	.893	.740	.139	**			
		60.0					**			
		70.0					**			
	39	80.0	.229	.672	-.047	.274	**			
	40	90.0	.294	.643	-.168	.239	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
C_z	UPPER	.427	1.146	.124
C_z	LOWER	-.018	.278	.034
C_z	TOTAL	.409	1.424	.158
C_m	UPPER	.034	-.181	-.013
C_m	LOWER	.010	.016	.036
C_m	TOTAL	.044	-.165	.023

*** LANN *** RUN 72 *** TABLE 9.14

TEST CONDITIONS			NORM. COEFF.		MOM. COEFF.			DISPLACEMENTS	**	VIBRATION MODE		
			Cz	Czi	Cm	Cmi		REL.TO LVDT	**Y/(B/2)!	HEAVE AT	PITCH	
			RE	IM	RE	IM		AMPL.! PHASE	**	X=.224 M		
								(-) ! (DEG)	**	(MM)	(DEG)	

RUNNR. = 72		SECT.1 .304 1.505 -.151 ! .014 .128 .053 !	LVDT !	1.00 0.00	** .000		
		SECT.2 .332 2.029 -.245 ! .015 .144 .076 !	CALC. 1!	1.47 -.49	** .100		
ALFA = .60 (DEG)		SECT.3 .383 2.522 -.126 ! .024 .133 .100 !	ACC. 2!	.59 -7.55	** .100	.11	.27
MACH = .821		SECT.4 .377 2.207 .006 ! .037 .029 .115 !	ACC. 3!	.51 -162.07	** .100		
RE*10**-6= 5.43		SECT.5 .344 2.019 -.101 ! .047 -.009 .079 !	ACC. 4!	.42 -35.57	** .420		
Q =45.18 (KPA)		SECT.6 .256 1.433 -.030 ! .049 -.113 .044 !	ACC. 5!	.32 -190.70	** .420		
P-SETTL. =149.2 (KPA)			ACC. 6!	1.13 -167.16	** .420	.31	.26
T-SETTL. =26.00		WING .325 1.866 -.121 ! .037 .387 .104 !	ACC. 7!	.43 -139.54	** .700		
		(WING : CM ABOUT !	CALC. 8!	1.01 -179.10	** .700		
DALFA = .251 (DEG)		AERODYN. CENTER) !	CALC. 9!	1.55 -168.57	** .700	.68	.29
FREQ. =12.00 (Hz)			CALC.10!	1.21 -176.34	** .920		
REDFR. = .038			ACC.11!	1.50 -172.16	** .920	.35	.19
HARM. = 1			ACC.12!	1.79 -169.29	** .920		

Section 1

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES) ** CALIBRATION (TRANSD.)						
UP ! LOW!			Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1		0.0	.746	.453			**		
2		.5	.127	.761			**		
3		1.5	-.499	1.061	-3.704	1.186	**		
4		3.0	-.871	1.264	-5.303	.991	**		
5		5.0	-.890	1.276			** -6.344	.845	105
6		7.5	-1.046	1.374			**		
7		10.0	-1.067	1.388	-3.814	.992	**		
8		15.0	-.982	1.332	-6.877	1.416	**		
9		20.0	-.629	1.128	-6.490	.546	**		
10		25.0	-.614	1.120	-3.170	.300	**		
11		30.0	-.609	1.117	-4.160	1.012	**		
12		35.0	-.599	1.112			**		
13		40.0	-.612	1.119	-2.505	.367	**		
14		45.0	-.549	1.086	-14.40	4.097	**		
15		50.0	-.429	1.025	-1.388	-1.136	**		
16		55.0	-.387	1.005	.244	-.784	**		
17		60.0	-.346	.985	-.041	-.646	**		
18		65.0	-.289	.957	-.240	-.379	**		
19		70.0	-.227	.927	-.287	-.230	** -.202	-.404	119
20		75.0	-.171	.901	-.124	-.219	**		
21		80.0	-.110	.872	.001	-.152	**		
22		85.0	-.033	.836			**		
23		90.0	.026	.808	.074	-.161	**		
24		95.0	.101	.773			**		
	25	.5	.705	.476			**		
	26	1.5	.370	.647	3.797	-.705	**		
	27	3.0	.307	.677	3.952	-.182	**		
	28	5.0	.221	.717	3.916	.061	**		
	29	7.5	.077	.785			**		
		10.0					**		
	31	15.0	-.098	.866	3.107	-.362	**		
	32	20.0	-.238	.932	4.028	.017	**		
	33	25.0	-.334	.979			**		
	34	30.0	-.453	1.038	3.366	-.460	**		
	35	40.0	-.507	1.065	3.383	-.933	**		
	36	50.0	-.493	1.057	1.778	-.011	**		
	37	60.0	-.251	.939	1.103	.226	**		
	38	70.0	-.003	.822	.806	.168	**		
	39	80.0	.168	.742	.709	.193	**		
	40	90.0	.277	.691	.437	.140	**		

OVERALL COEFFICIENTS *** SECTION 1 *****

		STEADY!	RE	IM
Cz	UPPER	.428	.852	-.114
Cz	LOWER	-.124	.653	-.037
Cz	TOTAL	.304	1.505	-.151
Cm	UPPER	.021	.038	.036
Cm	LOWER	-.007	.090	.018
Cm	TOTAL	.014	.128	.053

Section 2

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES) ** CALIBRATION (TRANSD.)						
UP ! LOW!			Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1		0.0	.777	.435			**		
2		.5	.168	.742			**		
3		1.5	-.488	1.055	-5.894	1.094	**		
4		3.0	-.794	1.219	-5.466	.829	**		
5		5.0	-.913	1.290	-5.849	.994	**		
6		7.5	-1.056	1.381			**		
7		10.0	-1.085	1.400	-2.239	.603	**		
8		15.0	-1.052	1.378	-4.635	.986	**		
9		20.0	-1.021	1.358	-7.114	1.698	**		
10		25.0	-.915	1.291	-21.87	6.100	**		
11		30.0	-.672	1.151	-9.147	1.750	**		
12		35.0	-.613	1.120	-7.467	1.352	**		
13		40.0	-.498	1.060	-12.26	.885	**		
14		45.0	-.430	1.026			**		
15		50.0	-.416	1.019	.813	-1.302	**		
16		55.0	-.373	.998	.348	-.940	**		
17		60.0	-.329	.976	.318	-.768	**		
18		65.0	-.286	.955	.274	-.516	**		
19		70.0	-.224	.926	.257	-.331	**		
20		75.0	-.162	.896	.154	-.295	**		
21		80.0	-.108	.871	.265	-.231	**		
22		85.0	-.039	.838			**		
23		90.0	.030	.807	.101	-.217	**		
24		95.0	.106	.771			**		
	25	.5	.702	.478			**		
	26	1.5	.370	.647	4.636	-.420	**		
	27	3.0	.273	.693			**		
	28	5.0	.162	.745	2.737	-1.014	**		
	29	7.5	.068	.789			**		
	30	10.0	.019	.812	3.306	-.405	**		
	31	15.0	-.127	.880	3.316	-.531	**		
	32	20.0	-.266	.946	4.409	-.353	**		
	33	25.0	-.362	.992			**		
	34	30.0	-.468	1.045	4.038	-.574	**		
	35	40.0	-.552	1.088	5.148	-.574	**		
	36	50.0	-.452	1.037	1.952	-.263	**		
	37	60.0	-.216	.922	1.204	.226	**		
	38	70.0	.023	.810	.792	.076	**		
	39	80.0	.186	.734	.757	.150	**		
	40	90.0	.286	.687	.418	.068	**		

OVERALL COEFFICIENTS *** SECTION 2 *****

		STEADY!	RE	IM
Cz	UPPER	.454	1.281	-.176
Cz	LOWER	-.123	.748	-.070
Cz	TOTAL	.332	2.029	-.245
Cm	UPPER	.017	.030	.060
Cm	LOWER	-.002	.114	.016
Cm	TOTAL	.015	.144	.076

*** LANN *** RUN 72 ***   TABLE 9.14 (cont'd)

NR. UP	NR. LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
			PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)		
1		0.0	.800	.421			**			
2		.5	.155	.749			**			
3		1.5	-.491	1.056	-4.786	.648	**			
4		3.0	-.759	1.200	-5.876	.514	**			
5		5.0	-.884	1.272	-5.215	.008	**			
6		7.5	-1.034	1.366			**			
7		10.0	-1.037	1.368	-3.434	.285	**	-4.710	.565	307
8		15.0	-1.050	1.377	-5.022	.459	**			
9		20.0	-1.036	1.367	-5.187	.466	**	-4.513	.573	309
10		25.0	-1.019	1.356	-5.948	.680	**			
		30.0					**			
12		35.0	-.722	1.179	-51.15	9.538	**			
13		40.0	-.458	1.040	-14.21	-.997	**	-11.11	.415	313
14		45.0	-.395	1.009	-.987	-1.671	**			
15		50.0	-.373	.998	2.245	-2.021	**	2.366	-1.546	315
16		55.0	-.343	.983	2.961	-1.621	**			
17		60.0	-.317	.970	2.241	-1.281	**	2.303	-1.082	317
18		65.0	-.278	.952	1.831	-.950	**			
19		70.0	-.230	.929	1.309	-.782	**	1.256	-.603	319
20		75.0	-.172	.901	.775	-.588	**			
21		80.0	-.112	.873	.567	-.408	**	.510	-.283	321
22		85.0	-.050	.844			**			
23		90.0	.020	.811	.272	-.363	**	.215	-.158	323
24		95.0	.102	.773			**			
	25	.5	.699	.479			**			
	26	1.5	.374	.645	5.112	-.612	**			
	27	3.0	.260	.699	5.821	.498	**			
		5.0					**			
	29	7.5	.049	.798			**			
	30	10.0	-.029	.834	3.466	-.588	**			
		15.0					**			
	32	20.0	-.272	.949	4.888	-.380	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.417	1.020	2.457	.006	**			
	37	60.0	-.191	.910	1.071	.039	**			
	38	70.0	.038	.803	.811	-.024	**			
	39	80.0	.199	.728	.971	.100	**			
	40	90.0	.299	.681	.583	.077	**			

OVERALL COEFFICIENTS — ** SECTION 3 **

		STEADY	RE	IM
Cz	UPPER	.466	1.744	-.092
Cz	LOWER	-.084	.778	-.034
Cz	TOTAL	.383	2.522	-.126
Cm	UPPER	.018	.036	.089
Cm	LOWER	.006	.097	.011
Cm	TOTAL	.024	.133	.100

NR. UP	NR. LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
			PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)		
1		0.0	.841	.396			**			
2		.5	.220	.718			**			
3		1.5	-.307	1.005	-7.154	.321	**			
4		3.0	-.692	1.162	-4.746	.429	**			
5		5.0	-.856	1.255	-3.861	.268	**	-5.123	.587	405
6		7.5	-.946	1.310			**			
7		10.0					**	-4.925	.689	407
8		15.0	-.967	1.323	-5.379	.061	**			
9		20.0	-.985	1.335	-4.862	.265	**	-5.112	.624	409
10		25.0	-.979	1.330	-6.437	.402	**			
		30.0					**			
12		35.0	-.901	1.282	-22.53	2.968	**			
13		40.0	-.533	1.078	-33.99	.914	**	-33.48	3.394	413
14		45.0	-.399	1.011	-5.181	-1.906	**			
15		50.0	-.372	.997	3.172	-1.893	**	3.168	-1.643	415
16		55.0	-.359	.991	4.948	-2.154	**			
17		60.0	-.340	.981	4.439	-1.400	**	4.244	-1.316	417
		65.0					**			
19		70.0	-.272	.949	2.256	-.616	**			
20		75.0	-.242	.934	2.112	-.310	**			
21		80.0	-.147	.890	.957	-.331	**	1.255	-.335	421
22		85.0	-.059	.848			**			
23		90.0	.016	.813	.346	-.225	**			
24		95.0	.092	.778			**			
	25	.5	.639	.512			**			
	26	1.5	.276	.692	5.722	-.672	**			
	27	3.0	.157	.747	5.214	-.454	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.170	.900	4.341	-.498	**			
	32	20.0	-.282	.954	5.275	-.329	**			
	33	25.0	-.363	.993			**			
		30.0					**			
	35	40.0	-.485	1.054	4.652	-.141	**			
	36	50.0	-.400	1.011	2.247	-.091	**			
	37	60.0	-.152	.892	1.175	.101	**			
	38	70.0	.061	.792	.802	.037	**			
	39	80.0	.226	.715	1.041	.110	**			
	40	90.0	.310	.676	.717	.092	**			

OVERALL COEFFICIENTS — ** SECTION 4 **

		STEADY	RE	IM
Cz	UPPER	.477	1.319	.046
Cz	LOWER	-.100	.888	-.039
Cz	TOTAL	.377	2.207	.006
Cm	UPPER	.028	-.082	.098
Cm	LOWER	.010	.111	.017
Cm	TOTAL	.037	.029	.115

*** LANN *** RUN 72 *** TABLE 9.14 (cont'd)

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.846	.393			**			
2		.5	.306	.678			**			
3		1.5	-.251	.939	-6.831	.377	**			
4		3.0	-.533	1.078	-5.072	.940	**			
5		5.0	-.676	1.154	-8.631	.555	**	-7.681	.561	505
6		7.5	-.752	1.175			**			
7		10.0	-.823	1.236	-3.835	.835	**			
		15.0					**			
9		20.0	-.829	1.239	-8.029	.724	**			
10		25.0	-.834	1.242	-5.063	.238	**			
11		30.0	-.862	1.259	-7.216	.663	**			
		35.0					**			
13		40.0	-.549	1.086	-41.05	3.060	**			
14		45.0	-.412	1.017	1.214	-2.749	**			
15		50.0	-.401	1.012	8.591	-2.435	**			
16		55.0	-.395	1.009	7.576	-1.728	**			
17		60.0	-.377	1.000	5.131	-1.117	**			
18		65.0	-.357	.990	3.109	-.606	**			
19		70.0	-.323	.974	1.986	-.282	**	2.059	-.312	519
20		75.0	-.286	.955	.774	-.416	**			
21		80.0	-.207	.918	.614	-.202	**			
22		85.0	-.093	.864			**			
23		90.0	-.005	.823	.068	-.131	**			
24		95.0	.088	.779			**			
	25	.5	.570	.548			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.140	.886	4.734	-1.183	**			
		15.0					**			
	32	20.0	-.307	.965	6.142	-.321	**			
		25.0					**			
	34	30.0	-.413	1.017	4.602	-.930	**			
		40.0					**			
	36	50.0	-.401	1.011	1.771	-.266	**			
		60.0					**			
		70.0					**			
	39	80.0	.232	.712	.982	.011	**			
	40	90.0	.316	.673	.710	-.073	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
Cz	UPPER	.442	1.220	.014
Cz	LOWER	-.098	.798	-.115
Cz	TOTAL	.344	2.019	-.101
Cm	UPPER	.040	-.145	.087
Cm	LOWER	.007	.136	-.008
Cm	TOTAL	.047	-.009	.079

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.835	.400			**			
		.5					**			
3		1.5	-.049	.844			**			
		3.0					**			
5		5.0	-.514	1.068	-8.047	.402	**			
		7.5					**			
7		10.0	-.718	1.177	-3.853	.216	**			
8		15.0	-.684	1.158	-9.818	1.313	**			
9		20.0	-.768	1.204			**			
10		25.0	-.795	1.220	-6.390	.732	**			
11		30.0	-.386	1.004			**			
12		35.0	-.462	1.042	-29.35	-.745	**			
13		40.0	-.326	.975	6.272	-1.018	**			
14		45.0	-.352	.988	8.238	-.777	**			
15		50.0	-.363	.993	4.537	-.474	**			
16		55.0	-.357	.990	1.985	-.393	**			
17		60.0	-.343	.983	.841	-.037	**			
18		65.0	-.338	.980	.212	-.106	**			
19		70.0	-.323	.973	-.146	.022	**			
20		75.0	-.285	.955	-.120	.164	**			
21		80.0	-.214	.921	-.671	.127	**			
22		85.0	-.086	.861			**			
23		90.0	.025	.809	-.790	-.050	**			
24		95.0	.110	.769			**			
	25	.5	.398	.634			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.307	.965	5.626	-.553	**			
		20.0					**			
	33	25.0	-.404	1.013			**			
	34	30.0	-.408	1.015	2.544	-.173	**			
	35	40.0	-.406	1.014	1.085	-.021	**			
	36	50.0	-.347	.970	.328	-.030	**			
		60.0					**			
		70.0					**			
	39	80.0	.235	.711	.045	.119	**			
	40	90.0	.300	.680	.253	.113	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
Cz	UPPER	.350	1.054	-.008
Cz	LOWER	-.094	.380	-.022
Cz	TOTAL	.256	1.433	-.030
Cm	UPPER	.036	-.103	.027
Cm	LOWER	.013	-.010	.016
Cm	TOTAL	.049	-.113	.044

*** LANN *** RUN 73 *** TABLE 9.15a

TEST CONDITIONS				NORM. COEFF		MOM. COEFF.				DISPLACEMENTS	**	VIBRATION MODE		
			Cz	Czi		Cm	Cmi			REL. TO LVDT	**Y/(B/2)!	HEAVE AT	!	PITCH
				RE	IM		RE	IM		AMPL.! PHASE	**	! X=.224 M		
										(--) ! (DEG)	**	! (MM)	!	(DEG)
RUNNR. = 73		!SECT.1 .300	1.429	-.297	! .014	.099	.082 !	! LVDT !	1.00 0.00	** .000			
		!SECT.2 .325	1.981	-.572	! .015	.128	.093 !	!CALC. 1!	1.13 1.52	** .100			
ALFA = .59 (DEG)		!SECT.3 .377	2.494	-.465	! .023	.131	.097 !	! ACC. 2!	.37 -.33	** .100	.01		.23
MACH = .822		!SECT.4 .371	2.592	-.147	! .037	.077	.140 !	! ACC. 3!	.55 -175.71	** .100			
RE*10**-6= 5.43		!SECT.5 .341	2.083	-.090	! .047	-.041	.107 !	! ACC. 4!	.13 -139.19	** .420			
Q =45.22 (KPA)		!SECT.6 .255	1.340	.024	! .049	-.162	.030 !	! ACC. 5!	.85 -175.73	** .420			
P-SETTL. =149.1 (KPA)									! ACC. 6!	1.52 -175.55	** .420	.05		.24
T-SETTL. =26.00		WING .320	1.889	-.296	! .037	.453	.156 !	! ACC. 7!	1.52 -170.87	** .700			
					!(WING	CM ABOUT	!	!CALC. 8!	2.01 -174.98	** .700	.24		.23
DALFA = .250 (DEG)					! AERODYN. CENTER) !			!CALC. 9!	2.50 -175.03	** .700			
FREQ. =24.00 (Hz)									!CALC.10!	2.61 -173.58	** .920			
REDFR. = .076									! ACC.11!	2.98 -174.16	** .920	.36		.22
HARM. = 1									! ACC.12!	3.35 -174.61	** .920			

NR.	XCHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)				OVERALL		***************** ** SECTION 1 ** *****************		
UP ! LOW!		Cp STEADY!	M-LOC.!	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.!		COEFFICIENTS !		! STEADY!	RE	! IM
1 !	0.0	.743 !	.455 !			**					Cz UPPER !	.424 !	.854 !	-.232 !
2 !	.5	.128 !	.762 !			**					Cz LOWER !	-.124 !	.575 !	-.065 !
3 !	1.5	-.500 !	1.063 !	-3.845 !	.974	**					Cz TOTAL !	.300 !	1.429 !	-.297 !
4 !	3.0	-.870 !	1.265 !	-6.380 !	1.912	**								
5 !	5.0	-.888 !	1.276 !			**	-6.142 !	1.929 !	105 !		Cm UPPER !	.021 !	.045 !	.060 !
6 !	7.5	-1.045 !	1.376 !			**					Cm LOWER !	-.007 !	.054 !	.021 !
7 !	10.0	-1.065 !	1.389 !	-4.034 !	1.197	**					Cm TOTAL !	.014 !	.099 !	.082 !
8 !	15.0	-.969 !	1.326 !	-9.239 !	4.004	**								
9 !	20.0	-.620 !	1.125 !	-5.258 !	2.427	**								
10 !	25.0	-.606 !	1.117 !	-2.512 !	1.003	**								
11 !	30.0	-.585 !	1.106 !	-3.414 !	1.534	**								
12 !	35.0	-.579 !	1.103 !			**								
13 !	.40.0	-.591 !	1.110 !	-2.899 !	1.567	**								
14 !	45.0	-.568 !	1.098 !	-8.638 !	4.836	**								
15 !	50.0	-.431 !	1.028 !	-2.773 !	-1.001	**								
16 !	55.0	-.386 !	1.005 !	-.694 !	-1.513	**								
17 !	60.0	-.345 !	.985 !	-.655 !	-.913	**								
18 !	65.0	-.289 !	.958 !	-.769 !	-.814	**								
19 !	70.0	-.226 !	.928 !	-.545 !	-.511	**	-.379 !	-.678 !	119 !					
20 !	75.0	-.171 !	.902 !	-.382 !	-.357	**								
21 !	80.0	-.110 !	.873 !	-.230 !	-.220	**								
22 !	85.0	-.033 !	.837 !			**								
23 !	90.0	.027 !	.809 !	-.147 !	-.163	**								
24 !	95.0	.101 !	.775 !			**								
! 25	.5	.703 !	.478 !			**								
! 26	1.5	.368 !	.649 !	3.781 !	-.242	**								
! 27	3.0	.306 !	.678 !	4.488 !	.202	**								
! 28	5.0	.221 !	.718 !	5.029 !	-.434	**								
! 29	7.5	.076 !	.786 !			**								
!	10.0					**								
! 31	15.0	-.099 !	.868 !	2.788 !	-.713	**								
! 32	20.0	-.239 !	.934 !	4.414 !	-.600	**								
! 33	25.0	-.333 !	.980 !			**								
! 34	30.0	-.454 !	1.039 !	2.426 !	-.644	**								
! 35	40.0	-.508 !	1.067 !	2.240 !	-.991	**								
! 36	50.0	-.491 !	1.058 !	1.144 !	.145	**								
! 37	60.0	-.250 !	.939 !	.949 !	.278	**								
! 38	70.0	-.003 !	.823 !	.762 !	.150	**								
! 39	80.0	.167 !	.744 !	.531 !	.123	**								
! 40	90.0	.277 !	.692 !	.509 !	.162	**								

NR.	XCHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)				OVERALL		***************** ** SECTION 2 ** *****************		
UP ! LOW!		Cp STEADY!	M-LOC.!	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.!		COEFFICIENTS !		! STEADY!	RE	! IM
1 !	0.0	.774 !	.437 !			**					Cz UPPER !	.448 !	1.332 !	-.476 !
2 !	.5	.168 !	.743 !			**					Cz LOWER !	-.123 !	.648 !	-.097 !
3 !	1.5	-.489 !	1.057 !	-6.240 !	1.177	**					Cz TOTAL !	.325 !	1.981 !	-.572 !
4 !	3.0	-.792 !	1.220 !	-6.242 !	1.958	**								
5 !	5.0	-.913 !	1.291 !	-6.733 !	1.297	**					Cm UPPER !	.017 !	.042 !	.073 !
6 !	7.5	-1.055 !	1.382 !			**					Cm LOWER !	-.002 !	.086 !	.020 !
7 !	10.0	-1.084 !	1.402 !	-2.500 !	.930	**					Cm TOTAL !	.015 !	.128 !	.093 !
8 !	15.0	-1.049 !	1.379 !	-4.612 !	1.744	**								
9 !	20.0	-1.018 !	1.358 !	-7.080 !	3.242	**								
10 !	25.0	-.864 !	1.262 !	-27.14 !	17.045	**								
11 !	30.0	-.645 !	1.139 !	-7.844 !	3.807	**								
12 !	35.0	-.588 !	1.108 !	-6.198 !	3.244	**								
13 !	40.0	-.488 !	1.057 !	-9.459 !	2.340	**								
14 !	45.0	-.431 !	1.028 !			**								
15 !	50.0	-.415 !	1.020 !	-.105 !	-1.798	**								
16 !	55.0	-.370 !	.997 !	-.375 !	-1.450	**								
17 !	60.0	-.328 !	.977 !	-.246 !	-1.113	**								
18 !	65.0	-.286 !	.957 !	-.020 !	-1.000	**								
19 !	70.0	-.223 !	.926 !	-.014 !	-.763	**								
20 !	75.0	-.161 !	.897 !	-.154 !	-.517	**								
21 !	80.0	-.107 !	.871 !	-.203 !	-.281	**								
22 !	85.0	-.038 !	.839 !			**								
23 !	90.0	.031 !	.807 !	-.070 !	-.200	**								
24 !	95.0	.106 !	.772 !			**								
! 25	.5	.701 !	.479 !			**								
! 26	1.5	.369 !	.648 !	5.005 !	.075	**								
! 27	3.0	.272 !	.694 !			**								
! 28	5.0	.162 !	.746 !	2.606 !	-.925	**								
! 29	7.5	.068 !	.790 !			**								
! 30	10.0	.018 !	.813 !	2.868 !	-.600	**								
! 31	15.0	-.127 !	.881 !	3.093 !	-.819	**								
! 32	20.0	-.267 !	.948 !	4.661 !	-.661	**								
! 33	25.0	-.362 !	.993 !			**								
! 34	30.0	-.469 !	1.047 !	2.071 !	-.803	**								
! 35	40.0	-.554 !	1.091 !	4.405 !	-1.278	**								
! 36	50.0	-.450 !	1.038 !	1.185 !	-.134	**								
! 37	60.0	-.214 !	.922 !	1.103 !	.240	**								
! 38	70.0	.024 !	.811 !	.661 !	.270	**								
! 39	80.0	.185 !	.735 !	.555 !	.128	**								
! 40	90.0	.287 !	.687 !	.531 !	.162	**								

*** LANN *** RUN 73 ***   TABLE 9.15a (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.797	.424			**			
2		.5	.155	.749			**			
3		1.5	-.491	1.058	-4.767	.915	**			
4		3.0	-.757	1.200	-6.496	1.365	**			
5		5.0	-.884	1.274	-6.490	1.048	**			
6		7.5	-1.034	1.368			**			
7		10.0	-1.036	1.370	-3.839	.672	**	-4.666	1.276	307
8		15.0	-1.048	1.378	-5.244	.897	**			
9		20.0	-1.034	1.369	-5.233	1.376	**	-4.519	1.287	309
10		25.0	-1.015	1.356	-6.677	1.915	**			
		30.0					**			
12		35.0	-.663	1.148	-46.21	23.813	**			
13		40.0	-.452	1.038	-13.10	2.223	**	-11.36	1.787	313
14		45.0	-.397	1.011	-2.309	-2.191	**			
15		50.0	-.372	.999	1.152	-2.545	**	1.717	-3.171	315
16		55.0	-.342	.984	2.153	-2.914	**			
17		60.0	-.317	.972	1.695	-2.116	**	1.980	-2.250	317
18		65.0	-.279	.953	1.475	-1.962	**			
19		70.0	-.229	.930	1.128	-1.175	**	1.137	-1.215	319
20		75.0	-.172	.902	.752	-.827	**			
21		80.0	-.112	.874	.238	-.465	**	.508	-.402	321
22		85.0	-.050	.845			**			
23		90.0	.020	.812	.218	-.246	**	.212	-.251	323
24		95.0	.101	.775			**			
	25	.5	.698	.481			**			
	26	1.5	.373	.646	5.474	.575	**			
	27	3.0	.258	.701	7.114	1.410	**			
		5.0					**			
	29	7.5	.048	.799			**			
	30	10.0	-.030	.835	2.922	-.579	**			
		15.0					**			
	32	20.0	-.273	.951	5.293	-.286	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.416	1.020	1.764	.249	**			
	37	60.0	-.191	.911	1.193	.121	**			
	38	70.0	.038	.804	.758	.141	**			
	39	80.0	.198	.729	.734	.173	**			
	40	90.0	.300	.681	.756	.153	**			

**OVERALL COEFFICIENTS — ** SECTION 3 **

		STEADY	RE	IM
Cz	UPPER	.461	1.733	-.405
Cz	LOWER	-.084	.762	.020
Cz	TOTAL	.377	2.494	-.465
Cm	UPPER	.018	.051	.076
Cm	LOWER	.006	.079	.021
Cm	TOTAL	.023	.131	.097

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.839	.399			**			
2		.5	.220	.719			**			
3		1.5	-.386	1.005	-7.913	.551	**			
4		3.0	-.689	1.162	-5.572	.597	**			
5		5.0	-.856	1.257	-4.940	.333	**	-5.295	1.227	405
6		7.5	-.946	1.312			**			
7		10.0					**	-5.226	1.411	407
8		15.0	-.965	1.324	-6.666	.572	**			
9		20.0	-.983	1.336	-5.795	.740	**	-5.218	1.276	409
10		25.0	-.975	1.330	-7.471	1.104	**			
		30.0					**			
12		35.0	-.854	1.256	-33.87	9.442	**			
13		40.0	-.510	1.068	-32.24	7.776	**	-33.16	8.471	413
14		45.0	-.403	1.014	-7.118	-1.607	**			
15		50.0	-.371	.998	1.961	-3.199	**	2.748	-3.404	415
16		55.0	-.360	.993	3.779	-3.707	**			
17		60.0	-.341	.983	3.886	-2.458	**	4.087	-2.813	417
		65.0					**			
19		70.0	-.271	.950	2.178	-1.232	**			
20		75.0	-.241	.935	2.157	-.855	**			
21		80.0	-.147	.890	.820	-.472	**	1.306	-.667	421
22		85.0	-.059	.849			**			
23		90.0	.017	.814	.158	-.089	**			
24		95.0	.091	.779			**			
	25	.5	.638	.513			**			
	26	1.5	.276	.693	5.754	.889	**			
	27	3.0	.157	.748	5.397	.522	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.171	.902	4.383	-.465	**			
	32	20.0	-.284	.956	5.544	-.201	**			
	33	25.0	-.364	.994			**			
		30.0					**			
	35	40.0	-.485	1.055	3.867	-.233	**			
	36	50.0	-.398	1.011	1.943	.089	**			
	37	60.0	-.151	.892	1.228	.474	**			
	38	70.0	.062	.793	.783	.306	**			
	39	80.0	.225	.717	.700	.218	**			
	40	90.0	.311	.676	.708	.251	**			

**OVERALL COEFFICIENTS — ** SECTION 4 **

		STEADY	RE	IM
Cz	UPPER	.471	1.745	-.175
Cz	LOWER	-.100	.847	.028
Cz	TOTAL	.371	2.592	-.147
Cm	UPPER	.027	-.007	.108
Cm	LOWER	.010	.084	.033
Cm	TOTAL	.037	.077	.140

*** LANN *** RUN 73 *** TABLE 9.15a (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.843	.396			**			
2		.5	.307	.678			**			
3		1.5	-.251	.940	-7.598	.092	**			
4		3.0	-.531	1.079	-6.074	.861	**			
5		5.0	-.676	1.155	-10.49	1.207	**	-8.189	1.382	505
6		7.5	-.751	1.196			**			
7		10.0	-.823	1.238	-5.059	.670	**			
		15.0					**			
9		20.0	-.827	1.240	-9.075	1.041	**			
10		25.0	-.830	1.242	-5.761	.655	**			
11		30.0	-.856	1.257	-8.904	1.080	**			
		35.0					**			
13		40.0	-.523	1.074	-37.22	7.446	**			
14		45.0	-.417	1.021	-1.345	-3.325	**			
15		50.0	-.399	1.012	6.811	-4.124	**			
16		55.0	-.397	1.011	6.366	-3.124	**			
17		60.0	-.379	1.002	4.280	-1.821	**			
18		65.0	-.357	.991	2.874	-1.122	**			
19		70.0	-.323	.974	2.043	-.365	**	2.217	-.584	519
20		75.0	-.285	.956	.712	-.038	**			
21		80.0	-.206	.919	.318	.016	**			
22		85.0	-.093	.865			**			
23		90.0	-.004	.823	-.146	.206	**			
24		95.0	.088	.781			**			
	25	.5	.569	.549			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.141	.887	4.790	-.908	**			
		15.0					**			
	32	20.0	-.308	.967	6.352	-.293	**			
		25.0					**			
	34	30.0	-.415	1.020	4.002	-.310	**			
		40.0					**			
	36	50.0	-.399	1.012	1.228	.110	**			
		60.0					**			
		70.0					**			
	39	80.0	.231	.714	.550	.127	**			
	40	90.0	.317	.673	.562	.173	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
Cz	UPPER	.439	1.386	-.059
Cz	LOWER	-.098	.696	-.031
Cz	TOTAL	.341	2.083	-.090
Cm	UPPER	.039	-.116	.080
Cm	LOWER	.007	.075	.028
Cm	TOTAL	.047	-.041	.107

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.832	.403			**			
		.5					**			
3		1.5	-.050	.845			**			
		3.0					**			
5		5.0	-.512	1.069	-9.074	.464	**			
		7.5					**			
7		10.0	-.718	1.178	-4.065	.121	**			
8		15.0	-.682	1.159	-10.28	.906	**			
9		20.0	-.763	1.203			**			
10		25.0	-.788	1.217	-6.810	.543	**			
11		30.0	-.424	1.024			**			
12		35.0	-.431	1.028	-22.73	.623	**			
13		40.0	-.330	.978	7.840	-1.931	**			
14		45.0	-.348	.987	8.309	-1.718	**			
15		50.0	-.362	.993	4.430	-.901	**			
16		55.0	-.357	.991	1.924	-.381	**			
17		60.0	-.343	.984	.861	-.169	**			
18		65.0	-.338	.982	.540	-.175	**			
19		70.0	-.322	.974	.176	.235	**			
20		75.0	-.285	.956	-.227	.175	**			
21		80.0	-.213	.922	-.689	.363	**			
22		85.0	-.085	.861			**			
23		90.0	.025	.810	-.699	.157	**			
24		95.0	.109	.771			**			
	25	.5	.397	.635			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.309	.968	6.550	.026	**			
		20.0					**			
	33	25.0	-.406	1.015			**			
	34	30.0	-.410	1.018	2.621	.245	**			
	35	40.0	-.406	1.015	1.105	-.057	**			
	36	50.0	-.315	.971	.485	.093	**			
		60.0					**			
		70.0					**			
	39	80.0	.233	.713	.117	.098	**			
	40	90.0	.300	.681	.313	.066	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
Cz	UPPER	.350	.908	-.001
Cz	LOWER	-.094	.433	.025
Cz	TOTAL	.255	1.340	.024
Cm	UPPER	.036	-.158	.018
Cm	LOWER	.013	-.004	.011
Cm	TOTAL	.049	-.162	.030

*** L.ANN *** RUN 74 *** **TABLE 9.15b**

TEST CONDITIONS			NORM. COEFF. Cz	Czi RE IM	MOM. COEFF. Cm	Cmi RE IM		DISPLACEMENTS REL.TO LVDT AMPL.! PHASE (-) ! (DEG)	** **Y/(B/2)! ** **	VIBRATION MODE HEAVE AT X=.224 M (MM)	PITCH (DEG)
RUNNR. = 74		SECT.1 .302	.009 -.079	.014 .012 .000		LVDT	1.00 0.00	** .000		
		SECT.2 .329	.071 -.105	.015 -.005 .005		CALC. 1!	3.49 -9.64	** .100		
ALFA = .59 (DEG)		SECT.3 .377	.068 -.001	.023 .015 -.005		ACC. 2!	1.98 -7.25	** .100	.01	.01
MACH = .821		SECT.4 .372	.176 -.254	.037 .017 -.030		ACC. 3!	.23 -315.07	** .100		
RE*10**-6= 5.43		SECT.5 .341	-.043 .188	.047 .016 .018		ACC. 4!	6.51 -55.74	** .420		
Q =45.17 (KPA)		SECT.6 .258	-.050 .103	.050 -.015 .002		ACC. 5!	1.75 21.70	** .420	.05	.02
P-SETTL. =149.0 (KPA)						ACC. 6!	.58 -200.88	** .420		
T-SETTL. =26.00		WING .322	.045 -.056	.036 .023 .036		ACC. 7!	1.15 -255.66	** .700		
				(WING : CM ABOUT		CALC. 8!	2.28 -308.50	** .700	.04	.01
DALFA = .250 (DEG)				AERODYN. CENTER)		CALC. 9!	.77 -246.89	** .700		
FREQ. =24.00 (Hz)						CALC.10!	4.92 -296.30	** .920		
REDFR. = .076						ACC.11!	3.20 -294.41	** .920	.11	.02
HARM. = 2						ACC.12!	1.46 -287.96	** .920		

NR. UP ! LOW!	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** **	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1	0.0	.744	.454			**			
2	.5	.126	.762			**			
3	1.5	-.502	1.063	.045	.373	**			
4	3.0	-.871	1.265	1.093	.070	**			
5	5.0	-.089	1.276			**	-.088	.103	105
6	7.5	-1.045	1.375			**			
7	10.0	-1.065	1.308	.515	.221	**			
8	15.0	-.972	1.327	-.344	2.548	**			
9	20.0	-.622	1.125	.185	.368	**			
10	25.0	-.613	1.121	.103	.521	**			
11	30.0	-.609	1.118	.017	.492	**			
12	35.0	-.588	1.107			**			
13	40.0	-.584	1.105	-.101	.590	**			
14	45.0	-.561	1.093	-1.146	1.850	**			
15	50.0	-.429	1.026	.622	-.849	**			
16	55.0	-.387	1.005	.287	.206	**			
17	60.0	-.346	.985	.430	.305	**			
18	65.0	-.289	.957	.162	.222	**			
19	70.0	-.227	.928	.274	.193	**	.047	.014	119
20	75.0	-.171	.901	.163	.203	**			
21	80.0	-.109	.872	.219	-.060	**			
22	85.0	-.033	.836			**			
23	90.0	.026	.809	.244	.010	**			
24	95.0	.100	.774			**			
25	.5	.704	.477			**			
26	1.5	.368	.648	-.075	.493	**			
27	3.0	.306	.678	.657	-.210	**			
28	5.0	.221	.718	.085	.073	**			
29	7.5	.076	.786			**			
30	10.0					**			
31	15.0	-.099	.867	-.147	.022	**			
32	20.0	-.239	.933	.216	.165	**			
33	25.0	-.334	.979			**			
34	30.0	-.453	1.038	.217	.359	**			
35	40.0	-.504	1.064	.200	.406	**			
36	50.0	-.495	1.059	.160	.132	**			
37	60.0	-.251	.939	.144	.105	**			
38	70.0	-.003	.823	.131	.069	**			
39	80.0	.168	.743	.217	-.010	**			
40	90.0	.277	.692	.385	.022	**			

OVERALL COEFFICIENTS			STEADY!	****SECTION 1**** RE	IM
Cz	UPPER		.426	-.045	-.125
Cz	LOWER		-.124	.054	.045
Cz	TOTAL		.302	.009	-.079
Cm	UPPER		.021	-.022	-.010
Cm	LOWER		-.007	.034	.011
Cm	TOTAL		.014	.012	.000

NR. UP ! LOW!	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** **	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1	0.0	.776	.456			**			
2	.5	.167	.743			**			
3	1.5	-.491	1.057	-.780	-.607	**			
4	3.0	-.793	1.220	-.482	-.456	**			
5	5.0	-.913	1.291	-1.568	.178	**			
6	7.5	-1.055	1.381			**			
7	10.0	-1.003	1.401	-.280	-.755	**			
8	15.0	-1.050	1.378	-.398	-.145	**			
9	20.0	-1.018	1.357	-.230	-.416	**			
10	25.0	-.894	1.279	-1.144	7.170	**			
11	30.0	-.666	1.149	-.477	-1.052	**			
12	35.0	-.599	1.113	-.771	.883	**			
13	40.0	-.487	1.055	-.961	-1.528	**			
14	45.0	-.432	1.028			**			
15	50.0	-.416	1.019	.355	-.055	**			
16	55.0	-.372	.998	-.117	.019	**			
17	60.0	-.328	.976	.116	-.020	**			
18	65.0	-.286	.956	-.095	.133	**			
19	70.0	-.223	.926	-.129	-.091	**			
20	75.0	-.161	.896	0.000	0.000	**			
21	80.0	-.107	.871	-.027	-.102	**			
22	85.0	-.038	.839			**			
23	90.0	.030	.807	.092	-.040	**			
24	95.0	.106	.772			**			
25	.5	.702	.478			**			
26	1.5	.369	.648	-.398	.130	**			
27	3.0	.273	.694			**			
28	5.0	.162	.746	-.091	-.077	**			
29	7.5	.069	.789			**			
30	10.0	.019	.812	-.107	.013	**			
31	15.0	-.127	.881	-.302	.045	**			
32	20.0	-.267	.947	-.209	-.161	**			
33	25.0	-.361	.993			**			
34	30.0	-.467	1.045	-.196	-.170	**			
35	40.0	-.546	1.085	-.027	-.661	**			
36	50.0	-.454	1.038	-.150	-.119	**			
37	60.0	-.215	.922	-.135	-.097	**			
38	70.0	.023	.810	-.063	.122	**			
39	80.0	.186	.734	.077	-.043	**			
40	90.0	.287	.687	-.009	.115	**			

OVERALL COEFFICIENTS			STEADY!	****SECTION 2**** RE	IM
Cz	UPPER		.451	.103	-.075
Cz	LOWER		-.122	-.032	-.030
Cz	TOTAL		.329	.071	-.105
Cm	UPPER		.017	-.003	.009
Cm	LOWER		-.002	-.002	-.004
Cm	TOTAL		.015	-.005	.005

*** LANN *** RUN 74 *** TABLE 9.15b (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.799	.423			**			
2		.5	.155	.749			**			
3		1.5	-.492	1.058	-.408	.052	**			
4		3.0	-.759	1.200	0.000	0.000	**			
5		5.0	-.884	1.273	0.000	0.000	**			
6		7.5	-1.034	1.367			**			
7		10.0	-1.037	1.369	1.137	-.963	**	.366	-.754	307
8		15.0	-1.049	1.378	-.305	-.688	**			
9		20.0	-1.034	1.368	-.418	-.135	**	-.115	.183	309
10		25.0	-1.017	1.356	-.553	.623	**			
		30.0					**			
12		35.0	-.673	1.153	-3.611	2.951	**			
13		40.0	-.448	1.036	-.190	-3.301	**	.468	-2.576	313
14		45.0	-.396	1.010	.184	-1.554	**			
15		50.0	-.374	.999	.438	.074	**	.214	-.336	315
16		55.0	-.343	.984	-.094	.299	**			
17		60.0	-.316	.971	.065	.408	**	.100	.127	317
18		65.0	-.278	.952	-.091	.290	**			
19		70.0	-.229	.929	-.109	.153	**	.053	.114	319
20		75.0	-.172	.902	.026	.126	**			
21		80.0	-.111	.873	.030	.121	**	.042	.056	321
22		85.0	-.050	.844			**			
23		90.0	.020	.812	-.108	.043	**	.027	.025	323
24		95.0	.101	.774			**			
	25	.5	.699	.480			**			
	26	1.5	.373	.646	0.000	0.000	**			
	27	3.0	.258	.700	.992	-.313	**			
		5.0					**			
	29	7.5	.049	.798			**			
	30	10.0	-.029	.835	-.124	.160	**			
		15.0					**			
	32	20.0	-.274	.950	-.252	-.194	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.419	1.021	-.320	.208	**			
	37	60.0	-.192	.911	-.023	-.141	**			
	38	70.0	.038	.803	-.077	.140	**			
	39	80.0	.199	.728	0.000	0.000	**			
	40	90.0	.300	.681	.195	.103	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 3 ** RE	IM
Cz	UPPER	.462	.095	-.006
Cz	LOWER	-.085	-.027	.005
Cz	TOTAL	.377	.068	-.001
Cm	UPPER	.018	.020	-.015
Cm	LOWER	.005	-.005	.010
Cm	TOTAL	.023	.015	-.005

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.840	.397			**			
2		.5	.218	.717			**			
3		1.5	-.388	1.006	0.000	0.000	**			
4		3.0	-.690	1.162	0.000	0.000	**			
5		5.0	-.856	1.256	0.000	0.000	**	-.062	.028	405
6		7.5	-.946	1.311			**			
7		10.0					**	-.199	.316	407
8		15.0	-.766	1.323	-.004	1.370	**			
9		20.0	-.983	1.334	0.000	0.000	**	.021	-.059	409
10		25.0	-.977	1.330	-.567	.847	**			
		30.0					**			
12		35.0	-.867	1.263	-8.042	11.465	**			
13		40.0	-.501	1.062	.088	-4.377	**	3.529	-7.923	413
14		45.0	-.401	1.012	1.218	-3.196	**			
15		50.0	-.373	.998	.919	-.258	**	.604	-1.174	415
16		55.0	-.359	.992	.172	.337	**			
17		60.0	-.339	.982	-.296	.405	**	.121	.197	417
		65.0					**			
19		70.0	-.271	.949	-.060	.358	**			
20		75.0	-.241	.934	.035	.223	**			
21		80.0	-.147	.890	.253	.163	**	.024	.178	421
22		85.0	-.059	.848			**			
23		90.0	.016	.813	.032	.090	**			
24		95.0	.091	.778			**			
	25	.5	.639	.512			**			
	26	1.5	.274	.693	.205	-.065	**			
	27	3.0	.157	.748	.220	-.067	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.171	.901	0.000	0.000	**			
	32	20.0	-.284	.955	-.024	-.195	**			
	33	25.0	-.363	.994			**			
		30.0					**			
	35	40.0	-.481	1.052	-.183	-.160	**			
	36	50.0	-.401	1.012	0.000	0.000	**			
	37	60.0	-.152	.892	.094	-.136	**			
	38	70.0	.061	.792	0.000	0.000	**			
	39	80.0	.226	.716	.075	-.037	**			
	40	90.0	.311	.676	.112	.022	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 4 ** RE	IM
Cz	UPPER	.472	.171	-.232
Cz	LOWER	-.100	.005	-.022
Cz	TOTAL	.372	.176	-.254
Cm	UPPER	.027	.012	-.026
Cm	LOWER	.010	.005	-.004
Cm	TOTAL	.037	.017	-.030

*** LANN *** RUN 74 *** TABLE 9.15b (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.844	.395			**			
2		.5	.306	.678			**			
3		1.5	-.252	.940	-.317	.063	**			
4		3.0	-.532	1.078	-.396	.045	**			
5		5.0	-.677	1.155	-.426	.487	**	.159	.251	505
6		7.5	-.751	1.196			**			
7		10.0	-.823	1.237	1.674	-1.491	**			
		15.0					**			
9		20.0	-.827	1.239	.630	-1.064	**			
10		25.0	-.834	1.243	-.668	-.132	**			
11		30.0	-.859	1.258	-.797	.805	**			
		35.0					**			
13		40.0	-.513	1.069	.699	-6.368	**			
14		45.0	-.415	1.019	2.052	-3.551	**			
15		50.0	-.406	1.015	-.057	.757	**			
16		55.0	-.396	1.010	-.236	.476	**			
17		60.0	-.376	1.000	-.467	.783	**			
18		65.0	-.355	.990	-.356	.477	**			
19		70.0	-.323	.974	-.346	.469	**	-.123	.435	519
20		75.0	-.285	.956	-.247	.174	**			
21		80.0	-.206	.918	.021	.127	**			
22		85.0	-.093	.865			**			
23		90.0	-.004	.823	-.103	.031	**			
24		95.0	.088	.780			**			
	25	.5	.570	.548			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.140	.887	0.000	0.000	**			
		15.0					**			
	32	20.0	-.308	.967	.204	-.260	**			
		25.0					**			
	34	30.0	-.412	1.018	-.019	-.222	**			
		40.0					**			
	36	50.0	-.402	1.013	-.328	.212	**			
		60.0					**			
		70.0					**			
	39	80.0	.232	.713	.173	-.077	**			
	40	90.0	.317	.673	.046	.077	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
Cz	UPPER	.439	-.035	.192
Cz	LOWER	-.098	-.008	-.005
Cz	TOTAL	.341	-.043	.188
Cm	UPPER	.039	.019	.010
Cm	LOWER	.007	-.003	.007
Cm	TOTAL	.047	.016	.018

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.834	.401			**			
		.5					**			
3		1.5	-.050	.844			**			
		3.0					**			
5		5.0	-.512	1.068	-1.231	.581	**			
		7.5					**			
7		10.0	-.717	1.177	-.480	-.686	**			
8		15.0	-.684	1.158	1.081	-1.603	**			
9		20.0	-.759	1.200			**			
10		25.0	-.792	1.219	-.454	.314	**			
11		30.0	-.456	1.040			**			
12		35.0	-.439	1.031	2.474	-4.720	**			
13		40.0	-.330	.977	1.439	-.191	**			
14		45.0	-.352	.988	-.630	.817	**			
15		50.0	-.365	.995	-.447	.783	**			
16		55.0	-.357	.991	.045	.352	**			
17		60.0	-.342	.983	.023	.171	**			
18		65.0	-.338	.981	.167	-.023	**			
19		70.0	-.323	.974	-.324	.046	**			
20		75.0	-.285	.955	-.023	-.158	**			
21		80.0	-.213	.921	.125	-.172	**			
22		85.0	-.085	.861			**			
23		90.0	.025	.809	-.112	.032	**			
24		95.0	.109	.770			**			
	25	.5	.398	.634			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.309	.967	-.285	.034	**			
		20.0					**			
	33	25.0	-.405	1.014			**			
	34	30.0	-.408	1.015	.229	-.273	**			
	35	40.0	-.404	1.014	0.000	0.000	**			
	36	50.0	-.318	.971	0.000	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.235	.711	-.035	-.094	**			
	40	90.0	.300	.681	-.049	.131	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
Cz	UPPER	.352	-.042	.115
Cz	LOWER	-.094	-.009	-.012
Cz	TOTAL	.258	-.050	.103
Cm	UPPER	.036	-.014	.004
Cm	LOWER	.013	-.001	-.001
Cm	TOTAL	.050	-.015	.002

*** LANN *** RUN 75 *** TABLE 9.15c

TEST CONDITIONS		NORM. COEFF.		MOM. COEFF.			DISPLACEMENTS ** VIBRATION MODE		
		Cz	Czi	Cm	Cmi		REL.TO LVDT **Y/(B/2)! HEAVE AT ! PITCH		
			RE IM		RE IM		AMPL.! PHASE ** ! X=.224 M !		
							(-) ! (DEG) ** ! (MM) ! (DEG)		
RUNNR. = 75	!SECT.1 .299 .038 .020 ! .014 .018 -.002 ! ! LVDT ! 1.00 0.00 ** .000								
	!SECT.2 .327 -.074 -.035 ! .015 .021 .022 ! !CALC. 1! 12.37 13.78 ** .100								
ALFA = .59 (DEG)	!SECT.3 .376 .019 .136 ! .023 .031 .027 ! ! ACC. 2! 5.86 7.95 ** .100								
MACH = .821	!SECT.4 .371 -.014 -.086 ! .037 .002 -.031 ! ! ACC. 3! 2.51 -134.51 ** .100 .01 .02								
RE*10**-6= 5.43	!SECT.5 .341 .053 .058 ! .047 -.007 .024 ! ! ACC. 4! 21.10 .04 ** .420								
Q =45.16 (KPA)	!SECT.6 .259 -.034 -.013 ! .050 -.008 .031 ! ! ACC. 5! 1.78 57.40 ** .420 .08 .03								
P-SETTL. =148.9 (KPA)		! ACC. 6! 4.24 -143.35 ** .420								
T-SETTL. =26.00	! WING .320 .006 .016 ! .037 .004 -.004 ! ! ACC. 7! 6.96 41.04 ** .700								
	!(WING : CM ABOUT ! !CALC. 8! 4.69 98.21 ** .700 .07 .02								
DALFA = .250 (DEG)	! AERODYN. CENTER) ! !CALC. 9! 3.10 -207.81 ** .700								
FREQ. =24.00 (Hz)		! !CALC.10! 9.96 87.92 ** .920								
REDFR. = .076		! ! ACC.11! 8.79 91.56 ** .920 .07 .01								
HARM. = 3		! ! ACC.12! 7.66 96.35 ** .920								

Section 1

NR. UP ! LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) ** CALIBRATION (TRANSD.)						
		Cp STEADY	M-LOC.	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1	0.0	.743	.455			**		
2	.5	.126	.763			**		
3	1.5	-.501	1.063	-.410	-.821	**		
4	3.0	-.868	1.264	-.651	-2.158	**		
5	5.0	-.886	1.275			** -.036	.032	105
6	7.5	-1.044	1.375			**		
7	10.0	-1.064	1.388	-.169	-.769	**		
8	15.0	-.959	1.320	.391	1.154	**		
9	20.0	-.617	1.123	-.342	-.150	**		
10	25.0	-.595	1.112	-.226	-.022	**		
11	30.0	-.588	1.108	-.429	-.040	**		
12	35.0	-.501	1.104			**		
13	40.0	-.595	1.112	-.192	-.017	**		
14	45.0	-.548	1.087	-.157	-.392	**		
15	50.0	-.428	1.026	-.188	-.011	**		
16	55.0	-.387	1.006	-.621	-.108	**		
17	60.0	-.345	.985	-.168	.168	**		
18	65.0	-.288	.957	-.082	-.069	**		
19	70.0	-.227	.928	-.263	.048	** -.053	.056	119
20	75.0	-.170	.901	-.202	.078	**		
21	80.0	-.110	.873	-.084	-.072	**		
22	85.0	-.033	.837			**		
23	90.0	.027	.809	-.069	-.055	**		
24	95.0	.100	.775			**		
25	.5	.703	.478			**		
26	1.5	.369	.648	-.381	-.457	**		
27	3.0	.306	.678	-.192	-.236	**		
28	5.0	.221	.718	-.213	.060	**		
29	7.5	.075	.787			**		
	10.0					**		
31	15.0	-.100	.868	-.232	-.020	**		
32	20.0	-.239	.934	.049	-.271	**		
33	25.0	-.331	.979			**		
34	30.0	-.452	1.038	-.137	-.179	**		
35	40.0	-.502	1.063	0.000	0.000	**		
36	50.0	-.493	1.059	-.220	-.022	**		
37	60.0	-.250	.939	-.088	-.081	**		
38	70.0	-.003	.823	.085	.078	**		
39	80.0	.169	.743	-.054	.063	**		
40	90.0	.276	.693	-.032	.038	**		

OVERALL COEFFICIENTS — SECTION 1

		STEADY	RE	IM
Cz	UPPER	.422	.064	.034
Cz	LOWER	-.123	-.027	-.014
Cz	TOTAL	.299	.038	.020
Cm	UPPER	.021	.020	-.008
Cm	LOWER	-.007	-.002	.006
Cm	TOTAL	.014	.018	-.002

Section 2

NR. UP ! LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) ** CALIBRATION (TRANSD.)						
		Cp STEADY	M-LOC.	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1	0.0	.775	.437			**		
2	.5	.167	.744			**		
3	1.5	-.490	1.057	.955	-.003	**		
4	3.0	-.791	1.219	.624	-.209	**		
5	5.0	-.911	1.290	1.120	.552	**		
6	7.5	-1.053	1.381			**		
7	10.0	-1.083	1.402	.869	.567	**		
8	15.0	-1.049	1.379	.800	.487	**		
9	20.0	-1.018	1.358	.167	.581	**		
10	25.0	-.876	1.269	2.613	2.834	**		
11	30.0	-.647	1.139	.306	-.066	**		
12	35.0	-.589	1.109	.267	.116	**		
13	40.0	-.485	1.055	.424	-.529	**		
14	45.0	-.431	1.028			**		
15	50.0	-.416	1.020	.094	-.083	**		
16	55.0	-.371	.998	-.167	-.005	**		
17	60.0	-.327	.976	.157	-.002	**		
18	65.0	-.285	.956	.214	-.088	**		
19	70.0	-.224	.927	.074	.054	**		
20	75.0	-.161	.897	-.061	.076	**		
21	80.0	-.107	.872	.139	-.158	**		
22	85.0	-.038	.839			**		
23	90.0	.030	.807	.066	.054	**		
24	95.0	.105	.772			**		
25	.5	.701	.479			**		
26	1.5	.369	.648	.215	-.179	**		
27	3.0	.272	.694			**		
28	5.0	.162	.746	-.008	.144	**		
29	7.5	.067	.790			**		
30	10.0	.019	.813	.084	.027	**		
31	15.0	-.128	.881	.209	.252	**		
32	20.0	-.267	.948	.110	.155	**		
33	25.0	-.359	.992			**		
34	30.0	-.466	1.045	.307	.041	**		
35	40.0	-.543	1.085	.238	.025	**		
36	50.0	-.453	1.039	.288	.354	**		
37	60.0	-.215	.923	.083	.077	**		
38	70.0	.023	.811	.316	-.013	**		
39	80.0	.186	.735	.061	.053	**		
40	90.0	.286	.688	.039	.033	**		

OVERALL COEFFICIENTS — SECTION 2

		STEADY	RE	IM
Cz	UPPER	.449	-.125	-.062
Cz	LOWER	-.122	.052	.028
Cz	TOTAL	.327	-.074	-.035
Cm	UPPER	.017	.001	.013
Cm	LOWER	-.002	.020	.009
Cm	TOTAL	.015	.021	.022

*** LANN *** RUN 75 ***   TABLE 9.15c (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.797	.424			**			
2		.5	.154	.750			**			
3		1.5	-.492	1.059	0.000	0.000	**			
4		3.0	-.756	1.199	.441	-.927	**			
5		5.0	-.882	1.273	.808	-.236	**			
6		7.5	-1.034	1.368			**			
7		10.0	-1.036	1.370	.979	-.211	**	-.109	-.302	307
8		15.0	-1.049	1.379	-.188	-.795	**			
9		20.0	-1.034	1.369	-.189	-.711	**	-.002	.036	309
10		25.0	-1.016	1.357	.457	-.847	**			
		30.0					**			
12		35.0	-.661	1.147	-1.053	-2.749	**			
13		40.0	-.449	1.037	.154	-.539	**	.014	.114	313
14		45.0	-.395	1.010	.185	.426	**			
15		50.0	-.373	.999	-.088	-.307	**	-.080	.117	315
16		55.0	-.343	.984	-.302	-.399	**			
17		60.0	-.316	.971	-.188	.001	**	-.104	-.001	317
18		65.0	-.278	.953	-.093	-.003	**			
19		70.0	-.230	.930	-.090	-.070	**	-.081	-.000	319
20		75.0	-.172	.902	-.165	.016	**			
21		80.0	-.112	.874	.084	-.093	**	-.036	-.013	321
22		85.0	-.050	.845			**			
23		90.0	.020	.812	-.084	-.071	**	-.030	-.011	323
24		95.0	.100	.775			**			
	25	.5	.698	.481			**			
	26	1.5	.373	.646	-.210	-.251	**			
	27	3.0	.259	.701	.483	.055	**			
		5.0					**			
	29	7.5	.048	.799			**			
	30	10.0	-.028	.835	.019	-.230	**			
		15.0					**			
	32	20.0	-.273	.951	.188	-.131	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.418	1.021	-.148	.119	**			
	37	60.0	-.191	.911	0.000	0.000	**			
	38	70.0	.038	.804	.197	-.004	**			
	39	80.0	.200	.728	.085	.077	**			
	40	90.0	.299	.682	.059	.052	**			

**OVERALL COEFFICIENTS — ** SECTION 3 **

COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.461	.004	.141
Cz	LOWER	-.084	.014	-.004
Cz	TOTAL	.376	.019	.136
Cm	UPPER	.018	.023	.017
Cm	LOWER	.005	.008	.010
Cm	TOTAL	.023	.031	.027

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.838	.399			**			
2		.5	.218	.720			**			
3		1.5	-.388	1.006	-.694	-.465	**			
4		3.0	-.689	1.162	-.200	-.507	**			
5		5.0	-.855	1.256	-.403	-1.308	**	-.006	.041	405
6		7.5	-.946	1.312			**			
7		10.0					**	-.003	.139	407
8		15.0	-.966	1.324	-.204	-.687	**			
9		20.0	-.983	1.335	-.955	-1.026	**	-.048	-.124	409
10		25.0	-.976	1.331	-.877	-.871	**			
		30.0					**			
12		35.0	-.850	1.254	.568	6.900	**			
13		40.0	-.502	1.064	.783	-1.342	**	.428	1.434	413
14		45.0	-.400	1.012	.156	.370	**			
15		50.0	-.372	.999	-.010	.174	**	-.005	.138	415
16		55.0	-.360	.992	-.336	-.188	**			
17		60.0	-.340	.983	-.161	-.172	**	-.084	-.044	417
19		70.0	-.272	.950	-.240	-.221	**			
		65.0					**			
20		75.0	-.242	.935	-.302	-.120	**			
21		80.0	-.148	.891	-.226	-.062	**	-.034	-.036	421
22		85.0	-.059	.849			**			
23		90.0	.016	.814	-.204	.084	**			
24		95.0	.090	.779			**			
	25	.5	.638	.513			**			
	26	1.5	.275	.693	-.178	-.222	**			
	27	3.0	.158	.748	-.657	.125	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.171	.902	-.351	-.177	**			
	32	20.0	-.284	.956	-.114	-.163	**			
	33	25.0	-.361	.993			**			
		30.0					**			
	35	40.0	-.480	1.052	-.279	-.035	**			
	36	50.0	-.401	1.013	-.421	-.268	**			
	37	60.0	-.152	.893	-.173	-.004	**			
	38	70.0	.061	.793	.085	.032	**			
	39	80.0	.226	.716	-.141	.006	**			
	40	90.0	.309	.677	-.165	-.045	**			

**OVERALL COEFFICIENTS — ** SECTION 4 **

COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.471	.054	-.067
Cz	LOWER	-.099	-.068	-.019
Cz	TOTAL	.371	-.014	-.086
Cm	UPPER	.027	.017	-.028
Cm	LOWER	.010	-.015	-.003
Cm	TOTAL	.037	.002	-.031

*** LANN *** RUN 75 *** TABLE 9.15c (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.843	.396			**			
2		.5	.306	.678			**			
3		1.5	-.252	.940	-.124	.533	**			
4		3.0	-.531	1.078	-.445	.213	**			
5		5.0	-.674	1.154	-.891	.999	**	-.055	.073	505
6		7.5	-.750	1.196			**			
7		10.0	-.823	1.238	-.341	.959	**			
		15.0					**			
9		20.0	-.827	1.240	-1.043	-.789	**			
10		25.0	-.830	1.242	-.241	.718	**			
11		30.0	-.856	1.257	-.740	.943	**			
		35.0					**			
13		40.0	-.515	1.070	-.152	-3.306	**			
14		45.0	-.414	1.019	.143	.963	**			
15		50.0	-.403	1.014	.082	.354	**			
16		55.0	-.396	1.010	-.224	-.020	**			
17		60.0	-.377	1.001	-.232	.197	**			
18		65.0	-.358	.991	-.427	.178	**			
19		70.0	-.323	.975	-.197	-.009	**	-.030	-.055	519
20		75.0	-.285	.956	-.096	.073	**			
21		80.0	-.207	.919	.006	.176	**			
22		85.0	-.093	.865			**			
23		90.0	-.004	.823	-.251	.271	**			
24		95.0	.087	.781			**			
	25	.5	.569	.549			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.139	.887	-.154	.121	**			
		15.0					**			
	32	20.0	-.308	.967	.280	.394	**			
		25.0					**			
	34	30.0	-.411	1.018	-.259	.518	**			
		40.0					**			
	36	50.0	-.401	1.013	-.305	.240	**			
		60.0					**			
		70.0					**			
	39	80.0	.232	.713	-.169	.181	**			
	40	90.0	.316	.674	.074	.068	**			

**OVERALL COEFFICIENTS ** SECTION 5 **

		STEADY	RE	IM
Cz	UPPER	.438	.094	-.016
Cz	LOWER	-.098	-.041	.074
Cz	TOTAL	.341	.053	.058
Cm	UPPER	.039	.016	-.002
Cm	LOWER	.007	-.022	.026
Cm	TOTAL	.047	-.007	.024

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.833	.402			**			
		.5					**			
3		1.5	-.051	.845			**			
		3.0					**			
5		5.0	-.512	1.068	0.000	0.000	**			
		7.5					**			
7		10.0	-.718	1.178	0.000	0.000	**			
8		15.0	-.680	1.157	.312	2.010	**			
9		20.0	-.756	1.200			**			
10		25.0	-.788	1.217	-.448	.246	**			
11		30.0	-.489	1.057			**			
12		35.0	-.431	1.028	.983	-1.057	**			
13		40.0	-.331	.978	-.152	.122	**			
14		45.0	-.354	.990	-.123	-.153	**			
15		50.0	-.364	.995	0.000	0.000	**			
16		55.0	-.358	.991	.026	-.263	**			
17		60.0	-.342	.984	0.000	0.000	**			
18		65.0	-.338	.982	-.246	-.021	**			
19		70.0	-.324	.975	0.000	0.000	**			
20		75.0	-.284	.956	.121	-.108	**			
21		80.0	-.213	.922	.003	-.215	**			
22		85.0	-.086	.862			**			
23		90.0	.025	.810	-.103	-.098	**			
24		95.0	.108	.771			**			
	25	.5	.396	.635			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.309	.968	-.166	-.240	**			
		20.0					**			
	33	25.0	-.401	1.013			**			
	34	30.0	-.407	1.016	0.000	0.000	**			
	35	40.0	-.403	1.014	0.000	0.000	**			
	36	50.0	-.318	.972	-.033	.280	**			
		60.0					**			
		70.0					**			
	39	80.0	.235	.712	-.217	.005	**			
	40	90.0	.299	.682	-.006	-.205	**			

**OVERALL COEFFICIENTS ** SECTION 6 **

		STEADY	RE	IM
Cz	UPPER	.353	-.008	-.016
Cz	LOWER	-.094	-.026	.003
Cz	TOTAL	.259	-.034	-.013
Cm	UPPER	.036	.004	.027
Cm	LOWER	.013	-.012	.004
Cm	TOTAL	.050	-.008	.031

*** LANN *** RUN 82 *** TABLE 9.16

TEST CONDITIONS			NORM. COEFF.		MOM. COEFF.			DISPLACEMENTS ** VIBRATION MODE		
			Cz	Czi	CM	Cmi		REL.TO LVDT **Y/(B/2)! HEAVE AT ! PITCH		
			RE	IM	RE	IM		AMPL.! PHASE ** ! X=.224 M !		
								(-) ! (DEG) ** ! (MM) ! (DEG)		

RUNNR. = 82		SECT.1 .298 1.694 -.175	.015 .097 .071	LVDT	1.00 0.00 ** .000		
		SECT.2 .326 2.043 -.277	.015 .136 .081	CALC. 1!	1.25 -4.70 ** .100		
ALFA = .60 (DEG)		SECT.3 .379 2.048 -.088	.023 .058 .105	ACC. 2!	.47 -11.98 ** .100		
MACH = .821		SECT.4 .366 2.462 -.103	.037 .070 .095	ACC. 3!	.50 -169.30 ** .100	.14	.47
RE*10**-6= 5.39		SECT.5 .345 1.814 -.083	.047 -.071 .078	ACC. 4!	.32 -33.86 ** .420		
Q =44.81 (KPA)		SECT.6 .273 1.262 -.055	.051 -.160 .035	ACC. 5!	.38 -178.32 ** .420	.47	.49
P-SETTL. =147.8 (KPA)				ACC. 6!	1.16 -172.49 ** .420		
T-SETTL. =26.00		WING .321 1.862 -.144	.038 .243 .109	ACC. 7!	.65 -149.50 ** .700		
			!(WING : CM ABOUT	CALC. 8!	1.05 -176.69 ** .700	1.00	.50
DALFA = .500 (DEG)			! AERODYN. CENTER)	CALC. 9!	1.60 -172.80 ** .700		
FREQ. =12.00 (Hz)				CALC.10!	1.19 -173.98 ** .920		
REDFR. = .038				ACC.11!	1.52 -173.18 ** .920	.63	.41
HARM. = 1				ACC.12!	1.86 -172.66 ** .920		

NR.			PRESSURE DISTRIBUTION (TUBES)			** CALIBRATION (TRANSD.)		
UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1		0.0	.742	.456					
2		.5	.125	.763					
3		1.5	-.500	1.062	-3.689	.509			
4		3.0	-.869	1.264	-5.489	.911			
5		5.0	-.888	1.276			-6.458	.906	105
6		7.5	-1.042	1.373					
7		10.0	-1.067	1.390	-3.683	.611			
8		15.0	-.902	1.284	-17.48	4.280			
9		20.0	-.627	1.128	-7.098	.473			
10		25.0	-.605	1.117	-3.691	.310			
11		30.0	-.600	1.114	-4.290	.511			
12		35.0	-.592	1.110					
13		40.0	-.588	1.108	-3.978	.694			
14		45.0	-.537	1.081	-9.166	1.663			
15		50.0	-.441	1.033	-2.792	-.778			
16		55.0	-.386	1.005	-.019	-1.051			
17		60.0	-.343	.984	-.274	-.694			
18		65.0	-.288	.957	-.296	-.513			
19		70.0	-.228	.928	-.180	-.405	-.243	-.388	119
20		75.0	-.169	.900	-.221	-.290			
21		80.0	-.110	.873	-.103	-.268			
22		85.0	-.033	.837					
23		90.0	.026	.809	-.147	-.256			
24		95.0	.100	.775					
	25	.5	.703	.478					
	26	1.5	.369	.648	3.786	-1.028			
	27	3.0	.305	.679	4.206	-.076			
	28	5.0	.220	.718	3.850	-.167			
	29	7.5	.076	.786					
		10.0							
	31	15.0	-.098	.867	3.030	-.525			
	32	20.0	-.237	.933	4.011	-.322			
	33	25.0	-.333	.979					
	34	30.0	-.451	1.037	3.512	-.680			
	35	40.0	-.504	1.064	3.464	-1.120			
	36	50.0	-.489	1.056	1.915	-.102			
	37	60.0	-.249	.939	1.026	.010			
	38	70.0	-.002	.822	.774	.149			
	39	80.0	.168	.743	.674	.047			
	40	90.0	.276	.692	.416	.061			

OVERALL COEFFICIENTS		** SECTION 1 **		
		STEADY	RE	IM
Cz	UPPER	.421	1.035	-.090
Cz	LOWER	-.123	.659	-.085
Cz	TOTAL	.298	1.694	-.175
Cm	UPPER	.022	.008	.067
Cm	LOWER	-.007	.089	.003
Cm	TOTAL	.015	.097	.071

NR.			PRESSURE DISTRIBUTION (TUBES)			** CALIBRATION (TRANSD.)		
UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1		0.0	.773	.438					
2		.5	.166	.744					
3		1.5	-.489	1.057	-5.772	.779			
4		3.0	-.794	1.220	-5.241	.964			
5		5.0	-.912	1.290	-5.795	1.255			
6		7.5	-1.058	1.384					
7		10.0	-1.083	1.401	-2.327	.448			
8		15.0	-1.050	1.378	-4.559	1.015			
9		20.0	-1.018	1.357	-5.741	1.612			
10		25.0	-.812	1.231	-24.39	6.726			
11		30.0	-.681	1.157	-11.58	2.010			
12		35.0	-.579	1.103	-9.097	1.741			
13		40.0	-.499	1.062	-7.528	-.186			
14		45.0	-.433	1.028					
15		50.0	-.416	1.020	.607	-1.213			
16		55.0	-.371	.998	.382	-1.011			
17		60.0	-.326	.976	.307	-.867			
18		65.0	-.285	.956	.410	-.633			
19		70.0	-.223	.926	.351	-.491			
20		75.0	-.160	.896	.181	-.399			
21		80.0	-.107	.871	.178	-.312			
22		85.0	-.039	.839					
23		90.0	.030	.807	.163	-.293			
24		95.0	.105	.772					
	25	.5	.700	.479					
	26	1.5	.370	.648	4.524	-.742			
	27	3.0	.273	.694					
	28	5.0	.161	.746	2.823	-1.139			
	29	7.5	.068	.789					
	30	10.0	.019	.812	3.490	-.442			
	31	15.0	-.126	.880	3.516	-.629			
	32	20.0	-.264	.946	4.473	-.540			
	33	25.0	-.360	.992					
	34	30.0	-.464	1.044	4.244	-.841			
	35	40.0	-.553	1.089	5.499	-1.118			
	36	50.0	-.452	1.038	2.020	-.293			
	37	60.0	-.215	.922	1.137	.035			
	38	70.0	.023	.810	.867	.088			
	39	80.0	.186	.735	.853	.064			
	40	90.0	.286	.687	.565	.045			

OVERALL COEFFICIENTS		** SECTION 2 **		
		STEADY	RE	IM
Cz	UPPER	.448	1.260	-.160
Cz	LOWER	-.122	.782	-.117
Cz	TOTAL	.326	2.043	-.277
Cm	UPPER	.017	.007	.077
Cm	LOWER	-.002	.128	.005
Cm	TOTAL	.015	.136	.081

***   L A N N   *** RUN 82 ***   TABLE 9.16 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.796	.424			**			
2		.5	.152	.751			**			
3		1.5	-.491	1.058	-4.801	.650	**			
4		3.0	-.761	1.201	-6.138	.650	**			
5		5.0	-.885	1.274	-5.578	.439	**			
6		7.5	-1.033	1.367			**			
7		10.0	-1.041	1.372	-3.476	.354	**	-4.174	.515	307
8		15.0	-1.049	1.378	-5.004	.603	**			
9		20.0	-1.032	1.367	-5.250	.664	**	-4.917	.669	309
10		25.0	-1.010	1.352	-6.410	.911	**			
		30.0					**			
12		35.0	-.659	1.145	-32.16	6.439	**			
13		40.0	-.474	1.049	-11.18	-.532	**	-10.30	.497	313
14		45.0	-.407	1.016	-1.183	-1.330	**			
15		50.0	-.378	1.001	1.568	-1.626	**	1.828	-1.423	315
16		55.0	-.343	.984	2.550	-1.487	**			
17		60.0	-.315	.970	2.159	-1.286	**	2.170	-1.067	317
18		65.0	-.277	.952	1.816	-.921	**			
19		70.0	-.228	.929	1.304	-.620	**	1.202	-.605	319
20		75.0	-.170	.901	.703	-.433	**			
21		80.0	-.111	.873	.466	-.348	**	.494	-.270	321
22		85.0	-.050	.845			**			
23		90.0	.020	.812	.213	-.158	**	.209	-.155	323
24		95.0	.100	.775			**			
	25	.5	.698	.481			**			
	26	1.5	.373	.646	4.844	-.605	**			
	27	3.0	.256	.702	5.649	.327	**			
		5.0					**			
	29	7.5	.049	.798			**			
	30	10.0	-.028	.834	3.515	-.509	**			
		15.0					**			
	32	20.0	-.270	.949	4.755	-.335	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.417	1.020	2.373	.033	**			
	37	60.0	-.191	.911	1.126	.127	**			
	38	70.0	.038	.803	.785	.188	**			
	39	80.0	.199	.728	.866	.137	**			
	40	90.0	.300	.681	.646	.142	**			

**OVERALL COEFFICIENTS ** SECTION 3 **

		STEADY	RE	IM
Cz	UPPER	.462	1.288	-.070
Cz	LOWER	-.083	.760	-.018
Cz	TOTAL	.379	2.048	-.088
Cm	UPPER	.018	-.038	.080
Cm	LOWER	.006	.096	.025
Cm	TOTAL	.023	.058	.105

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.837	.399			**			
2		.5	.215	.721			**			
3		1.5	-.386	1.005	-7.318	.357	**			
4		3.0	-.689	1.162	-4.915	.617	**			
5		5.0	-.859	1.258	-3.411	.417	**	-5.299	.601	405
6		7.5	-.946	1.311			**			
7		10.0					**	-4.672	.709	407
8		15.0	-.961	1.320	-6.078	.012	**			
9		20.0	-.983	1.335	-5.533	.391	**	-5.165	.671	409
10		25.0	-.966	1.324	-7.191	.478	**			
		30.0					**			
12		35.0	-.730	1.184	-36.58	5.945	**			
13		40.0	-.554	1.090	-24.63	1.301	**	-29.52	3.223	413
14		45.0	-.424	1.024	-4.087	-1.599	**			
15		50.0	-.387	1.005	1.818	-1.635	**	2.160	-1.443	415
16		55.0	-.362	.993	3.892	-1.870	**			
17		60.0	-.339	.982	3.982	-1.264	**	3.847	-1.263	417
		65.0					**			
19		70.0	-.268	.948	2.416	-.663	**			
20		75.0	-.239	.933	1.853	-.299	**			
21		80.0	-.146	.890	.835	-.287	**	1.195	-.328	421
22		85.0	-.059	.849			**			
23		90.0	.016	.814	.182	-.154	**			
24		95.0	.091	.779			**			
	25	.5	.637	.513			**			
	26	1.5	.275	.693	5.576	-.678	**			
	27	3.0	.156	.749	5.109	-.448	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.168	.900	4.478	-.440	**			
	32	20.0	-.281	.954	5.194	-.463	**			
	33	25.0	-.362	.993			**			
		30.0					**			
	35	40.0	-.482	1.053	4.665	-.331	**			
	36	50.0	-.400	1.012	2.194	-.171	**			
	37	60.0	-.152	.892	1.094	.175	**			
	38	70.0	.061	.793	.768	.167	**			
	39	80.0	.225	.716	.957	.131	**			
	40	90.0	.310	.676	.822	.134	**			

**OVERALL COEFFICIENTS ** SECTION 4 **

		STEADY	RE	IM
Cz	UPPER	.465	1.580	-.057
Cz	LOWER	-.099	.882	-.047
Cz	TOTAL	.366	2.462	-.103
Cm	UPPER	.027	-.039	.074
Cm	LOWER	.010	.109	.021
Cm	TOTAL	.037	.070	.095

*** LANN *** RUN 82 *** TABLE 9.16 (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.842	.396			**			
2		.5	.305	.678			**			
3		1.5	-.250	.939	-6.836	.176	**			
4		3.0	-.532	1.078	-5.441	1.077	**			
5		5.0	-.674	1.153	-8.685	.365	**	-7.876	.887	505
6		7.5	-.744	1.192			**			
7		10.0	-.831	1.242	-4.470	.438	**			
		15.0					**			
9		20.0	-.825	1.238	-8.047	.798	**			
10		25.0	-.834	1.243	-7.219	.640	**			
11		30.0	-.822	1.237	-12.56	1.228	**			
		35.0					**			
13		40.0	-.576	1.101	-22.38	.899	**			
14		45.0	-.446	1.035	.254	-2.049	**			
15		50.0	-.411	1.017	6.238	-2.045	**			
16		55.0	-.393	1.008	6.141	-1.573	**			
17		60.0	-.372	.998	4.209	-.932	**			
18		65.0	-.352	.988	2.847	-.624	**			
19		70.0	-.318	.972	2.243	-.340	**	1.881	-.321	519
20		75.0	-.282	.954	.709	-.352	**			
21		80.0	-.205	.917	.458	-.127	**			
22		85.0	-.093	.865			**			
23		90.0	-.005	.823	-.067	-.031	**			
24		95.0	.087	.781			**			
	25	.5	.570	.549			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.139	.886	4.926	-1.054	**			
		15.0					**			
	32	20.0	-.305	.965	5.788	-.683	**			
		25.0					**			
	34	30.0	-.410	1.017	4.456	-.807	**			
		40.0					**			
	36	50.0	-.400	1.012	1.633	-.247	**			
		60.0					**			
		70.0					**			
	39	80.0	.231	.713	.853	.085	**			
	40	90.0	.316	.673	.691	-.040	**			

OVERALL COEFFICIENTS ** SECTION 5 **

		STEADY	RE	IM
Cz	UPPER	.442	1.054	.027
Cz	LOWER	-.097	.760	-.109
Cz	TOTAL	.345	1.814	-.083
Cm	UPPER	.040	-.192	.079
Cm	LOWER	.007	.121	-.001
Cm	TOTAL	.047	-.071	.078

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.832	.402			**			
		.5					**			
3		1.5	-.050	.845			**			
		3.0					**			
5		5.0	-.506	1.065	-8.546	.445	**			
		7.5					**			
7		10.0	-.708	1.172	-5.980	.297	**			
8		15.0	-.686	1.160	-9.703	1.170	**			
9		20.0	-.728	1.183			**			
10		25.0	-.779	1.212	-7.359	.551	**			
11		30.0	-.759	1.201			**			
12		35.0	-.475	1.049	-16.24	-.694	**			
13		40.0	-.348	.986	4.156	-.930	**			
14		45.0	-.350	.988	6.192	-1.003	**			
15		50.0	-.357	.991	3.851	-.716	**			
16		55.0	-.353	.989	1.952	-.484	**			
17		60.0	-.340	.982	.823	-.156	**			
18		65.0	-.337	.981	.383	-.192	**			
19		70.0	-.322	.974	.129	-.103	**			
20		75.0	-.283	.955	-.255	.020	**			
21		80.0	-.213	.921	-.558	.057	**			
22		85.0	-.086	.861			**			
23		90.0	.024	.810	-.705	-.017	**			
24		95.0	.108	.771			**			
	25	.5	.396	.635			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.306	.966	5.712	-.774	**			
		20.0					**			
	33	25.0	-.403	1.013			**			
	34	30.0	-.406	1.015	2.549	-.470	**			
	35	40.0	-.405	1.014	1.078	-.337	**			
	36	50.0	-.317	.971	.353	-.177	**			
		60.0					**			
		70.0					**			
	39	80.0	.234	.712	.042	.017	**			
	40	90.0	.300	.681	.249	-.002	**			

OVERALL COEFFICIENTS ** SECTION 6 **

		STEADY	RE	IM
Cz	UPPER	.366	.880	.013
Cz	LOWER	-.093	.381	-.068
Cz	TOTAL	.273	1.262	-.055
Cm	UPPER	.037	-.151	.038
Cm	LOWER	.013	-.009	-.003
Cm	TOTAL	.051	-.160	.035

```
***   LANN   ***  RUN  79 ***                    TABLE 9.17
```

TEST CONDITIONS			NORM. COEFF.			MOM. COEFF.				DISPLACEMENTS REL. TO LVDT	**	VIBRATION MODE **Y/(B/2)! HEAVE AT		PITCH
			Cz	Czi RE IM		CM	Cmi RE IM			AMPL.! (-)	PHASE (DEG)	** ** **	X=.224 M (MM)	(DEG)
RUNNR. = 79		!SECT.1 .296	1.545 -.382		.014	.071 .109		! LVDT !	1.00	0.00	** .000		
		!SECT.2 .323	1.835 -.598		.015	.131 .088		!CALC. 1!	1.11	1.39	** .100		
ALFA = .58 (DEG)		!SECT.3 .376	2.130 -.331		.023	.077 .126		! ACC. 2!	.35	-.55	** .100	.02	.46
MACH = .821		!SECT.4 .362	2.697 -.296		.036	.089 .108		! ACC. 3!	.57	-175.93	** .100		
RE*10**-6= 5.40		!SECT.5 .340	2.054 -.081		.047	-.077 .111		! ACC. 4!	.23	-150.27	** .420		
Q =44.88 (KPA)		!SECT.6 .262	1.368 .006		.050	-.192 .036		! ACC. 5!	.87	-175.58	** .420	.15	.46
P-SETTL. =148.1 (KPA)									! ACC. 6!	1.54	-175.82	** .420		
T-SETTL. =26.00		! WING .317	1.860 -.329		.037	.375 .192		! ACC. 7!	1.56	-170.86	** .700		
					!(WING : CM ABOUT			!CALC. 8!	2.05	-175.44	** .700	.50	.47
DALFA = .502 (DEG)					! AERODYN. CENTER)			!CALC. 9!	2.55	-175.67	** .700		
FREQ. =24.00 (Hz)									!CALC.10!	2.66	-174.32	** .920		
REDFR. = .076									! ACC.11!	3.05	-175.02	** .920	.68	.48
HARM. = 1									! ACC.12!	3.44	-175.57	** .920		

NR. UP ! LOW!	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** **	CALIBRATION (TRANSD.)! Cp RE	Cp IM	NR.!
1	0.0	.744	.454			**			
2	.5	.129	.761			**			
3	1.5	-.499	1.061	-3.987	1.451	**			
4	3.0	-.868	1.263	-6.019	2.516	**			
5	5.0	-.885	1.273		1.	**	-6.302	2.001	105
6	7.5	-1.041	1.371			**			
7	10.0	-1.066	1.388	-3.291	1.644	**			
8	15.0	-.909	1.288	-14.77	7.005	**			
9	20.0	-.625	1.126	-6.084	2.700	**			
10	25.0	-.606	1.116	-2.943	1.451	**			
11	30.0	-.594	1.110	-3.142	1.690	**			
12	35.0	-.587	1.106			**			
13	40.0	-.588	1.107	-3.096	1.789	**			
14	45.0	-.536	1.080	-7.536	4.041	**			
15	50.0	-.441	1.032	-3.016	-.517	**			
16	55.0	-.386	1.004	-.537	-1.365	**			
17	60.0	-.344	.984	-.462	-.957	**			
18	65.0	-.287	.956	-.489	-.888	**			
19	70.0	-.226	.927	-.300	-.688	**	-.419	-.705	119
20	75.0	-.170	.900	-.218	-.259	**			
21	80.0	-.110	.872	-.125	-.219	**			
22	85.0	-.033	.836			**			
23	90.0	.028	.808	-.094	-.147	**			
24	95.0	.101	.774			**			
25	.5	.704	.477			**			
26	1.5	.368	.648	4.266	-.033	**			
27	3.0	.304	.679	5.028	.508	**			
28	5.0	.221	.718	5.817	-.961	**			
29	7.5	.075	.786			**			
	10.0					**			
31	15.0	-.099	.867	3.100	-.762	**			
32	20.0	-.238	.933	4.552	-.667	**			
33	25.0	-.335	.979			**			
34	30.0	-.453	1.038	2.543	-.003	**			
35	40.0	-.506	1.065	2.377	-.945	**			
36	50.0	-.491	1.057	1.550	.242	**			
37	60.0	-.250	.939	1.110	.250	**			
38	70.0	-.003	.822	.846	.270	**			
39	80.0	.168	.743	.600	.216	**			
40	90.0	.276	.692	.525	.180	**			

OVERALL COEFFICIENTS			STEADY!	** SECTION 1 ** RE	IM
Cz	UPPER		.420	.908	-.315
Cz	LOWER		-.124	.637	-.067
Cz	TOTAL		.296	1.545	-.382
Cm	UPPER		.021	.009	.078
Cm	LOWER		-.007	.062	.032
Cm	TOTAL		.014	.071	.109

NR. UP ! LOW!	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** **	CALIBRATION (TRANSD.)! Cp RE	Cp IM	NR.!
1	0.0	.777	.436			**			
2	.5	.170	.742			**			
3	1.5	-.487	1.055	-6.136	1.770	**			
4	3.0	-.792	1.219	-5.590	1.954	**			
5	5.0	-.909	1.288	-6.440	1.636	**			
6	7.5	-1.056	1.381			**			
7	10.0	-1.081	1.399	-2.197	.817	**			
8	15.0	-1.048	1.376	-4.250	1.605	**			
9	20.0	-1.018	1.356	-1.767	2.410	**			
10	25.0	-.807	1.227	-21.41	14.666	**			
11	30.0	-.670	1.151	-8.954	5.305	**			
12	35.0	-.573	1.099	-7.823	4.162	**			
13	40.0	-.505	1.064	-7.676	1.893	**			
14	45.0	-.434	1.028			**			
15	50.0	-.414	1.019	-.274	-1.735	**			
16	55.0	-.370	.997	-.242	-1.402	**			
17	60.0	-.327	.976	-.104	-1.216	**			
18	65.0	-.285	.955	-.042	-1.038	**			
19	70.0	-.223	.925	-.019	-.844	**			
20	75.0	-.161	.896	.017	-.501	**			
21	80.0	-.107	.871	.034	-.387	**			
22	85.0	-.038	.838			**			
23	90.0	.031	.806	-.013	-.216	**			
24	95.0	.106	.771			**			
25	.5	.701	.479			**			
26	1.5	.370	.647	4.930	.070	**			
27	3.0	.269	.695			**			
28	5.0	.162	.745	3.844	-1.425	**			
29	7.5	.067	.790			**			
30	10.0	.018	.812	3.339	-.811	**			
31	15.0	-.128	.881	3.467	-.925	**			
32	20.0	-.267	.946	4.605	-.903	**			
33	25.0	-.363	.993			**			
34	30.0	-.466	1.044	3.025	-1.110	**			
35	40.0	-.554	1.089	4.176	-1.234	**			
36	50.0	-.453	1.038	1.403	-.324	**			
37	60.0	-.215	.922	1.193	.138	**			
38	70.0	.023	.810	.837	.182	**			
39	80.0	.186	.734	.673	.133	**			
40	90.0	.286	.687	.534	.090	**			

OVERALL COEFFICIENTS			STEADY!	** SECTION 2 ** RE	IM
Cz	UPPER		.446	1.141	-.459
Cz	LOWER		-.123	.694	-.139
Cz	TOTAL		.323	1.835	-.598
Cm	UPPER		.017	.042	.075
Cm	LOWER		-.002	.089	.014
Cm	TOTAL		.015	.131	.088

*** LANN *** RUN 79 ***   TABLE 9.17 (cont'd)

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)		
UP	LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.798	.423			**			
2		.5	.155	.748			**			
3		1.5	-.489	1.056	-5.137	1.095	**			
4		3.0	-.759	1.200	-6.878	1.452	**			
5		5.0	-.883	1.272	-6.462	.975	**			
6		7.5	-1.030	1.364			**			
7		10.0	-1.039	1.370	-3.591	.688	**	-4.166	1.140	307
8		15.0	-1.047	1.375	-4.988	1.175	**			
9		20.0	-1.031	1.365	-5.327	1.367	**	-4.916	1.433	309
10		25.0	-1.009	1.351	-6.489	2.028	**			
		30.0					**			
12		35.0	-.639	1.134	-31.11	15.050	**			
13		40.0	-.480	1.051	-11.79	2.351	**	-11.80	2.105	313
14		45.0	-.411	1.017	-2.313	-1.924	**			
15		50.0	-.378	1.000	.783	-2.259	**	1.044	-2.867	315
16		55.0	-.341	.983	1.842	-2.631	**			
17		60.0	-.313	.969	1.635	-2.113	**	1.891	-2.253	317
18		65.0	-.276	.951	1.490	-1.964	**			
19		70.0	-.228	.928	.999	-1.248	**	1.109	-1.256	319
20		75.0	-.171	.901	.611	-.793	**			
21		80.0	-.111	.873	.372	-.521	**	.486	-.505	321
22		85.0	-.049	.844			**			
23		90.0	.021	.811	.160	-.192	**	.202	-.269	323
24		95.0	.101	.774			**			
	25	.5	.698	.480			**			
	26	1.5	.372	.646	5.404	.587	**			
	27	3.0	.254	.702	6.870	1.123	**			
		5.0					**			
	29	7.5	.047	.799			**			
	30	10.0	-.030	.835	3.107	-.654	**			
		15.0					**			
	32	20.0	-.272	.949	5.183	-.583	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.418	1.020	2.012	.051	**			
	37	60.0	-.192	.911	1.166	.199	**			
	38	70.0	.038	.803	.773	.210	**			
	39	80.0	.199	.728	.809	.202	**			
	40	90.0	.299	.681	.648	.179	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 3 ** RE	IM
Cz	UPPER	.460	1.359	-.318
Cz	LOWER	-.084	.771	-.013
Cz	TOTAL	.376	2.130	-.331
Cm	UPPER	.018	-.006	.101
Cm	LOWER	.006	.083	.024
Cm	TOTAL	.023	.077	.126

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)		
UP	LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.840	.397			**			
2		.5	.219	.719			**			
3		1.5	-.384	1.003	-7.753	.565	**			
4		3.0	-.686	1.160	-6.878	.777	**			
5		5.0	-.857	1.256	-3.755	.690	**	-5.471	1.331	405
6		7.5	-.941	1.307			**			
7		10.0					**	-4.732	1.329	407
8		15.0	-.958	1.318	-6.779	.330	**			
9		20.0	-.982	1.333	-5.771	.702	**	-5.351	1.334	409
10		25.0	-.963	1.321	-7.716	1.419	**			
		30.0					**			
12		35.0	-.708	1.171	-41.15	14.309	**			
13		40.0	-.551	1.087	-25.98	7.262	**	-31.36	8.249	413
14		45.0	-.432	1.027	-5.143	-1.426	**			
15		50.0	-.387	1.005	1.035	-2.801	**	1.335	-2.800	415
16		55.0	-.361	.992	2.916	-3.103	**			
17		60.0	-.335	.979	3.563	-2.438	**	3.688	-2.692	417
		65.0					**			
19		70.0	-.267	.947	2.317	-1.417	**			
20		75.0	-.238	.933	2.132	-.885	**			
21		80.0	-.145	.889	.940	-.508	**	1.300	-.701	421
22		85.0	-.057	.848			**			
23		90.0	.018	.812	.232	-.112	**			
24		95.0	.092	.778			**			
	25	.5	.637	.513			**			
	26	1.5	.273	.693	6.501	.785	**			
	27	3.0	.154	.749	5.829	.612	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.170	.901	4.844	-.451	**			
	32	20.0	-.283	.954	5.786	-.353	**			
	33	25.0	-.365	.994			**			
		30.0					**			
	35	40.0	-.484	1.053	3.910	-.251	**			
	36	50.0	-.400	1.012	1.909	-.070	**			
	37	60.0	-.152	.892	1.315	.268	**			
	38	70.0	.062	.792	.974	.221	**			
	39	80.0	.226	.716	.840	.227	**			
	40	90.0	.310	.676	.736	.183	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 4 ** RE	IM
Cz	UPPER	.462	1.799	-.302
Cz	LOWER	-.100	.897	.006
Cz	TOTAL	.362	2.697	-.296
Cm	UPPER	.027	.000	.088
Cm	LOWER	.010	.089	.020
Cm	TOTAL	.036	.089	.108

*** LANN *** RUN 79 ***   TABLE 9.17 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cal Cp RE	Cal Cp IM	NR.
1		0.0	.843	.395			**			
2		.5	.310	.676			**			
3		1.5	-.247	.937	-7.646	.196	**			
4		3.0	-.528	1.076	-6.173	.973	**			
5		5.0	-.671	1.151	-9.964	1.238	**	-8.340	1.729	505
6		7.5	-.740	1.189			**			
7		10.0	-.829	1.240	-5.573	.158	**			
		15.0					**			
9		20.0	-.822	1.236	-9.303	.933	**			
10		25.0	-.824	1.237	-8.036	1.125	**			
11		30.0	-.790	1.217	-17.89	2.662	**			
		35.0					**			
13		40.0	-.577	1.101	-22.49	3.950	**			
14		45.0	-.459	1.041	-1.731	-2.612	**			
15		50.0	-.410	1.016	4.730	-3.490	**			
16		55.0	-.389	1.006	5.105	-2.777	**			
17		60.0	-.368	.996	3.989	-1.798	**			
18		65.0	-.349	.986	2.867	-1.194	**			
19		70.0	-.317	.971	2.297	-.635	**	2.134	-.636	519
20		75.0	-.282	.954	.666	-.248	**			
21		80.0	-.204	.917	.481	.010	**			
22		85.0	-.092	.864			**			
23		90.0	-.003	.822	-.071	.107	**			
24		95.0	.088	.780			**			
	25	.5	.569	.549			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.141	.887	5.088	-.793	**			
		15.0					**			
	32	20.0	-.307	.966	6.156	-.357	**			
		25.0					**			
	34	30.0	-.412	1.017	3.758	-.708	**			
		40.0					**			
	36	50.0	-.401	1.012	1.317	-.014	**			
		60.0					**			
		70.0					**			
	39	80.0	.231	.713	.678	.170	**			
	40	90.0	.316	.673	.509	.088	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
C_z	UPPER	.438	1.352	-.023
C_z	LOWER	-.098	.702	-.058
C_z	TOTAL	.340	2.054	-.081
C_m	UPPER	.039	-.160	.093
C_m	LOWER	.007	.080	.017
C_m	TOTAL	.047	-.079	.111

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cal Cp RE	Cal Cp IM	NR.
1		0.0	.834	.401			**			
		.5					**			
3		1.5	-.046	.842			**			
		3.0					**			
5		5.0	-.500	1.062	-9.726	.527	**			
		7.5					**			
7		10.0	-.699	1.167	-7.984	.188	**			
8		15.0	-.685	1.159	-10.03	.537	**			
9		20.0	-.736	1.187			**			
10		25.0	-.777	1.210	-8.334	.695	**			
11		30.0	-.587	1.107			**			
12		35.0	-.483	1.053	-15.84	.628	**			
13		40.0	-.351	.988	2.901	-1.262	**			
14		45.0	-.343	.983	5.973	-1.376	**			
15		50.0	-.354	.989	3.694	-.842	**			
16		55.0	-.352	.988	1.855	-.436	**			
17		60.0	-.339	.981	1.017	-.258	**			
18		65.0	-.335	.980	.501	-.131	**			
19		70.0	-.321	.973	.059	.027	**			
20		75.0	-.284	.955	-.161	.208	**			
21		80.0	-.213	.921	-.537	.179	**			
22		85.0	-.085	.861			**			
23		90.0	.026	.808	-.689	.242	**			
24		95.0	.110	.770			**			
	25	.5	.395	.635			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.309	.967	6.384	-.024	**			
		20.0					**			
	33	25.0	-.407	1.015			**			
	34	30.0	-.408	1.015	2.185	.020	**			
	35	40.0	-.405	1.014	.849	-.135	**			
	36	50.0	-.317	.971	.312	.074	**			
		60.0					**			
		70.0					**			
	39	80.0	.235	.711	.068	.193	**			
	40	90.0	.300	.681	.143	.125	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
C_z	UPPER	.357	.986	-.010
C_z	LOWER	-.094	.382	.016
C_z	TOTAL	.262	1.368	.006
C_m	UPPER	.037	-.169	.017
C_m	LOWER	.013	-.023	.019
C_m	TOTAL	.050	-.192	.036

*** LANN *** RUN 85 *** TABLE 9.18

TEST CONDITIONS			NORM. COEFF.		MOM. COEFF.			DISPLACEMENTS	**	VIBRATION MODE		
			Cz	Czi	CM	Cmi		REL.TO LVDT	**Y/(B/2)!	HEAVE AT	PITCH	
			RE	IM	RE	IM		AMPL.! PHASE	**	X=.224 M		
								(-) ! (DEG)	**	(MM)	(DEG)	

RUNNR. = 85		SECT.1	.302	.942	-.569	.014	.146	.124	LVDT	1.00	0.00	** .000	
		SECT.2	.329	1.037	-.920	.015	.141	.097	CALC. 1	1.33	1.68	** .100	
ALFA = .60 (DEG)		SECT.3	.378	1.212	-.784	.023	.114	.144	ACC. 2	.61	2.27	** .100	
MACH = .821		SECT.4	.374	1.400	-.842	.037	.107	.189	ACC. 3	.25	-181.47	** .100	.15	.21
RE*10**-6= 5.40		SECT.5	.341	1.049	-.750	.047	-.014	.196	ACC. 4	.95	6.54	** .420	
Q =45.07 (KPA)		SECT.6	.272	.706	-.531	.051	-.091	.140	ACC. 5	.34	12.94	** .420	.54	.20
P-SETTL. =148.8 (KPA)									ACC. 6	.23	160.23	** .420	
T-SETTL. =27.00		WING	.323	1.041	-.701	.037	.227	.039	ACC. 7	1.15	10.29	** .700	
						(WING : CM ABOUT			CALC. 8	.74	16.79	** .700	1.09	.18
DALFA = .252 (DEG)						AERODYN. CENTER)			CALC. 9	.42	32.49	** .700	
FREQ. =48.00 (Hz)									CALC.10	1.71	12.58	** .920	
REDFR. = .151									ACC.11	1.47	15.15	** .920	1.65	.16
HARM. = 1									ACC.12	1.22	18.81	** .920	

Section 1 pressure distribution:

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.745	.454			**			
2		.5	.127	.762			**			
3		1.5	-.501	1.062	-1.444	3.373	**			
4		3.0	-.871	1.265	-2.984	4.445	**			
5		5.0	-.891	1.276			**	-3.864	3.081	105
6		7.5	-1.047	1.375			**			
7		10.0	-1.066	1.388	-2.209	2.760	**			
8		15.0	-.982	1.333	-2.464	4.017	**			
9		20.0	-.622	1.125	-1.727	3.187	**			
10		25.0	-.601	1.113	-.715	1.804	**			
11		30.0	-.608	1.117	-.493	2.185	**			
12		35.0	-.582	1.103			**			
13		40.0	-.612	1.119	-.596	1.983	**			
14		45.0	-.553	1.088	-1.264	7.061	**			
15		50.0	-.430	1.026	-3.335	.072	**			
16		55.0	-.387	1.005	-2.008	-.817	**			
17		60.0	-.346	.985	-1.121	-.413	**			
18		65.0	-.288	.956	-1.024	-.664	**			
19		70.0	-.228	.928	-.833	-.485	**	-.955	-.667	119
20		75.0	-.171	.901	-.584	-.212	**			
21		80.0	-.110	.872	-.194	-.300	**			
22		85.0	-.034	.836			**			
23		90.0	.027	.808	-.230	-.259	**			
24		95.0	.101	.774			**			
	25	.5	.706	.476			**			
	26	1.5	.370	.647	4.168	-2.710	**			
	27	3.0	.307	.677	4.134	-2.912	**			
	28	5.0	.222	.717	5.941	-2.668	**			
	29	7.5	.076	.785			**			
		10.0					**			
	31	15.0	-.099	.867	2.651	-1.283	**			
	32	20.0	-.238	.933	3.013	-1.350	**			
	33	25.0	-.333	.978			**			
	34	30.0	-.453	1.038	2.313	-.818	**			
	35	40.0	-.511	1.067	2.002	-.833	**			
	36	50.0	-.495	1.059	1.252	.772	**			
	37	60.0	-.251	.939	.871	.525	**			
	38	70.0	-.002	.821	.860	.504	**			
	39	80.0	.169	.742	.907	.067	**			
	40	90.0	.277	.691	.695	-.046	**			

OVERALL COEFFICIENTS — SECTION 1

		STEADY	RE	IM
Cz	UPPER	.426	.375	-.436
Cz	LOWER	-.124	.567	-.133
Cz	TOTAL	.302	.942	-.569
CM	UPPER	.021	.074	.055
CM	LOWER	-.007	.072	.069
CM	TOTAL	.014	.146	.124

Section 2 pressure distribution:

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.776	.436			**			
2		.5	.167	.743			**			
3		1.5	-.491	1.057	-3.101	4.321	**			
4		3.0	-.794	1.219	-2.862	3.947	**			
5		5.0	-.915	1.291	-3.363	4.022	**			
6		7.5	-1.057	1.382			**			
7		10.0	-1.086	1.401	-.898	1.329	**			
8		15.0	-1.051	1.378	-1.962	2.294	**			
9		20.0	-1.019	1.357	-1.925	3.541	**			
10		25.0	-.914	1.290	-5.132	16.676	**			
11		30.0	-.661	1.145	-1.216	3.819	**			
12		35.0	-.591	1.108	-.983	5.229	**			
13		40.0	-.481	1.051	-3.593	6.039	**			
14		45.0	-.433	1.027			**			
15		50.0	-.416	1.019	-2.127	-1.351	**			
16		55.0	-.371	.997	-1.443	-.949	**			
17		60.0	-.328	.976	-1.286	-.785	**			
18		65.0	-.285	.955	-.961	-.942	**			
19		70.0	-.224	.926	-.941	-.916	**			
20		75.0	-.162	.896	-.725	-.643	**			
21		80.0	-.107	.871	-.360	-.564	**			
22		85.0	-.039	.839			**			
23		90.0	.030	.807	-.211	-.242	**			
24		95.0	.106	.771			**			
	25	.5	.703	.477			**			
	26	1.5	.370	.647	4.416	-3.224	**			
	27	3.0	.276	.692			**			
	28	5.0	.162	.745	5.427	-2.605	**			
	29	7.5	.068	.789			**			
	30	10.0	.019	.812	2.797	-1.506	**			
	31	15.0	-.128	.880	2.393	-1.698	**			
	32	20.0	-.266	.946	2.911	-1.535	**			
	33	25.0	-.361	.992			**			
	34	30.0	-.468	1.045	2.311	-1.486	**			
	35	40.0	-.554	1.089	2.904	-.879	**			
	36	50.0	-.454	1.038	1.026	-.048	**			
	37	60.0	-.216	.922	.495	.162	**			
	38	70.0	.024	.809	.688	.255	**			
	39	80.0	.187	.734	.548	-.058	**			
	40	90.0	.287	.687	.581	-.133	**			

OVERALL COEFFICIENTS — SECTION 2

		STEADY	RE	IM
Cz	UPPER	.452	.496	-.697
Cz	LOWER	-.123	.540	-.223
Cz	TOTAL	.329	1.037	-.920
CM	UPPER	.017	.092	.063
CM	LOWER	-.002	.049	.034
CM	TOTAL	.015	.141	.097

9.48

*** LANN *** RUN 85 ***   TABLE 9.18 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.799	.422			**			
2		.5	.153	.749			**			
3		1.5	-.494	1.058	-2.993	2.788	**			
4		3.0	-.761	1.201	-4.484	2.850	**			
5		5.0	-.886	1.273	-3.867	3.054	**			
6		7.5	-1.036	1.368			**			
7		10.0	-1.037	1.368	-1.634	1.722	**	-2.601	2.508	307
8		15.0	-1.050	1.377	-3.295	1.959	**			
9		20.0	-1.036	1.368	-2.501	2.178	**	-2.199	2.209	309
10		25.0	-1.020	1.357	-2.589	2.574	**			
		30.0					**			
12		35.0	-.669	1.150	-9.958	22.611	**			
13		40.0	-.447	1.034	-5.954	6.189	**	-7.369	6.213	313
14		45.0	-.393	1.008	-3.174	-1.380	**			
15		50.0	-.373	.998	-1.356	-2.993	**	-1.754	-3.561	315
16		55.0	-.343	.983	-1.174	-3.301	**			
17		60.0	-.318	.971	-.655	-2.297	**	-.555	-2.993	317
18		65.0	-.279	.952	-.101	-2.270	**			
19		70.0	-.231	.929	-.372	-1.638	**	-.260	-1.752	319
20		75.0	-.173	.902	-.319	-1.151	**			
21		80.0	-.112	.873	-.253	-.858	**	-.040	-.771	321
22		85.0	-.051	.844			**			
23		90.0	.019	.812	-.007	-.426	**	-.084	-.395	323
24		95.0	.101	.774			**			
	25	.5	.700	.479			**			
	26	1.5	.374	.645	5.131	-2.899	**			
	27	3.0	.260	.699	6.242	-4.063	**			
		5.0					**			
	29	7.5	.049	.798			**			
	30	10.0	-.028	.834	2.697	-1.188	**			
		15.0					**			
	32	20.0	-.272	.949	3.033	-1.402	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.419	1.021	1.180	-.180	**			
	37	60.0	-.192	.911	.501	.096	**			
	38	70.0	.039	.802	.506	.100	**			
	39	80.0	.200	.727	.438	-.132	**			
	40	90.0	.300	.681	.535	-.267	**			

**OVERALL COEFFICIENTS ** SECTION 3 **

		STEADY	RE	IM
Cz	UPPER	.462	.722	-.589
Cz	LOWER	-.084	.490	-.194
Cz	TOTAL	.378	1.212	-.784
Cm	UPPER	.018	.078	.128
Cm	LOWER	.005	.036	.016
Cm	TOTAL	.023	.114	.144

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.840	.397			**			
2		.5	.218	.719			**			
3		1.5	-.389	1.006	-4.896	4.431	**			
4		3.0	-.692	1.162	-3.751	2.551	**			
5		5.0	-.857	1.256	-1.796	1.759	**	-2.457	2.609	405
6		7.5	-.948	1.312			**			
7		10.0					**	-1.855	2.630	407
8		15.0	-.968	1.324	-4.507	2.252	**			
9		20.0	-.984	1.334	-2.946	2.952	**	-2.461	2.880	409
10		25.0	-.978	1.330	-3.356	2.983	**			
		30.0					**			
12		35.0	-.883	1.272	-13.79	19.650	**			
13		40.0	-.497	1.060	-9.284	12.035	**	-16.65	21.274	413
14		45.0	-.394	1.008	-4.419	.623	**			
15		50.0	-.371	.997	-1.225	-4.525	**	-1.166	-4.533	415
16		55.0	-.361	.992	-1.014	-4.444	**			
17		60.0	-.343	.983	.307	-3.894	**	.291	-4.510	417
		65.0					**			
19		70.0	-.274	.950	.310	-2.472	**			
20		75.0	-.243	.935	.694	-2.074	**			
21		80.0	-.148	.890	.243	-1.060	**	.219	-1.356	421
22		85.0	-.060	.849			**			
23		90.0	.016	.813	-.023	-.491	**			
24		95.0	.092	.778			**			
	25	.5	.639	.512			**			
	26	1.5	.275	.692	4.741	-3.158	**			
	27	3.0	.157	.748	4.448	-3.232	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.171	.901	2.855	-1.593	**			
	32	20.0	-.282	.954	3.148	-1.701	**			
	33	25.0	-.362	.992			**			
		30.0					**			
	35	40.0	-.487	1.055	2.161	-.722	**			
	36	50.0	-.401	1.012	1.008	-.549	**			
	37	60.0	-.153	.892	.732	-.262	**			
	38	70.0	.062	.792	.414	.082	**			
	39	80.0	.227	.715	.583	-.314	**			
	40	90.0	.311	.675	.745	-.414	**			

**OVERALL COEFFICIENTS ** SECTION 4 **

		STEADY	RE	IM
Cz	UPPER	.474	.858	-.561
Cz	LOWER	-.100	.542	-.281
Cz	TOTAL	.374	1.400	-.842
Cm	UPPER	.027	.058	.191
Cm	LOWER	.010	.048	-.001
Cm	TOTAL	.037	.107	.189

*** LANN *** RUN 85 *** TABLE 9.18 (cont'd)

NR. UP	NR. LOW	XCHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.845	.394			**			
2		.5	.306	.678			**			
3		1.5	-.252	.939	-4.598	4.953	**			
4		3.0	-.532	1.078	-3.281	4.056	**			
5		5.0	-.677	1.154	-5.478	6.902	**	-3.441	4.811	505
6		7.5	-.753	1.196			**			
7		10.0	-.820	1.234	-3.208	1.918	**			
		15.0					**			
9		20.0	-.826	1.238	-5.244	5.786	**			
10		25.0	-.841	1.246	-3.292	3.807	**			
11		30.0	-.858	1.257	-3.885	5.343	**			
		35.0					**			
13		40.0	-.504	1.063	-10.39	13.851	**			
14		45.0	-.410	1.016	-2.462	-4.183	**			
15		50.0	-.404	1.013	.752	-7.016	**			
16		55.0	-.398	1.010	.793	-5.060	**			
17		60.0	-.381	1.002	.911	-3.734	**			
18		65.0	-.359	.991	.689	-2.147	**			
19		70.0	-.326	.975	.853	-1.756	**	.958	-1.792	519
20		75.0	-.287	.956	.286	-.655	**			
21		80.0	-.207	.918	.445	-.452	**			
22		85.0	-.094	.864			**			
23		90.0	-.005	.823	.020	.151	**			
24		95.0	.089	.779			**			
	25	.5	.571	.548			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.139	.886	3.213	-2.569	**			
		15.0					**			
	32	20.0	-.306	.965	3.104	-2.296	**			
		25.0					**			
	34	30.0	-.413	1.017	2.037	-2.036	**			
		40.0					**			
	36	50.0	-.402	1.012	.633	-.573	**			
		60.0					**			
		70.0					**			
	39	80.0	.233	.712	.368	-.243	**			
	40	90.0	.317	.672	.326	-.277	**			

OVERALL COEFFICIENTS		STEADY	SECTION 5 RE	IM
Cz	UPPER	.439	.667	-.428
Cz	LOWER	-.098	.383	-.322
Cz	TOTAL	.341	1.049	-.750
Cm	UPPER	.039	-.053	.231
Cm	LOWER	.007	.038	-.035
Cm	TOTAL	.047	-.014	.196

NR. UP	NR. LOW	XCHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	**	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.835	.400			**			
		.5					**			
3		1.5	-.050	.844			**			
		3.0					**			
5		5.0	-.514	1.069	-4.802	6.160	**			
		7.5					**			
7		10.0	-.720	1.178	-2.375	1.772	**			
8		15.0	-.681	1.156	-5.460	5.690	**			
9		20.0	-.686	1.159			**			
10		25.0	-.790	1.217	-3.505	4.763	**			
11		30.0	-.803	1.224			**			
12		35.0	-.429	1.026	-11.13	8.616	**			
13		40.0	-.330	.977	2.371	-5.974	**			
14		45.0	-.359	.971	2.749	-5.297	**			
15		50.0	-.366	.994	2.156	-3.123	**			
16		55.0	-.358	.991	.869	-1.510	**			
17		60.0	-.344	.984	.486	-.695	**			
18		65.0	-.338	.980	.123	-.347	**			
19		70.0	-.324	.974	.116	-.112	**			
20		75.0	-.285	.955	.219	.224	**			
21		80.0	-.213	.921	-.105	.313	**			
22		85.0	-.087	.861			**			
23		90.0	.024	.809	-.126	.351	**			
24		95.0	.109	.770			**			
	25	.5	.398	.634			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.309	.967	3.064	-2.464	**			
		20.0					**			
	33	25.0	-.403	1.013			**			
	34	30.0	-.408	1.015	1.414	-.585	**			
	35	40.0	-.408	1.015	.330	-.290	**			
	36	50.0	-.318	.971	.268	.007	**			
		60.0					**			
		70.0					**			
	39	80.0	.235	.711	-.029	-.140	**			
	40	90.0	.300	.680	.223	.011	**			

OVERALL COEFFICIENTS		STEADY	SECTION 6 RE	IM
Cz	UPPER	.366	.503	-.395
Cz	LOWER	-.094	.203	-.137
Cz	TOTAL	.272	.706	-.531
Cm	UPPER	.037	-.087	.137
Cm	LOWER	.013	-.003	.011
Cm	TOTAL	.051	-.091	.148

*** L∩NN *** RUN 143 ***   TABLE 9.19a

! TEST CONDITIONS	! !	!	NORM. COEFF.		! MOM. COEFF.		! !	! DISPLACEMENTS	**	VIBRATION MODE	
!	! !	!	Cz	Czi	! Cm	Cmi	! !	! REL.TO LVDT	**Y/(B/2)!	HEAVE AT ! PITCH	
!	! !	!	RE	IM	! RE	IM	! !	! AMPL.! PHASE	**	! X=.224 M !	
!	! !	!			!		! !	! (-) ! (DEG)	**	! (MM) ! (DEG)	

| ! RUNNR. = 143 | ! !SECT.1 .484 1.628 -.275 ! .022 .209 .105 ! ! LVDT ! 1.00 0.00 ** .000 |
| ! | !SECT.2 .534 1.823 -.505 ! .021 .303 .018 ! !CALC. 1! 1.02 5.05 ** .100 |
| ! ALFA = 2.60 (DEG) ! !SECT.3 .598 1.980 .039 ! .037 .607 .054 ! ! ACC. 2! .27 12.67 ** .100 .05 .22 |
| ! MACH = .822 ! !SECT.4 .567 .719 1.366 ! .048 .435 .590 ! ! ACC. 3! .65 -182.11 ** .100 |
| ! RE*10**-6= 5.32 ! !SECT.5 .515 -.746 1.574 ! .042 -.782 .731 ! ! ACC. 4! .56 -197.48 ** .420 |
| ! Q =45.08 (KPA) ! !SECT.6 .414 .355 .714 ! .041 -.333 .126 ! ! ACC. 5! 1.35 -191.17 ** .420 .29 .24 |
| ! P-SETTL. =148.6 (KPA) ! ! ! ! ! ACC. 6! 1.95 -185.76 ** .420 |
| ! T-SETTL. =30.00 ! ! WING .508 1.202 .252 ! .048 -.345 .832 ! ! ACC. 7! 2.59 -190.29 ** .700 |
| ! ! !(WING : CM ABOUT ! !CALC. 8! 3.11 -190.28 ** .700 .78 .23 |
| ! DALFA = .249 (DEG) ! ! AERODYN. CENTER) ! !CALC. 9! 3.57 -188.42 ** .700 |
| ! FREQ. =24.00 (Hz) ! ! ! !CALC.10! 4.28 -191.14 ** .920 |
| ! REDFR. = .075 ! ! ! ! ACC.11! 4.73 -190.51 ** .920 1.01 .27 |
| ! HARM. = 1 ! ! ! ! ACC.12! 5.18 -189.98 ** .920 |

! !	! PRESSURE DISTRIBUTION (TUBES)	**	CALIBRATION (TRANSD.)		! OVERALL	** SECTION 1 **		
! NR. ! %CHORD	! Cp ! M-LOC.! Cp ! Cp	** Cp ! Cp ! NR.	! COEFFICIENTS		! STEADY! RE ! IM
! UP ! LOW!	! STEADY! ! RE ! IM	** RE ! IM !			

! 1 !	0.0	.667 ! .498 ! ! **		! Cz UPPER ! .537 ! 1.081 ! -.335 !
! 2 !	.5	-.032 ! .837 ! ! **		! Cz LOWER ! -.053 ! .547 ! .059 !
! 3 !	1.5	-.709 ! 1.173 ! -4.718 ! 2.182 **		! Cz TOTAL ! .484 ! 1.628 ! -.275 !
! 4 !	3.0	-1.058 ! 1.385 ! -5.927 ! 1.025 **		! ! ! !
! 5 !	5.0	-1.109 ! 1.420 ! ! ** -5.308 ! 1.362 ! 105 !	! Cm UPPER ! .022 ! .125 ! .051 !
! 6 !	7.5	-1.179 ! 1.470 ! ! **		! Cm LOWER ! -.001 ! .084 ! .053 !
! 7 !	10.0	-1.201 ! 1.487 ! -3.362 ! 1.368 **		! Cm TOTAL ! .022 ! .209 ! .105 !
! 8 !	15.0	-1.158 ! 1.455 ! -3.045 ! 1.510 **
! 9 !	20.0	-1.132 ! 1.436 ! -4.083 ! 1.940 **
! 10 !	25.0	-.854 ! 1.256 ! -19.25 ! 8.492 **
! 11 !	30.0	-.732 ! 1.186 ! -4.130 ! 1.941 **
! 12 !	35.0	-.710 ! 1.174 ! ! **
! 13 !	40.0	-.704 ! 1.171 ! -2.674 ! 1.487 **
! 14 !	45.0	-.725 ! 1.182 ! -2.429 ! 1.375 **
! 15 !	50.0	-.753 ! 1.198 ! -2.364 ! 1.160 **
! 16 !	55.0	-.503 ! 1.064 ! -15.24 ! 4.558 **
! 17 !	60.0	-.327 ! .977 ! -1.534 ! -1.593 **
! 18 !	65.0	-.270 ! .949 ! .155 ! -1.887 **
! 19 !	70.0	-.212 ! .922 ! .308 ! -1.490 ** .491 ! -1.573 ! 119 !
! 20 !	75.0	-.159 ! .896 ! .098 ! -.837 **
! 21 !	80.0	-.100 ! .869 ! .191 ! -.394 **
! 22 !	85.0	-.026 ! .834 ! ! **
! 23 !	90.0	.032 ! .807 ! .121 ! -.246 **
! 24 !	95.0	.102 ! .774 ! ! **
! ! 25 !	.5	.789 ! .429 ! ! **
! ! 26 !	1.5	.504 ! .582 ! 3.424 ! .468 **
! ! 27 !	3.0	.426 ! .621 ! 3.917 ! 1.146 **
! ! 28 !	5.0	.335 ! .665 ! 3.794 ! .063 **
! ! 29 !	7.5	.187 ! .734 ! ! **
! ! 10.0		! ! ! **
! ! 31 !	15.0	.002 ! .821 ! 2.426 ! -.323 **
! ! 32 !	20.0	-.134 ! .884 ! 3.213 ! -.198 **
! ! 33 !	25.0	-.228 ! .929 ! ! **
! ! 34 !	30.0	-.337 ! .981 ! 3.285 ! -.009 **
! ! 35 !	40.0	-.374 ! 1.000 ! 1.904 ! -.144 **
! ! 36 !	50.0	-.402 ! 1.013 ! 2.117 ! .073 **
! ! 37 !	60.0	-.211 ! .921 ! 1.315 ! .824 **
! ! 38 !	70.0	.023 ! .811 ! .741 ! .501 **
! ! 39 !	80.0	.192 ! .732 ! .411 ! .364 **
! ! 40 !	90.0	.295 ! .683 ! .358 ! .264 **

! !	! PRESSURE DISTRIBUTION (TUBES)	**	CALIBRATION (TRANSD.)		! OVERALL	** SECTION 2 **		
! NR. ! %CHORD	! Cp ! M-LOC.! Cp ! Cp	** Cp ! Cp ! NR.	! COEFFICIENTS		! STEADY! RE ! IM
! UP ! LOW!	! STEADY! ! RE ! IM	** RE ! IM !			

! 1 !	0.0	.696 ! .482 ! ! **		! Cz UPPER ! .583 ! 1.240 ! -.508 !
! 2 !	.5	.009 ! .817 ! ! **		! Cz LOWER ! -.049 ! .583 ! .003 !
! 3 !	1.5	-.748 ! 1.195 ! -5.616 ! 1.394 **		! Cz TOTAL ! .534 ! 1.823 ! -.505 !
! 4 !	3.0	-.995 ! 1.344 ! -4.925 ! .628 **		! ! ! !
! 5 !	5.0	-1.105 ! 1.417 ! -4.532 ! 1.171 **		! Cm UPPER ! .017 ! .222 ! -.026 !
! 6 !	7.5	-1.223 ! 1.504 ! ! **		! Cm LOWER ! .004 ! .080 ! .044 !
! 7 !	10.0	-1.233 ! 1.512 ! -3.189 ! .850 **		! Cm TOTAL ! .021 ! .303 ! .018 !
! 8 !	15.0	-1.201 ! 1.487 ! -3.357 ! 1.358 **
! 9 !	20.0	-1.186 ! 1.475 ! -1.880 ! .825 **
! 10 !	25.0	-1.174 ! 1.466 ! -2.861 ! 1.469 **
! 11 !	30.0	-1.174 ! 1.467 ! -2.791 ! 1.579 **
! 12 !	35.0	-1.128 ! 1.434 ! -5.213 ! 3.079 **
! 13 !	40.0	-.943 ! 1.310 ! -25.07 ! 17.079 **
! 14 !	45.0	-.677 ! 1.156 ! ! **
! 15 !	50.0	-.478 ! 1.051 ! -9.783 ! 2.315 **
! 16 !	55.0	-.365 ! .995 ! -4.686 ! -.175 **
! 17 !	60.0	-.290 ! .959 ! -.581 ! -2.287 **
! 18 !	65.0	-.243 ! .936 ! .930 ! -2.407 **
! 19 !	70.0	-.188 ! .910 ! 1.160 ! -1.899 **
! 20 !	75.0	-.134 ! .884 ! .643 ! -1.226 **
! 21 !	80.0	-.085 ! .861 ! .635 ! -.655 **
! 22 !	85.0	-.023 ! .832 ! ! **
! 23 !	90.0	.041 ! .803 ! .188 ! -.317 **
! 24 !	95.0	.112 ! .770 ! ! **
! ! 25 !	.5	.788 ! .430 ! ! **
! ! 26 !	1.5	.506 ! .581 ! 4.380 ! .609 **
! ! 27 !	3.0	.401 ! .633 ! ! **
! ! 28 !	5.0	.277 ! .692 ! 1.821 ! -.525 **
! ! 29 !	7.5	.186 ! .735 ! ! **
! ! 30 !	10.0	.130 ! .761 ! 2.759 ! -.411 **
! ! 31 !	15.0	-.016 ! .829 ! 2.638 ! -.544 **
! ! 32 !	20.0	-.150 ! .892 ! 3.619 ! -.430 **
! ! 33 !	25.0	-.243 ! .936 ! ! **
! ! 34 !	30.0	-.335 ! .981 ! 3.800 ! -.245 **
! ! 35 !	40.0	-.413 ! 1.019 ! 2.722 ! -.290 **
! ! 36 !	50.0	-.377 ! 1.001 ! 1.660 ! -.030 **
! ! 37 !	60.0	-.179 ! .905 ! 1.275 ! .663 **
! ! 38 !	70.0	.048 ! .799 ! .635 ! .363 **
! ! 39 !	80.0	.210 ! .724 ! .399 ! .283 **
! ! 40 !	90.0	.307 ! .678 ! .346 ! .193 **

*** LANN *** RUN 143 *** TABLE 9.19a (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.720	.469			**			
2		.5	-.010	.826			**			
3		1.5	-.698	1.167	-5.956	.985	**			
4		3.0	-.991	1.341	-6.573	.205	**			
5		5.0	-1.092	1.408	-5.976	.559	**			
6		7.5	-1.199	1.486			**			
7		10.0	-1.190	1.478	-3.574	.821	**	-4.175	.820	307
8		15.0	-1.204	1.490	-2.932	1.578	**			
9		20.0	-1.179	1.471	-3.627	1.192	**	-4.351	.889	309
10		25.0	-1.173	1.466	-3.361	.860	**			
		30.0					**			
12		35.0	-1.163	1.459	-4.493	2.239	**			
13		40.0	-1.150	1.449	-3.707	-1.644	**	-4.752	.024	313
14		45.0	-.662	1.147	-2.621	-4.892	**			
15		50.0	-.587	1.108	-4.983	-.479	**	-6.011	-.524	315
16		55.0	-.515	1.071	-10.80	.523	**			
17		60.0	-.411	1.018	-12.92	2.716	**	-13.02	1.402	317
18		65.0	-.307	.967	-12.41	2.373	**			
19		70.0	-.210	.920	-7.215	1.575	**	-6.654	.901	319
20		75.0	-.137	.886	-2.534	.675	**			
21		80.0	-.078	.858	-.715	.206	**	.268	-.290	321
22		85.0	-.020	.831			**			
23		90.0	.034	.806	-.257	.247	**	-.029	.137	323
24		95.0	.102	.774			**			
	25	.5	.792	.427			**			
	26	1.5	.519	.575	4.544	1.377	**			
	27	3.0	.403	.632	4.411	1.717	**			
		5.0					**			
	29	7.5	.178	.739			**			
	30	10.0	.094	.778	2.769	-.046	**			
		15.0					**			
	32	20.0	-.148	.891	3.881	.235	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.345	.986	1.949	.969	**			
	37	60.0	-.157	.895	.784	1.107	**			
	38	70.0	.059	.794	.187	.786	**			
	39	80.0	.220	.719	.071	.804	**			
	40	90.0	.315	.674	.088	.745	**			

OVERALL COEFFICIENTS — SECTION 3

		STEADY	RE	IM
Cz	UPPER	.615	1.430	-.172
Cz	LOWER	-.017	.550	.211
Cz	TOTAL	.598	1.980	.039
Cm	UPPER	.027	.579	-.064
Cm	LOWER	.009	.028	.118
Cm	TOTAL	.037	.607	.054

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.773	.438			**			
2		.5	.032	.807			**			
3		1.5	-.669	1.151	-8.280	.100	**			
4		3.0	-.888	1.277	-5.195	.018	**			
5		5.0	-1.056	1.384	-4.549	.032	**	-5.992	.776	405
6		7.5	-1.123	1.430			**			
7		10.0					**	-3.944	.700	407
8		15.0	-1.136	1.439	-5.218	.608	**			
9		20.0	-1.144	1.445	-4.702	.704	**	-5.173	.602	409
10		25.0	-1.135	1.438	-5.266	.854	**			
		30.0					**			
12		35.0	-1.135	1.439	-.199	-1.670	**			
13		40.0	-.858	1.258	48.576	-33.73	**	49.923	-33.55	413
14		45.0	-.621	1.126	13.661	-8.064	**			
15		50.0	-.560	1.094	4.763	-3.883	**	2.204	-3.561	415
16		55.0	-.506	1.066	.239	-4.579	**			
17		60.0	-.436	1.030	-3.663	-4.284	**	-3.821	-3.600	417
		65.0					**			
19		70.0	-.274	.951	-9.062	-2.998	**			
20		75.0	-.198	.915	-9.386	-1.122	**			
21		80.0	-.140	.887	-9.005	.294	**	-9.725	.514	421
22		85.0	-.079	.859			**			
23		90.0	-.030	.835	-14.46	3.592	**			
24		95.0	.020	.812			**			
	25	.5	.750	.452			**			
	26	1.5	.444	.612	4.898	1.835	**			
	27	3.0	.315	.674	4.442	1.458	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.044	.842	2.945	.313	**			
	32	20.0	-.156	.895	3.834	.900	**			
	33	25.0	-.237	.933			**			
		30.0					**			
	35	40.0	-.369	.997	2.014	1.998	**			
	36	50.0	-.343	.785	-.132	2.032	**			
	37	60.0	-.133	.884	-1.613	2.350	**			
	38	70.0	.064	.792	-2.289	1.920	**			
	39	80.0	.231	.714	-2.255	1.772	**			
	40	90.0	.306	.679	-2.749	2.091	**			

OVERALL COEFFICIENTS — SECTION 4

		STEADY	RE	IM
Cz	UPPER	.602	.552	.858
Cz	LOWER	-.035	.167	.508
Cz	TOTAL	.567	.719	1.366
Cm	UPPER	.039	.785	.297
Cm	LOWER	.010	-.350	.293
Cm	TOTAL	.048	.435	.590

*** L∧NN *** RUN 143 ***   TABLE 9.19a (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.782	.433			**			
2		.5	.105	.773			**			
3		1.5	-.461	1.043	-4.959	-.463	**			
4		3.0	-.798	1.224	-5.172	-.532	**			
5		5.0	-.914	1.292	-6.741	-.528	**	-6.144	.172	505
6		7.5	-.968	1.326			**			
7		10.0	-1.017	1.358	-5.619	-.498	**			
		15.0					**			
9		20.0	-1.049	1.379	-5.785	-.425	**			
10		25.0	-1.042	1.374	-5.867	.098	**			
11		30.0	-1.060	1.387	-4.528	.157	**			
		35.0					**			
13		40.0	-.996	1.344	20.606	-7.400	**			
14		45.0	-.722	1.180	43.125	-26.01	**			
15		50.0	-.524	1.075	11.208	-7.725	**			
16		55.0	-.432	1.028	4.119	-8.124	**			
17		60.0	-.349	.988	.185	-7.221	**			
18		65.0	-.283	.955	-.263	-5.419	**			
19		70.0	-.227	.929	.444	-2.654	**	-1.185	-2.412	519
20		75.0	-.186	.909	.880	-.462	**			
21		80.0	-.133	.884	.625	-.146	**			
22		85.0	-.064	.852			**			
23		90.0	-.010	.826	-5.818	.645	**			
24		95.0	.052	.797			**			
	25	.5	.703	.478			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	.005	.819	2.673	.645	**			
		15.0					**			
	32	20.0	-.180	.906	3.448	1.771	**			
		25.0					**			
	34	30.0	-.300	.964	2.019	2.395	**			
		40.0					**			
	36	50.0	-.366	.996	-1.934	2.145	**			
		60.0					**			
		70.0					**			
	39	80.0	.234	.712	-2.369	1.127	**			
	40	90.0	.312	.676	-2.313	1.079	**			

OVERALL COEFFICIENTS — ** SECTION 5 **

		STEADY	RE	IM
Cz	UPPER	.554	-.659	1.105
Cz	LOWER	-.039	-.087	.469
Cz	TOTAL	.515	-.746	1.574
Cm	UPPER	.035	-.428	.513
Cm	LOWER	.007	-.354	.217
Cm	TOTAL	.042	-.782	.731

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.773	.438			**			
		.5					**			
3		1.5	-.286	.957			**			
		3.0					**			
5		5.0	-.754	1.199	-5.829	-1.471	**			
		7.5					**			
7		10.0	-.870	1.266	-7.310	-2.622	**			
8		15.0	-.908	1.289	-5.090	-1.595	**			
9		20.0	-.963	1.323	-3.207	-1.468	**			
10		25.0	-.997	1.345	-4.864	-1.431	**			
11		30.0	-1.032	1.367			**			
12		35.0	-1.065	1.390	-3.224	-1.165	**			
13		40.0	.545	1.086	2.613	-10.79	**			
14		45.0	-.387	1.006	-2.431	-9.253	**			
15		50.0	-.288	.958	-.980	-5.037	**			
16		55.0	-.258	.943	1.434	.441	**			
17		60.0	-.265	.947	2.045	1.446	**			
18		65.0	-.281	.954	1.921	1.108	**			
19		70.0	-.284	.956	1.796	.490	**			
20		75.0	-.266	.947	1.129	-.118	**			
21		80.0	-.212	.921	.671	-.077	**			
22		85.0	-.097	.867			**			
23		90.0	.009	.817	-.055	-.113	**			
24		95.0	.094	.778			**			
	25	.5	.592	.537			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.182	.907	2.453	1.241	**			
		20.0					**			
	33	25.0	-.315	.971			**			
	34	30.0	-.346	.986	.053	1.747	**			
	35	40.0	-.379	1.002	-.768	.887	**			
	36	50.0	-.315	.971	-1.626	.508	**			
		60.0					**			
		70.0					**			
	39	80.0	.233	.713	-.485	.160	**			
	40	90.0	.301	.681	-.219	.078	**			

OVERALL COEFFICIENTS — ** SECTION 6 **

		STEADY	RE	IM
Cz	UPPER	.464	.423	.529
Cz	LOWER	-.050	-.068	.184
Cz	TOTAL	.414	.355	.714
Cm	UPPER	.031	-.199	.091
Cm	LOWER	.009	-.134	.034
Cm	TOTAL	.041	-.333	.126

```
***  L.ANN   *** RUN 144 ***              TABLE 9.19b
```

TEST CONDITIONS				NORM. COEFF.		MOM. COEFF.				DISPLACEMENTS REL. TO LVDT	**	VIBRATION MODE **Y/(B/2)	HEAVE AT X=.224 M	PITCH
				Cz RE	Czi IM	Cm RE	Cmi IM			AMPL. (-)	PHASE (DEG)	** **	(MM)	(DEG)
RUNNR. = 144			SECT.1 .484	.087	-.018	.022 -.027	-.028		LVDT	1.00	0.00	** .000		
			SECT.2 .533	.008	-.123	.021 -.015	-.041		CALC. 1	6.24	20.78	** .100		
ALFA = 2.60	(DEG)		SECT.3 .598	-.010	.016	.037 -.036	.009		ACC. 2	4.52	28.94	** .100	.02	.01
MACH = .821			SECT.4 .568	-.022	-.520	.049 -.093	-.171		ACC. 3	2.73	52.15	** .100		
RE*10**-6= 5.32			SECT.5 .518	.142	-.540	.043 -.017	-.141		ACC. 4	13.79	14.37	** .420		
Q =45.03	(KPA)		SECT.6 .414	.047	-.167	.041 .042	-.032		ACC. 5	11.39	42.08	** .420	.09	.02
P-SETTL.=148.5	(KPA)								ACC. 6	10.09	47.10	** .420		
T-SETTL.=30.00			WING .508	.043	-.170	.048 -.043	-.218		ACC. 7	23.82	38.99	** .700		
						(WING : CM ABOUT			CALC. 8	24.20	39.61	** .700	.16	.00
DALFA = .249	(DEG)					AERODYN. CENTER)			CALC. 9	23.81	39.98	** .700		
FREQ. =24.00	(Hz)								CALC.10	37.90	38.07	** .920		
REDFR. = .075									ACC.11	38.72	37.43	** .920	.22	.01
HARM. = 2									ACC.12	39.55	36.81	** .920		

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	** CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.666	.498					
2		.5	-.032	.836					
3		1.5	-.709	1.172	-1.837	.501			
4		3.0	-1.058	1.384	-1.149	1.140			
5		5.0	-1.109	1.419			.011	.013	105
6		7.5	-1.179	1.469					
7		10.0	-1.200	1.485	-1.050	-.589			
8		15.0	-1.157	1.453	-1.535	-.180			
9		20.0	-1.131	1.435	-.941	.094			
10		25.0	-.859	1.259	-1.671	.414			
11		30.0	-.732	1.185	-.482	-.339			
12		35.0	-.710	1.173					
13		40.0	-.702	1.169	-.448	.009			
14		45.0	-.725	1.182	-.583	.162			
15		50.0	-.753	1.197	-.276	.298			
16		55.0	-.500	1.062	.212	.600			
17		60.0	-.328	.976	.245	-.175			
18		65.0	-.270	.949	.038	.257			
19		70.0	-.212	.921	-.309	.423	.069	.109	119
20		75.0	-.159	.896	-.215	.169			
21		80.0	-.100	.868	-.200	.178			
22		85.0	-.027	.834					
23		90.0	.032	.806	-.162	.208			
24		95.0	.102	.774					
	25	.5	.789	.428					
	26	1.5	.504	.582	-.404	.121			
	27	3.0	.425	.621	-.271	-.149			
	28	5.0	.335	.665	.067	-.070			
	29	7.5	.187	.734					
	31	15.0	.003	.820	-.219	.267			
	32	20.0	-.133	.883	-.339	-.123			
	33	25.0	-.228	.928					
	34	30.0	-.337	.981	-.363	.054			
	35	40.0	-.376	1.000	-.469	.203			
	36	50.0	-.398	1.011	-.424	.186			
	37	60.0	-.211	.920	-.143	-.111			
	38	70.0	.023	.810	-.176	.155			
	39	80.0	.191	.732	-.127	-.044			
	40	90.0	.295	.683	-.123	-.017			

OVERALL COEFFICIENTS		STEADY	** SECTION 1 ** RE	IM
Cz	UPPER	.537	.162	-.032
Cz	LOWER	-.052	-.075	.014
Cz	TOTAL	.484	.087	-.018
Cm	UPPER	.022	-.001	-.032
Cm	LOWER	-.001	-.026	.004
Cm	TOTAL	.022	-.027	-.028

NR. UP	LOW	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	** CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.695	.482					
2		.5	.010	.817					
3		1.5	-.747	1.194	-.446	.909			
4		3.0	-.995	1.343	-.309	1.197			
5		5.0	-1.106	1.417	0.000	0.000			
6		7.5	-1.224	1.503					
7		10.0	-1.233	1.510	-.301	.510			
8		15.0	-1.201	1.486	.434	.224			
9		20.0	-1.185	1.474	.179	-.390			
10		25.0	-1.173	1.465	-.291	.724			
11		30.0	-1.173	1.465	0.000	0.000			
12		35.0	-1.129	1.433	.168	.731			
13		40.0	-.922	1.297	-1.373	3.119			
14		45.0	-.675	1.154					
15		50.0	-.474	1.049	-.082	-.480			
16		55.0	-.365	.995	.318	-.444			
17		60.0	-.290	.958	.389	.067			
18		65.0	-.243	.936	.283	.318			
19		70.0	-.188	.909	-.034	.474			
20		75.0	-.133	.884	.025	.110			
21		80.0	-.085	.861	.030	.107			
22		85.0	-.023	.832					
23		90.0	.041	.802	.096	.197			
24		95.0	.112	.769					
	25	.5	.788	.429					
	26	1.5	.506	.581	.246	.133			
	27	3.0	.401	.633					
	28	5.0	.276	.692	.146	-.005			
	29	7.5	.185	.735					
	30	10.0	.129	.761	-.082	.095			
	31	15.0	-.017	.829	.012	.118			
	32	20.0	-.149	.891	0.000	0.000			
	33	25.0	-.243	.936					
	34	30.0	-.336	.980	.016	.175			
	35	40.0	-.415	1.020	-.159	.011			
	36	50.0	-.375	.999	-.139	.014			
	37	60.0	-.179	.905	-.016	-.118			
	38	70.0	.048	.799	.025	.073			
	39	80.0	.210	.724	.038	.079			
	40	90.0	.307	.678	-.098	-.135			

OVERALL COEFFICIENTS		STEADY	** SECTION 2 ** RE	IM
Cz	UPPER	.582	.015	-.132
Cz	LOWER	-.049	-.007	.008
Cz	TOTAL	.533	.008	-.123
Cm	UPPER	.017	-.007	-.037
Cm	LOWER	.004	-.008	-.004
Cm	TOTAL	.021	-.015	-.041

*** LANN *** RUN 144 *** TABLE 9.19b (cont'd)

NR UP	LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.720	.468			**			
2		.5	-.010	.826			**			
3		1.5	-.697	1.166	-.503	.013	**			
4		3.0	-.990	1.339	-.698	-.173	**			
5		5.0	-1.092	1.407	-1.580	-.601	**			
6		7.5	-1.199	1.485			**			
7		10.0	-1.189	1.477	-.633	-.365	**	.025	.008	307
8		15.0	-1.203	1.488	-.534	-.286	**			
9		20.0	-1.178	1.469	-.949	-.445	**	-.056	.123	309
10		25.0	-1.172	1.464	-.441	-.186	**			
		30.0					**			
12		35.0	-1.163	1.457	-.801	-.266	**			
13		40.0	-1.143	1.443	1.908	.485	**	.406	.329	313
14		45.0	-.662	1.147	-.163	1.011	**			
15		50.0	-.586	1.107	-.501	.486	**	-.142	.683	315
16		55.0	-.515	1.070	-.501	1.303	**			
17		60.0	-.411	1.018	-.558	.929	**	.367	.436	317
18		65.0	-.309	.968	-.165	-.121	**			
19		70.0	-.213	.921	.389	-1.011	**	.768	-1.070	319
20		75.0	-.137	.885	.156	-1.122	**			
21		80.0	-.075	.856	-.132	-.930	**	.066	-.508	321
22		85.0	-.021	.831			**			
23		90.0	.035	.805	-.398	-.243	**	-.104	-.248	323
24		95.0	.102	.774			**			
	25	.5	.793	.426			**			
	26	1.5	.519	.574	-.221	.067	**			
	27	3.0	.402	.632	-.636	.440	**			
		5.0					**			
	29	7.5	.177	.739			**			
	30	10.0	.094	.778	-.225	.017	**			
		15.0					**			
	32	20.0	-.148	.890	-.372	.042	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.342	.984	-.546	-.290	**			
	37	60.0	-.157	.895	-.162	-.122	**			
	38	70.0	.059	.794	-.360	-.030	**			
	39	80.0	.220	.719	-.275	-.113	**			
	40	90.0	.315	.674	-.277	-.066	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.615	.095	.035
Cz	LOWER	-.016	-.105	-.019
Cz	TOTAL	.598	-.010	.016
Cm	UPPER	.027	.008	.029
Cm	LOWER	.010	-.044	-.020
Cm	TOTAL	.037	-.036	.009

*** SECTION 3 ***

NR UP	LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.773	.438			**			
2		.5	.033	.806			**			
3		1.5	-.667	1.150	-.816	.028	**			
4		3.0	-.888	1.276	-1.038	-.128	**			
5		5.0	-1.056	1.383	-.631	-.210	**	.040	.052	405
6		7.5	-1.123	1.429			**			
7		10.0					**	-.021	.080	407
8		15.0	-1.135	1.437	-.459	-1.450	**			
9		20.0	-1.143	1.443	-.222	-.628	**	.017	.078	409
10		25.0	-1.134	1.437	-.390	-.165	**			
		30.0					**			
12		35.0	-1.129	1.433	-1.021	5.235	**			
13		40.0	-.879	1.270	-.512	17.056	**	.080	13.118	413
14		45.0	-.623	1.126	-1.444	-1.262	**			
15		50.0	-.561	1.094	-.994	1.053	**	-.395	.803	415
16		55.0	-.508	1.066	-.420	1.560	**			
17		60.0	-.436	1.030	-.521	2.075	**	-.306	1.729	417
		65.0					**			
19		70.0	-.277	.952	.001	1.677	**			
20		75.0	-.197	.914	1.046	.387	**			
21		80.0	-.134	.884	1.187	-.572	**	1.249	-.511	421
22		85.0	-.085	.861			**			
23		90.0	-.026	.833	.985	-2.208	**			
24		95.0	.023	.811			**			
	25	.5	.751	.451			**			
	26	1.5	.444	.612	-.248	-.136	**			
	27	3.0	.315	.674	-.263	-.147	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.044	.842	-.277	-.227	**			
	32	20.0	-.155	.894	-.196	-.305	**			
	33	25.0	-.236	.932			**			
		30.0					**			
	35	40.0	-.372	.998	-.383	-.637	**			
	36	50.0	-.339	.982	-.360	-.695	**			
	37	60.0	-.133	.883	-.288	-.320	**			
	38	70.0	.065	.791	-.178	-.351	**			
	39	80.0	.231	.714	-.115	-.539	**			
	40	90.0	.306	.678	-.211	-.602	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.602	.055	-.388
Cz	LOWER	-.034	-.077	-.132
Cz	TOTAL	.568	-.022	-.520
Cm	UPPER	.039	-.063	-.095
Cm	LOWER	.010	-.029	-.076
Cm	TOTAL	.049	-.093	-.171

*** SECTION 4 ***

*** **LANN** *** RUN 144 *** TABLE 9.19b (cont'd)

NR. UP	NR. LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.782	.433			**			
2		.5	.106	.772			**			
3		1.5	-.461	1.042	0.000	0.000	**			
4		3.0	-.799	1.223	.516	.536	**			
5		5.0	-.913	1.291	0.000	0.000	**	.075	.142	505
6		7.5	-.969	1.326			**			
7		10.0	-1.016	1.356	0.000	0.000	**			
		15.0					**			
9		20.0	-1.047	1.377	0.000	0.000	**			
10		25.0	-1.041	1.373	.422	.165	**			
11		30.0	-1.059	1.385	.302	-.798	**			
		35.0					**			
13		40.0	-1.017	1.356	-5.281	14.198	**			
14		45.0	-.721	1.180	-4.465	3.053	**			
15		50.0	-.524	1.075	-1.703	.821	**			
16		55.0	-.433	1.029	-1.020	2.276	**			
17		60.0	-.350	.987	-.448	2.440	**			
18		65.0	-.284	.955	.078	1.648	**			
19		70.0	-.228	.928	.702	.546	**	.822	.567	519
20		75.0	-.185	.908	.555	-.458	**			
21		80.0	-.132	.883	.910	-1.026	**			
22		85.0	-.066	.852			**			
23		90.0	-.009	.825	1.996	-1.891	**			
24		95.0	.053	.797			**			
	25	.5	.704	.477			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	.003	.820	.108	-.269	**			
		15.0					**			
	32	20.0	-.179	.905	-.080	-.779	**			
		25.0					**			
	34	30.0	-.300	.963	-.038	-.422	**			
		40.0					**			
	36	50.0	-.362	.993	-.045	-.532	**			
		60.0					**			
		70.0					**			
	39	80.0	.234	.712	.275	-.418	**			
	40	90.0	.312	.675	.138	-.385	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
Cz	UPPER	.556	.124	-.405
Cz	LOWER	-.038	.017	-.135
Cz	TOTAL	.518	.142	-.540
Cm	UPPER	.036	-.037	-.077
Cm	LOWER	.007	.020	-.064
Cm	TOTAL	.043	-.017	-.141

NR. UP	NR. LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.773	.438			**			
		.5					**			
3		1.5	-.285	.956			**			
		3.0					**			
5		5.0	-.753	1.197	.003	.550	**			
		7.5					**			
7		10.0	-.870	1.265	0.000	0.000	**			
8		15.0	-.907	1.287	.654	-1.808	**			
9		20.0	-.961	1.321	0.000	0.000	**			
10		25.0	-.997	1.344	.786	.864	**			
11		30.0	-1.031	1.366			**			
12		35.0	-1.064	1.388	-.515	1.334	**			
13		40.0	-.537	1.081	.262	2.289	**			
14		45.0	-.387	1.005	-.699	2.028	**			
15		50.0	-.287	.957	-.868	1.600	**			
16		55.0	-.258	.943	-.322	-.117	**			
17		60.0	-.265	.946	.049	-.929	**			
18		65.0	-.281	.954	.067	-.779	**			
19		70.0	-.284	.955	-.069	-.607	**			
20		75.0	-.265	.946	.133	-.168	**			
21		80.0	-.212	.921	-.162	-.126	**			
22		85.0	-.098	.867			**			
23		90.0	.009	.817	0.000	0.000	**			
24		95.0	.094	.778			**			
	25	.5	.594	.536			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.183	.907	-.069	-.692	**			
		20.0					**			
	33	25.0	-.314	.970			**			
	34	30.0	-.346	.985	.228	-.268	**			
	35	40.0	-.382	1.003	.195	-.467	**			
	36	50.0	-.312	.969	.351	-.426	**			
		60.0					**			
		70.0					**			
	39	80.0	.232	.713	0.000	0.000	**			
	40	90.0	.301	.680	.151	-.168	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
Cz	UPPER	.463	.010	-.084
Cz	LOWER	-.049	.037	-.082
Cz	TOTAL	.414	.047	-.167
Cm	UPPER	.031	.019	-.008
Cm	LOWER	.009	.023	-.024
Cm	TOTAL	.041	.042	-.032

*** L.ANN *** RUN 145 *** TABLE 9.19c

TEST CONDITIONS			NORM. COEFF.			MOM. COEFF.					DISPLACEMENTS ** VIBRATION MODE				
											REL. TO LVDT	**Y/(B/2) HEAVE AT	PITCH	
			Cz	Czi		Cm	Cmi				AMPL. PHASE	** X=.224 M	
				RE IM		RE IM					(-) (DEG)	** (MM)	(DEG)

RUNNR. = 145		SECT.1 .486	.009 -.042	.022 -.028 .014	LVDT	1.00 0.00	** .000		
		SECT.2 .535	.027 -.047	.021 -.005 -.012	CALC. 1 14.69 -7.66	** .100			
ALFA = 2.60 (DEG)	SECT.3 .599	-.016 .037	.037 -.015 -.018	ACC. 2 6.08 -9.84	** .100	.01	.02
MACH = .821	SECT.4 .565	.121 .069	.047 -.007 .036	ACC. 3 4.45 -181.04	** .100		
RE*10**-6= 5.32	SECT.5 .516	-.133 .166	.042 -.029 .024	ACC. 4 25.30 -15.80	** .420		
Q =44.96 (KPA)	SECT.6 .415	-.035 .092	.041 -.005 .001	ACC. 5 2.51 -22.97	** .420	.08	.03
P-SETTL. =148.4 (KPA)					ACC. 6 4.86 -150.78	** .420		
T-SETTL. =30.00	WING .509	.007 .018	.048 -.036 .077	ACC. 7 9.81 -21.77	** .700		
			(WING CM ABOUT	CALC. 8 4.05 -23.02	** .700	.07	.02
DALFA = .249 (DEG)			AERODYN. CENTER)	CALC. 9 2.62 -100.08	** .700		
FREQ. =24.00 (Hz)				CALC.10 11.41 -17.87	** .920		
REDFR. = .075				ACC.11 8.27 -17.55	** .920	.10	.01
HARM. = 3				ACC.12 5.09 -16.82	** .920		

NR.	%CHORD	PRESSURE DISTRIBUTION (TUBES)				** CALIBRATION (TRANSD.)			
UP LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1	0.0	.667	.497			**		
2	.5	-.032	.836			**		
3	1.5	-.710	1.172	-.385	.784	**		
4	3.0	-1.059	1.383	-1.346	3.075	**		
5	5.0	-1.111	1.419			** -.013	.013	105
6	7.5	-1.180	1.468			**		
7	10.0	-1.202	1.485	.094	.732	**		
8	15.0	-1.159	1.453	-.563	.784	**		
9	20.0	-1.134	1.435	.114	.603	**		
10	25.0	-.854	1.255	-.138	-.280	**		
11	30.0	-.733	1.185	-.204	.344	**		
12	35.0	-.712	1.174			**		
13	40.0	-.706	1.170	.048	.334	**		
14	45.0	-.724	1.180	-.040	.208	**		
15	50.0	-.755	1.197	.165	.251	**		
16	55.0	-.513	1.068	2.015	1.244	**		
17	60.0	-.330	.977	.320	-.013	**		
18	65.0	-.269	.948	.044	.257	**		
19	70.0	-.213	.921	-.027	-.111	** -.080	.021	119
20	75.0	-.159	.895	-.055	.075	**		
21	80.0	-.100	.867	.082	.070	**		
22	85.0	-.027	.833			**		
23	90.0	.031	.806	.012	.105	**		
24	95.0	.101	.774			**		
25	.5	.789	.428			**		
26	1.5	.504	.581	.362	.442	**		
27	3.0	.424	.621	.597	.279	**		
28	5.0	.336	.664	.050	.187	**		
29	7.5	.188	.733			**		
31	15.0	.003	.819	.048	.520	**		
32	20.0	-.133	.883	.104	.135	**		
33	25.0	-.229	.928			**		
34	30.0	-.335	.979	.071	.425	**		
35	40.0	-.376	1.000	.318	.422	**		
36	50.0	-.402	1.012	-.156	.322	**		
37	60.0	-.212	.920	-.003	.178	**		
38	70.0	.024	.810	.086	.258	**		
39	80.0	.192	.731	.130	-.004	**		
40	90.0	.296	.683	.003	.081	**		

OVERALL COEFFICIENTS		****SECTION 1 **		
		STEADY	RE	IM
Cz	UPPER	.538	-.017	-.117
Cz	LOWER	-.053	.026	.075
Cz	TOTAL	.486	.009	-.042
Cm	UPPER	.023	-.032	-.005
Cm	LOWER	-.001	.004	.019
Cm	TOTAL	.022	-.028	.014

NR.	%CHORD	PRESSURE DISTRIBUTION (TUBES)				** CALIBRATION (TRANSD.)			
UP LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	** Cp RE	Cp IM	NR.
1	0.0	.696	.481			**		
2	.5	.010	.816			**		
3	1.5	-.748	1.194	0.000	0.000	**		
4	3.0	-.997	1.342	-1.600	.325	**		
5	5.0	-1.108	1.417	.865	.630	**		
6	7.5	-1.223	1.501			**		
7	10.0	-1.234	1.509	0.000	0.000	**		
8	15.0	-1.202	1.485	-.757	-.568	**		
9	20.0	-1.187	1.474	-.609	.099	**		
10	25.0	-1.175	1.465	0.000	0.000	**		
11	30.0	-1.174	1.464	.100	.510	**		
12	35.0	-1.130	1.432	0.000	0.000	**		
13	40.0	-.954	1.315	-.036	.944	**		
14	45.0	-.661	1.146			**		
15	50.0	-.479	1.051	-.011	.170	**		
16	55.0	-.367	.995	.250	.724	**		
17	60.0	-.292	.959	.189	-.090	**		
18	65.0	-.242	.935	-.149	.072	**		
19	70.0	-.188	.909	-.091	-.157	**		
20	75.0	-.134	.883	-.075	-.061	**		
21	80.0	-.084	.860	-.064	.076	**		
22	85.0	-.023	.831			**		
23	90.0	.041	.802	-.053	-.042	**		
24	95.0	.111	.769			**		
25	.5	.790	.428			**		
26	1.5	.507	.580	.379	.038	**		
27	3.0	.400	.633			**		
28	5.0	.278	.691	0.000	0.000	**		
29	7.5	.187	.734			**		
30	10.0	.130	.760	.014	-.155	**		
31	15.0	-.016	.828	0.000	0.000	**		
32	20.0	-.149	.890	.133	-.099	**		
33	25.0	-.243	.935			**		
34	30.0	-.333	.979	-.149	.108	**		
35	40.0	-.415	1.019	.396	-.068	**		
36	50.0	-.378	1.000	-.117	.091	**		
37	60.0	-.179	.905	-.166	-.176	**		
38	70.0	.049	.798	.082	.082	**		
39	80.0	.210	.723	-.065	-.062	**		
40	90.0	.307	.677	-.040	.043	**		

OVERALL COEFFICIENTS		****SECTION 2 **		
		STEADY	RE	IM
Cz	UPPER	.584	.022	-.043
Cz	LOWER	-.049	.005	-.004
Cz	TOTAL	.535	.027	-.047
Cm	UPPER	.017	.000	-.012
Cm	LOWER	.004	-.006	-.000
Cm	TOTAL	.021	-.005	-.012

*** LANN *** RUN 145 *** TABLE 9.19c (cont'd)

NR. UP	NR. LOW	XCHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.720	.468					
2		.5	-.010	.826					
3		1.5	-.700	1.167	.414	-.853			
4		3.0	-.993	1.340	-.195	-.933			
5		5.0	-1.095	1.408	-.173	-1.060			
6		7.5	-1.200	1.483					
7		10.0	-1.190	1.476	-.105	-.818	.023	-.022	307
8		15.0	-1.206	1.488	-.108	-.790			
9		20.0	-1.181	1.469	-.119	-.735	.012	.055	309
10		25.0	-1.174	1.464	0.000	0.000			
		30.0							
12		35.0	-1.164	1.457	.583	-.115			
13		40.0	-1.154	1.450	-.521	.110	-.186	.342	313
14		45.0	-.658	1.144	.046	-.358			
15		50.0	-.588	1.107	.182	.019	-.039	.087	315
16		55.0	-.518	1.071	.157	.401			
17		60.0	-.421	1.022	.208	-.187	-.109	-.027	317
18		65.0	-.307	.966	0.000	0.000			
19		70.0	-.205	.917	-.366	-.121	-.103	.094	319
20		75.0	-.140	.886	-.018	-.156			
21		80.0	-.077	.856	.088	.075	.064	.042	321
22		85.0	-.020	.830					
23		90.0	.034	.805	.054	-.066	.041	-.008	323
24		95.0	.102	.773					
	25	.5	.793	.426					
	26	1.5	.519	.574	.043	-.441			
	27	3.0	.402	.632	.516	-.404			
		5.0							
	29	7.5	.178	.738					
	30	10.0	.094	.777	-.086	-.105			
		15.0							
	32	20.0	-.147	.890	.041	-.275			
		25.0							
		30.0							
		40.0							
	36	50.0	-.346	.985	-.144	.110			
	37	60.0	-.159	.895	-.087	-.326			
	38	70.0	.060	.793	0.000	0.000			
	39	80.0	.220	.718	-.001	-.177			
	40	90.0	.315	.674	-.063	.066			

OVERALL COEFFICIENTS — ************ ** SECTION 3 ** ************

		STEADY	RE	IM
Cz	UPPER	.616	-.007	.068
Cz	LOWER	-.017	-.009	-.031
Cz	TOTAL	.599	-.016	.037
Cm	UPPER	.027	-.005	-.012
Cm	LOWER	.009	-.009	-.006
Cm	TOTAL	.037	-.015	-.018

NR. UP	NR. LOW	XCHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY	M-LOC.	Cp RE	Cp IM	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1		0.0	.774	.437					
2		.5	.032	.806					
3		1.5	-.670	1.150	-.504	.182			
4		3.0	-.890	1.276	-1.211	1.043			
5		5.0	-1.059	1.383	-.847	.149	-.009	.005	405
6		7.5	-1.123	1.428			-.074	.001	407
7		10.0							
8		15.0	-1.137	1.437	-.445	1.428	-.003	-.003	409
9		20.0	-1.146	1.444	-.629	.104			
10		25.0	-1.136	1.437	-.591	.105			
		30.0							
12		35.0	-1.120	1.425	-7.601	-3.658	8.621	2.313	413
13		40.0	-.854	1.255	5.391	1.748			
14		45.0	-.623	1.125	.502	.634			
15		50.0	-.561	1.093	.350	.627	.076	.145	415
16		55.0	-.508	1.065	.057	.264			
17		60.0	-.438	1.030	.236	.283	-.060	.045	417
		65.0							
19		70.0	-.270	.948	-.296	-.255			
20		75.0	-.201	.915	-.398	-.079			
21		80.0	-.137	.885	-.224	-.199	-.317	-.232	421
22		85.0	-.069	.853					
23		90.0	-.023	.831	-.339	.087			
24		95.0	.027	.808					
	25	.5	.751	.450					
	26	1.5	.444	.611	-.211	.168			
	27	3.0	.313	.674	-.055	.397			
		5.0							
		7.5							
		10.0							
	31	15.0	-.043	.841	-.161	.494			
	32	20.0	-.154	.893	0.000	0.000			
	33	25.0	-.237	.932					
		30.0							
	35	40.0	-.372	.997	-.040	.256			
	36	50.0	-.344	.984	-.247	.188			
	37	60.0	-.135	.884	-.288	.251			
	38	70.0	.066	.790	-.179	.169			
	39	80.0	.231	.713	-.079	.237			
	40	90.0	.304	.679	-.133	.271			

OVERALL COEFFICIENTS — ************ ** SECTION 4 ** ************

		STEADY	RE	IM
Cz	UPPER	.600	.160	-.001
Cz	LOWER	-.035	-.038	.071
Cz	TOTAL	.565	.121	.069
Cm	UPPER	.038	.015	.007
Cm	LOWER	.010	-.022	.029
Cm	TOTAL	.047	-.007	.036

*** LANN *** RUN 145 *** TABLE 9.19c (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.782	.432			**			
2		.5	.105	.772			**			
3		1.5	-.463	1.043	.615	.217	**			
4		3.0	-.801	1.223	-.708	.208	**			
5		5.0	-.917	1.292	0.000	0.000	**	-.011	-.003	505
6		7.5	-.969	1.325			**			
7		10.0	-1.017	1.356	1.238	-.208	**			
		15.0					**			
9		20.0	-1.051	1.378	.774	-.151	**			
10		25.0	-1.043	1.372	.711	-.151	**			
11		30.0	-1.061	1.385	.145	.666	**			
		35.0					**			
13		40.0	-.989	1.337	-.182	-10.31	**			
14		45.0	-.727	1.182	4.972	3.038	**			
15		50.0	-.524	1.074	1.018	.828	**			
16		55.0	-.434	1.028	.225	-.181	**			
17		60.0	-.352	.988	.638	.323	**			
18		65.0	-.283	.954	.001	-.174	**			
19		70.0	-.226	.927	-.019	-.324	**	-.067	-.170	519
20		75.0	-.185	.908	.243	-.092	**			
21		80.0	-.133	.883	.088	.254	**			
22		85.0	-.062	.850			**			
23		90.0	-.007	.824	-.246	.256	**			
24		95.0	.056	.795			**			
	25	.5	.704	.477			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	.004	.819	.091	.115	**			
		15.0					**			
	32	20.0	-.178	.904	.165	-.112	**			
		25.0					**			
	34	30.0	-.296	.960	.305	.059	**			
		40.0					**			
	36	50.0	-.367	.995	.156	-.115	**			
		60.0					**			
		70.0					**			
	39	80.0	.234	.712	0.000	0.000	**			
	40	90.0	.310	.676	-.084	.084	**			

**OVERALL COEFFICIENTS — ** SECTION 5 **

COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.554	-.166	.170
Cz	LOWER	-.039	.032	-.004
Cz	TOTAL	.516	-.133	.166
Cm	UPPER	.035	-.033	.026
Cm	LOWER	.007	.004	-.002
Cm	TOTAL	.042	-.029	.024

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.774	.437			**			
		.5					**			
3		1.5	-.287	.956			**			
		3.0					**			
5		5.0	-.756	1.198	.722	-.228	**			
		7.5					**			
7		10.0	-.870	1.264	0.000	0.000	**			
8		15.0	-.909	1.287	.324	-2.057	**			
9		20.0	-.964	1.321	0.000	0.000	**			
10		25.0	-.998	1.343	0.000	0.000	**			
11		30.0	-1.033	1.366			**			
12		35.0	-1.066	1.388	-.889	-.577	**			
13		40.0	-.551	1.088	.439	-.555	**			
14		45.0	-.382	1.002	.902	-.724	**			
15		50.0	-.289	.957	.439	.030	**			
16		55.0	-.258	.942	.231	-.205	**			
17		60.0	-.263	.945	-.206	-.234	**			
18		65.0	-.280	.953	.102	.118	**			
19		70.0	-.285	.955	-.117	.101	**			
20		75.0	-.266	.946	0.000	0.000	**			
21		80.0	-.211	.920	0.000	0.000	**			
22		85.0	-.097	.866			**			
23		90.0	.008	.817	-.098	-.295	**			
24		95.0	.093	.777			**			
	25	.5	.594	.536			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.181	.906	-.263	.448	**			
		20.0					**			
	33	25.0	-.314	.969			**			
	34	30.0	-.341	.982	0.000	0.000	**			
	35	40.0	-.382	1.002	0.000	0.000	**			
	36	50.0	-.315	.970	0.000	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.233	.712	0.000	0.000	**			
	40	90.0	.302	.680	-.213	-.216	**			

**OVERALL COEFFICIENTS — ** SECTION 6 **

COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.465	-.024	.084
Cz	LOWER	-.049	-.012	.008
Cz	TOTAL	.415	-.035	.092
Cm	UPPER	.031	.004	.015
Cm	LOWER	.009	-.009	-.013
Cm	TOTAL	.041	-.005	.001

*** LANN *** RUN 92 *** TABLE 9.20

TEST CONDITIONS		NORM. COEFF. Cz	Czi RE IM	MOM. COEFF. Cm	Cmi RE IM		DISPLACEMENTS REL.TO LVDT AMPL.! PHASE (-) ! (DEG)	** **Y/(B/2)! ** **	VIBRATION MODE HEAVE AT X=.224 M ! (MM)	PITCH ! (DEG)
RUNNR. = 92	SECT.1 .327	1.803 -.490	.031 .473	-.113	LVDT	1.00 0.00	** .000		
	SECT.2 .338	2.095 -.639	.023 .818	-.216	CALC. 1!	1.06 3.86	** .100		
ALFA = .59 (DEG)	SECT.3 .373	2.406 -.349	.032 1.129	-.221	ACC. 2!	.30 7.29	** .100	.03	.23
MACH = .871	SECT.4 .324	1.077 1.073	.043 .241	.688	ACC. 3!	.62 -179.84	** .100		
RE*10**-6= 5.52	SECT.5 .209	-.266 .996	.018 -.586	.730	ACC. 4!	.40 -193.01	** .420		
Q =48.38 (KPA)	SECT.6 .215	.406 .437	.036 -.416	.291	ACC. 5!	1.19 -187.67	** .420	.19	.25
P-SETTL. =149.4 (KPA)					ACC. 6!	1.84 -182.89	** .420		
T-SETTL. =29.00	WING .307	1.483 -.026	.025 -.042	.581	ACC. 7!	2.26 -186.38	** .700		
			(WING : CM ABOUT		CALC. 8!	2.78 -186.73	** .700	.58	.23
DALFA = .248 (DEG)			AERODYN. CENTER)		CALC. 9!	3.27 -185.08	** .700		
FREQ. =24.00 (Hz)					CALC.10!	3.78 -187.17	** .920		
REDFR. = .071					ACC.11!	4.20 -186.77	** .920	.80	.26
HARM. = 1					ACC.12!	4.63 -186.43	** .920		

NR. UP ! LOW!	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** **	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1	0.0	.787	.460						
2	.5	.224	.760						
3	1.5	-.364	1.060	-2.970	.570				
4	3.0	-.712	1.263	-4.940	.998				
5	5.0	-.747	1.286			-4.818	1.186	105	
6	7.5	-.898	1.389						
7	10.0	-.925	1.409	-3.345	1.175				
8	15.0	-.882	1.378	-4.013	1.400				
9	20.0	-.709	1.261	-24.50	9.383				
10	25.0	-.574	1.179	-2.114	.936				
11	30.0	-.585	1.185	-1.522	1.031				
12	35.0	-.593	1.190						
13	40.0	-.604	1.196	-1.857	.949				
14	45.0	-.630	1.212	-1.639	.689				
15	50.0	-.659	1.230	-1.890	.595				
16	55.0	-.682	1.244	-1.813	.777				
17	60.0	-.704	1.258	-1.864	.924				
18	65.0	-.729	1.274	-2.340	.902				
19	70.0	-.334	1.043	-6.763	3.506	-8.239	3.038	119	
20	75.0	-.170	.957	-2.904	1.094				
21	80.0	-.086	.914	-1.419	.094				
22	85.0	-.015	.879						
23	90.0	.044	.849	-.748	-.041				
24	95.0	.107	.818						
25	.5	.709	.506						
26	1.5	.375	.684	3.739	.165				
27	3.0	.319	.712	4.028	.661				
28	5.0	.233	.755	4.048	-.260				
29	7.5	.093	.824						
31	15.0	-.077	.910	3.080	-.307				
32	20.0	-.218	.982	3.150	-.418				
33	25.0	-.317	1.035						
34	30.0	-.449	1.107	1.760	-.094				
35	40.0	-.514	1.144	1.266	-.520				
36	50.0	-.706	1.259	2.388	-1.066				
37	60.0	-.277	1.013	2.261	.659				
38	70.0	-.047	.894	4.175	-.307				
39	80.0	.139	.802	2.254	-.395				
40	90.0	.277	.733	.511	-.111				

OVERALL COEFFICIENTS		STEADY!	** SECTION 1 ** RE ! IM
Cz	UPPER	.478	1.086 ! -.410
Cz	LOWER	-.151	.717 ! -.079
Cz	TOTAL	.327	1.803 ! -.490
Cm	UPPER	.048	.212 ! -.082
Cm	LOWER	-.018	.260 ! -.032
Cm	TOTAL	.031	.473 ! -.113

NR. UP ! LOW!	%CHORD	PRESSURE DISTRIBUTION (TUBES) Cp STEADY!	M-LOC.!	Cp RE	Cp IM	** **	CALIBRATION (TRANSD.) Cp RE	Cp IM	NR.
1	0.0	.815	.443						
2	.5	.267	.738						
3	1.5	-.342	1.048	-4.612	.767				
4	3.0	-.634	1.214	-4.777	1.292				
5	5.0	-.752	1.289	-5.845	1.303				
6	7.5	-.901	1.391						
7	10.0	-.935	1.416	-1.254	.850				
8	15.0	-.916	1.402	-2.918	.877				
9	20.0	-.908	1.397	-3.745	1.805				
10	25.0	-.889	1.383	-3.308	1.385				
11	30.0	-.892	1.385	-2.850	1.469				
12	35.0	-.715	1.265	-18.12	10.705				
13	40.0	-.649	1.224	-2.157	1.035				
14	45.0	-.665	1.234						
15	50.0	-.704	1.258	-1.580	.848				
16	55.0	-.726	1.272	-1.730	.926				
17	60.0	-.756	1.292	-1.752	1.042				
18	65.0	-.418	1.090	-5.299	-.174				
19	70.0	-.223	.985	-4.403	.559				
20	75.0	-.134	.939	-2.333	.495				
21	80.0	-.066	.904	-1.492	.031				
22	85.0	-.004	.873						
23	90.0	.054	.844	-1.007	.170				
24	95.0	.115	.814						
25	.5	.699	.512						
26	1.5	.367	.688	4.671	.399				
27	3.0	.279	.732						
28	5.0	.170	.786	2.381	-.644				
29	7.5	.079	.832						
30	10.0	.032	.855	2.722	-.694				
31	15.0	-.112	.928	3.718	-.305				
32	20.0	-.255	1.002	3.102	-.526				
33	25.0	-.354	1.054						
34	30.0	-.479	1.124	2.160	-.349				
35	40.0	-.620	1.206	2.432	-.751				
36	50.0	-.772	1.302	2.003	-.764				
37	60.0	-.213	.979	2.386	.897				
38	70.0	-.029	.886	5.105	-.370				
39	80.0	.131	.806	4.854	-1.650				
40	90.0	.261	.741	2.122	-1.136				

OVERALL COEFFICIENTS		STEADY!	** SECTION 2 ** RE ! IM
Cz	UPPER	.511	1.173 ! -.474
Cz	LOWER	-.172	.923 ! -.165
Cz	TOTAL	.338	2.095 ! -.639
Cm	UPPER	.041	.362 ! -.106
Cm	LOWER	-.019	.456 ! -.110
Cm	TOTAL	.023	.818 ! -.216

*** LANN *** RUN 92 *** TABLE 9.20 (cont'd)

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)		
UP	LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.834	.431			**			
2		.5	.259	.742			**			
3		1.5	-.341	1.047	-4.211	1.023	**			
4		3.0	-.593	1.190	-5.512	.832	**			
5		5.0	-.723	1.270	-5.243	.846	**			
6		7.5	-.869	1.369			**			
7		10.0	-.886	1.380	-3.101	.735	**	-3.273	.645	307
8		15.0	-.910	1.398	-4.031	.952	**			
9		20.0	-.907	1.396	-3.856	1.174	**	-3.452	.676	309
10		25.0	-.906	1.395	-3.764	1.014	**			
		30.0					**			
12		35.0	-.898	1.389	-5.283	1.842	**			
13		40.0	-.901	1.392	-4.150	1.629	**	-4.332	1.085	313
14		45.0	-.911	1.399	-4.345	1.954	**			
15		50.0	-.927	1.410	-4.266	2.731	**	-4.549	1.374	315
16		55.0	-.866	1.366	-5.860	-5.756	**			
17		60.0	-.441	1.102	-4.571	-1.614	**	-4.189	-1.754	317
18		65.0	-.341	1.047	-10.68	3.537	**			
19		70.0	-.252	1.000	-10.79	5.333	**	-9.745	2.946	319
20		75.0	-.159	.952	-7.800	4.726	**			
21		80.0	-.070	.906	-3.522	1.849	**	-2.538	.590	321
22		85.0	.001	.870			**			
23		90.0	.057	.842	-1.152	.790	**	-.304	-.241	323
24		95.0	.127	.808			**			
	25	.5	.683	.521			**			
	26	1.5	.355	.694	4.898	.761	**			
	27	3.0	.247	.748	5.918	1.562	**			
		5.0					**			
	29	7.5	.046	.848			**			
	30	10.0	-.029	.885	2.854	-.231	**			
		15.0					**			
	32	20.0	-.280	1.015	2.832	-.078	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.779	1.307	3.255	-.080	**			
	37	60.0	-.174	.959	.955	1.571	**			
	38	70.0	.005	.869	3.205	.675	**			
	39	80.0	.146	.798	4.958	-.190	**			
	40	90.0	.266	.739	3.213	-.500	**			

OVERALL COEFFICIENTS		** SECTION 3 **		
		STEADY	RE	IM
Cz	UPPER	.542	1.466	-.404
Cz	LOWER	-.169	.941	.055
Cz	TOTAL	.373	2.406	-.349
Cm	UPPER	.046	.686	-.239
Cm	LOWER	-.014	.443	.018
Cm	TOTAL	.032	1.129	-.221

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)		
UP	LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.867	.410			**			
2		.5	.322	.710			**			
3		1.5	-.234	.991	-5.733	-.084	**			
4		3.0	-.526	1.151	-4.772	.575	**			
5		5.0	-.700	1.255	-3.610	.637	**	-4.330	.672	405
6		7.5	-.791	1.315			**	-4.552	.889	407
7		10.0					**			
8		15.0	-.830	1.341	-5.985	.182	**			
9		20.0	-.858	1.361	-3.817	.575	**	-3.607	.545	409
10		25.0	-.866	1.367	-4.893	.811	**			
		30.0					**			
12		35.0	-.876	1.374	-4.736	.953	**			
13		40.0	-.886	1.381	-4.911	1.332	**	-4.549	1.085	413
14		45.0	-.899	1.390	-4.236	1.160	**			
15		50.0	-.656	1.228	37.126	-33.40	**	40.569	-29.59	415
16		55.0	-.421	1.091	9.974	-9.152	**			
17		60.0	-.362	1.059	3.388	-3.345	**	2.137	-3.043	417
		65.0					**			
19		70.0	-.277	1.013	-2.024	-2.811	**			
20		75.0	-.221	.984	-4.139	-2.091	**			
21		80.0	-.173	.959	-6.869	-.882	**	-6.425	-.411	421
22		85.0	-.129	.936			**			
23		90.0	-.089	.916	-10.31	2.247	**			
24		95.0	-.048	.895			**			
	25	.5	.611	.561			**			
	26	1.5	.241	.751	5.334	1.072	**			
	27	3.0	.133	.805	4.838	1.052	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.189	.967	4.471	.719	**			
	32	20.0	-.312	1.032	2.761	.119	**			
	33	25.0	-.405	1.082			**			
		30.0					**			
	35	40.0	-.644	1.221	3.088	.250	**			
	36	50.0	-.794	1.317	2.284	1.335	**			
	37	60.0	-.167	.956	-1.277	2.832	**			
	38	70.0	.006	.868	.680	2.867	**			
	39	80.0	.154	.794	1.127	1.618	**			
	40	90.0	.254	.744	-.523	1.284	**			

OVERALL COEFFICIENTS		** SECTION 4 **		
		STEADY	RE	IM
Cz	UPPER	.512	.488	.691
Cz	LOWER	-.188	.589	.382
Cz	TOTAL	.324	1.077	1.073
Cm	UPPER	.055	.250	.425
Cm	LOWER	-.013	-.009	.264
Cm	TOTAL	.043	.241	.688

*** LANN *** RUN 92 *** TABLE 9.20 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.862	.414			**			
2		.5	.403	.670			**			
3		1.5	-.115	.929	-5.472	-.608	**			
4		3.0	-.386	1.072	-3.975	.432	**			
5		5.0	-.529	1.152	-6.896	.221	**	-6.422	.715	505
6		7.5	-.614	1.203			**			
7		10.0	-.684	1.246	-2.620	.257	**			
		15.0					**			
9		20.0	-.735	1.278	-6.801	-.017	**			
10		25.0	-.763	1.296	-4.547	.519	**			
11		30.0	-.792	1.316	-4.577	.378	**			
		35.0					**			
13		40.0	-.826	1.338	-4.714	.498	**			
14		45.0	-.842	1.350	-3.846	.470	**			
15		50.0	-.739	1.281	26.962	-9.292	**			
16		55.0	-.455	1.110	25.126	-8.408	**			
17		60.0	-.338	1.046	7.444	-2.897	**			
18		65.0	-.278	1.014	3.621	-2.904	**			
19		70.0	-.224	.985	.067	-3.160	**	-1.879	-2.380	519
20		75.0	-.174	.959	-1.688	-.927	**			
21		80.0	-.126	.935	-4.870	-2.328	**			
22		85.0	-.081	.912			**			
23		90.0	-.041	.892	-7.793	-1.834	**			
24		95.0	-.002	.872			**			
	25	.5	.533	.602			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.177	.961	6.361	.718	**			
		15.0					**			
	32	20.0	-.359	1.057	3.172	.248	**			
		25.0					**			
	34	30.0	-.514	1.143	2.773	.539	**			
		40.0					**			
	36	50.0	-.783	1.310	-11.59	3.372	**			
		60.0					**			
		70.0					**			
	39	80.0	.142	.800	1.619	2.086	**			
	40	90.0	.256	.743	.448	.836	**			

OVERALL COEFFICIENTS — ** SECTION 5 **

		STEADY	RE	IM
Cz	UPPER	.453	.103	.510
Cz	LOWER	-.243	-.369	.486
Cz	TOTAL	.209	-.266	.996
Cm	UPPER	.050	-.130	.417
Cm	LOWER	-.032	-.456	.313
Cm	TOTAL	.018	-.586	.730

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.847	.423			**			
		.5					**			
3		1.5	.065	.838			**			
		3.0					**			
5		5.0	-.399	1.079	-6.278	-.609	**			
		7.5					**			
7		10.0	-.593	1.190	-3.016	-.757	**			
8		15.0	-.615	1.203	-11.10	-1.547	**			
9		20.0	-.673	1.239	-4.737	-.599	**			
10		25.0	-.732	1.276	-3.691	-.522	**			
11		30.0	-.770	1.301			**			
12		35.0	-.831	1.342	-4.295	-.115	**			
13		40.0	-.861	1.363	-4.214	-.048	**			
14		45.0	-.888	1.382	-4.607	.180	**			
15		50.0	-.547	1.162	17.319	-6.534	**			
16		55.0	-.329	1.041	3.065	-2.921	**			
17		60.0	-.230	.988	-.852	-2.466	**			
18		65.0	-.174	.960	-.479	-.774	**			
19		70.0	-.160	.952	1.098	.699	**			
20		75.0	-.147	.945	1.341	.684	**			
21		80.0	-.108	.926	1.241	.833	**			
22		85.0	-.017	.879			**			
23		90.0	.065	.838	-.607	-.377	**			
24		95.0	.128	.807			**			
	25	.5	.353	.695			**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.373	1.065	2.867	.335	**			
		20.0					**			
	33	25.0	-.523	1.149			**			
	34	30.0	-.599	1.193	2.391	.707	**			
	35	40.0	-.756	1.292	2.241	.248	**			
	36	50.0	-.210	.978	-3.613	-1.921	**			
		60.0					**			
		70.0					**			
	39	80.0	.139	.802	-.617	2.925	**			
	40	90.0	.225	.759	.114	2.662	**			

OVERALL COEFFICIENTS — ** SECTION 6 **

		STEADY	RE	IM
Cz	UPPER	.383	.403	.244
Cz	LOWER	-.169	.002	.193
Cz	TOTAL	.215	.406	.437
Cm	UPPER	.034	-.237	.075
Cm	LOWER	.002	-.179	.216
Cm	TOTAL	.036	-.416	.291

```
***   L.ANN   *** RUN 260 ***          TABLE 9.21
```

TEST CONDITIONS				NORM. COEFF.		MOM. COEFF.	
				Cz	Czi RE IM	Cм	Cмi RE IM
RUNNR. = 260			SECT.1 .263 1.355			.015 .023	
			SECT.2 .295 1.447			.021 .002	
ALFA = .61 (DEG)			SECT.3 .332 1.531			.030 -.004	
MACH = .620			SECT.4 .334 1.642			.043 -.019	
RE*10**-6= 4.85			SECT.5 .307 1.571			.055 -.014	
Q =31.10 (KPA)			SECT.6 .264 1.153			.057 -.120	
P-SETTL. =149.6 (KPA)							
T-SETTL. =15.00			WING .287 1.413			.042 .134	
						(WING : CM ABOUT	
						AERODYN. CENTER)	
DALFA = .248 (DEG)							
FREQ. = 0.00 (Hz)				QUASI STEADY			
HARM. = 1							

	NR.		XCHORD	PRESSURE DISTRIBUTION (TUBES)			**	CALIBRATION (TRANSD.)			
UP	LOW			Cp STEADY	M-LOC.	Cp RE	IM **	Cp RE	Cp IM	NR.	
1			0.0	.592	.403	-5.082	0.000 **				
2			.5	-.233	.697	-11.12	0.000 **				
3			1.5	-.931	.921	-13.78	0.000 **				
4			3.0	-1.036	.955	-12.86	0.000 **				
5			5.0	-1.020	.950	-9.865	0.000 **	0.000	0.000	105	
6			7.5	-.841	.892	-7.336	0.000 **				
7			10.0	-.686	.842	-5.548	0.000 **				
8			15.0	-.567	.804	-3.970	0.000 **				
9			20.0	-.495	.781	-3.377	0.000 **				
10			25.0	-.456	.768	-2.696	0.000 **				
11			30.0	-.420	.757	-2.496	0.000 **				
12			35.0	-.395	.749	-2.030	0.000 **				
13			40.0	-.376	.743	-1.826	0.000 **				
14			45.0	-.361	.738	-1.741	0.000 **				
15			50.0	-.340	.731	-1.237	0.000 **				
16			55.0	-.311	.722	-1.119	0.000 **				
17			60.0	-.284	.713	-1.054	0.000 **				
18			65.0	-.246	.701	-.762	0.000 **				
19			70.0	-.200	.686	-.829	0.000 **	0.000	0.000	119	
20			75.0	-.162	.674	-.601	0.000 **				
21			80.0	-.117	.659	-.255	0.000 **				
22			85.0	-.051	.637	-.259	0.000 **				
23			90.0	-.001	.621	-.221	0.000 **				
24			95.0	.067	.598	-.069	0.000 **				
	25		.5	.707	.351	3.706	0.000 **				
	26		1.5	.386	.484	5.522	0.000 **				
	27		3.0	.305	.515	4.573	0.000 **				
	28		5.0	.213	.547	4.331	0.000 **				
	29		7.5	.076	.595	4.001	0.000 **				
		31	10.0				**				
		31	15.0	-.084	.648	3.556	0.000 **				
	32		20.0	-.193	.684	3.203	0.000 **				
	33		25.0	-.256	.704	3.013	0.000 **				
	34		30.0	-.325	.727	2.797	0.000 **				
	35		40.0	-.345	.733	2.270	0.000 **				
	36		50.0	-.321	.725	1.724	0.000 **				
	37		60.0	-.197	.685	1.245	0.000 **				
	38		70.0	-.003	.621	.879	0.000 **				
	39		80.0	.152	.569	.609	0.000 **				
	40		90.0	.252	.534	.480	0.000 **				

OVERALL COEFFICIENTS			STEADY	** SECTION 1 ** RE	IM
Cz	UPPER		.336	.743	0.000
Cz	LOWER		-.073	.613	0.000
Cz	TOTAL		.263	1.355	0.000
Cм	UPPER		.016	.050	0.000
Cм	LOWER		-.001	.073	0.000
Cм	TOTAL		.015	.023	0.000

	NR.		XCHORD	PRESSURE DISTRIBUTION (TUBES)			**	CALIBRATION (TRANSD.)			
UP	LOW			Cp STEADY	M-LOC.	Cp RE	IM **	Cp RE	Cp IM	NR.	
1			0.0	.626	.388	-5.545	0.000 **				
2			.5	-.211	.690	-12.08	0.000 **				
3			1.5	-.937	.923	-15.74	0.000 **				
4			3.0	-1.073	.968	-14.17	0.000 **				
5			5.0	-1.105	.978	-11.84	0.000 **				
6			7.5	-.876	.903	-8.374	0.000 **				
7			10.0	-.732	.857	-6.189	0.000 **				
8			15.0	-.601	.815	-4.418	0.000 **				
			20.0				**				
10			25.0	-.489	.779	-2.952	0.000 **				
11			30.0	-.461	.770	-2.703	0.000 **				
12			35.0	-.417	.756	-2.211	0.000 **				
13			40.0	-.393	.748	-2.081	0.000 **				
			45.0				**				
15			50.0	-.361	.738	-1.360	0.000 **				
16			55.0	-.325	.726	-1.224	0.000 **				
17			60.0	-.296	.717	-1.151	0.000 **				
18			65.0	-.269	.708	-.843	0.000 **				
19			70.0	-.217	.692	-.876	0.000 **				
20			75.0	-.169	.676	-.615	0.000 **				
21			80.0	-.127	.663	-.300	0.000 **				
22			85.0	-.069	.643	-.329	0.000 **				
23			90.0	-.007	.623	-.297	0.000 **				
24			95.0	.066	.598	-.200	0.000 **				
	25		.5	.721	.344	3.776	0.000 **				
	26		1.5	.404	.478	5.725	0.000 **				
			3.0				**				
	28		5.0	.181	.559	4.553	0.000 **				
	29		7.5	.089	.591	4.213	0.000 **				
	30		10.0	.041	.607	3.894	0.000 **				
	31		15.0	-.086	.649	3.652	0.000 **				
	32		20.0	-.191	.683	3.305	0.000 **				
	33		25.0	-.251	.703	3.097	0.000 **				
	34		30.0	-.308	.721	2.834	0.000 **				
	35		40.0	-.342	.732	2.348	0.000 **				
	36		50.0	-.313	.723	1.715	0.000 **				
	37		60.0	-.177	.679	1.200	0.000 **				
	38		70.0	.015	.615	.770	0.000 **				
	39		80.0	.168	.563	.556	0.000 **				
	40		90.0	.262	.530	.371	0.000 **				

OVERALL COEFFICIENTS			STEADY	** SECTION 2 ** RE	IM
Cz	UPPER		.358	.829	0.000
Cz	LOWER		-.063	.618	0.000
Cz	TOTAL		.295	1.447	0.000
Cм	UPPER		.018	-.057	0.000
Cм	LOWER		.002	.059	0.000
Cм	TOTAL		.021	.002	0.000

*** LANN *** RUN 260 *** TABLE 9.21 (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.661	.372	-5.492	0.000	**			
2		.5	-.213	.690	-12.48	0.000	**			
3		1.5	-.951	.927	-16.54	0.000	**			
4		3.0	-1.029	.953	-14.63	0.000	**			
5		5.0	-1.025	.952	-11.67	0.000	**			
6		7.5	-.878	.904	-8.584	0.000	**			
7		10.0	-.741	.859	-6.609	0.000	**	0.000	0.000	307
8		15.0	-.626	.823	-4.818	0.000	**			
9		20.0	-.550	.798	-4.066	0.000	**	0.000	0.000	309
10		25.0	-.498	.782	-3.166	0.000	**			
		30.0					**			
12		35.0	-.434	.761	-2.363	0.000	**			
13		40.0	-.414	.755	-2.047	0.000	**	0.000	0.000	313
14		45.0	-.396	.749	-2.009	0.000	**			
15		50.0	-.373	.742	-1.414	0.000	**	0.000	0.000	315
16		55.0	-.340	.731	-1.238	0.000	**			
17		60.0	-.314	.723	-1.181	0.000	**	0.000	0.000	317
18		65.0	-.281	.712	-.843	0.000	**			
19		70:0	-.239	.699	-.852	0.000	**	0.000	0.000	319
20		75.0	-.194	.684	-.638	0.000	**			
21		80.0	-.144	.668	-.292	0.000	**	0.000	0.000	321
22		85.0	-.089	.650	-.249	0.000	**			
23		90.0	-.020	.627	-.214	0.000	**	0.000	0.000	323
24		95.0	.058	.601	-.086	0.000	**			
	25	.5	.733	.339	4.146	0.000	**			
	26	1.5	.435	.466	6.935	0.000	**			
	27	3.0	.307	.514	5.439	0.000	**			
		5.0					**			
	29	7.5	.090	.590	4.687	0.000	**			
	30	10.0	.015	.615	4.314	0.000	**			
		15.0					**			
	32	20.0	-.180	.680	3.573	0.000	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.291	.716	1.856	0.000	**			
	37	60.0	-.161	.674	1.299	0.000	**			
	38	70.0	.025	.612	.828	0.000	**			
	39	80.0	.182	.558	.589	0.000	**			
	40	90.0	.276	.525	.448	0.000	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 3 ** RE	IM
Cz	UPPER	.369	.861	0.000
Cz	LOWER	-.036	.669	0.000
Cz	TOTAL	.332	1.531	0.000
Cm	UPPER	.023	-.066	0.000
Cm	LOWER	.007	.062	0.000
Cm	TOTAL	.030	-.004	0.000

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.736	.337	-4.472	0.000	**			
2		.5	-.107	.656	-13.07	0.000	**			
3		1.5	-.736	.858	-16.20	0.000	**			
4		3.0	-.903	.912	-14.95	0.000	**			
5		5.0	-.944	.925	-12.02	0.000	**	0.000	0.000	405
6		7.5	-.792	.876	-9.198	0.000	**			
7		10.0					**	0.000	0.000	407
8		15.0	-.620	.821	-5.266	0.000	**			
9		20.0	-.554	.800	-4.365	0.000	**	0.000	0.000	409
10		25.0	-.507	.785	-3.426	0.000	**			
		30.0					**			
12		35.0	-.445	.765	-2.551	0.000	**			
13		40.0	-.429	.760	-2.238	0.000	**	0.000	0.000	413
14		45.0	-.412	.754	-2.088	0.000	**			
15		50.0	-.389	.747	-1.513	0.000	**	0.000	0.000	415
16		55.0	-.368	.740	-1.362	0.000	**			
17		60.0	-.340	.731	-1.278	0.000	**	0.000	0.000	417
18		65.0	-.315	.723	-.936	0.000	**			
19		70.0	-.278	.711	-.918	0.000	**			
20		75.0	-.262	.706	-.581	0.000	**			
21		80.0	-.176	.678	-.278	0.000	**	0.000	0.000	421
22		85.0	-.099	.653	-.262	0.000	**			
23		90.0	-.027	.629	-.248	0.000	**			
24		95.0	.046	.605	-.070	0.000	**			
	25	.5	.676	.366	5.225	0.000	**			
	26	1.5	.338	.503	7.136	0.000	**			
	27	3.0	.209	.549	6.507	0.000	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.099	.653	4.238	0.000	**			
	32	20.0	-.183	.681	3.680	0.000	**			
	33	25.0	-.236	.698	3.488	0.000	**			
		30.0					**			
	35	40.0	-.306	.720	2.538	0.000	**			
	36	50.0	-.281	.712	1.870	0.000	**			
	37	60.0	-.129	.663	1.270	0.000	**			
	38	70.0	.047	.605	.821	0.000	**			
	39	80.0	.207	.550	.599	0.000	**			
	40	90.0	.285	.522	.476	0.000	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 4 ** RE	IM
Cz	UPPER	.375	.919	0.000
Cz	LOWER	-.041	.723	0.000
Cz	TOTAL	.334	1.642	0.000
Cm	UPPER	.032	-.069	0.000
Cm	LOWER	.012	.050	0.000
Cm	TOTAL	.043	-.019	0.000

*** L.ANN *** RUN 260 *** TABLE 9.21 (cont'd)

NR. UP	NR. LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	Cp RE	Cp IM	NR.
1		0.0	.779	.316	-3.163	0.000			
2		.5	.090	.590	-12.17	0.000			
3		1.5	-.489	.779	-14.16	0.000			
4		3.0	-.677	.839	-12.71	0.000			
5		5.0	-.694	.844	-10.69	0.000	0.000	0.000	505
6		7.5	-.710	.849	-9.083	0.000			
7		10.0	-.601	.815	-7.225	0.000			
		15.0							
9		20.0	-.522	.790	-4.548	0.000			
10		25.0	-.491	.780	-3.617	0.000			
11		30.0	-.462	.770	-3.252	0.000			
		35.0							
13		40.0	-.419	.756	-2.261	0.000			
14		45.0	-.407	.753	-2.188	0.000			
15		50.0	-.391	.748	-1.534	0.000			
16		55.0	-.372	.742	-1.403	0.000			
17		60.0	-.353	.736	-1.313	0.000			
18		65.0	-.339	.731	-.996	0.000			
19		70.0	-.313	.723	-1.010	0.000	0.000	0.000	519
20		75.0	-.293	.716	-.703	0.000			
21		80.0	-.237	.698	-.244	0.000			
22		85.0	-.134	.665	-.298	0.000			
23		90.0	-.052	.638	-.229	0.000			
24		95.0	.042	.606	-.113	0.000			
	25	.5	.604	.397	7.239	0.000			
		1.5							
		3.0							
		5.0							
		7.5							
	30	10.0	-.208	.689	4.030	0.000			
		15.0							
	32	20.0	-.198	.686	3.731	0.000			
		25.0							
	34	30.0	-.271	.709	2.794	0.000			
		40.0							
	36	50.0	-.299	.718	1.621	0.000			
		60.0							
		70.0							
	39	80.0	.214	.547	.407	0.000			
	40	90.0	.290	.520	.271	0.000			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.359	.908	0.000
Cz	LOWER	-.052	.663	0.000
Cz	TOTAL	.307	1.571	0.000
Cm	UPPER	.042	-.046	0.000
Cm	LOWER	.013	.033	0.000
Cm	TOTAL	.055	-.014	0.000

** SECTION 5 **

NR. UP	NR. LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	Cp RE	Cp IM	NR.
1		0.0	.787	.311	-2.067	0.000			
		.5							
3		1.5	-.182	.680	-11.00	0.000			
		3.0							
5		5.0	-.487	.778	-8.655	0.000			
		7.5							
7		10.0	-.499	.782	-6.129	0.000			
8		15.0	-.472	.773	-4.236	0.000			
9		20.0	-.536	.794	1.191	0.000			
10		25.0	-.435	.762	-2.698	0.000			
11		30.0	-.407	.753	-2.281	0.000			
12		35.0	-.388	.747	-1.795	0.000			
13		40.0	-.362	.738	-1.513	0.000			
14		45.0	-.351	.735	-1.493	0.000			
15		50.0	-.341	.732	-.980	0.000			
16		55.0	-.330	.728	-.886	0.000			
17		60.0	-.317	.724	-.865	0.000			
18		65.0	-.316	.724	-.640	0.000			
19		70.0	-.307	.721	-.726	0.000			
20		75.0	-.289	.715	-.551	0.000			
21		80.0	-.247	.701	-.172	0.000			
22		85.0	-.138	.666	-.220	0.000			
23		90.0	-.027	.630	-.312	0.000			
24		95.0	.060	.600	-.252	0.000			
	25	.5	.408	.476	9.522	0.000			
		1.5							
		3.0							
		5.0							
		7.5							
		10.0							
	31	15.0	-.196	.685	3.593	).000			
		20.0							
	33	25.0	-.253	.703	2.401	0.000			
	34	30.0	-.268	.708	2.007	0.000			
	35	40.0	-.292	.716	1.369	0.000			
	36	50.0	-.261	.706	.758	0.000			
		60.0							
		70.0							
	39	80.0	.218	.546	-.126	0.000			
	40	90.0	.282	.523	-.078	0.000			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.305	.600	0.000
Cz	LOWER	-.040	.552	0.000
Cz	TOTAL	.264	1.153	0.000
Cm	UPPER	.043	-.032	0.000
Cm	LOWER	.014	-.088	0.000
Cm	TOTAL	.057	-.120	0.000

** SECTION 6 **

```
***  LANN  *** RUN 272 ***           TABLE 9.22
```

```
-----------------------------------------------------------------
!                        ! !  !        NORM. COEFF.  !  MOM. COEFF.   !
! TEST CONDITIONS        ! !  !        !                !                !
!                        ! !  !        ! Cz      Czi  ! Cm      Cmi    !
!                        ! !  !        !    RE    IM  !    RE    IM    !
!                        ! !  !-----------------------------------------
!                        ! !  !                                        !
!                        ! !  !                                        !
-----------------------------------------------------------------
!                        ! !  !                                        !
! RUNNR.   = 272         ! !  !SECT.1 .448  1.586  ! .013  .226       !
!                        ! !  !SECT.2 .488  1.514  ! .013 -.041       !
! ALFA     = 2.60  (DEG) ! !  !SECT.3 .558  1.950  ! .020 -.066       !
! MACH     = .771        ! !  !SECT.4 .558  1.544  ! .033 -.137       !
! RE*10**-6= 5.24        ! !  !SECT.5 .530  2.042  ! .043 -.129       !
! Q        =41.88  (KPA) ! !  !SECT.6 .414  1.312  ! .044 -.200       !
! P-SETTL. =149.1  (KPA) ! !  !                                       !
! T-SETTL. =27.00        ! !  ! WING  .482  1.614  ! .045  .232       !
!                        ! !  !                    !(WING  CM ABOUT   !
!                        ! !  !                    ! AERODYN. CENTER) !
! DALFA    = .251  (DEG) ! !  !                                       !
! FREQ.    = 0.00  ( Hz) ! !  !         QUASI STEADY                  !
! HARM.    = 1           ! !  !                                       !
-----------------------------------------------------------------
```

Section 1:

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.599	.500	-3.396	0.000	**			
2		.5	-.178	.848	-5.844	0.000	**			
3		1.5	-.916	1.190	-8.896	0.000	**			
4		3.0	-1.266	1.388	14.862	0.000	**	-		
5		5.0	-1.311	1.417	-1.410	0.000	**	0.000	0.000	105
6		7.5	-1.367	1.454	-1.219	0.000	**			
7		10.0	-1.375	1.459	-6.452	0.000	**			
8		15.0	-1.306	1.414	-6.285	0.000	**			
9		20.0	-.750	1.107	-15.21	0.000	**			
10		25.0	-.621	1.045	-3.881	0.000	**			
11		30.0	-.569	1.021	-2.454	0.000	**			
12		35.0	-.530	1.003	-1.402	0.000	**			
13		40.0	-.500	.990	-.967	0.000	**			
14		45.0	-.471	.977	-.550	0.000	**			
15		50.0	-.437	.961	-.653	0.000	**			
16		55.0	-.394	.942	-.103	0.000	**			
17		60.0	-.351	.923	-.240	0.000	**			
18		65.0	-.297	.899	-.282	0.000	**			
19		70.0	-.237	.873	-.192	0.000	**	0.000	0.000	119
20		75.0	-.182	.849	-.122	0.000	**			
21		80.0	-.123	.824	-.032	0.000	**			
22		85.0	-.047	.791	.062	0.000	**			
23		90.0	.012	.766	-.053	0.000	**			
24		95.0	.086	.734	.022	0.000	**			
	25	.5	.791	.397	2.101	0.000	**			
	26	1.5	.518	.540	3.907	0.000	**			
	27	3.0	.430	.581	3.457	0.000	**			
	28	5.0	.338	.623	3.005	0.000	**			
	29	7.5	.191	.688	3.469	0.000	**			
		10.0					**			
	31	15.0	.006	.768	3.105	0.000	**			
	32	20.0	-.122	.824	3.184	0.000	**			
	33	25.0	-.209	.861	.296	0.000	**			
	34	30.0	-.302	.902	8.143	0.000	**			
	35	40.0	-.318	.909	2.630	0.000	**			
	36	50.0	-.345	.921	6.886	0.000	**			
	37	60.0	-.195	.855	7.894	0.000	**			
	38	70.0	.022	.761	4.396	0.000	**			
	39	80.0	.184	.691	-1.802	0.000	**			
	40	90.0	.286	.646	-1.781	0.000	**			

OVERALL COEFFICIENTS — ** SECTION 1 **

COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.485	.581	0.000
Cz	LOWER	-.037	1.005	0.000
Cz	TOTAL	.448	1.586	0.000
Cm	UPPER	.012	-.029	0.000
Cm	LOWER	.001	.255	0.000
Cm	TOTAL	.013	.226	0.000

Section 2:

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.628	.485	-3.480	0.000	**			
2		.5	-.139	.831	-5.956	0.000	**			
3		1.5	-.962	1.214	-7.286	0.000	**			
4		3.0	-1.208	1.352	-5.971	0.000	**			
5		5.0	-1.314	1.419	-6.297	0.000	**			
6		7.5	-1.425	1.494	-6.027	0.000	**			
7		10.0	-1.428	1.496	-6.412	0.000	**			
8		15.0	-1.371	1.457	-7.374	0.000	**			
9		20.0	-1.336	1.433	-5.165	0.000	**			
10		25.0	-.774	1.118	-17.93	0.000	**			
11		30.0	-.590	1.031	-11.89	0.000	**			
12		35.0	-.481	.981	-2.047	0.000	**			
13		40.0	-.451	.968	1.298	0.000	**			
14		45.0	-.431	.959	1.303	0.000	**			
15		50.0	-.419	.953	1.045	0.000	**			
16		55.0	-.376	.934	.916	0.000	**			
17		60.0	-.336	.917	.402	0.000	**			
18		65.0	-.298	.900	.507	0.000	**			
19		70.0	-.236	.873	.253	0.000	**			
20		75.0	-.174	.846	.252	0.000	**			
21		80.0	-.123	.824	.178	0.000	**			
22		85.0	-.057	.795	.003	0.000	**			
23		90.0	.011	.766	-.032	0.000	**			
24		95.0	.087	.733	.040	0.000	**			
	25	.5	.798	.393	2.093	0.000	**			
	26	1.5	.528	.535	3.804	0.000	**			
	27	3.0	.417	.587	3.706	0.000	**			
	28	5.0	.291	.644	3.395	0.000	**			
	29	7.5	.199	.685	3.527	0.000	**			
	30	10.0	.142	.710	3.442	0.000	**			
	31	15.0	-.002	.772	3.335	0.000	**			
	32	20.0	-.126	.825	3.513	0.000	**			
	33	25.0	-.211	.862	3.369	0.000	**			
	34	30.0	-.290	.896	3.436	0.000	**			
	35	40.0	-.351	.923	2.878	0.000	**			
	36	50.0	-.330	.914	2.377	0.000	**			
	37	60.0	-.167	.843	1.354	0.000	**			
	38	70.0	.044	.752	.920	0.000	**			
	39	80.0	.202	.683	.629	0.000	**			
	40	90.0	.298	.641	.566	0.000	**			

OVERALL COEFFICIENTS — ** SECTION 2 **

COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.519	.861	0.000
Cz	LOWER	-.031	.654	0.000
Cz	TOTAL	.488	1.514	0.000
Cm	UPPER	.008	-.152	0.000
Cm	LOWER	.005	.111	0.000
Cm	TOTAL	.013	-.041	0.000

*** LANN *** RUN 272 ***   TABLE 9.22 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	Cal Cp RE	Cal Cp IM	NR.
1		0.0	.651	.474	-3.502	0.000			
2		.5	-.166	.843	-6.235	0.000			
3		1.5	-.917-	1.191	-7.599	0.000			
4		3.0	-1.215-	1.357	-6.631	0.000			
5		5.0	-1.313	1.418	-6.903	0.000			
6		7.5	-1.404	1.479	-6.186	0.000			
7		10.0	-1.389	1.469	-6.244	0.000	0.000	0.000	307
8		15.0	-1.383	1.465	-6.510	0.000			
9		20.0	-1.340	1.436	-7.339	0.000	0.000	0.000	309
10		25.0	-1.242	1.373	-26.06	0.000			
		30.0							
12		35.0	-.536	1.006	-13.04	0.000			
13		40.0	-.438	.962	-3.992	0.000	0.000	0.000	313
14		45.0	-.408	.949	1.719	0.000			
15		50.0	-.394	.942	2.626	0.000	0.000	0.000	315
16		55.0	-.363	.928	2.040	0.000			
17		60.0	-.333	.915	1.391	0.000	0.000	0.000	317
18		65.0	-.293	.898	1.176	0.000			
19		70.0	-.245	.877	.860	0.000	0.000	0.000	319
20		75.0	-.188	.852	.690	0.000			
21		80.0	-.128	.826	.500	0.000	0.000	0.000	321
22		85.0	-.069	.801	.228	0.000			
23		90.0	.001	.778	.124	0.000	0.000	0.000	323
24		95.0	.081	.736	.021	0.000			
	25	.5	.806	.388	2.054	0.000			
	26	1.5	.548	.525	3.957	0.000			
	27	3.0	.422	.584	4.335	0.000			
		5.0							
	29	7.5	.199	.685	3.743	0.000			
	30	10.0	.115	.721	3.701	0.000			
		15.0							
	32	20.0	-.117	.821	3.620	0.000			
		25.0							
		30.0							
		40.0							
	36	50.0	-.301	.901	2.301	0.000			
	37	60.0	-.146	.834	1.316	0.000			
	38	70.0	.056	.747	.855	0.000			
	39	80.0	.215	.678	.610	0.000			
	40	90.0	.310	.636	.490	0.000			

OVERALL COEFFICIENTS — ** SECTION 3 **

		STEADY	RE	IM
Cz	UPPER	.557	1.294	0.000
Cz	LOWER	.001	.656	0.000
Cz	TOTAL	.558	1.950	0.000
Cm	UPPER	.010	-.160	0.000
Cm	LOWER	.010	.095	0.000
Cm	TOTAL	.020	-.066	0.000

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	Cal Cp RE	Cal Cp IM	NR.
1		0.0	.713	.440	-3.206	0.000			
2		.5	-.126	.825	-6.865	0.000			
3		1.5	-.900	1.182	-9.788	0.000			
4		3.0	-1.110	1.295	-6.982	0.000			
5		5.0	-1.277	1.395	-7.352	0.000	0.000	0.000	405
6		7.5	-1.328	1.428	-6.645	0.000			
7		10.0				0.000	0.000	0.000	407
8		15.0	-1.312	1.417	-7.052	0.000			
9		20.0	-1.302	1.411	-7.135	0.000	0.000	0.000	409
10		25.0	-1.269	1.390	-8.001	0.000			
		30.0							
12		35.0	-.541	1.009	-14.07	0.000			
13		40.0	-.445	.965	-4.691	0.000	0.000	0.000	413
14		45.0	-.420	.954	1.929	0.000			
15		50.0	-.407	.948	3.389	0.000	0.000	0.000	415
16		55.0	-.392	.941	2.914	0.000			
17		60.0	-.363	.928	2.082	0.000	0.000	0.000	417
18		65.0				0.000			
19		70.0	-.286	.895	1.314	0.000			
20		75.0	-.255	.881	1.016	0.000			
21		80.0	-.163	.841	.745	0.000	0.000	0.000	421
22		85.0	-.078	.805	.322	0.000			
23		90.0	-.004	.773	.102	0.000			
24		95.0	.071	.740	-.051	0.000			
	25	.5	.772	.408	2.580	0.000			
	26	1.5	.483	.556	4.509	0.000			
	27	3.0	.350	.617	4.646	.0.000			
		5.0							
		7.5							
		10.0							
	31	15.0	-.014	.777	3.696	0.000			
	32	20.0	-.117	.821	3.754	0.000			
	33	25.0	-.192	.854	3.462	0.000			
		30.0							
	35	40.0	-.306	.903	2.867	0.000			
	36	50.0	-.288	.896	2.289	0.000			
	37	60.0	-.111	.819	1.256	0.000			
	38	70.0	.077	.738	.808	0.000			
	39	80.0	.243	.665	.594	0.000			
	40	90.0	.322	.630	.546	0.000			

OVERALL COEFFICIENTS — ** SECTION 4 **

		STEADY	RE	IM
Cz	UPPER	.561	.864	0.000
Cz	LOWER	-.003	.680	0.000
Cz	TOTAL	.558	1.544	0.000
Cm	UPPER	.018	-.225	0.000
Cm	LOWER	.014	.088	0.000
Cm	TOTAL	.033	-.137	0.000

*** LANN *** RUN 272 *** TABLE 9.22 (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.732	.430	-3.389	0.000	**			
2		.5	-.046	.791	-7.726	0.000	**			
3		1.5	-.655	1.061	-8.672	0.000	**			
4		3.0	-1.009	1.239	-8.803	0.000	**			
5		5.0	-1.116	1.299	-9.427	0.000	**	0.000	0.000	505
6		7.5	-1.154	1.321	-8.244	0.000	**			
7		10.0	-1.192	1.343	-8.119	0.000	**			
		15.0					**			
9		20.0	-1.176	1.334	-10.23	0.000	**			
10		25.0	-1.142	1.313	-11.60	0.000	**			
11		30.0	-.618	1.044	-36.37	0.000	**			
		35.0					**			
13		40.0	-.457	.971	4.172	0.000	**			
14		45.0	-.460	.972	4.807	0.000	**			
15		50.0	-.450	.967	3.482	0.000	**			
16		55.0	-.428	.957	2.353	0.000	**			
17		60.0	-.400	.945	1.417	0.000	**			
18		65.0	-.375	.934	1.115	0.000	**			
19		70.0	-.339	.918	.875	0.000	**	0.000	0.000	519
20		75.0	-.301	.901	.596	0.000	**			
21		80.0	-.225	.868	.230	0.000	**			
22		85.0	-.114	.820	.047	0.000	**			
23		90.0	-.026	.782	-.161	0.000	**			
24		95.0	.067	.742	.017	0.000	**			
	25	.5	.737	.428	3.423	0.000	**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	.045	.752	4.398	0.000	**			
		15.0					**			
	32	20.0	-.129	.826	3.775	0.000	**			
		25.0					**			
	34	30.0	-.239	.874	3.401	0.000	**			
		40.0					**			
	36	50.0	-.305	.903	2.076	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.244	.665	.467	0.000	**			
	40	90.0	.321	.631	.430	0.000	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 5 ** RE	IM
Cz	UPPER	.531	1.361	0.000
Cz	LOWER	-.001	.680	0.000
Cz	TOTAL	.530	2.042	0.000
Cm	UPPER	.031	-.218	0.000
Cm	LOWER	.012	.089	0.000
Cm	TOTAL	.043	-.129	0.000

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.735	.429	-3.674	0.000	**			
		.5					**			
3		1.5	-.438	.962	-9.291	0.000	**			
		3.0					**			
5		5.0	-.919	1.191	-8.994	0.000	**			
		7.5					**			
7		10.0	-.994	1.231	-10.22	0.000	**			
8		15.0	-1.018	1.244	-5.241	0.000	**			
9		20.0	-1.024	1.247	-25.34	0.000	**			
10		25.0	-.492	.986	-7.838	0.000	**			
11		30.0	-.479	.980	6.633	0.000	**			
12		35.0	-.464	.974	3.468	0.000	**			
13		40.0	-.436	.961	1.491	0.000	**			
14		45.0	-.417	.952	.546	0.000	**			
15		50.0	-.399	.945	.213	0.000	**			
16		55.0	-.381	.937	.218	0.000	**			
17		60.0	-.361	.928	-.178	0.000	**			
18		65.0	-.355	.925	-.197	0.000	**			
19		70.0	-.340	.918	-.278	0.000	**			
20		75.0	-.305	.903	-.353	0.000	**			
21		80.0	-.237	.873	-.462	0.000	**			
22		85.0	-.116	.821	-.853	0.000	**			
23		90.0	-.007	.774	-.804	0.000	**			
24		95.0	.077	.738	-.613	0.000	**			
	25	.5	.639	.480	5.018	0.000	**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.133	.828	3.679	0.000	**			
		20.0					**			
	33	25.0	-.244	.876	2.617	0.000	**			
	34	30.0	-.272	.889	2.419	0.000	**			
	35	40.0	-.317	.908	1.500	0.000	**			
	36	50.0	-.282	.893	.939	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.229	.672	-.130	0.000	**			
	40	90.0	.294	.643	-.156	0.000	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 6 ** RE	IM
Cz	UPPER	.432	.838	0.000
Cz	LOWER	-.018	.475	0.000
Cz	TOTAL	.414	1.312	0.000
Cm	UPPER	.034	-.161	0.000
Cm	LOWER	.010	-.039	0.000
Cm	TOTAL	.044	-.200	0.000

*** LANN *** RUN 264 ***   TABLE 9.23

TEST CONDITIONS		NORM. COEFF.			MOM. COEFF.	
			Cz	Czi RE IM	Cm	Cmi RE IM

RUNNR. = 264	SECT.1 .301 1.551	.014 .105
	SECT.2 .332 1.962	.015 .027
ALFA = .59 (DEG)	SECT.3 .379 2.235	.023 .057
MACH = .820	SECT.4 .378 2.428	.037 .022
RE*10**-6= 5.45	SECT.5 .338 1.844	.047 -.153
Q =45.25 (KPA)	SECT.6 .264 1.409	.050 -.258
P-SETTL. =149.5 (KPA)		
T-SETTL. =26.00	WING .323 1.838	.037 .315
		(WING : CM ABOUT
		AERODYN. CENTER)
DALFA = .246 (DEG)		
FREQ. = 0.00 (Hz)		QUASI STEADY
HARM. = 1		

SECTION 1

Pressure distribution table 1:

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	CAL RE	CAL IM	NR.
1		0.0	.741	.455	-2.135	0.000			
2		.5	.123	.762	-4.674	0.000			
3		1.5	-.505	1.063	-5.514	0.000			
4		3.0	-.877	1.266	-7.098	0.000			
5		5.0	-.893	1.276	-7.147	0.000	0.000	0.000	105
6		7.5	-1.050	1.375	-1.423	0.000			
7		10.0	-1.066	1.386	-3.681	0.000			
8		15.0	-.991	1.337	-12.70	0.000			
9		20.0	-.617	1.121	-6.832	0.000			
10		25.0	-.595	1.109	-1.660	0.000			
11		30.0	-.580	1.102	-2.528	0.000			
12		35.0	-.576	1.100	-.285	0.000			
13		40.0	-.577	1.100	-2.988	0.000			
14		45.0	-.580	1.101	-13.82	0.000			
15		50.0	-.433	1.026	-.245	0.000			
16		55.0	-.389	1.005	.188	0.000			
17		60.0	-.348	.985	-.210	0.000			
18		65.0	-.290	.956	-.134	0.000			
19		70.0	-.228	.927	-.111	0.000	0.000	0.000	119
20		75.0	-.171	.900	.054	0.000			
21		80.0	-.111	.872	.006	0.000			
22		85.0	-.034	.836	.025	0.000			
23		90.0	.026	.808	.030	0.000			
24		95.0	.100	.774	-.039	0.000			
	25	.5	.706	.476	2.821	0.000			
	26	1.5	.371	.646	4.447	0.000			
	27	3.0	.309	.676	3.665	0.000			
	28	5.0	.221	.717	3.806	0.000			
	29	7.5	.076	.785	3.448	0.000			
		10.0							
	31	15.0	-.099	.866	3.326	0.000			
	32	20.0	-.238	.932	3.284	0.000			
	33	25.0	-.334	.978	3.180	0.000			
	34	30.0	-.453	1.037	3.665	0.000			
	35	40.0	-.505	1.063	4.771	0.000			
	36	50.0	-.496	1.058	2.577	0.000			
	37	60.0	-.250	.937	1.290	0.000			
	38	70.0	-.003	.821	.778	0.000			
	39	80.0	.168	.742	.601	0.000			
	40	90.0	.276	.691	.401	0.000			

OVERALL COEFFICIENTS — SECTION 1

		STEADY	RE	IM
Cz	UPPER	.425	.837	0.000
Cz	LOWER	-.124	.713	0.000
Cz	TOTAL	.301	1.551	0.000
Cm	UPPER	.021	-.011	0.000
Cm	LOWER	-.007	.116	0.000
Cm	TOTAL	.014	.105	0.000

SECTION 2

Pressure distribution table 2:

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM
1		0.0	.774	.437	-2.190	0.000
2		.5	.166	.743	-4.588	0.000
3		1.5	-.493	1.057	-6.943	0.000
4		3.0	-.798	1.220	-6.597	0.000
5		5.0	-.917	1.291	-6.655	0.000
6		7.5	-1.061	1.382	-6.027	0.000
7		10.0	-1.087	1.400	-1.999	0.000
8		15.0	-1.054	1.378	-4.865	0.000
9		20.0	-1.023	1.357	-7.431	0.000
10		25.0	-.951	1.312	-34.69	0.000
11		30.0	-.634	1.130	-8.040	0.000
12		35.0	-.590	1.107	-7.094	0.000
13		40.0	-.478	1.049	-5.036	0.000
14		45.0	-.434	1.027	.540	0.000
15		50.0	-.418	1.019	.869	0.000
16		55.0	-.372	.996	.543	0.000
17		60.0	-.330	.976	.335	0.000
18		65.0	-.286	.955	.476	0.000
19		70.0	-.224	.925	.379	0.000
20		75.0	-.161	.895	.333	0.000
21		80.0	-.108	.870	.255	0.000
22		85.0	-.039	.838	.208	0.000
23		90.0	.030	.806	.077	0.000
24		95.0	.106	.771	-.089	0.000
	25	.5	.703	.477	2.944	0.000
	26	1.5	.371	.646	4.576	0.000
	27	3.0	.276	.691	4.064	0.000
	28	5.0	.162	.745	3.855	0.000
	29	7.5	.069	.788	3.676	0.000
	30	10.0	.018	.811	3.520	0.000
	31	15.0	-.127	.879	3.600	0.000
	32	20.0	-.266	.945	3.663	0.000
	33	25.0	-.361	.991	3.599	0.000
	34	30.0	-.467	1.044	4.453	0.000
	35	40.0	-.544	1.083	5.067	0.000
	36	50.0	-.453	1.036	2.322	0.000
	37	60.0	-.214	.920	1.209	0.000
	38	70.0	.024	.809	.726	0.000
	39	80.0	.187	.733	.676	0.000
	40	90.0	.286	.686	.522	0.000

OVERALL COEFFICIENTS — SECTION 2

		STEADY	RE	IM
Cz	UPPER	.453	1.203	0.000
Cz	LOWER	-.121	.759	0.000
Cz	TOTAL	.332	1.962	0.000
Cm	UPPER	.017	-.090	0.000
Cm	LOWER	-.002	.117	0.000
Cm	TOTAL	.015	.027	0.000

*** LANN *** RUN 264 *** TABLE 9.23 (cont'd)

NR. UP	LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.797	.423	-2.099	0.000	**			
2		.5	.153	.749	-5.008	0.000	**			
3		1.5	-.496	1.058	-5.945	0.000	**			
4		3.0	-.763	1.200	-7.197	0.000	**			
5		5.0	-.888	1.273	-6.039	0.000	**			
6		7.5	-1.038	1.367	-4.837	0.000	**			
7		10.0	-1.031	1.363	-3.079	0.000	**	0.000	0.000	307
8		15.0	-1.050	1.375	-4.775	0.000	**			
9		20.0	-1.036	1.366	-4.876	0.000	**	0.000	0.000	309
10		25.0	-1.022	1.357	-6.442	0.000	**			
		30.0					**			
12		35.0	-.682	1.155	-46.83	0.000	**			
13		40.0	-.436	1.028	-8.572	0.000	**	0.000	0.000	313
14		45.0	-.391	1.006	.903	0.000	**			
15		50.0	-.375	.998	3.280	0.000	**	0.000	0.000	315
16		55.0	-.346	.984	2.766	0.000	**			
17		60.0	-.319	.971	2.175	0.000	**	0.000	0.000	317
18		65.0	-.280	.952	1.776	0.000	**			
19		70.0	-.231	.928	1.317	0.000	**	0.000	0.000	319
20		75.0	-.173	.901	1.032	0.000	**			
21		80.0	-.113	.873	.629	0.000	**	0.000	0.000	321
22		85.0	-.051	.844	.460	0.000	**			
23		90.0	.019	.811	.269	0.000	**	0.000	0.000	323
24		95.0	.101	.773	.116	0.000	**			
	25	.5	.699	.479	3.249	0.000	**			
	26	1.5	.375	.644	5.074	0.000	**			
	27	3.0	.263	.697	4.844	0.000	**			
		5.0					**			
	29	7.5	.049	.797	4.108	0.000	**			
	30	10.0	-.029	.834	3.890	0.000	**			
		15.0					**			
	32	20.0	-.272	.948	3.999	0.000	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.419	1.020	2.449	0.000	**			
	37	60.0	-.191	.909	1.250	0.000	**			
	38	70.0	.038	.802	.792	0.000	**			
	39	80.0	.200	.727	.758	0.000	**			
	40	90.0	.299	.680	.523	0.000	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
SECTION 3				
Cz	UPPER	.463	1.523	0.000
Cz	LOWER	-.084	.712	0.000
Cz	TOTAL	.379	2.235	0.000
Cm	UPPER	.018	-.036	0.000
Cm	LOWER	.005	.093	0.000
Cm	TOTAL	.023	.057	0.000

NR. UP	LOW	XCHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.837	.398	-1.790	0.000	**			
2		.5	.218	.718	-5.654	0.000	**			
3		1.5	-.390	1.005	-7.450	0.000	**			
4		3.0	-.694	1.162	-6.050	0.000	**			
5		5.0	-.859	1.256	-5.656	0.000	**	0.000	0.000	405
6		7.5	-.951	1.311	-5.817	0.000	**			
7		10.0					**	0.000	0.000	407
8		15.0	-.970	1.324	-5.096	0.000	**			
9		20.0	-.984	1.332	-4.815	0.000	**	0.000	0.000	409
10		25.0	-.982	1.331	-6.464	0.000	**			
		30.0					**			
12		35.0	-.942	1.306	-42.60	0.000	**			
13		40.0	-.475	1.047	-23.21	0.000	**	0.000	0.000	413
14		45.0	-.387	1.004	-1.040	0.000	**			
15		50.0	-.371	.996	4.515	0.000	**	0.000	0.000	415
16		55.0	-.364	.993	5.018	0.000	**			
17		60.0	-.343	.982	3.986	0.000	**	0.000	0.000	417
		65.0					**			
19		70.0	-.274	.949	2.226	0.000	**			
20		75.0	-.244	.934	1.991	0.000	**			
21		80.0	-.149	.890	.944	0.000	**	0.000	0.000	421
22		85.0	-.061	.848	.535	0.000	**			
23		90.0	.016	.813	.176	0.000	**			
24		95.0	.091	.778	.063	0.000	**			
	25	.5	.639	.512	3.926	0.000	**			
	26	1.5	.277	.691	6.008	0.000	**			
	27	3.0	.159	.746	5.201	0.000	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.170	.899	4.308	0.000	**			
	32	20.0	-.282	.953	4.234	0.000	**			
	33	25.0	-.363	.992	4.283	0.000	**			
		30.0					**			
	35	40.0	-.481	1.051	4.813	0.000	**			
	36	50.0	-.401	1.011	2.415	0.000	**			
	37	60.0	-.152	.891	1.206	0.000	**			
	38	70.0	.061	.791	.737	0.000	**			
	39	80.0	.226	.715	.800	0.000	**			
	40	90.0	.310	.675	.652	0.000	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
SECTION 4				
Cz	UPPER	.478	1.588	0.000
Cz	LOWER	-.100	.840	0.000
Cz	TOTAL	.378	2.428	0.000
Cm	UPPER	.028	-.083	0.000
Cm	LOWER	.010	.106	0.000
Cm	TOTAL	.037	.022	0.000

***   LANN   *** RUN 264 ***   TABLE 9.23 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.843	.395	-1.531	0.000	**			
2		.5	.302	.679	-6.489	0.000	**			
3		1.5	-.256	.940	-6.702	0.000	**			
4		3.0	-.537	1.079	-8.581	0.000	**			
5		5.0	-.680	1.155	-10.22	0.000	**	0.000	0.000	505
6		7.5	-.758	1.198	-6.872	0.000	**			
7		10.0	-.815	1.230	-5.006	0.000	**			
		15.0					**			
9		20.0	-.818	1.231	-8.393	0.000	**			
10		25.0	-.836	1.242	-6.068	0.000	**			
11		30.0	-.864	1.259	-8.553	0.000	**			
		35.0					**			
13		40.0	-.470	1.045	-28.77	0.000	**			
14		45.0	-.398	1.009	5.691	0.000	**			
15		50.0	-.407	1.014	8.564	0.000	**			
16		55.0	-.404	1.012	6.291	0.000	**			
17		60.0	-.382	1.001	3.888	0.000	**			
18		65.0	-.360	.990	2.382	0.000	**			
19		70.0	-.325	.974	1.716	0.000	**	0.000	0.000	519
20		75.0	-.287	.955	1.232	0.000	**			
21		80.0	-.209	.918	.483	0.000	**			
22		85.0	-.095	.864	.331	0.000	**			
23		90.0	-.005	.822	.001	0.000	**			
24		95.0	.088	.779	.073	0.000	**			
	25	.5	.570	.548	5.409	0.000	**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	-.141	.886	5.393	0.000	**			
		15.0					**			
	32	20.0	-.306	.964	4.696	0.000	**			
		25.0					**			
	34	30.0	-.413	1.017	4.517	0.000	**			
		40.0					**			
	36	50.0	-.402	1.011	1.896	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.232	.712	.665	0.000	**			
	40	90.0	.316	.672	.501	0.000	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.436	1.018	0.000
Cz	LOWER	-.098	.827	0.000
Cz	TOTAL	.338	1.844	0.000
Cm	UPPER	.039	-.231	0.000
Cm	LOWER	.007	.078	0.000
Cm	TOTAL	.047	-.153	0.000

SECTION 5

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.833	.401	-1.338	0.000	**			
		.5					**			
3		1.5	-.051	.844	-7.874	0.000	**			
		3.0					**			
5		5.0	-.517	1.069	-9.241	0.000	**			
		7.5					**			
7		10.0	-.721	1.177	-3.500	0.000	**			
8		15.0	-.679	1.154	-12.70	0.000	**			
		20.0					**			
10		25.0	-.791	1.216	-8.442	0.000	**			
		30.0					**			
12		35.0	-.410	1.015	-10.93	0.000	**			
13		40.0	-.329	.975	8.560	0.000	**			
14		45.0	-.358	.990	6.236	0.000	**			
15		50.0	-.369	.995	3.087	0.000	**			
16		55.0	-.360	.991	1.360	0.000	**			
17		60.0	-.345	.983	.574	0.000	**			
18		65.0	-.339	.980	.412	0.000	**			
19		70.0	-.323	.973	.148	0.000	**			
20		75.0	-.285	.954	-.121	0.000	**			
21		80.0	-.214	.920	-.437	0.000	**			
22		85.0	-.086	.860	-.624	0.000	**			
23		90.0	.025	.808	-.667	0.000	**			
24		95.0	.109	.769	-.524	0.000	**			
	25	.5	.398	.633	7.722	0.000	**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.307	.965	4.960	0.000	**			
		20.0					**			
	33	25.0	-.403	1.012	3.455	0.000	**			
	34	30.0	-.408	1.014	2.593	0.000	**			
	35	40.0	-.405	1.012	1.569	0.000	**			
	36	50.0	-.318	.970	.648	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.235	.710	.011	0.000	**			
	40	90.0	.300	.680	.098	0.000	**			

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.358	.793	0.000
Cz	LOWER	-.094	.616	0.000
Cz	TOTAL	.264	1.409	0.000
Cm	UPPER	.037	-.189	0.000
Cm	LOWER	.013	-.069	0.000
Cm	TOTAL	.050	-.258	0.000

SECTION 6

```
***   LANN   *** RUN 274 ***            TABLE 9.24
```

TEST CONDITIONS			NORM. COEFF.		MOM. COEFF.	
			Cz	Czi	Cm	Cmi
				RE IM		RE IM
RUNNR. = 274		SECT.1 .483 1.881			.021 .182	
		SECT.2 .535 1.912			.021 .150	
ALFA = 2.59 (DEG)		SECT.3 .599 1.861			.036 .415	
MACH = .820		SECT.4 .578 .699			.048 .222	
RE*10**-6= 5.40		SECT.5 .532 -.330			.044 -.747	
Q =45.47 (KPA)		SECT.6 .421 .688			.042 -.248	
P-SETTL. =150.3 (KPA)						
T-SETTL. =29.00		WING .512 1.341			.050 -.416	
					(WING : CM ABOUT	
					AERODYN. CENTER)	
DALFA = .256 (DEG)						
FREQ. = 0.00 (Hz)				QUASI STEADY	
HARM. = 1						

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)			
UP	LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.	
1		0.0	.664	.498	-2.379	0.000	**				
2		.5	-.037	.837	-4.941	0.000	**				
3		1.5	-.716	1.174	-7.843	0.000	**				
4		3.0	-1.064	1.384	-5.379	0.000	**				
5		5.0	-1.114	1.419	-6.866	0.000	**	0.000	0.000	105	
6		7.5	-1.183	1.468	-6.387	0.000	**				
7		10.0	-1.204	1.484	-4.794	0.000	**				
8		15.0	-1.161	1.452	-4.677	0.000	**				
9		20.0	-1.137	1.435	-5.291	0.000	**				
10		25.0	-.858	1.255	-20.94	0.000	**				
11		30.0	-.726	1.180	-4.879	0.000	**				
12		35.0	-.705	1.168	-4.289	0.000	**				
13		40.0	-.700	1.165	-4.083	0.000	**				
14		45.0	-.720	1.176	-3.691	0.000	**				
15		50.0	-.753	1.194	-4.418	0.000	**				
16		55.0	-.431	1.025	-13.97	0.000	**				
17		60.0	-.327	.975	-.177	0.000	**				
18		65.0	-.273	.948	.756	0.000	**				
19		70.0	-.216	.921	.623	0.000	**	0.000	0.000	119	
20		75.0	-.162	.895	.489	0.000	**				
21		80.0	-.102	.867	.492	0.000	**				
22		85.0	-.028	.833	.320	0.000	**				
23		90.0	.030	.806	.240	0.000	**				
24		95.0	.100	.773	.166	0.000	**				
	25	.5	.789	.427	2.297	0.000	**				
	26	1.5	.504	.581	3.805	0.000	**				
	27	3.0	.426	.620	3.129	0.000	**				
	28	5.0	.337	.662	3.139	0.000	**				
	29	7.5	.188	.733	3.061	0.000	**				
		10.0					**				
	31	15.0	.001	.819	3.026	0.000	**				
	32	20.0	-.133	.882	3.209	0.000	**				
	33	25.0	-.228	.927	3.217	0.000	**				
	34	30.0	-.334	.978	3.755	0.000	**				
	35	40.0	-.374	.997	3.562	0.000	**				
	36	50.0	-.400	1.010	2.835	0.000	**				
	37	60.0	-.210	.918	.946	0.000	**				
	38	70.0	.024	.808	.540	0.000	**				
	39	80.0	.192	.730	.512	0.000	**				
	40	90.0	.295	.682	.596	0.000	**				

OVERALL COEFFICIENTS			** SECTION 1 **		
		STEADY	RE	IM	
Cz	UPPER	.534	1.235	0.000	
Cz	LOWER	-.052	.646	0.000	
Cz	TOTAL	.483	1.881	0.000	
Cm	UPPER	.021	.074	0.000	
Cm	LOWER	-.001	.108	0.000	
Cm	TOTAL	.021	.182	0.000	

NR.		%CHORD	PRESSURE DISTRIBUTION (TUBES)				**	CALIBRATION (TRANSD.)			
UP	LOW		Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.	
1		0.0	.693	.482	-2.432	0.000	**				
2		.5	.004	.818	-4.860	0.000	**				
3		1.5	-.756	1.196	-7.046	0.000	**				
4		3.0	-1.000	1.342	-5.695	0.000	**				
5		5.0	-1.111	1.417	-6.084	0.000	**				
6		7.5	-1.224	1.499	-5.584	0.000	**				
7		10.0	-1.237	1.509	-5.434	0.000	**				
8		15.0	-1.205	1.485	-5.412	0.000	**				
9		20.0	-1.185	1.470	-4.498	0.000	**				
10		25.0	-1.178	1.465	-4.919	0.000	**				
11		30.0	-1.176	1.463	-4.998	0.000	**				
12		35.0	-1.133	1.432	-6.860	0.000	**				
13		40.0	-.952	1.312	-29.92	0.000	**				
14		45.0	-.655	1.141	-6.824	0.000	**				
15		50.0	-.466	1.043	-6.992	0.000	**				
16		55.0	-.351	.986	-3.158	0.000	**				
17		60.0	-.291	.957	.878	0.000	**				
18		65.0	-.246	.935	1.974	0.000	**				
19		70.0	-.192	.910	1.706	0.000	**				
20		75.0	-.136	.883	1.248	0.000	**				
21		80.0	-.087	.860	1.057	0.000	**				
22		85.0	-.026	.832	.683	0.000	**				
23		90.0	.039	.802	.391	0.000	**				
24		95.0	.110	.769	.325	0.000	**				
	25	.5	.790	.427	2.524	0.000	**				
	26	1.5	.506	.580	3.821	0.000	**				
	27	3.0	.401	.632	3.531	0.000	**				
	28	5.0	.279	.690	3.135	0.000	**				
	29	7.5	.187	.733	3.171	0.000	**				
	30	10.0	.130	.759	3.103	0.000	**				
	31	15.0	-.017	.828	3.294	0.000	**				
	32	20.0	-.148	.889	3.638	0.000	**				
	33	25.0	-.242	.933	3.659	0.000	**				
	34	30.0	-.331	.976	4.203	0.000	**				
	35	40.0	-.414	1.017	3.564	0.000	**				
	36	50.0	-.376	.998	2.269	0.000	**				
	37	60.0	-.177	.903	.744	0.000	**				
	38	70.0	.049	.797	.365	0.000	**				
	39	80.0	.211	.722	.453	0.000	**				
	40	90.0	.307	.677	.579	0.000	**				

OVERALL COEFFICIENTS			** SECTION 2 **		
		STEADY	RE	IM	
Cz	UPPER	.584	1.266	0.000	
Cz	LOWER	-.048	.646	0.000	
Cz	TOTAL	.535	1.912	0.000	
Cm	UPPER	.017	.065	0.000	
Cm	LOWER	.004	.085	0.000	
Cm	TOTAL	.021	.150	0.000	

*** LANN *** RUN 274 *** TABLE 9.24 (cont'd)

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.717	.469	-2.451	0.000	**			
2		.5	-.016	.827	-5.234	0.000	**			
3		1.5	-.706	1.168	-7.822	0.000	**			
4		3.0	-.996	1.340	-6.274	0.000	**			
5		5.0	-1.099	1.408	-6.751	0.000	**			
6		7.5	-1.203	1.483	-6.034	0.000	**			
7		10.0	-1.194	1.476	-5.393	0.000	**	0.000	0.000	307
8		15.0	-1.208	1.487	-5.178	0.000	**			
9		20.0	-1.184	1.469	-5.144	0.000	**	0.000	0.000	309
10		25.0	-1.174	1.461	-4.525	0.000	**			
		30.0					**			
12		35.0	-1.166	1.456	-5.469	0.000	**			
13		40.0	-1.160	1.452	-.675	0.000	**	0.000	0.000	313
14		45.0	-.662	1.145	-.290	0.000	**			
15		50.0	-.590	1.106	-4.854	0.000	**	0.000	0.000	315
16		55.0	-.502	1.061	-8.987	0.000	**			
17		60.0	-.405	1.012	-11.03	0.000	**	0.000	0.000	317
18		65.0	-.292	.957	-9.430	0.000	**			
19		70.0	-.194	.911	-5.432	0.000	**	0.000	0.000	319
20		75.0	-.129	.880	-2.308	0.000	**			
21		80.0	-.073	.854	-.330	0.000	**	0.000	0.000	321
22		85.0	-.021	.829	.265	0.000	**			
23		90.0	.035	.803	-.370	0.000	**	0.000	0.000	323
24		95.0	.103	.772	-.756	0.000	**			
	25	.5	.793	.425	2.374	0.000	**			
	26	1.5	.520	.573	3.712	0.000	**			
	27	3.0	.401	.631	3.412	0.000	**			
		5.0					**			
	29	7.5	.178	.737	3.343	0.000	**			
	30	10.0	.095	.776	3.327	0.000	**			
		15.0					**			
	32	20.0	-.146	.888	3.749	0.000	**			
		25.0					**			
		30.0					**			
		40.0					**			
	36	50.0	-.343	.982	1.850	0.000	**			
	37	60.0	-.155	.892	.291	0.000	**			
	38	70.0	.061	.791	-.111	0.000	**			
	39	80.0	.221	.717	-.064	0.000	**			
	40	90.0	.316	.672	-.040	0.000	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 3 ** RE	IM
Cz	UPPER	.614	1.348	0.000
Cz	LOWER	-.015	.513	0.000
Cz	TOTAL	.599	1.861	0.000
Cm	UPPER	.026	.421	0.000
Cm	LOWER	.010	-.005	0.000
Cm	TOTAL	.036	.415	0.000

NR. UP	LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.769	.439	-2.173	0.000	**			
2		.5	.027	.807	-5.625	0.000	**			
3		1.5	-.678	1.153	-9.054	0.000	**			
4		3.0	-.892	1.275	-6.373	0.000	**			
5		5.0	-1.063	1.384	-6.684	0.000	**	0.000	0.000	405
6		7.5	-1.125	1.427	-5.806	0.000	**			
7		10.0					**	0.000	0.000	407
8		15.0	-1.140	1.437	-5.407	0.000	**			
9		20.0	-1.149	1.443	-5.367	0.000	**	0.000	0.000	409
10		25.0	-1.140	1.437	-5.844	0.000	**			
		30.0					**			
12		35.0	-1.150	1.444	-2.587	0.000	**			
13		40.0	-1.036	1.366	50.439	0.000	**	0.000	0.000	413
14		45.0	-.623	1.124	8.903	0.000	**			
15		50.0	-.567	1.094	1.402	0.000	**	0.000	0.000	415
16		55.0	-.512	1.066	-.338	0.000	**			
17		60.0	-.442	1.031	-2.570	0.000	**	0.000	0.000	417
		65.0					**			
19		70.0	-.267	.945	-6.034	0.000	**			
20		75.0	-.188	.908	-6.655	0.000	**			
21		80.0	-.117	.874	-6.914	0.000	**	0.000	0.000	421
22		85.0	-.054	.845	-7.937	0.000	**			
23		90.0	-.002	.821	-8.869	0.000	**			
24		95.0	.042	.800	-9.334	0.000	**			
	25	.5	.751	.450	2.680	0.000	**			
	26	1.5	.445	.610	3.965	0.000	**			
	27	3.0	.316	.672	3.883	0.000	**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.043	.840	3.370	0.000	**			
	32	20.0	-.152	.891	3.471	0.000	**			
	33	25.0	-.234	.929	3.404	0.000	**			
		30.0					**			
	35	40.0	-.368	.994	2.210	0.000	**			
	36	50.0	-.338	.980	.451	0.000	**			
	37	60.0	-.128	.880	-1.317	0.000	**			
	38	70.0	.072	.787	-2.016	0.000	**			
	39	80.0	.238	.709	-2.111	0.000	**			
	40	90.0	.311	.675	-2.686	0.000	**			

OVERALL COEFFICIENTS		STEADY	** SECTION 4 ** RE	IM
Cz	UPPER	.609	.497	0.000
Cz	LOWER	-.031	.202	0.000
Cz	TOTAL	.578	.699	0.000
Cm	UPPER	.037	.531	0.000
Cm	LOWER	.011	-.309	0.000
Cm	TOTAL	.048	.222	0.000

*** LANN *** RUN 274 *** TABLE 9.24 (cont'd)

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.779	.434	-1.916	0.000	**			
2		.5	.098	.774	-5.572	0.000	**			
3		1.5	-.470	1.045	-6.164	0.000	**			
4		3.0	-.806	1.224	-7.168	0.000	**			
5		5.0	-.922	1.293	-7.400	0.000	**	0.000	0.000	505
6		7.5	-.974	1.326	-6.277	0.000	**			
7		10.0	-1.021	1.356	-5.625	0.000	**			
		15.0					**			
9		20.0	-1.054	1.377	-5.839	0.000	**			
10		25.0	-1.047	1.373	-6.115	0.000	**			
11		30.0	-1.064	1.384	-4.445	0.000	**			
		35.0					**			
13		40.0	-1.084	1.398	8.605	0.000	**			
14		45.0	-.797	1.220	49.284	0.000	**			
15		50.0	-.532	1.077	5.878	0.000	**			
16		55.0	-.441	1.030	2.474	0.000	**			
17		60.0	-.356	.989	.863	0.000	**			
18		65.0	-.284	.953	.207	0.000	**			
19		70.0	-.226	.926	.765	0.000	**	0.000	0.000	519
20		75.0	-.183	.905	1.771	0.000	**			
21		80.0	-.130	.881	1.541	0.000	**			
22		85.0	-.056	.846	-.899	0.000	**			
23		90.0	.005	.817	-2.681	0.000	**			
24		95.0	.068	.788	-4.793	0.000	**			
	25	.5	.705	.476	2.990	0.000	**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
	30	10.0	.008	.816	3.208	0.000	**			
		15.0					**			
	32	20.0	-.174	.901	3.124	0.000	**			
		25.0					**			
	34	30.0	-.290	.956	2.749	0.000	**			
		40.0					**			
	36	50.0	-.359	.990	-.882	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.240	.708	-2.037	0.000	**			
	40	90.0	.316	.672	-2.266	0.000	**			

**OVERALL COEFFICIENTS — ** SECTION 5 **

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.565	-.435	0.000
Cz	LOWER	-.033	.104	0.000
Cz	TOTAL	.532	-.330	0.000
Cm	UPPER	.036	-.445	0.000
Cm	LOWER	.008	-.302	0.000
Cm	TOTAL	.044	-.747	0.000

NR. UP	NR. LOW	%CHORD	Cp STEADY	M-LOC.	Cp RE	Cp IM	**	Cp RE	Cp IM	NR.
1		0.0	.771	.438	-1.750	0.000	**			
		.5					**			
3		1.5	-.294	.958	-6.173	0.000	**			
		3.0					**			
5		5.0	-.760	1.199	-5.918	0.000	**			
		7.5					**			
7		10.0	-.875	1.265	-5.989	0.000	**			
8		15.0	-.908	1.285	-4.575	0.000	**			
9		20.0	-.968	1.322	-3.612	0.000	**			
10		25.0	-1.002	1.343	-4.652	0.000	**			
11		30.0	-1.037	1.367	-4.424	0.000	**			
12		35.0	-1.074	1.391	-3.601	0.000	**			
13		40.0	-.555	1.088	5.331	0.000	**			
14		45.0	-.392	1.006	-.014	0.000	**			
15		50.0	-.289	.956	-.604	0.000	**			
16		55.0	-.259	.942	.428	0.000	**			
17		60.0	-.267	.945	.769	0.000	**			
18		65.0	-.282	.953	.797	0.000	**			
19		70.0	-.287	.955	.794	0.000	**			
20		75.0	-.269	.946	.672	0.000	**			
21		80.0	-.214	.920	.419	0.000	**			
22		85.0	-.100	.867	.089	0.000	**			
23		90.0	.007	.817	-.206	0.000	**			
24		95.0	.091	.777	-.325	0.000	**			
	25	.5	.596	.534	3.816	0.000	**			
		1.5					**			
		3.0					**			
		5.0					**			
		7.5					**			
		10.0					**			
	31	15.0	-.180	.904	2.780	0.000	**			
		20.0					**			
	33	25.0	-.308	.965	2.428	0.000	**			
	34	30.0	-.334	.978	2.158	0.000	**			
	35	40.0	-.377	.999	.255	0.000	**			
	36	50.0	-.311	.967	-.662	0.000	**			
		60.0					**			
		70.0					**			
	39	80.0	.233	.711	-.292	0.000	**			
	40	90.0	.301	.679	.059	0.000	**			

**OVERALL COEFFICIENTS — ** SECTION 6 **

OVERALL COEFFICIENTS		STEADY	RE	IM
Cz	UPPER	.468	.431	0.000
Cz	LOWER	-.047	.257	0.000
Cz	TOTAL	.421	.688	0.000
Cm	UPPER	.032	-.150	0.000
Cm	LOWER	.010	-.098	0.000
Cm	TOTAL	.042	-.248	0.000

Fig. 9.1 Wing platform (dimensions in mm)

Fig. 9.2 Test conditions of LANN wing model

STEADY

UNSTEADY

Fig. 9.3 Steady and unsteady pressure distribution at y/s = 0.65
(Run 73: M = 0.82, α_m = 0.6 deg, k = 0.103)

STEADY

UNSTEADY

Fig. 9.4 Steady and unsteady spanwise load distribution
(Run 73: M = 0.82, α_m = 0.6 deg, k = 0.103)

Fig. 9.5 Influence of Mach number and frequency on nodal line position

Fig. 9.6 Model instrumentation (dimensions in m) (see table 9.2, 9.3, 9.4)

Fig. 9.7 Block-diagram of the test set-up during unsteady measurements

AGARD Report No.702 Addendum No.1 Advisory Group for Aerospace Research and Development, NATO COMPENDIUM OF UNSTEADY AERODYNAMIC MEASUREMENTS Published May 1985 128 pages This Addendum contains two further sets of windtunnel measurements made on the AGARD Aeroelastic Configurations already chosen as computational test cases. General comments on the experimental programme and its relationship to the theoretical computations are contained in the initial volume of R-702. This report was sponsored by the Structures and Materials Panel of AGARD. ISBN 92-835-1495-5	AGARD-R-702 Aerodynamic characteristics Unsteady flow Transonic flow Aeroelasticity Aerodynamic configurations Experimental data Applications of mathematics	AGARD Report No.702 Addendum No.1 Advisory Group for Aerospace Research and Development, NATO COMPENDIUM OF UNSTEADY AERODYNAMIC MEASUREMENTS Published May 1985 128 pages This Addendum contains two further sets of windtunnel measurements made on the AGARD Aeroelastic Configurations already chosen as computational test cases. General comments on the experimental programme and its relationship to the theoretical computations are contained in the initial volume of R-702. This report was sponsored by the Structures and Materials Panel of AGARD. ISBN 92-835-1495-5	AGARD-R-702 Aerodynamic characteristics Unsteady flow Transonic flow Aeroelasticity Aerodynamic configurations Experimental data Applications of mathematics
AGARD Report No.702 Addendum No.1 Advisory Group for Aerospace Research and Development, NATO COMPENDIUM OF UNSTEADY AERODYNAMIC MEASUREMENTS Published May 1985 128 pages This Addendum contains two further sets of windtunnel measurements made on the AGARD Aeroelastic Configurations already chosen as computational test cases. General comments on the experimental programme and its relationship to the theoretical computations are contained in the initial volume of R-702. This report was sponsored by the Structures and Materials Panel of AGARD. ISBN 92-835-1495-5	AGARD-R-702 Aerodynamic characteristics Unsteady flow Transonic flow Aeroelasticity Aerodynamic configurations Experimental data Applications of mathematics	AGARD Report No.702 Addendum No.1 Advisory Group for Aerospace Research and Development, NATO COMPENDIUM OF UNSTEADY AERODYNAMIC MEASUREMENTS Published May 1985 128 pages This Addendum contains two further sets of windtunnel measurements made on the AGARD Aeroelastic Configurations already chosen as computational test cases. General comments on the experimental programme and its relationship to the theoretical computations are contained in the initial volume of R-702. This report was sponsored by the Structures and Materials Panel of AGARD. ISBN 92-835-1495-5	AGARD-R-702 Aerodynamic characteristics Unsteady flow Transonic flow Aeroelasticity Aerodynamic configurations Experimental data Applications of mathematics

AGARD

NATO ⊕ OTAN

7 RUE ANCELLE · 92200 NEUILLY-SUR-SEINE
FRANCE

Telephone 745.08.10 · Telex 610176

**DISTRIBUTION OF UNCLASSIFIED
AGARD PUBLICATIONS**

AGARD does NOT hold stocks of AGARD publications at the above address for general distribution. Initial distribution of AGARD publications is made to AGARD Member Nations through the following National Distribution Centres.Further copies are sometimes available from these Centres, but if not may be purchased in Mircrofiche or Photocopy form from the Purchase Agencies listed below.

NATIONAL DISTRIBUTION CENTRES

BELGIUM
Coordonna…
Etat-Major…
Quartier R…
Rue d'Ever…

CANADA
Defence Sc…
Dept of Na…
Ottawa, On…

DENMARK
Danish Def…
Ved Idraets…
2100 Cope…

FRANCE
O.N.E.R.A…
29 Avenue…
92320 Châ…

GERMANY
Fachinform…
Physik, Mat…
Kernforsch…
D-7514 Eg…

ITALY

GREECE
Hellenic Air Force General Staff
Research and Development Directorate
Holargos, Athens

ICELAND
Director of Aviation
c/o Flugrad
Reyjavik

TURKEY
Department of Research and Development (ARGE)
Ministry of National Defence, Ankara

UNITED KINGDOM
Defence Research Information Centre
Station Square House
St Mary Cray
Orpington, Kent BR5 3RE

UNITED STATES
National Aeronautics and Space Administration (NASA)
Langley Research Center
M/S 180
Hampton, Virginia 23665
Attn. Report Distribution and Storage Unit

THE UNITED STATES NATIONAL DISTRIBUTION CENTRE (NASA) DOES NOT HOLD
STOCKS OF AGARD PUBLICATIONS, AND APPLICATIONS FOR COPIES SHOULD BE MADE
DIRECT TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS) AT THE ADDRESS BELOW.

PURCHASE AGENCIES

Microfiche or Photocopy

National Technical
Information Service (NTIS)
5285 Port Royal Road
Springfield
Virginia 22161, USA

Microfiche

ESA/Information Retrieval Service
European Space Agency
10, rue Mario Nikis
75015 Paris, France

Microfiche or Photocopy

British Library Lending
Division
Boston Spa, Wetherby
West Yorkshire LS23 7BQ
England

Requests for microfiche or photocopies of AGARD documents should include the AGARD serial number, title, author or editor, and publication date. Requests to NTIS should include the NASA accession report number. Full bibliographical references and abstracts of AGARD publications are given in the following journals:

Scientific and Technical Aerospace Reports (STAR)
published by NASA Scientific and Technical
Information Branch
NASA Headquarters (NIT-40)
Washington D.C. 20546, USA

Government Reports Announcements (GRA)
published by the National Technical
Information Services, Springfield
Virginia 22161, USA

SPS

*Printed by Specialised Printing Services Limited
40 Chigwell Lane, Loughton, Essex IG10 3TZ*

ISBN 92-835-1495-5